



Submittal Data Sheet

daikin ah inverter, 4ton_r32

DFVE48DP1300

STANDARD FEATURES

- Electronic Expansion Valve (EEV) for cooling and heat pump applications
- 7 mm evaporator coil tube size
- Variable-speed ECM blower motor
- Compatible with Daikin One+ smart thermostat and other Daikin communicating equipment
- Provides constant CFM over a wide range of static pressure conditions independent of duct system
- CFM indicator
- Thermostat provides adjustable low CFM for efficient fan-only operation
- All-aluminum evaporator coil
- Fault recall of six most recent faults
- Improved humidity and comfort control
- AHRI certified
- ETL listed
- Cabinet air leakage less than 2.0% at 1.0 inch H₂O when tested in accordance with ASHRAE standard 193
- Cabinet air leakage less than 1.4% at 0.5 inch H₂O when tested in accordance with ASHRAE standard 193
- 3 kW – 25 kW electric heater kits
- Horizontal or vertical configuration capabilities
- 21" depth for easier attic access
- DecaBDE-free thermoplastic drain pan with secondary drain connections
- Screw-less sides and back helps to reduce condensation when installed in humid locations
- Foil-faced insulation covers the internal casing to reduce cabinet condensation
- Galvanized, leather grain-embossed finish
- Glue-less cabinet insulation retention
- Tool-less filter access



CABINET FEATURES

- Cabinet air leakage less than 2.0% at 1.0 inch H₂O when tested in accordance with ASHRAE standard 193
- Cabinet air leakage less than 1.4% at 0.5 inch H₂O when tested in accordance with ASHRAE standard 193
- 3 kW – 25 kW electric heater kits
- Horizontal or vertical configuration capabilities
- 21" depth for easier attic access
- DecaBDE-free thermoplastic drain pan with secondary drain connections
- Screw-less sides and back helps to reduce condensation when installed in humid locations
- Foil-faced insulation covers the internal casing to reduce cabinet condensation
- Galvanized, leather grain-embossed finish
- Glue-less cabinet insulation retention
- Tool-less filter access



Submittal Data Sheet

daikin ah inverter, 4ton_r32

DFVE48DP1300

PERFORMANCE

Product Model No.	DFVE48DP1300	Product Model Name:	daikin ah inverter, 4ton_r32
Type:	Air Handler	Cooling Capacity (Nominal) (Btu/hr):	48,000
Blower Motor Rating (HP):	3/4		

PRODUCT DETAILS

Power Supply (V/Hz/Ph):	208/230 / 60 / 1	Airflow Rate (High) (CFM):	
Min. Circuit Amps MCA (A):		Suction Valve Connection Size (inch):	7/8
Max Overcurrent Protection (MOP) (A):		Liquid Valve Connection Size (inch):	3/8
Dimensions (HxWxD) (in):	53.4375 x 24-1/2 x 21	Condensate Connection (inch):	
Net Weight (lb):	150	Blower Size Diameter (inch):	12
Gross Weight (lb):	153	Blower Size Width (inch):	10.625

MODELS	CIRCUIT 1 (208V/240V)			CIRCUIT 2 (208V/240V)			SINGLE-POINT KIT (208V/240V)	
	HEATER AMPS	MCA ¹	MOP ²	HEATER AMPS	MCA ¹	MOP ²	MCA ¹	MOP ²
DFVE48CP1300AA	0.0/0.0	6.5/6.5	15/15	---	---	---	---	---
HKTS*05X1	17.3/20.0	28.1/31.5	30/35	---	---	---	---	---
HKTSN06X1	21.7/25.0	33.6/37.8	35/40	---	---	---	---	---
HKTS*08X1	28.9/33.3	42.6/48.1	45/50	---	---	---	---	---
HKTS*10X1	34.7/40.0	49.9/56.5	50/60	---	---	---	---	---
HKTS*15X3 ^	0/0	6.5/6.5	15/15	30/34.6	37.5/43.3	40/45	---	---
HKTSD15XA/B	34.7/40	49.9/56.5	50/60	17.3/20	21.6/25.0	25/25	71.5/81.5	80/90
HKTS*20X3 ^	0/0	6.5/6.5	15/15	37.5/43.3	46.9/54.1	50/60	---	---

¹ Minimum Circuit Ampacity (Heater Amps + Motor Amps) X 1.25

² Maximum Overcurrent Protection = 2.25 X Motor Amps + Heater Amps

^ Three-phase Heater Kits (Circuit 1: Single-phase for Air Handlers Circuit 2: Three-phase for Heater Kits)

* D - Service disconnect, N - No service disconnect

--- indicates Not Required



Submittal Data Sheet
daikin ah inverter, 4ton_r32
DFVE48DP1300

DIMENSIONAL DRAWING





Submittal Data Sheet
daikin ah inverter, 4ton_r32
DFVE48DP1300

ACCESSORIES

PART NUMBER	DESCRIPTION	INCLUDED
0160M00015	MERV 15 Replacement Filter For DV15-2124-AD	No
ALFH20231E	20X23X1 Permanent Washable Filter	No
CMK0017	Condensate Management Kits	No
DFKE-02	Downflow Kit	No
DV15-2124-AD	DAIKIN PREMIUM AIR CLEANER,	No
HHK0003	High Humidity Kits	No
HKTSD15XA	Electric Heat Kit, 15 KW	No
HKTSD15XB	Electric Heat Kit, 15 KW	No
HKTSD20DA	Electric Heat Kit, 20 KW	No
HKTSD20DB	Electric Heat Kit, 20 KW	No
UC18S15-24	15" SGL LAMP UV24V COIL PURIFIER	No
UC18S15-24B	15" SGL LAMP UV 24V COIL PURIFIER w/ MAG	No