



Submittal Data Sheet

16 SEER2 HP R32, 2.5 Ton

DH5SEA3010

STANDARD FEATURES

- High-efficiency Copeland® scroll compressor
- Advanced Copeland® CoreSense™ technology
- Enhanced aluminum fin with coil-5mm diameter copper tubes in 1.5T-3.5T
- Enhanced aluminum fin coil with 7mm diameter copper tubes 4.0-5.0 ton
- Single-speed PSC condenser fan motor
- High density foam compressor sound blanket
- Time-delay technology to ensure quiet reliable defrost
- Factory-installed bi-flow liquid line filter drier
- High density foam compressor sound blanket
- Factory-installed suction line accumulator
- Factory-installed compressor crank case heater
- Factory-installed high capacity muffler
- High- and low-pressure switches
- Service valves with sweat connections and easy access to gauge ports
- Fully enclosed contactor
- Capacitor with extended life Copper tube/enhanced aluminum fin coil
- Fully charged for 15' of tubing length
- AHRI Certified
- ETL Listed



CABINET FEATURES

- Removable grille-style top design compliant with UL 60335-2-40
- Custom Nickel Gray powder-paint finish
- 500-hour salt-spray tested
- Wire fan discharge grille
- Steel louver coil guard
- Rust-resistant screws
- Top and side maintenance access
- Single-panel access to controls with space provided for field-installed accessories
- When properly anchored, meets the 2023 Florida Building Code unit integrity requirements for hurricane-type winds (Anchor bracket kits available.)

NOTES

- R32 Outdoor



Submittal Data Sheet

16 SEER2 HP R32, 2.5 Ton

DH5SEA3010

PERFORMANCE COMBINATION (HSVTC)

* VALUES SHOWN ARE FOR AHRI RATED HIGH SALES VOLUME TESTED

Outdoor Unit Model No.	DH5SEA3010	Outdoor Unit Name:	16 SEER2 HP R32, 2.5 Ton
Rated Cooling Conditions:	Indoor (°F DB/WB): / Ambient (°F DB/WB): 95 / 75	Rated Heating Conditions:	Indoor (°F DB/WB): / Ambient (°F DB/WB): 47 / 43
Max/Min Cooling Capacity (Btu/hr):		Max/Min Heating Capacity (Btu/hr):	
* Rated Cooling Capacity (Btu/hr):		* Rated Heating Capacity (Btu/hr):	28,600
* EER:		* EER2:	12.50
* SEER:		* SEER2:	15.20
* HSPF:	7.8	* HSPF2:	7.8
* Heating COP:			

OUTDOOR UNIT DETAILS

Power Supply (V/Hz/Ph):	208/230 / 60 / 1	Compressor Stage:	Single Stage
Min. Circuit Amps MCA (A):	17.1	Suction Valve Connection Size (inch):	3/4
Max Overcurrent Protection (MOP) (A):	25	Liquid Valve Connection Size (inch):	3/8
Running Load:		Sound Power (High) (dBA):	73
Refrigerant Type:	R-32	Cooling Operation Range (°F DB):	55 - 125
Holding Refrigerant Charge (ozs):	94	Heating Operation Range (°F DB):	-20 - 70
Additional Charge (ounces/ft):	0.55	Max. Pipe Length (Vertical) (ft):	79
Pre-charge Piping (Length) (ft):	15	Min. Cooling Range w/Baffle (°F DB):	
Max. Pipe Length (Total) (ft):	200	Min. Heating Range w/Baffle (°F DB):	
Net Weight (lb):	215	Gross Weight (lb):	235
Dimensions (HxWxD) (in):	39.5 x 35-1/2 x 35.5		




Submittal Data Sheet
16 SEER2 HP R32, 2.5 Ton
DH5SEA3010

DIMENSIONAL DRAWING

DIMENSIONS

MODEL	DIMENSIONS		
	W"	D"	H"
DH5SEA1810A*	29	29	39½
DH5SEA2410A*	29	29	39½
DH5SEA3010A*	35½	35½	39½
DH5SEA3610A*	35½	35½	39½
DH5SEA4210A*	35½	35½	35½
DH5SEA4810A*	35½	35½	36½
DH5SEA6010A*	35½	35½	41½





Submittal Data Sheet
16 SEER2 HP R32, 2.5 Ton
DH5SEA3010

ACCESSORIES

PART NUMBER	DESCRIPTION	INCLUDED
0161R00128	Cap, Spiral Grill	No
ABK-20	ANCHOR BRACKET KIT	No
CSR-U-1	Compressor Saver - Hard Start Kit - 1 TO 3 Ton	No
FSK01A	Freeze-Stat Kit	No
OT18-60A	Outdoor Thermostat Kit	No
TXV-FX-KX-3T	TXV-FX-KX-3T-Srv Kit	No