



Submittal Data Sheet

4.0T Cased Upflow/Downflow R-32 Coil with EEV

CAPEA4830D3

STANDARD FEATURES

- All-Aluminum evaporator coil
- Optimized for use with R-32 refrigerant including circuits and manifolds
- R-32 sensor designed for the life span of the coil
- Factory-installed electronic expansion valve (EEV) for precise refrigerant control - Compatibility with Daikin One+ smart thermostat and other Daikin communicating equipment - Cooling and heat pump applications - Fault recall of six most recent faults
- Standardized copper suction tube stub length
- 21" depth for easier attic access
- Foil-faced insulation covers the internal casing to reduce cabinet condensation
- Galvanized, leather grain-embossed finish
- Rust resistant, thermoplastic drain pans featuring a low water-retention design
- DecaBDE-free thermoplastic drain pan with secondary drain connections
- Drain pan rails designed to remove and reposition coils with ease without compromising structural integrity
- UV-resistant drain pan
- AHRI certified; ETL listed



CABINET FEATURES

- Single front access panel Foil-faced insulation covers the internal casing to reduce cabinet condensation Galvanized, leather grain-embossed finish



Submittal Data Sheet
4.0T Cased Upflow/Downflow R-32 Coil with EEV
CAPEA4830D3

PERFORMANCE

Product Model No.	CAPEA4830D3	Product Model Name:	4.0T Cased Upflow/Downflow R-32 Coil with EEV
Type:	Coil	Cooling Capacity (Nominal) (Btu/hr):	48,000

PRODUCT DETAILS

Dimensions (HxWxD) (in):	30 x 26 x 21	Suction Valve Connection Size (inch):	1-1/8
Net Weight (lb):	68	Liquid Valve Connection Size (inch):	3/8
Gross Weight (lb):	71	Condensate Connection (inch):	3/4



Submittal Data Sheet

4.0T Cased Upflow/Downflow R-32 Coil with EEV

CAPEA4830D3

DIMENSIONAL DRAWING

CAPEA— CASED HORIZONTAL INDOOR COILS



SPECIFICATIONS

MODEL	CABINET DIMENSIONS			NOMINAL TONS	CONNECTION		SHIP WEIGHT (LBS)
	W	D	H		LIQUID	SUCTION	
CAPEA2418B3	17½"	21	18	2	5/16" or 3/8"	3/8" or 1/2"	43
CAPEA2418C3	21	21	18	2	5/16" or 3/8"	3/8" or 1/2"	45
CAPEA3022B3	17½"	21	22	2½	5/16" or 3/8"	3/8" or 1/2"	48
CAPEA3022C3	21	21	22	2½	5/16" or 3/8"	3/8" or 1/2"	51
CAPEA3626B3	17½"	21	26	3	5/16" or 3/8"	3/8" or 1/2"	54
CAPEA3626C3	21	21	26	3	5/16" or 3/8"	3/8" or 1/2"	57
CAPEA3626D3	24½"	21	26	3	5/16" or 3/8"	3/8" or 1/2"	62
CAPEA4830C3	21	21	30	4	3/8"	3/8" or 1½"	68
CAPEA4830D3	24½"	21	30	4	3/8"	3/8" or 1½"	70
CAPEA6030C3	21	21	30	5	3/8"	3/8" or 1½"	75
CAPEA6030D3	24½"	21	30	5	3/8"	3/8" or 1½"	78

Note: For a properly matched system and piston sizing information, refer to Daikin piston kit chart of the corresponding Daikin outdoor unit.

DIMENSIONS

