Observation:
Observed a highway scene with a central metal guardrail separating oncoming lanes on the left and a stone retaining wall/embankment on the right; no variable lane sign is visible. In the ego direction, there is one dashed white lane divider between two motor-vehicle lanes, with solid white boundary lines at the left edge near the median and at the right edge near the shoulder; no pedestrians, construction barriers, or stopped vehicles are present in the adjacent lanes.

Reasoning:
Step 1 (lane count): No variable lane sign is present, so use lane-divider counting; there is 1 same-direction dashed white lane divider (excluding the solid boundary lines), therefore motor vehicle lanes = 1 + 1 = 2 in the current direction. Step 2 (ego position): The ego vehicle is traveling in the left lane adjacent to the median-side solid boundary line; there are 0 same-direction lanes to the left and 1 same-direction lane to the right, so the ego position index (left to right) is 0+1 = 1. Step 3 (three-dimensional feasibility): Structured—left lane change is not allowed because the ego is already in the leftmost lane and the left side is bounded by the median-side solid edge line/guardrail; right lane change is allowed because the divider to the right is a dashed white line. Vehicle-impacted—no vehicles are visible occupying the immediate left side (median/guardrail) or the right adjacent lane ahead, so left yes and right yes. Obstacle-impacted—no pedestrians, non-motorized vehicles, or roadblocks are visible on either side affecting a lane change, so left yes and right yes. Step 4 (final): Final feasibility requires structured, vehicle, and obstacle all "yes"; left is "no" because structured is "no", while right is "yes" because all three dimensions are "yes".

Observation:
Observed a suburban/highway-like curved road with green guardrails on both sides; there is no variable lane sign visible. The roadway shows a single solid yellow centerline separating oncoming traffic and a solid white edge line on the right, with no same-direction dashed/solid lane divider inside the ego direction; no surrounding vehicles or pedestrians/non-motorized vehicles/construction obstacles are visible.

Reasoning:
Step 1 (lane count): No variable lane sign is present, so use lane-divider counting; within the ego direction there are 0 same-direction lane dividers (only a solid yellow centerline for oncoming separation and a solid white right edge line as boundary), therefore motor vehicle lanes in the current direction = 0+1 = 1. Step 2 (ego position): With only 1 lane in the current direction, there are 0 same-direction lanes to the left of the ego-vehicle and 0 same-direction lanes to the right, so the ego-vehicle is in lane position 1 (left-to-right). Step 3 (three-dimensional feasibility): Structured—left change is not allowed because the left side is the oncoming side separated by a solid yellow centerline, and right change is not allowed because the right side is a solid white edge line/guardrail boundary and there is no adjacent same-direction lane; Vehicle—no vehicles are present in adjacent areas, so vehicle impact is yes for both directions; Obstacle—no pedestrians, non-motorized vehicles, or roadblocks are visible on either side, so obstacle impact is yes for both directions. Step 4 (final): Final feasibility requires structured, vehicle, and obstacle all yes; since structured is no for both left and right, the final lane change feasibility is no for both directions.

Observation:
Observed a suburban/park road with curbs on both sides: a green-belt/vegetation curb on the left and a sidewalk curb on the right; there is no variable lane sign visible and no oncoming-lane divider (double yellow/median) shown in the forward view. The roadway shows only solid white boundary lines on both sides with no same-direction dashed/solid lane divider inside the carriageway; a white van is ahead in the same lane, and there are no pedestrians, non-motorized vehicles, or construction barriers on either side of the travel lane.

Reasoning:
Step 1 (lane count): No variable lane sign is present; within the motor-vehicle carriageway there are 0 same-direction lane dividers (no internal dashed/solid separators), and the visible white lines are road-edge boundary lines at the curbs, so lane_count = 0 + 1 = 1. Step 2 (ego position): With only 1 motor-vehicle lane, there are 0 same-direction lanes to the left of the ego-vehicle and 0 same-direction lanes to the right, so the ego-vehicle is in position index 1 (left-to-right). Step 3 (lane change feasibility by dimension): Structured—because the ego lane is simultaneously the leftmost and rightmost lane and both sides are bounded by solid edge lines/curbs (no adjacent motor-vehicle lane exists), left lane change = no and right lane change = no; Vehicle-impacted—there is no vehicle occupying a left or right adjacent lane (none exists), so vehicle impact does not block either side, left = yes and right = yes; Obstacle-impacted—no pedestrians, bicycles/e-bikes, cones, or barriers are present intruding from left or right, so left = yes and right = yes. Step 4 (final): Final feasibility requires structured, vehicle, and obstacle all be yes; since structured is no for both directions, final left = no and final right = no.