

Functors in a Web-Scalable Module System

Guided Research Presentation

Elena Agapie

Supervisors: Prof.Dr. Michael Kohlhase, Florian Rabe

Jacobs University Bremen

May 16, 2008

Outline

- Introduction
- MMT and Theory Representation
- Functor Representation
- Well-formed Expressions
- Conclusions and Future Work

Introduction


- mathematical knowledge is increasing in size - needs to be organized
- representation as networks of mathematical theories
- several systems can represent mathematical theories (MMT [1], PVS[2], Isabelle[3])
- **functors** cannot be represented in either of the systems
→ we will present a **solution**.

Theory Representation in MMT

Representation:

- theory graph \rightarrow theories \rightarrow symbol declarations and axioms
- theory morphisms
- Representation of categories through theories

Monoid := {
symbols and axioms of FOL
 $e : i,$
 $\circ : i \rightarrow i \rightarrow i,$
 $e_l : \text{true forall } [x] e \circ x \text{ eq } x,$
 $e_r : \text{true forall } [x] x \circ e \text{ eq } x,$
 $\text{assoc} : \text{true forall } [x] \text{ forall } [y] \text{ forall } [z] (x \circ y) \circ z \text{ eq } x \circ (y \circ z) \}$




Theory Representation in MMT


Representation:

- theory graph \rightarrow theories \rightarrow symbol declarations and axioms
- theory morphisms
- Representation of categories through theories

Monoid := {
symbols and axioms of FOL
 $e : i,$
 $\circ : i \rightarrow i \rightarrow i,$
 $e_l : \text{true forall } [x] e \circ x \text{ eq } x,$
 $e_r : \text{true forall } [x] x \circ e \text{ eq } x,$
 $\text{assoc} : \text{true forall } [x] \text{ forall } [y] \text{ forall } [z] (x \circ y) \circ z \text{ eq } x \circ (y \circ z) \}$




Representing Functors




$R(F) := \lambda m : \text{Monoid} \rightarrow \text{ZFC} ($
 $\text{universe} \mapsto \{ x \in \text{universe}^m \},$
 $e \mapsto e^m,$
 $\text{inv} \mapsto \text{unique existing inverse in } \text{universe}^m$
 $\circ \mapsto \circ^m,$
 $e_l \mapsto \text{axiom for left unit},$
 $e_r \mapsto \text{axiom for right unit},$
 $\text{inv}_l \mapsto \text{axiom for left inverse},$
 $\text{inv}_r \mapsto \text{axiom for right inverse},$
 $\text{assoc} \mapsto \text{assoc}^m$
 $) : \text{Group} \rightarrow \text{ZFC}$

Representing Functors




Representing Functors



$R(F) := \lambda m : \text{Monoid} \rightarrow \text{ZFC} ($
 $\text{universe} \mapsto \{ x \in \text{universe}^m \},$
 $e \mapsto e^m,$
 $\text{inv} \mapsto \text{unique existing inverse in } \text{universe}^m$
 $\circ \mapsto \circ^m,$
 $e_l \mapsto \text{axiom for left unit},$
 $e_r \mapsto \text{axiom for right unit},$
 $\text{inv}_l \mapsto \text{axiom for left inverse},$
 $\text{inv}_r \mapsto \text{axiom for right inverse},$
 $\text{assoc} \mapsto \text{assoc}^m$
 $) : \text{Group} \rightarrow \text{ZFC}$


Representing Functors



$R(F) := \lambda m : \text{Monoid} \rightarrow \text{ZFC}(\$
 $\text{universe} \mapsto \{x \in \text{universe}^m\},$
 $e \mapsto e^m,$
 $\text{inv} \mapsto \text{unique existing inverse in } \text{universe}^m$
 $\circ \mapsto \circ^m,$
 $e_l \mapsto \text{axiom for left unit},$
 $e_r \mapsto \text{axiom for right unit},$
 $\text{inv}_l \mapsto \text{axiom for left inverse},$
 $\text{inv}_r \mapsto \text{axiom for right inverse},$
 $\text{assoc} \mapsto \text{assoc}^m$

$) : \text{Group} \rightarrow \text{ZFC}$


Representing Functors



$R(F) := \lambda m : \text{Monoid} \rightarrow \text{ZFC}$
 $\text{universe} \mapsto \{x \in \text{universe}^m\},$
 $e \mapsto e^m,$
 $\text{inv} \mapsto \text{unique existing inverse in } \text{universe}^m$
 $\circ \mapsto \circ^m,$
 $e_l \mapsto \text{axiom for left unit},$
 $e_r \mapsto \text{axiom for right unit},$
 $\text{inv}_l \mapsto \text{axiom for left inverse},$
 $\text{inv}_r \mapsto \text{axiom for right inverse},$
 $\text{assoc} \mapsto \text{assoc}^m$

) : Group \rightarrow ZFC


Representing Functors



$R(F) := \lambda m : \text{Monoid} \rightarrow \text{ZFC}(\text{universe} \mapsto \{x \in \text{universe}^m\},$
 $e \mapsto e^m,$
 $\text{inv} \mapsto \text{unique existing inverse in universe}^m$
 $\circ \mapsto \circ^m,$
 $e_l \mapsto \text{axiom for left unit},$
 $e_r \mapsto \text{axiom for right unit},$
 $\text{inv}_l \mapsto \text{axiom for left inverse},$
 $\text{inv}_r \mapsto \text{axiom for right inverse},$
 $\text{assoc} \mapsto \text{assoc}^m$

$) : \text{Group} \rightarrow \text{ZFC}$

Representing Functors



$R(F) := \lambda m : \text{Monoid} \rightarrow \text{ZFC}(\$
 $\text{universe} \mapsto \{x \in \text{universe}^m\},$
 $e \mapsto e^m,$
 $\text{inv} \mapsto \text{unique existing inverse in } \text{universe}^m$
 $\circ \mapsto \circ^m,$
 $e_l \mapsto \text{axiom for left unit},$
 $e_r \mapsto \text{axiom for right unit},$
 $\text{inv}_l \mapsto \text{axiom for left inverse},$
 $\text{inv}_r \mapsto \text{axiom for right inverse},$
 $\text{assoc} \mapsto \text{assoc}^m$

$) : \text{Group} \rightarrow \text{ZFC}$

Syntax

- We modify the flat grammar of MMT to represent functors.
- Changes are orthogonal to the omitted rules.
- Our solution can be extended to the general case without much difficulty.

View declarations	$View ::= m := \{\sigma\} : \tau$
Type	$\tau ::= (S \rightarrow T) \mid \tau' \Rightarrow \tau$
Substitutions	$\sigma ::= (c \mapsto \omega)^* \mid \lambda x : \tau. \sigma$
Morphisms	$\mu ::= m \mid \mu \bullet \mu' \mid m(\mu)$

Figure: Section from the grammar

Well-formed Expressions

- An expression is well-formed if it is semantically meaningful.
- We define a list of judgments that can appear in expressions.
- The context used by the judgements is γ or $\gamma; \Gamma$:

$$\gamma = (T := \{\vartheta\} \mid m := \{\sigma\} : \tau)^*$$

$$\Gamma = (x : S \rightarrow T)^*$$

$$\frac{\gamma; \Gamma, x : \tau' \triangleright \sigma : \tau}{\gamma; \Gamma \triangleright \lambda x : \tau'. \sigma : \tau' \Rightarrow \tau} (Viw_{\lambda})$$

$$\frac{\gamma; \Gamma \triangleright_T \omega_i \quad \text{dom}(S) = \{c_1, \dots, c_n\}}{\gamma; \Gamma \triangleright c_1 \mapsto \omega_1, \dots, c_n \mapsto \omega_n : S \rightarrow T} (Viw_{base})$$

Example:

$$Mon, Gr, ZFC; x : Mon \rightarrow ZFC, \sigma : Gr \rightarrow ZFC \triangleright$$

$$R := \{\lambda x : Mon \rightarrow ZFC. \sigma : (Mon \rightarrow ZFC) \Rightarrow (Gr \rightarrow ZFC)\}$$

Well-formed Expressions

- An expression is well-formed if it is semantically meaningful.
- We define a list of judgments that can appear in expressions.
- The context used by the judgements is γ or $\gamma; \Gamma$:

$$\gamma = (T := \{\vartheta\} \mid m := \{\sigma\} : \tau)^*$$

$$\Gamma = (x : S \rightarrow T)^*$$

$$\frac{\gamma; \Gamma, x : \tau' \triangleright \sigma : \tau}{\gamma; \Gamma \triangleright \lambda x : \tau'. \sigma : \tau' \Rightarrow \tau} (ViW_{\lambda})$$

$$\frac{\gamma; \Gamma \triangleright_T \omega_i \quad \text{dom}(S) = \{c_1, \dots, c_n\}}{\gamma; \Gamma \triangleright c_1 \mapsto \omega_1, \dots, c_n \mapsto \omega_n : S \rightarrow T} (ViW_{base})$$

Example:

$$Mon, Gr, ZFC; x : Mon \rightarrow ZFC, \sigma : Gr \rightarrow ZFC \triangleright$$

$$R := \{\lambda x : Mon \rightarrow ZFC. \sigma : (Mon \rightarrow ZFC) \Rightarrow (Gr \rightarrow ZFC)\}$$

Well-formed Expressions

- An expression is well-formed if it is semantically meaningful.
- We define a list of judgments that can appear in expressions.
- The context used by the judgements is γ or $\gamma; \Gamma$:

$$\gamma = (T := \{\vartheta\} \mid m := \{\sigma\} : \tau)^* \qquad \Gamma = (x : S \rightarrow T)^*$$

$$\frac{\gamma; \Gamma, x : \tau' \triangleright \sigma : \tau}{\gamma; \Gamma \triangleright \lambda x : \tau'. \sigma : \tau' \Rightarrow \tau} (Viw_{\lambda})$$

$$\frac{\gamma; \Gamma \triangleright_T \omega_i \quad \text{dom}(S) = \{c_1, \dots, c_n\}}{\gamma; \Gamma \triangleright c_1 \mapsto \omega_1, \dots, c_n \mapsto \omega_n : S \rightarrow T} (Viw_{base})$$

Example:

$$Mon, Gr, ZFC; x : Mon \rightarrow ZFC, \sigma : Gr \rightarrow ZFC \triangleright$$

$$R := \{\lambda x : Mon \rightarrow ZFC. \sigma : (Mon \rightarrow ZFC) \Rightarrow (Gr \rightarrow ZFC)\}$$

Well-formed Expressions

- An expression is well-formed if it is semantically meaningful.
- We define a list of judgments that can appear in expressions.
- The context used by the judgements is γ or $\gamma; \Gamma$:

$$\gamma = (T := \{\vartheta\} \mid m := \{\sigma\} : \tau)^* \qquad \Gamma = (x : S \rightarrow T)^*$$

$$\frac{\gamma; \Gamma, x : \tau' \triangleright \sigma : \tau}{\gamma; \Gamma \triangleright \lambda x : \tau'. \sigma : \tau' \Rightarrow \tau} (Viw_{\lambda})$$

$$\frac{\gamma; \Gamma \triangleright_T \omega_i \quad \text{dom}(S) = \{c_1, \dots, c_n\}}{\gamma; \Gamma \triangleright c_1 \mapsto \omega_1, \dots, c_n \mapsto \omega_n : S \rightarrow T} (Viw_{base})$$

Example:

$$Mon, Gr, ZFC; x : Mon \rightarrow ZFC, \sigma : Gr \rightarrow ZFC \triangleright$$

$$R := \{\lambda x : Mon \rightarrow ZFC. \sigma : (Mon \rightarrow ZFC) \Rightarrow (Gr \rightarrow ZFC)\}$$

Well-formed Expressions

- An expression is well-formed if it is semantically meaningful.
- We define a list of judgments that can appear in expressions.
- The context used by the judgements is γ or $\gamma; \Gamma$:

$$\gamma = (T := \{\vartheta\} \mid m := \{\sigma\} : \tau)^* \qquad \Gamma = (x : S \rightarrow T)^*$$

$$\frac{\gamma; \Gamma, x : \tau' \triangleright \sigma : \tau}{\gamma; \Gamma \triangleright \lambda x : \tau'. \sigma : \tau' \Rightarrow \tau} (Viw_{\lambda})$$

$$\frac{\gamma; \Gamma \triangleright_T \omega_i \quad \text{dom}(S) = \{c_1, \dots, c_n\}}{\gamma; \Gamma \triangleright c_1 \mapsto \omega_1, \dots, c_n \mapsto \omega_n : S \rightarrow T} (Viw_{base})$$

Example:

$$Mon, Gr, ZFC; x : Mon \rightarrow ZFC, \sigma : Gr \rightarrow ZFC \triangleright$$

$$R := \{\lambda x : Mon \rightarrow ZFC. \sigma : (Mon \rightarrow ZFC) \Rightarrow (Gr \rightarrow ZFC)\}$$

Conclusions and Future Work

- We represented functors building upon the MMT language.
- We gave the rules for well-formed expressions.
- We will integrate functors in the complete MMT grammar.
- This is posible and requires the adjustment of the language to the new productions.
- We will try to integrate the morphism component of a functor in MMT.

References

beamericonarticle

Morhan Rabe, Michael Kohlhase.

A Web-Scalable Module System for Mathematical Theories.

to be submitted, 2008.

beamericonarticle

Stefan Edelwe and N. Shankar and J.M. Rushby and D.W.J. Stringer-Calvert.

PVS Language Reference, 2001.

beamericonarticle

Clemens Ballarin.

Locales and Locale Expressions in Isabelle/Isar.

Third International Workshop of the Types Working Group, TYPES 2003.

Thank you!

Questions?