



Courses @90% Refund Data Science IBM Certification Data Science Data Science Projects Data Analysis

Last Updated : 07 Dec, 2023

A Machine Learning model is defined as a mathematical model with several parameters that need to be learned from the data. By training a model with existing data, we can fit the model parameters.

However, there is another kind of parameter, known as ***Hyperparameters***, that cannot be directly learned from the regular training process. They are usually fixed before the actual training process begins. These parameters express important properties of the model such as its complexity or how fast it should learn. This article aims to explore various strategies to tune hyperparameters for Machine learning models.

Hyperparameter Tuning

Hyperparameter tuning is the process of selecting the optimal values for a [machine learning](#) model's hyperparameters. Hyperparameters are settings that control the learning process of the model, such as the learning rate, the number of neurons in a neural network, or the kernel size in a support vector machine. The goal of hyperparameter tuning is to find the values that lead to the best performance on a given task.

What are Hyperparameters?

In the context of machine learning, hyperparameters are configuration variables that are set before the training process of a model begins. They control the learning process itself, rather than being learned from the data. Hyperparameters are often used to tune the performance of a model, and

they can have a significant impact on the model's accuracy, generalization, and other metrics.

Different Ways of Hyperparameters Tuning

Hyperparameters are configuration variables that control the learning process of a machine learning model. They are distinct from model parameters, which are the weights and biases that are learned from the data. There are several different types of hyperparameters:

Hyperparameters in Neural Networks

[Neural networks](#) have several essential hyperparameters that need to be adjusted, including:

- **Learning rate:** This hyperparameter controls the step size taken by the optimizer during each iteration of training. Too small a learning rate can result in slow convergence, while too large a learning rate can lead to instability and divergence.
- **Epochs:** This hyperparameter represents the number of times the entire training dataset is passed through the model during training. Increasing the number of epochs can improve the model's performance but may lead to overfitting if not done carefully.
- **Number of layers:** This hyperparameter determines the depth of the model, which can have a significant impact on its complexity and learning ability.
- **Number of nodes per layer:** This hyperparameter determines the width of the model, influencing its capacity to represent complex relationships in the data.
- **Architecture:** This hyperparameter determines the overall structure of the neural network, including the number of layers, the number of neurons per layer, and the connections between layers. The optimal architecture depends on the complexity of the task and the size of the dataset

- **Activation function:** This hyperparameter introduces non-linearity into the model, allowing it to learn complex decision boundaries. Common activation functions include sigmoid, tanh, and Rectified Linear Unit (ReLU).

Hyperparameters in Support Vector Machine

We take into account some essential hyperparameters for fine-tuning [SVMs](#):

- **C:** The regularization parameter that controls the trade-off between the margin and the number of training errors. A larger value of C penalizes training errors more heavily, resulting in a smaller margin but potentially better generalization performance. A smaller value of C allows for more training errors but may lead to overfitting.
- **Kernel:** The kernel function that defines the similarity between data points. Different kernels can capture different relationships between data points, and the choice of kernel can significantly impact the performance of the SVM. Common kernels include linear, polynomial, radial basis function (RBF), and sigmoid.
- **Gamma:** The parameter that controls the influence of support vectors on the decision boundary. A larger value of gamma indicates that nearby support vectors have a stronger influence, while a smaller value indicates that distant support vectors have a weaker influence. The choice of gamma is particularly important for RBF kernels.

Hyperparameters in XGBoost

The following essential [XGBoost](#) hyperparameters need to be adjusted:

- **learning_rate:** This hyperparameter determines the step size taken by the optimizer during each iteration of training. A larger learning rate can lead to faster convergence, but it may also increase the risk of overfitting. A smaller learning rate may result in slower convergence but can help prevent overfitting.
- **n_estimators:** This hyperparameter determines the number of boosting trees to be trained. A larger number of trees can improve the model's

accuracy, but it can also increase the risk of overfitting. A smaller number of trees may result in lower accuracy but can help prevent overfitting.

- **max_depth:** This hyperparameter determines the maximum depth of each tree in the ensemble. A larger max_depth can allow the trees to capture more complex relationships in the data, but it can also increase the risk of overfitting. A smaller max_depth may result in less complex trees but can help prevent overfitting.
- **min_child_weight:** This hyperparameter determines the minimum sum of instance weight (hessian) needed in a child node. A larger min_child_weight can help prevent overfitting by requiring more data to influence the splitting of trees. A smaller min_child_weight may allow for more aggressive tree splitting but can increase the risk of overfitting.
- **subsample:** This hyperparameter determines the percentage of rows used for each tree construction. A smaller subsample can improve the efficiency of training but may reduce the model's accuracy. A larger subsample can increase the accuracy but may make training more computationally expensive.

Some other examples of model hyperparameters include:

1. The penalty in Logistic Regression Classifier i.e. L1 or L2 regularization
2. Number of Trees and Depth of Trees for Random Forests.
3. The learning rate for training a neural network.
4. Number of Clusters for Clustering Algorithms.
5. The k in k-nearest neighbors.

Hyperparameter Tuning techniques

Models can have many hyperparameters and finding the best combination of parameters can be treated as a search problem. The two best strategies for Hyperparameter tuning are:

1. [GridSearchCV](#)
2. [RandomizedSearchCV](#)

3. Bayesian Optimization

1. GridSearchCV

Grid search can be considered as a “brute force” approach to hyperparameter optimization. We fit the model using all possible combinations after creating a grid of potential discrete hyperparameter values. We log each set’s model performance and then choose the combination that produces the best results. This approach is called GridSearchCV, because it searches for the best set of hyperparameters from a grid of hyperparameters values.

An exhaustive approach that can identify the ideal hyperparameter combination is grid search. But the slowness is a disadvantage. It often takes a lot of processing power and time to fit the model with every potential combination, which might not be available.

For example: if we want to set two hyperparameters C and Alpha of the Logistic Regression Classifier model, with different sets of values. The grid search technique will construct many versions of the model with all possible combinations of hyperparameters and will return the best one.

As in the image, for C = [0.1, 0.2, 0.3, 0.4, 0.5] and Alpha = [0.1, 0.2, 0.3, 0.4]. For a combination of **C=0.3 and Alpha=0.2**, the performance score comes out to be **0.726(Highest)**, therefore it is selected.

C	0.5	0.701	0.703	0.697	0.696
	0.4	0.699	0.702	0.698	0.702
	0.3	0.721	0.726	0.713	0.703
	0.2	0.706	0.705	0.704	0.701
	0.1	0.698	0.692	0.688	0.675
		0.1	0.2	0.3	0.4
		Alpha			

The following code illustrates how to use GridSearchCV

Python3

```
# Necessary imports
from sklearn.linear_model import LogisticRegression
from sklearn.model_selection import GridSearchCV
import numpy as np
from sklearn.datasets import make_classification

X, y = make_classification(
    n_samples=1000, n_features=20, n_informative=10, n_classes=2, random_stat

# Creating the hyperparameter grid
c_space = np.logspace(-5, 8, 15)
param_grid = {'C': c_space}

# Instantiating logistic regression classifier
logreg = LogisticRegression()

# Instantiating the GridSearchCV object
logreg_cv = GridSearchCV(logreg, param_grid, cv=5)

# Assuming X and y are your feature matrix and target variable
# Fit the GridSearchCV object to the data
logreg_cv.fit(X, y)

# Print the tuned parameters and score
print("Tuned Logistic Regression Parameters: {}".format(logreg_cv.best_params_))
print("Best score is {}".format(logreg_cv.best_score_))
```

Output:

```
Tuned Logistic Regression Parameters: {'C': 0.006105402296585327}
Best score is 0.853
```

Drawback: GridSearchCV will go through all the intermediate combinations of hyperparameters which makes grid search

computationally very expensive.

2. RandomizedSearchCV

As the name suggests, the random search method selects values at random as opposed to the grid search method's use of a predetermined set of numbers. Every iteration, random search attempts a different set of hyperparameters and logs the model's performance. It returns the combination that provided the best outcome after several iterations. This approach reduces unnecessary computation.

RandomizedSearchCV solves the drawbacks of GridSearchCV, as it goes through only a fixed number of hyperparameter settings. It moves within the grid in a random fashion to find the best set of hyperparameters. The advantage is that, in most cases, a random search will produce a comparable result faster than a grid search.

The following code illustrates how to use RandomizedSearchCV

Python3

```
import numpy as np
from sklearn.datasets import make_classification

# Generate a synthetic dataset for illustration
X, y = make_classification(n_samples=1000, n_features=20, n_informative=10, r

# Rest of your code (including the RandomizedSearchCV part)
from scipy.stats import randint
from sklearn.tree import DecisionTreeClassifier
from sklearn.model_selection import RandomizedSearchCV

param_dist = {
    "max_depth": [3, None],
    "max_features": randint(1, 9),
    "min_samples_leaf": randint(1, 9),
    "criterion": ["gini", "entropy"]
}

tree = DecisionTreeClassifier()
tree_cv = RandomizedSearchCV(tree, param_dist, cv=5)
```



```
tree_cv.fit(X, y)

print("Tuned Decision Tree Parameters: {}".format(tree_cv.best_params_))
print("Best score is {}".format(tree_cv.best_score_))
```

Output:

```
Tuned Decision Tree Parameters: {'criterion': 'entropy',
 'max_depth': None, 'max_features': 8, 'min_samples_leaf': 7}
Best score is 0.842
```

Drawback: It's possible that the outcome could not be the ideal hyperparameter combination is a disadvantage.

3. Bayesian Optimization

Grid search and random search are often inefficient because they evaluate many unsuitable hyperparameter combinations without considering the previous iterations' results. Bayesian optimization, on the other hand, treats the search for optimal hyperparameters as an optimization problem. It considers the previous evaluation results when selecting the next hyperparameter combination and applies a probabilistic function to choose the combination that will likely yield the best results. This method discovers a good hyperparameter combination in relatively few iterations.

Data scientists use a probabilistic model when the objective function is unknown. The probabilistic model estimates the probability of a hyperparameter combination's objective function result based on past evaluation results.

$$P(\text{score}(y)|\text{hyperparameters}(x))$$

It is a “surrogate” of the objective function, which can be the root-mean-square error (RMSE), for example. The objective function is calculated using the training data with the hyperparameter combination, and we try

to optimize it (maximize or minimize, depending on the objective function selected).

Applying the probabilistic model to the hyperparameters is computationally inexpensive compared to the objective function. Therefore, this method typically updates and improves the surrogate probability model every time the objective function runs. Better hyperparameter predictions decrease the number of objective function evaluations needed to achieve a good result. Gaussian processes, random forest regression, and tree-structured Parzen estimators (TPE) are examples of surrogate models.

The Bayesian optimization model is complex to implement, but off-the-shelf libraries like Ray Tune can simplify the process. It's worth using this type of model because it finds an adequate hyperparameter combination in relatively few iterations. However, compared to grid search or random search, we must compute Bayesian optimization sequentially, so it doesn't allow distributed processing. Therefore, Bayesian optimization takes longer yet uses fewer computational resources.

Drawback: Requires an understanding of the underlying probabilistic model.

Challenges in Hyperparameter Tuning

- Dealing with High-Dimensional Hyperparameter Spaces: Efficient Exploration and Optimization
- Handling Expensive Function Evaluations: Balancing Computational Efficiency and Accuracy
- Incorporating Domain Knowledge: Utilizing Prior Information for Informed Tuning
- Developing Adaptive Hyperparameter Tuning Methods: Adjusting Parameters During Training

Applications of Hyperparameter Tuning

- Model Selection: Choosing the Right Model Architecture for the Task
- Regularization Parameter Tuning: Controlling Model Complexity for Optimal Performance
- Feature Preprocessing Optimization: Enhancing Data Quality and Model Performance
- Algorithmic Parameter Tuning: Adjusting Algorithm-Specific Parameters for Optimal Results

Advantages of Hyperparameter tuning:

- Improved model performance
- Reduced overfitting and underfitting
- Enhanced model generalizability
- Optimized resource utilization
- Improved model interpretability

Disadvantages of Hyperparameter tuning:

- Computational cost
- Time-consuming process
- Risk of overfitting
- No guarantee of optimal performance
- Requires expertise

Frequently Asked Question(FAQ's)

1. What are the methods of hyperparameter tuning?

There are several methods for hyperparameter tuning, including grid search, random search, and Bayesian optimization. Grid search exhaustively evaluates all possible combinations of hyperparameter values, while random search randomly samples combinations. Bayesian optimization uses a probabilistic model to guide the search for optimal hyperparameters.

2. What is the difference between parameter tuning and hyperparameter tuning?

Parameters are the coefficients or weights learned during the training process of a machine learning model, while hyperparameters are settings that control the training process itself. For example, the learning rate is a hyperparameter that controls how quickly the model learns from the data

3. What is the purpose of hyperparameter tuning?

The purpose of hyperparameter tuning is to find the best set of hyperparameters for a given machine learning model. This can improve the model's performance on unseen data, prevent overfitting, and reduce training time.

4. Which hyperparameter to tune first?

The order in which you tune hyperparameters depends on the specific model and dataset. However, a good rule of thumb is to start with the most important hyperparameters, such as the learning rate, and then move on to less important ones.

5. What is hyperparameter tuning and cross validation?

Cross validation is a technique used to evaluate the performance of a machine learning model. Hyperparameter tuning is often performed within a cross-validation loop to ensure that the selected hyperparameters generalize well to unseen data.

What is Hyperparameter tuning? | Machine Learning

Get IBM Certification and a **90% fee refund** on completing 90% course in 90 days! [Take the Three 90 Challenge today.](#)

Master Machine Learning, Data Science & AI with this complete program and also get a 90% refund. What more motivation do you need? [Start the challenge right away!](#)

[Comment](#)[More info](#)[Advertise with us](#)

Next Article

Introduction to Convolution Neural
Network

Similar Reads

SVM Hyperparameter Tuning using GridSearchCV | ML

A Machine Learning model is defined as a mathematical model with a number of parameters that need to be learned from the data. However, the...

4 min read

Random Forest Hyperparameter Tuning in Python

In this article, we shall implement Random Forest Hyperparameter Tuning in Python using Sci-kit Library. Sci-kit aka Sklearn is a Machine Learning librar...

5 min read

Cross-validation and Hyperparameter tuning of LightGBM Model

In a variety of industries, including finance, healthcare, and marketing, machine learning models have become essential for resolving challenging...

14 min read

CatBoost Cross-Validation and Hyperparameter Tuning

CatBoost is a powerful gradient-boosting algorithm of machine learning that is very popular for its effective capability to handle categorical features of...

11 min read

Hyperparameter tuning using GridSearchCV and KerasClassifier

Hyperparameter tuning is done to increase the efficiency of a model by tuning the parameters of the neural network. Some scikit-learn APIs like...

2 min read

How to tune a Decision Tree in Hyperparameter tuning

Decision trees are powerful models extensively used in machine learning for classification and regression tasks. The structure of decision trees resemble...

14 min read

Hyperparameter Tuning in Linear Regression

Linear regression is one of the simplest and most widely used algorithms in machine learning. Despite its simplicity, it can be quite powerful, especially...

7 min read

Hyperparameter tuning SVM parameters using Genetic Algorithm

The performance support Vector Machines (SVMs) are heavily dependent on hyperparameters such as the regularization parameter (C) and the kernel...

9 min read

HyperParameter Tuning: Fixing Overfitting in Neural Networks

Overfitting is a pervasive problem in neural networks, where the model becomes too specialized to the training data and fails to generalize well to...

6 min read

Hyperparameter tuning with Ray Tune in PyTorch

Hyperparameter tuning is a crucial step in the machine learning pipeline that can significantly impact the performance of a model. Choosing the right set...

8 min read



Corporate & Communications Address:

A-143, 7th Floor, Sovereign Corporate
Tower, Sector- 136, Noida, Uttar Pradesh
(201305)

Registered Address:

K 061, Tower K, Gulshan Vivante
Apartment, Sector 137, Noida, Gautam
Buddh Nagar, Uttar Pradesh, 201305



Advertise with us

Company

About Us
Legal
Careers
In Media
Contact Us
Advertise with us
GFG Corporate Solution
Placement Training Program

Languages

Python
Java
C++
PHP
GoLang
SQL
R Language
Android Tutorial

Data Science & ML

Data Science With Python
Data Science For Beginner
Machine Learning
ML Maths
Data Visualisation
Pandas
NumPy
NLP
Deep Learning

Python Tutorial

Python Programming Examples
Django Tutorial
Python Projects
Python Tkinter
Web Scraping
OpenCV Tutorial
Python Interview Question

DevOps

Git
AWS
Docker

Explore

Job-A-Thon Hiring Challenge
Hack-A-Thon
GfG Weekly Contest
Offline Classes (Delhi/NCR)
DSA in JAVA/C++
Master System Design
Master CP
GeeksforGeeks Videos
Geeks Community

DSA

Data Structures
Algorithms
DSA for Beginners
Basic DSA Problems
DSA Roadmap
DSA Interview Questions
Competitive Programming

Web Technologies

HTML
CSS
JavaScript
TypeScript
ReactJS
NextJS
NodeJs
Bootstrap
Tailwind CSS

Computer Science

GATE CS Notes
Operating Systems
Computer Network
Database Management System
Software Engineering
Digital Logic Design
Engineering Maths

System Design

High Level Design
Low Level Design
UML Diagrams

Kubernetes
Azure
GCP
DevOps Roadmap

Interview Guide
Design Patterns
OOAD
System Design Bootcamp
Interview Questions

School Subjects

Mathematics
Physics
Chemistry
Biology
Social Science
English Grammar

Commerce

Accountancy
Business Studies
Economics
Management
HR Management
Finance
Income Tax

Databases

SQL
MYSQL
PostgreSQL
PL/SQL
MongoDB

Preparation Corner

Company-Wise Recruitment Process
Resume Templates
Aptitude Preparation
Puzzles
Company-Wise Preparation
Companies
Colleges

Competitive Exams

JEE Advanced
UGC NET
UPSC
SSC CGL
SBI PO
SBI Clerk
IBPS PO
IBPS Clerk

More Tutorials

Software Development
Software Testing
Product Management
Project Management
Linux
Excel
All Cheat Sheets
Recent Articles

Free Online Tools

Typing Test
Image Editor
Code Formatters
Code Converters
Currency Converter
Random Number Generator
Random Password Generator

Write & Earn

Write an Article
Improve an Article
Pick Topics to Write
Share your Experiences
Internships

DSA/Placements

DSA - Self Paced Course
DSA in JavaScript - Self Paced Course

Development/Testing

JavaScript Full Course
React JS Course

DSA in Python - Self Paced

C Programming Course Online - Learn C with Data Structures

Complete Interview Preparation

Master Competitive Programming

Core CS Subject for Interview Preparation

Mastering System Design: LLD to HLD

Tech Interview 101 - From DSA to System Design [LIVE]

DSA to Development [HYBRID]

Placement Preparation Crash Course [LIVE]

Machine Learning/Data Science

Complete Machine Learning & Data Science Program - [LIVE]

Data Analytics Training using Excel, SQL, Python & PowerBI -
[LIVE]

Data Science Training Program - [LIVE]

Mastering Generative AI and ChatGPT

Data Science Course with IBM Certification

Clouds/Devops

DevOps Engineering

AWS Solutions Architect Certification

Salesforce Certified Administrator Course

React Native Course

Django Web Development Course

Complete Bootstrap Course

Full Stack Development - [LIVE]

JAVA Backend Development - [LIVE]

Complete Software Testing Course [LIVE]

Android Mastery with Kotlin [LIVE]

Programming Languages

C Programming with Data Structures

C++ Programming Course

Java Programming Course

Python Full Course

GATE

GATE CS & IT Test Series - 2025

GATE DA Test Series 2025

GATE CS & IT Course - 2025

GATE DA Course 2025

@GeeksforGeeks, Sanchhaya Education Private Limited, All rights reserved