


# Creating and managing tablespaces

Tablespaces are logical storage groups that can be used to store logical database constructs, such as tables and indexes  
Logically it stores the database files

A Segment is a set of Extents, one or more Extents, allocated for certain logical structures inside the database ( ex: table, index)

An Extent is a set of contiguous Oracle Data Blocks  
it is much more efficient, when allocating space


Oracle data stored in DB blocks  
1 Block= 8 K by default  
A single Oracle Data Block contains one or more rows



SAN: Storage area network  
NAS: network attached storage  
NFS: network file system  
ASM: automatic storage management

# Creating and managing tablespaces

☐ SYSTEM  
☐ SYSAUX  
☐ TEMP  
☐ UNDO  
☐ USERS



# Creating and managing tablespaces

## SYSTEM tablespace

Used for core functionality.

Stores the data dictionary ( belong to sys schema).

Oracle create system tablespace automatically when the database is created.  
you cannot rename or drop the SYSTEM tablespace.

## SYSAUX tablespace

The SYSAUX tablespace is an auxiliary tablespace to the SYSTEM tablespace.

It reduces the load on the SYSTEM tablespace.

Oracle create it automatically when the database is created  
you cannot rename or drop the SYSAUX tablespace.

## TEMP tablespace

are used to manage space for database sort and joining operations and for storing global temporary tables.

Other SQL operations that might require disk sorting are: CREATE INDEX, ANALYZE, SELECT DISTINCT, ORDER BY, GROUP BY, UNION, INTERSECT, MINUS,...

# Creating and managing tablespaces

## UNDO tablespace

is used to roll back, or undo, changes to the database.

- Roll back transactions when a ROLLBACK statement is issued
- Recover the database
- Provide read consistency

## USERS tablespace

Stores users objects and data


every database should have a tablespace for permanent user data that is assigned to users. Otherwise, user objects will be created in the SYSTEM tablespace, **which is not good practice**.

In the preconfigured database, USERS is designated as the default tablespace for all new users.

Note: all these tablespaces exists in the container database and also the pluggable databases .

# Creating and managing tablespaces


## How Table Data Is Stored



- ❑ If an entire row can be inserted into a single data block, then Oracle stores the row as one row piece.
- ❑ if all of a row's data cannot be inserted into a single data block or if an update to an existing row causes the row to outgrow its data block, then Oracle stores the row using multiple row pieces
- ❑ A data block usually contains only one row piece for each row.
- ❑ When Oracle must store a row in more than one row piece, it is **chained** across multiple blocks.

# Creating and managing tablespaces

## Database block content



# Creating and managing tablespaces

## About creating tablespace

- Creating tablespace is an allocation of space in the DB that can contain schema objects.
- We can do this by **create tablespace** statement or EM express .
- We can create 3 types of tablespaces

- **Permanent tablespace:** Contains persistent schema objects. Objects in permanent tablespaces are stored in data files.

- **Undo tablespace:** Is a type of permanent tablespace used by Oracle Database to manage undo data

- **Temporary tablespace:** Contains schema objects only for the duration of a session.

Prerequisites: the DB must be opened, you must have **create tablespace system privilege**.

**Note:** to create sysaux tablespace you must have **SYSDBA system privilege**

# Creating and managing tablespaces

## About creating tablespace

### 1- file name and size

- You must specify **DATAFILE** or **TEMPFILE** clause when you create a tablespace, this will specify the name and the location of the data file or the temp file.
- A tablespace must have at least one data file or temp file.
- You must also specify initial file size.
- You can include **AUTOEXTEND ON** clause to automatically extend the file when it is full. in this case you need to specify increment amount +max size
- You can include **bigfile** or **smallfile** clause to override the default tablespace type.

A **bigfile tablespace** contains only one data file or temp file, which can contain up to approximately 4 billion blocks

A **smallfile tablespace** is a traditional Oracle tablespace, which can contain 1022 data files or temp files, each of which can contain up to approximately 4 million blocks



# Creating and managing tablespaces

## About creating tablespace

### 2- Availability

- You can also include the **online** or **offline** clause to make the tablespace available or not available
- **online** or **offline** clause can not be used with temporary tablespace .
- **online** is the default .
- **DBA\_tablespaces** indicates whether each tablespace **online** or **offline** .

### 3- Block size

- you can include the **BLOCKSIZE** to specify nonstandard block size.
- In order to specify this clause, the **DB\_CACHE\_SIZE** and at least one **DB\_nK\_CACHE\_SIZE** parameter must be set, and the integer you specify in this clause must correspond with the setting of one **DB\_nK\_CACHE\_SIZE** parameter setting.
- You cannot specify nonstandard block sizes for a temporary tablespace or if you intend to assign this tablespace as the temporary tablespace for any users
- The default is 8kB

# Creating and managing tablespaces

## About creating tablespace

### 4- Extent management

- you can include **EXTENT MANAGEMENT** clause to specify how the extents of the tablespace will be managed.
- **AUTOALLOCATE** specifies that the tablespace is system managed. Users cannot specify an extent size. You cannot specify AUTOALLOCATE for a temporary tablespace.
- **UNIFORM**  
specifies that the tablespace is managed with uniform extents of SIZE bytes. The default SIZE is 1mb.

All extents of temporary tablespaces are of uniform size, so this keyword is optional for a temporary tablespace.

However, you must specify UNIFORM in order to specify SIZE. You cannot specify UNIFORM for an undo tablespace.

- If you do not specify AUTOALLOCATE or UNIFORM, then the default is UNIFORM for temporary tablespaces and AUTOALLOCATE for all other types of tablespaces

# Creating and managing tablespaces

## About creating tablespace

### 5- *logging clause*

- Specify the default logging attributes of all tables, indexes, materialized views, materialized view logs, and partitions within the tablespace.
- The logging\_clause lets you specify whether creation of a database object will be logged in the redo log file (**LOGGING**) or not (**NOLOGGING**).
- If you omit this clause, then the default is **LOGGING**.
- This clause is not valid for a temporary or undo tablespace.
- Oracle recommend using **LOGGING**.

### 6- *segment management clause*

- It lets you specify whether Oracle Database should track the used and free space in the segments in the tablespace using free lists or bitmaps. This clause is not valid for a temporary tablespace.
  - AUTO** :Specify AUTO if you want the database to manage the free space of segments in the tablespace using a bitmap.
  - MANUAL** :Specify MANUAL if you want the database to manage the free space of segments in the tablespace using free lists

### 7- *data segment compression* ( it is disabled by default )

<https://docs.oracle.com/en/database/oracle/oracle-database/12.2/sqlrf/CREATE-TABLESPACE.html#GUID-51F07BF5-EFAF-4910-9040-C473B86A8BF9>

# Creating and managing tablespaces

## Altering and Dropping Tablespaces

- ❑ When you create a tablespace, it is initially a read/write tablespace.
- ❑ Use the `ALTER TABLESPACE` statement to take a tablespace offline or online, add data files or temp files to it, or make it a read-only tablespace.
- ❑ A tablespace can be in one of three different statuses or states:
  - Read Write
  - Read Only
  - Offline with one of the following options:
    - ✓ Normal
    - ✓ Temporary
    - ✓ Immediate

**Note:** System tablespaces may not be taken offline.

<https://docs.oracle.com/en/database/oracle/oracle-database/18/sqlrf/ALTER-TABLESPACE.html#GUID-CA074861-55D3-4768-8995-43D4DA26365D>

- ❑ Add space to an existing tablespace by either adding data files to the tablespace or changing the size of an existing data file.
- ❑ Use the `DROP TABLESPACE` statement to drop a tablespace and its contents from the database if you no longer need its content.