Database Instance

System Global Area (SGA) Part 1


What we will learn in this lecture?

- > What is System Global Area (SGA)?
- > Main tasks of SGA
- > Shared Pool
- Database buffer cache
- > Redo Log Buffer

Oracle DBA

Database Instance

A database instance is a set of memory structures and processes that manage database files




What is System Global Area (SGA)

The SGA is a group of shared memory structures that contain data and control information for one database instance.


Main tasks of SGA

- ✓ Maintaining internal data structures that many processes access concurrently
- ✓ Caching data blocks read from disk
- Buffering redo data before writing it to the online redo log files
- ✓ Storing SQL execution plans



Shared Pool

- > The most important component of SGA
- > Cache non user Data like Data dictionary (metadata: data about data ex: DBA_tables)
- > Shared Pool contains sub components like Data dictionary cache, library cache, server result cache and many others
- > Store the cached information about each SQL statement that is executed, like execution plan




Select * from DEPT;

Select * from DEPT;

Prepared By : Khaled AlKhudari

Oracle DBA




Database buffer cache

- responsible for caching database user data.
- > The buffer cache caches frequently accessed database data into memory.


Note: The buffer cache caches blocks of data instead of individual rows (1 block=8 kB by default)

- All users who are concurrently connected to the database share and access a single database buffer cache
- > The buffer cache including the keep pool, recycle pool, and others



Redo Log Buffer

- > circular buffer that hold information about changes made to the database
- designed to store redo entries (small records that reflect any changes made to the database as part of transactions or database structure changes)
 - Note: Redo entries are used for database recovery when and if needed.
- the Redo Log entries in the RedoLog buffer are also written on a periodic basis to a set of files in our Oracle database storage known as Redo logs files



Prepared By : Khaled AlKhudari

Oracle DBA

Thank You

6