

Material Safety Data Sheet

TC-880 PART A

Date of Preparation: 04/24/2003

Revision: 04/24/2003

Section 1 - Chemical Product and Company Identification

Product Name: TC-880 PART A

Product Class: Polyurethane Resin

Chemical Type: Aromatic Diisocyanate, Mixture

Manufacturer: BJB Enterprises, Inc., 14791 Franklin Avenue, Tustin, CA 92780, Phone (714) 734-8450, Fax (714) 734-8929, (M-Th: 8-4:30, F: 7:30-4), Emergency Phone: Chemtrec (800) 424-9300 or (703) 527-3887

Section 2 - Composition / Information on Ingredients

Ingredient Name	CASRN	% wt
1. 4,4' Diphenylmethane Diisocyanate (MDI)	101-68-8	<70
2. Polyurethane prepolymer	NL	<30
3. Proprietary non reactive ingredient	NL	<10

Trace Impurities:

Ingredient	OSHA PEL		ACGIH TLV		NIOSH REL		NIOSH IDLH
	TWA	STEL	TWA	STEL	TWA	STEL	
#1	0.02 ppm	NE	0.005 ppm	NE	NE	NE	NE
#2	NE	NE	NE	NE	NE	NE	NE
#3	NE	NE	NE	NE	NE	NE	NE

Section 3 - Hazards Identification

☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

Appearance: Translucent yellow liquid; Odor: slight, sweet; Avoid skin contact. Avoid breathing vapors. May cause eye and skin irritation; Harmful if inhaled; Use in well ventilated areas; Burning material will generate toxic fumes/gases.

HMIS

H 2

F 1

R 1

PPE†

†Sec. 8

Potential Health Effects

Primary Entry Routes: Eye and skin contact; inhalation of vapors/considered low toxicity to ingestion.

Inhalation/Ingestion: Not likely. Excessive vapors caused by heat or spray mist can cause respiratory irritation/Respiratory sensitization is possible in some individuals.

Eye: May cause irritation, redness and/or tearing.

Skin: May cause irritation and possible allergic sensitivity, redness, or rash with repeated or long-term contact.

Carcinogenicity: The components of this product are not listed by NTP, IARC or regulated as a carcinogen by OSHA.

Medical Conditions Aggravated by Long-Term Exposure: Pre-existing skin or respiratory disorders.

Section 4 - First Aid Measures

Inhalation: Not likely. Remove to fresh air environment.

Ingestion: If swallowed, call a physician immediately. Remove stomach contents by gastric suction or induce vomiting only as directed by medical personnel. Never give anything by mouth to an unconscious person.

Eye Contact: Flush eyes with clean, lukewarm water for 15 minutes. Obtain medical attention if irritation develops.

Skin Contact: Remove contaminated clothing and wash affected areas well with soap and water. Launder contaminated clothing before use.

Note to Physicians: Treat any ill effects symptomatically.

Section 5 - Fire-Fighting Measures

Flash Point/Method: 390°F (199°C) COC


Autoignition Temperature: Not established

Extinguishing Media: Foam, carbon dioxide or water spray. (Dry chemical for class B fires).

Unusual Fire or Explosion Hazards: Burning material will generate toxic fumes/gases containing Hydrochloric Acid, CO₂ and HCN. Closed containers, when exposed to high heat, may generate pressure and cause explosive rupture. Cool containers with water spray.

Fire-Fighting Instructions: Cool fire exposed containers with water spray. Remove containers from fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

NEPA



Fire-Fighting Equipment: Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

Section 6 - Accidental Release Measures

Spill /Leak Procedures: Provide adequate ventilation and wear personal protective equipment. Evacuate personnel as a precaution. Prevent product spill from entering sewers, streams or drinking water supplies. Collect liquid or soak up with inert filler or an absorbent, such as dry earth, sand or oil absorbent (sweeping) compound. Collect material into suitable containers for disposal. Wash area with dilute ammonia solution.

Containment: For large spills, dike ahead of liquid spill for later neutralization, absorption, clean up and disposal.

Section 7 - Handling and Storage

Handling Precautions: Avoid contact with eyes, skin and clothing. Avoid breathing vapor over open container. Avoid open container exposure to damp air.

Handling/Storage Requirements: Store in a cool, dry place, away from excessive heat in original or similar waterproof containers. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

Shelf life: 6 months from date of shipment under manufacturers recommended storage conditions.

Section 8 - Exposure Controls / Personal Protection

Eye Protection Requirements: Safety goggles or glasses are mandatory. Plastic face shields may be worn for complete face protection.

Skin Protection Requirements: Impermeable gloves. Employees should wash their hands and face before eating, drinking or using tobacco products.

Ventilation/Respiratory Requirements: Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

Additional Protective Measures: Safety showers and eye wash stations should be easily accessible to the work area. Work training is important. Follow all label precautions.

Section 9 - Physical and Chemical Properties

Physical State: Liquid

Appearance and Odor: Translucent yellow/slight sweet

Vapor Pressure: <0.0001 mm Hg @ 77°F (25°C)

Vapor Density (Air=1): N/A

Specific Gravity (H₂O=1): 1.18

pH: N/A

Water Solubility: Reacts with water slowly

Boiling Point: @ 5mm Hg at 392°F (200°C),
@ 640°F (340°C) decomposes

Viscosity: 200 cps

% Volatile: None

V.O.C. (ref EPA meth 24): Contains no VOC's

Section 10 - Stability and Reactivity

Stability: Stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: May occur.

Chemical Incompatibilities/Conditions to Avoid: Water, acids, strong bases, alcohols, amines and oxidizers/excessive heating. Exposure to damp air will cause some product deterioration.

Hazardous Decomposition: Thermal oxidative decomposition can produce Hydrochloric Acid, CO and HCN.

Section 11- Toxicological Information

Eye Effects: Irritation

Skin Effects: Irritation

Mutagenicity: None determined

Teratogenicity: None determined

Section 12 - Ecological Information

No Ecological Information Available

Section 13 - Disposal Considerations

Waste Disposal Method: Landfill burial unless prohibited. Dispose of in accordance with federal, state or local environmental control regulations.

Section 14 - Transport Information

DOT
Not Regulated

IATA/ICAO
Not Regulated

IMO/IMDG
Not Regulated

Section 15 - Regulatory Information**U.S. Federal Regulations:****OSHA:**

This document has been prepared in accordance with the MSDS requirements of the OSHA Hazard Communication Standard.

SARA TITLE III:**Sections 311/312 Hazard Classification:**

Immediate Health Hazard; Delayed Health Hazard; Reactive Hazard.

Section 313: This product contains the following substances subject to the reporting requirements of EPCRA, Section 313 and 40 CFR Part 372:

4,4' Diphenylmethane Diisocyanate (MDI) CAS# 101-68-8 70% (max)

TSCA: This product or its components are listed in or exempt from the TSCA inventory requirements.

This product contains the following substances subject to export notification under Section 12 (b) of TSCA:

None

Section 16 - Other Information

Reason for Issue: Revision to Sections 2, 3, 9 & 15

Prepared By: S.F. Marks

Approval Date: 04/24/2003

Supersedes Date: 11/19/1998

Disclaimer: This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon these data.