Material Safety Data Sheet

TC-818 PART A

Date of Preparation: 12/15/2004 Revision: 12/15/2004

Section 1 - Chemical Product and Company Identification

Product Name: TC-818 PART A

Product Class: Polyurethane foam, isocyanate resin

Chemical Type: Aromatic diisocyanate and related oligomers

Manufacturer: BJB Enterprises, Inc., 14791 Franklin Avenue, Tustin, CA 92780, Phone (714) 734-8450, Fax (714) 734-8929,

(M-Th: 8-4:30, F: 7:30-4), Emergency Phone: Chemtrec (800) 424-9300 or (703) 527-3887

Section 2 - Composition / Information on Ingredients

Ingredient Name	CASRN	% wt
1. 4,4 Diphenylmethane diisocyanate (MDI)	101-68-8	30 - 60
2. MDI oligomers	Proprietary	30 - 60

Trace Impurities: N/A

•	OSHA	OSHA PEL		ACGIH TLV		NIOSH REL	
Ingredient	TWA	STEL	TWA	STEL	TWA	STEL	IDLH
#1	0.02 ppm	NE	0.005 ppm	NE	NE	NE	NE
#2	NE	NE	NE	NE	NE	NE	NE

Section 3 - Hazards Identification

Appearance: Clear, yellow liquid; Odor: Slight odor; Avoid skin contact. Avoid breathing vapors. May cause eye and skin irritation. Harmful if inhaled. Use in well-ventilated areas. Burning material will generate trace amounts of toxic fumes/gases.

HMIS H 3 F 1 R 1 PPE[†]

Potential Health Effects

Primary Entry Routes: Eye and skin contact; inhalation of vapors, accidental ingestion.

Inhalation/Ingestion: Breathlessness, chest discomfort, in high concentrations. /Ingestion not likely.

Eve: May cause irritation.

Skin: May cause irritation and possible allergic sensitivity with repeated contact.

Medical Conditions Aggravated by Long-Term Exposure: Prior sensitization to isocyanates or pre-existing respiratory problems.

Section 4 - First Aid Measures

Inhalation: Not likely. Remove to fresh air environment.

Ingestion: If swallowed, call a physician immediately. Remove stomach contents by gastric suction or induce vomiting only as directed by medical personnel. Never give anything by mouth to an unconscious person.

Eye Contact: Flush eyes with clean, lukewarm water for 15 minutes. Obtain medical attention if irritation develops.

Skin Contact: Remove contaminated clothing and wash affected areas well with soap and water. Launder contaminated clothing before use.

Note to Physicians: Treat any ill effects symptomatically.

Section 5 - Fire-Fighting Measures

Flash Point/Method: >230°F (>110°C) closed cup

Extinguishing Media: Carbon dioxide, dry chemical extinguisher or foam.

Unusual Fire or Explosion Hazards: Water contamination and heat may generate pressure in partially sealed containers, resulting in tank or line rupture.

Hazardous Combustion Products: May generate toxic fumes/gases.

Fire-Fighting Instructions: Cool fire exposed containers with water spray. Remove containers from fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Firefighters should wear positive pressure self–contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.



Section 6 - Accidental Release Measures

Spill /Leak Procedures: Provide adequate ventilation and wear personal protective equipment. Evacuate personnel as a precaution. Prevent product spill from entering sewers, streams, or drinking water supplies. Collect liquid or soak up with inert filler or an absorbent, such as dry earth, sand, or oil absorbent (sweeping) compound. Collect material into suitable containers for disposal. Wash area with dilute ammonia solution.

Containment: For large spills, dike ahead of liquid spill for later neutralization, absorption, clean up, and disposal.

Section 7 - Handling and Storage

Handling Precautions: Avoid contact with eyes, skin and clothing. Avoid breathing vapor over open container.

Storage Requirements: Store in a cool, dry place away from excessive heat in original or similar waterproof containers. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

Shelf life: 6 months from date of shipment under manufacturers recommended storage conditions.

Section 8 - Exposure Controls / Personal Protection

Eye Protection Requirements: Safety goggles or glasses are recommended. Plastic face shield should be worn for complete face protection.

Skin Protection Requirements: Impermeable gloves should be worn. Employees should wash their hands and face before eating, drinking, or using tobacco products.

Ventilation/Respiratory Requirements: Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH certified) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

Additional Protective Measures: Safety showers and eye wash stations should be easily accessible to the work area. Training is important. Follow all label precautions.

Section 9 - Physical and Chemical Properties

Physical State: Liquid

Appearance and Odor: Clear, yellow; slight odor

Vapor Pressure: <0.000004 mm Hg at 68°F (20°C)

Specific Gravity (H₂O=1): 1.15

pH: N/A

Water Solubility: Reacts slowly with water **Boiling Point:** Decomposes @ 571°F (300°C)

Revision date: 12/15/2004

Viscosity: 425 cps % Volatile: None

V.O.C. (ref EPA method 24): None

Section 10 - Stability and Reactivity

Stability: Stable at room temperature in closed containers under normal storage and handling conditions.

Hazardous Polymerization: May occur.

Chemical Incompatibilities/Conditions to Avoid: Water, strong acids, inorganic bases, oxidizers, alcohols and amines/Water contamination and heat may generate pressure in partially sealed containers, resulting in tank or line rupture.

Hazardous Decomposition: Thermal oxidative decomposition can produce toxic fumes/gases.

Section 11- Toxicological Information

No Toxicological Information Available

Section 12 - Ecological Information

No Ecological Information Available

Section 13 - Disposal Considerations

Waste Disposal Method: Landfill burial unless prohibited. Dispose of in compliance with federal, state, or local environmental control regulations.

Revision date: 12/15/2004 **TC-818 PART A**

Section 14 - Transport Information

DOT

IATA/ICAO

IMO/IMDG

Not regulated

Not regulated

Not regulated

Section 15 - Regulatory Information

U.S. Federal Regulations:

OSHA:

This document has been prepared in accordance with the MSDS requirements of the OSHA Hazard Communication Standard.

SARA TITLE III:

Sections 311/312 Hazard Classification:

None

Section 313: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

4,4' Diphenylmethane diisocyanate (MDI)

CAS# - 101-68-8

60% (max.)

TSCA: This product or its components are listed in or exempt from the TSCA inventory requirements.

This product contains the following substances subject to export notification under Section 12 (b) of TSCA:

None

Section 16 - Other Information

Reason for Issue: Revised Section 5 & 9

Prepared By: M. Rose **Approval Date:** 12/15/2004 **Supersedes Date:** 09/15/2004

Disclaimer: This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon these data.