Material Safety Data Sheet

WC-765 PART B

Date of Preparation: 08/29/2001 Revision: 08/29/2001

Section 1 - Chemical Product and Company Identification

Product Name: WC-765 PART B

Product Class: Polyol

Chemical Type: Polyether polyol blend

Manufacturer: BJB Enterprises, Inc., 14791 Franklin Avenue, Tustin, CA 92780, Phone (714) 734-8450, Fax (714) 734-8929,

(M-Th: 8-4:30, F: 7:30-4), Emergency Phone: Chemtrec (800) 424-9300 or (703) 527-3887

Section 2 - Composition / Information on Ingredients

Ingredient Name	CASRN	% wt
1. Polyether polyols mixture	Proprietary	<97
2. Aryl mercuric carboxylate	26545-49-3	<0.15 (as Hg)

Trace Impurities: N/A

	OSHA PEL		ACGIH TLV		NIOSH REL		NIOSH
Ingredient	TWA	STEL	TWA	STEL	TWA	STEL	IDLH
#1	NE	NE	NE	NE	NE	NE	NE
#2	0.1 mg/m^3	NE	0.1 mg/m^3	NE	NE	NE	NE

Section 3 - Hazards Identification

፟፟፟፟፟፟፟፟፟፟፟፟፟፟፟፟፟፟፟፟፟፟፟፟ Emergency Overview ፟፟፟፟፟፟፟፟፟፟፟፟፟፟፟፟

Appearance: Clear liquid; Odor: Odorless; Avoid skin contact. Avoid breathing vapors. May cause eye and skin irritation. Harmful if inhaled. Use in well-ventilated areas.

HMIS H 1 F 0 R 0 PPE[†]

Potential Health Effects

Primary Entry Routes: Eye and skin contact; inhalation of vapors, accidental ingestion.

Inhalation/Ingestion: Excessive vapors caused by heat or spray mist can cause respiratory problems/May cause gastric

discomfort.

Eye: May cause irritation. Skin: May cause irritation.

Medical Conditions Aggravated by Long-Term Exposure: None known

Section 4 - First Aid Measures

Inhalation: Not likely. Remove to fresh air environment.

Ingestion: If swallowed, call a physician immediately. Remove stomach contents by gastric suction or induce vomiting only as

directed by medical personnel. Never give anything by mouth to an unconscious person.

Eye Contact: Flush eyes with clean, lukewarm water for 15 minutes. Obtain medical attention if irritation develops. **Skin Contact:** Remove contaminated clothing and wash affected areas well with soap and water. Launder contaminated

clothing before use.

Note to Physicians: Treat any ill effects symptomatically.

Section 5 - Fire-Fighting Measures

Flash Point/Method: >350°F (177°C) SETA

Extinguishing Media: Water spray, foam, or dry chemical extinguisher.

Unusual Fire or Explosion Hazards: None

Fire-Fighting Instructions: Cool fire exposed containers with water spray. Remove containers from fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Firefighters should wear positive pressure self–contained breathing apparatus

(SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.



Revision date: 08/29/2001

Section 6 - Accidental Release Measures

Spill /Leak Procedures: Provide adequate ventilation and wear personal protective equipment. Evacuate personnel as a precaution. Prevent product spill from entering sewers, streams, or drinking water supplies. Collect liquid or soak up with inert filler or an absorbent, such as dry earth, sand, or oil absorbent (sweeping) compound. Collect material into suitable containers for disposal. Wash area with dilute ammonia solution.

Containment: For large spills, dike ahead of liquid spill for later neutralization, absorption, clean up, and disposal.

Section 7 - Handling and Storage

Handling Precautions: Avoid contact with eyes, skin and clothing. Avoid breathing vapor over open container.

Storage Requirements: Store in a cool, dry place away from excessive heat in original or similar waterproof containers. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

Shelf life: 6 months, from date of shipment, under manufacturers recommended storage conditions.

Section 8 - Exposure Controls / Personal Protection

Eye Protection Requirements: Safety goggles or glasses are recommended. Plastic face shield should be worn for complete face protection.

Skin Protection Requirements: Impermeable gloves should be worn. Employees should wash their hands and face before eating, drinking, or using tobacco products.

Ventilation Requirement: Local exhaust or well-ventilated work area must be provided. Mechanical exhaust preferred.

Respiratory Requirement: Avoid breathing vapors. If exposures cannot be kept at a minimum, a respirator may be necessary in addition to ventilation. The use of a positive pressure air supplied respirator is mandatory when airborne isocyanate concentrations are "not known" or exceeds OSHA'S TWA of 0.005 ppm. Air purifying, organic cartridge type respirators are not generally recommended to use when handling this material without implementation of an end of life service program. Observe OSHA regulations for respirator use (29 CFR 1910.134). Employers are responsible for selecting the correct respirator for each situation.

Additional Protective Measures: Safety showers and eye wash stations should be easily accessible to the work area. Training is important. Follow all label precautions.

Section 9 - Physical and Chemical Properties

Physical State: Liquid
Appearance and Odor: Clear; Odorless
Vapor Pressure: Not determined

Specific Gravity (H₂O=1): 1.03

pH: N/A

Water Solubility: Slight Boiling Point: Not determined

Viscosity: 550 cps % Volatile: <0.1

V.O.C. (ref EPA meth 24): 5 gm/liter

Section 10 - Stability and Reactivity

Stability: WC-765 PART B is stable at room temperature in closed containers under normal storage and handling conditions.

Hazardous Polymerization: Will not occur.

Chemical Incompatibilities/Conditions to Avoid: isocyanates, oxidizers, and mineral acids

Hazardous Decomposition: Not established.

Section 11- Toxicological Information

No Toxicological Information Available

Section 12 - Ecological Information

No Ecological Information Available

Section 13 - Disposal Considerations

Waste Disposal Method: Dispose of in compliance with federal, state, or local environmental control regulations.

Revision date: 08/29/2001 WC-765 PART B

Section 14 - Transport Information

DOTNot regulated

IATA/ICAO
Not regulated

IMO/IMDG
Not regulated

Section 15 - Regulatory Information

U.S. Federal Regulations:

OSHA:

This document has been prepared in accordance with the MSDS requirements of the OSHA Hazard Communication Standard.

SARA TITLE III:

Sections 311/312 Hazard Classification: None

Section 313: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

None

TSCA: This product or its components are listed in or exempt from the TSCA inventory requirements.

This product contains the following substances subject to export notification under Section 12 (b) of TSCA:

None

Section 16 - Other Information

Reason for Issue: Revised to ANSI format

Prepared By: S.F. Marks **Approval Date:** 08/29/2001 **Supersedes Date:** 07/25/1997

Disclaimer: This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon these data.