Material Safety Data Sheet

WC-780 PART B-180

Date of Preparation: 08/15/2001 Revision: 08/15/2001

Section 1 - Chemical Product and Company Identification

Product Name: WC-780 PART B-180 **Product Class:** Polyurethane curing agent **Chemical Type:** Polyether polyol mixture

Manufacturer: BJB Enterprises, Inc., 14791 Franklin Avenue, Tustin, CA 92780, Phone (714) 734-8450, Fax (714) 734-8929,

(M-Th: 8-4:30, F: 7:30-4), Emergency Phone: Chemtrec (800) 424-9300 or (703) 527-3887

Section 2 - Composition / Information on Ingredients

Ingredient Name	CASRN	% wt
1. Polyether polyols/proprietary mixture	Proprietary	> 95
2. Organomercury compound, mixture	NL	< 0.02 (as Hg)

Trace Impurities: N/A

•	OSHA I	OSHA PEL		ACGIH TLV		NIOSH REL	
Ingredient	TWA	STEL	TWA	STEL	TWA	STEL	IDLH
#1	NE	NE	NE	NE	NE	NE	NE
#2	0.10 mg/m^3	NE	0.10 mg/m^3	NE	NE	NE	NE
	_						

Section 3 - Hazards Identification

አ፟፟፟፟፟፟፟፟፟፟፟፟፟፟፟ Emergency Overview ፟፟፟፟፟፟፟፟፟፟፟፟፟፟፟፟፟፟፟፟

Appearance: Clear liquid; Odorless; May cause eye and skin irritation. May be toxic by ingestion.

Potential Health Effects

Primary Entry Routes: Eye and skin contact; inhalation of vapors, accidental ingestion.

Inhalation: Not likely. Heated material may cause irritation. **Ingestion:** Not likely. May cause gastric irritation. May be toxic.

Eye: Possible redness and irritation.

Skin: Possible redness or rash upon repeated contact. May cause skin dryness.

Medical Conditions Aggravated by Long-Term Exposure: Pre-existing skin disorders.

Section 4 - First Aid Measures

Inhalation: Remove to fresh air.

Ingestion: If swallowed, call a physician immediately. Remove stomach contents by gastric suction or induce vomiting only as directed by medical personnel. Never give anything by mouth to an unconscious person.

Eye Contact: Flush eyes with clean, lukewarm water for 15 minutes. Obtain medical attention if irritation develops.

Skin Contact: Remove contaminated clothing and wash affected areas well with soap and water. Launder contaminated clothing before use.

Section 5 - Fire-Fighting Measures

Flash Point/Method: 420°F (216°C) COC

Extinguishing Media: Water spray, foam, carbon dioxide or dry chemical.

Unusual Fire or Explosion Hazards: None, but nearby fires may cause pressure build up in containers, which could rupture them. Cool containers with a water spray or stream in fire conditions.

Fire-Fighting Instructions: Cool fire exposed containers with water spray. Remove containers from fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Firefighters must wear positive pressure self-contained breathing apparatus (SCBA) for fighting large fires. Consider the use of unmanned hose holders or monitor nozzles when fighting large fires.

HMIS H 1 F 0 R 0 PPE[†] †Sec. 8



Section 6 - Accidental Release Measures

Spill /Leak Procedures: Confine area of spill with absorbent such as sand or sawdust. Sweep up spilled material into suitable containers for disposal.

Containment: For large spills, dike ahead of liquid spill for later neutralization, absorption, clean up and disposal.

Section 7 - Handling and Storage

Handling Precautions: Keep containers sealed when not in use. Hygroscopic material.

Storage Requirements: Store in a cool, dry place away from excessive heat in original or similar waterproof containers. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials and humidity.

Shelf life: 6 months, from date of shipment, under manufacturers recommended storage conditions.

Section 8 - Exposure Controls / Personal Protection

Eye Protection Requirements: Safety goggles or glasses are recommended. Plastic face shield should be worn for complete face protection.

Skin Protection Requirements: Impermeable gloves should be worn. Employees should wash their hands and face before eating, drinking, or using tobacco products.

Ventilation Requirements: Local exhaust or well-ventilated work area recommended.

Respiratory Requirements: Vapor TLV concentration not to be exceeded in work place. An organic vapor cartridge or fresh air supplied respirator may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

Additional Protective Measures: Safety showers and eye wash stations should be easily accessible to the work area. Working training is important. Follow all label precautions.

Section 9 - Physical and Chemical Properties

Physical State: Liquid

Appearance and Odor: Clear/nearly odorless **Vapor Pressure:** <1 mm Hg at 77°F (25°C)

3.5 mm Hg at 212°F (100°C)

Vapor Density (Air=1): N/A Specific Gravity (H₂O=1): 1.03

pH: N/A

Water Solubility: Slight to negligible

Revision date: 08/15/2001

Boiling Point: not available **Freezing/Melting Point:** N/A

% Volatile: <1%

V.O.C. (ref EPA meth 24): 5 g/l

Section 10 - Stability and Reactivity

Stability: WC-780 PART B-180 is stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization will not occur.

Chemical Incompatibilities/Conditions to Avoid: Acids, strong oxidizers, permanganate and chromate salts. Avoid excessive exposure to damp air.

Section 11- Toxicological Information

No Toxicological Information Available

Section 12 - Ecological Information

No Ecological Information Available

Section 13 - Disposal Considerations

Waste Disposal Method: Dispose of in compliance with federal, state or local environmental control regulations.

Revision date: 08/15/2001 WC-780 PART B-180

Section 14 - Transport Information

 $\overline{\mathbf{DOT}}$

IATA/ICAO
Not regulated

IMO/IMDG
Not regulated

Not regulated Not regulate

Section 15 - Regulatory Information

U.S. Federal Regulations:

OSHA:

This document has been prepared in accordance with the MSDS requirements of the OSHA Hazard Communication Standard.

SARA TITLE III:

Sections 311/312 Hazard Classification:

None

Section 313: This product contains the following substances subject to the reporting requirements of EPCRA, Section 313 and 40 CFR Part 372:

None

TSCA: This product or its components are listed in or exempt from the TSCA inventory requirements.

This product contains the following substances subject to export notification under Section 12 (b) of TSCA:

None

Section 16 - Other Information

Reason for Issue: New Issue **Prepared By:** S.F. Marks **Approval Date:** 08/16/2001 **Supersedes Date:** 08/11/1999

Disclaimer: This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon these data.