

Mobile Patient Monitoring System


Andrew Carp, Cody Chen, Inbar Fried,
Michael Nuzzolo, and Emily Quigley

Product Overview


We have created a supplementary patient monitoring system that allows remote access to patients' most vital data and direct communication with patients' caregivers. This fosters increased efficiency and therefore better patient care overall. Furthermore, our product is mobile, allowing patients to comfortably continue to be monitored while out of their rooms.

This product will be available for in-hospital use by doctors and nurses by July, 2015.


Customer Sequence




Hospital Buyer/Administrator



Doctor



Nurse/Caregiver/Technician



Patient




Increased
mobility

Awareness of
constant care

Visually pleasing
display/familiar technology

Minimized stress
levels

Better patient
perception of care



Purpose of Design: Hardware

- Patient mobility and comfort
- Awareness of continuous monitoring
- Compatible with other devices



change amplitude (size) of ECG wave



enter profile menu, or
revert to default profile



change Screen, or
revert to default screen



- start/stop manual NBP measurement
- start auto series
- stop current automatic measurement
within series



show BIS Sensor



previous Screen



start NBP measurement and
measurement series



freeze waves



quick admit a patient



start veni puncture (inflate cuff to
subdiastolic pressure)



set alarm limits



enter patient identification menu to
admit/discharge/transfer



access patient reports



change alarm volume



end case to discharge a patient



start a delayed recording



change QRS volume



view information for patients in other
beds



access **Vital Signs** recording
function



enter standby mode - suspends patient
monitoring. All waves and numerics
disappear from the display. All settings
and patient data information are
retained.



change screen brightness (not for
independent displays)



set wide automatic alarm limits



review beat labels (annotate
arrhythmia wave)



re-learn arrhythmia



access wedge procedure window



access the Loop:

| | | |
|---|------------------------------|---|
| | 1 | 2 |
| 3 | Main Screen - close all open | |
| 4 | Back - go back one step to | |
| 5 | SpeedPoint knob - rotate | |
| 6 | Function keys on remote | |
| 7 | On/standby key | |



display external device information



access remote applications (if Application
Server is connected)



review vital signs trend



review graph tre



access ProtocolWatch



access the EEG montage



access event surveillance



access calculation



switch CO₂ pump off



access timers



access the calculator



access the Drug



enter data manually



new lead setup



gas analyzer - exit standby mode



suppress zero for all gas measurements




open the histogram window



start/stop car seat assessment record




open unit conversion window



ly available
nnected)

ECG



BP

120 mmHg
78

SPO2



93%

PULSE

21 bpm

TEMP

112.0° °C | °F

ALARM: TEMP

A. Renel Room #133A

SETTINGS

ACCOUNTS

PATIENTS

MESSAGES

RECORDS




Purpose of Design: UI

- Clean, simple, and familiar
- Emphasizes significant information
- Customizable
- Secure


Purpose of Design: Alarms

- Audible and visual
- Alarm data archived for doctor needs
- Lessen alarm fatigue



Purpose of Design: Messaging

- Alert doctor when necessary
- Information finds the doctor



Ideal/Future Product

- Compact hardware
- Increase measurement accuracy
- Screen share
- Video calls
- Security
- Market testing

Lessons Learned

Develop a product guided by existing customer problems and direct solutions to them, rather than building features and technology and trying to fit it to a problem afterwards

Q&A