



Hartwig Thomas, 4. December 2013

Document version 1.01

SIARD Suite

Data Type Mapping for MySQL

Published by:

Swiss Federal Archives
Archivstrasse 24
3003 Bern
Switzerland

1 Introduction

The Swiss Federal Archives developed the database archival called SIARD (Software Independent Archiving of Relational Databases) within the framework of the ARELDA (ARchivierung ELEktronischer DATen) project. The SIARD format is used for long-term archiving of relational database content.

On behalf of the Swiss Federal Archives, Enter AG implemented the software SIARD Suite which supports converting database content from live proprietary database systems to the normalized SIARD format as well as uploading database content in SIARD format to such a live database system.

Unfortunately most real database systems do not support the SQL:1999 standard fully, on which the SIARD format is based. Therefore SIARD Suite needs to normalize/denormalize the data types during the conversion process.

This document specifies, how the MySQL data are converted to the SIARD format and how SIARD data are converted to MySQL on upload.

The conversions are *idempotent*. I.e. after the initial download any number of up- and download can be executed without changing the data types or values.

2 Mapping of MySQL Data Types

2.1 MySQL => SIARD

See also <http://dev.mysql.com/doc/refman/5.0/en/data-types.html> and <http://dev.mysql.com/doc/refman/5.5/en/data-types.html>

<i>MySQL</i>	<i>JDBC (java.sql.Types)</i>	<i>SQL:1999 (SIARD)</i>	<i>XML</i>
CHAR	CHAR(1)	CHARACTER(1)	xs:string
CHAR(n)	CHAR(n)	CHARACTER(n)	xs:string
VARCHAR(n)	VARCHAR(n)	CHARACTER VARYING(n)	xs:string
TINYTEXT (up to 255)	VARCHAR(255)	CHARACTER VARYING(255)	xs:string
TEXT (up to 65'535)	LONGVARCHAR (65'535)	CHARACTER LARGE OBJECT	clobType
MEDIUMTEXT (up to 16'777'215)	LONGVARCHAR (16'777'215)	CHARACTER LARGE OBJECT	clobType
LONGTEXT (up to 2'147'483'647)	LONGVARCHAR (2'147'483'647)	CHARACTER LARGE OBJECT	clobType
TINYINT (1 Byte)	TINYINT(3)	SMALLINT	xs:integer
SMALLINT (2 Bytes)	SMALLINT(5)	SMALLINT	xs:integer
MEDIUMINT (3 Bytes)	INTEGER(7)	INTEGER	xs:integer
INT (4 Bytes)	INTEGER(10)	INTEGER	xs:integer
BIGINT (8 Bytes)	BIGINT(19)	NUMERIC(19)	xs:decimal
DECIMAL	DECIMAL(10)	DECIMAL(10)	xs:decimal
DECIMAL(n)	DECIMAL(n)	DECIMAL(n)	xs:decimal

SIARD Suite

<i>MySQL</i>	<i>JDBC (java.sql.Types)</i>	<i>SQL:1999 (SIARD)</i>	<i>XML</i>
DECIMAL(p,q)	DECIMAL(p,q)	DECIMAL(p,q)	xs:decimal
NUMERIC	DECIMAL(10)	DECIMAL(10)	xs:decimal
NUMERIC(n)	DECIMAL(n)	DECIMAL(n)	xs:decimal
NUMERIC(p,q)	DECIMAL(p,q)	DECIMAL(p,q)	xs:decimal
FLOAT	REAL(12)	REAL	xs:float
FLOAT(p)	REAL(12)	REAL	xs:float
FLOAT(p,q)	REAL(p,q)	FLOAT(p)	xs:float
DOUBLE	DOUBLE(22)	DOUBLE PRECISION	xs:float
DOUBLE(p,q)	DOUBLE(p,q)	DOUBLE PRECISION	xs:float
BIT	BIT(1)	BOOLEAN	xs:boolean
BIT(n)	BIT(n)	BIT(n)	xs:hexBinary
BINARY(n)	BINARY(n)	BIT(8*n)	xs:hexBinary
VARBINARY(n)	VARBINARY(n)	BIT VARYING(8*n)	xs:hexBinary
TINYBLOB (up to 255)	BINARY(255)	BIT VARYING(2040)	xs:hexBinary
BLOB (up to 65'535)	LONGVARBINARY(65'535)	BINARY LARGE OBJECT	blobType
MEDIUMBLOB (up to 16'777'215)	LONGVARBINARY(16'777'215)	BINARY LARGE OBJECT	blobType
LOB (up to 2'147'483'647)	LONGVARBINARY(2'147'483'647)	BINARY LARGE OBJECT	blobType
DATETIME	TIMESTAMP(19)	TIMESTAMP	xs:dateTime
TIMESTAMP	TIMESTAMP(19)	TIMESTAMP(19)	xs:dateTime
DATE	DATE(10)	DATE	xs:date
TIME	TIME(8)	TIME	xs:time

SIARD Suite

<i>MySQL</i>	<i>JDBC</i> <i>(java.sql.Types)</i>	<i>SQL:1999 (SIARD)</i>	<i>XML</i>
YEAR	DATE(o)	DATE	xs:date

2.2 SIARD => MySQL

<i>XML</i>	<i>SQL:1999 (SIARD)</i>	<i>MySQL</i>
xs:decimal	NUMERIC	NUMERIC(10)
xs:decimal	NUMERIC(n)	NUMERIC(n)
xs:decimal	NUMERIC(p,q)	NUMERIC(p,q)
xs:decimal	DECIMAL	DECIMAL(10)
xs:decimal	DECIMAL(n)	DECIMAL(n)
xs:decimal	DECIMAL(p,q)	DECIMAL (p,q)
xs:hexBinary	BIT(n)	if (n < 8*68) BIT(n) else if (n <= 8*255) BINARY((n+7)/8) else if (n <= 8*65535) BLOB else if (n <= 8*16777215) MEDIUMBLOB else LONGBLOB
xs:hexBinary	BINARY LARGE OBJECT	if (n < 256) TINYBLOB (n) else if (n < 65536) BLOB else if (n < 16777216) MEDIUMBLOB else LONGBLOB
xs:boolean	BOOLEAN	BIT(1)
xs:string	CHARACTER	CHAR
xs:string	CHARACTER(n)	if (n < 256) CHAR(n) else if (n < 65536) TEXT else if (n < 16777216) MEDIUMTEXT else LONGTEXT
xs:string	NATIONAL CHARACTER	CHAR

SIARD Suite

<i>XML</i>	<i>SQL:1999 (SIARD)</i>	<i>MySQL</i>
xs:string	NATIONAL CHARACTER(n)	if (n < 256) CHAR(n) else if (n < 65536) TEXT else if (n < 16777216) MEDIUMTEXT else LONGTEXT
xs:string	CHARACTER LARGE OBJECT	if (n < 256) TINYTEXT (n) else if (n < 65536) TEXT else if (n < 16777216) MEDIUMTEXT else LONGTEXT
xs:string	NATIONAL CHARACTER LARGE OBJECT	if (n < 256) TINYTEXT (n) else if (n < 65536) TEXT else if (n < 16777216) MEDIUMTEXT else LONGTEXT
xs:date	DATE	DATE
xs:time	TIME(p)	TIME
xs:dateTime	TIMESTAMP(p)	DATETIME
xs:decimal	DECIMAL(n)	DECIMAL(n)
xs:decimal	DECIMAL(p,q)	DECIMAL (p,q)
xs:float	REAL	FLOAT(12)
xs:float	DOUBLE PRECISION	DOUBLE
xs:float	FLOAT(p,q)	FLOAT(p,q)
xs:integer	INTEGER	INTEGER
xs:integer	SMALLINT	SMALLINT
xs:hexBinary	BIT VARYING(n)	if (n < 65536) VARBINARY(n) else if (n < 16777216) MEDIUMBLOB else LONGBLOB
xs:string	CHARACTER VARYING(n)	if (n < 65536) VARCHAR (n) else if (n < 16777216) MEDIUMTEXT else LONGTEXT

SIARD Suite

<i>XML</i>	<i>SQL:1999 (SIARD)</i>	<i>MySQL</i>
xs:string	NATIONAL CHARACTER VARYING(n)	VARCHAR(n)

If a string is longer than 4000 characters then „clobType“ and „xs:string“ are replaced by an external reference to a text file.

If a binary array is longer than 2000 bytes then „blobType“ and „xs:hexBinary“ are replaced by an external reference to a binary file.

Characters that cannot be represented in UNICODE (Codes 0-8, 14-31, 127-159) as well as the escape character '\' and multiple space characters are escaped as \u00<xx> in XML. Less-than and ampersand characters are represented as entity references in XML.