

Documentation of MSAP3-31 for PLATO

Consistency checks

Earl Patrick Bellinger

March 7, 2023

Table 1: Author information

Prepared by	Date
Earl P. Bellinger	March 4, 2023
Checked by	
Approved by	
Authorized by	

Table 2: Version history

Issue	Date	Nº change	description	Page(s)	Paragraph(s)
1.0	March 4, 2023		Initial release	All	All

Contents

1	Introduction	3
1.1	Scope of the document	3
1.2	Nomenclature	3
1.3	Referenced documents	3
1.4	Abbreviations	3
2	General overview	4
2.1	Name of the algorithm and status	4
2.2	Synopsis	4
2.3	Model	4
3	Lists of inputs and outputs	5
3.1	Complete list of inputs	5
3.2	Complete list of outputs	5
4	Processing description	6
4.1	Type of delivery	6
4.2	Algorithm maturity	6
4.3	Algorithm source	6
4.4	Pseudo-code	6
4.5	Flow diagram	6
5	Test case(s)	7
5.1	Implementation test case(s)	7
5.2	Scientific test case(s)	7
	Bibliography	8

1 Introduction

1.1 Scope of the document

This document aims to provide a description of the consistency checking algorithm for the selection and validation module of the MSAP5. It provides technical details (inputs, outputs, data types) as well as the functional description (implementation). The justification for the choice of this specific algorithm and a description of its scientific performances is provided in [please provide the reference of the justification document]. Moreover, the exact position of this algorithm within the data processing pipeline is described in [RD1].

TODO – Andrea, can you help here?

1.2 Nomenclature

See 3 and 4.

Table 3: Nomenclature

Term	Description
M	mass of the star in units of the solar mass M_{\odot}
R	radius of the star in units of the solar radius R_{\odot}
A	age of the star in units of Gyr

Table 4: Standard data types

Type	Size	Values
array	arbitrary	floats

1.3 Referenced documents

The following documents are referenced:

TODO – Andrea, can you help here?

1.4 Abbreviations

HSD Tukey’s Honestly Significantly Different statistical test

2 General overview

2.1 Name of the algorithm and status

The algorithm is MSAP5-31, *Consistency checks*. The baseline algorithm has been implemented and the prototype is complete with only minor revisions expected.

2.2 Synopsis

The objective of MSAP5-31 is to determine whether different measurements of mass (M), radius (R), and age (A) from different modules of the PLATO pipeline are consistent with one another on a star-by-star basis.

We test for consistency using the Honestly Significantly Different (HSD) algorithm proposed by [Tukey \[1949\]](#). The documentation from `scipy` [[Virtanen et al., 2020](#)] summarizes the HSD algorithm as:

“a pairwise comparison of means for a set of samples... The null hypothesis is that the distributions underlying the samples all have the same mean. The test statistic, which is computed for every possible pairing of samples, is simply the difference between the sample means. For each pair, the p-value is the probability under the null hypothesis of observing such an extreme value of the statistic, considering that many pairwise comparisons are being performed... In case of unequal sample sizes, the test uses the Tukey-Kramer method [[Kramer, 1956](#)].”

2.3 Model

The algorithm runs on M, R, and A independently. For each of these, the algorithm accepts a variable number of inputs corresponding to the measurements of that quantity from different methods used in the PLATO pipeline. Each input is an array containing samples from the posterior distribution according to that method. The algorithm then computes the HSD on the inputs, and reports whether any of the measurements are inconsistent at a significance level of 0.05. The implementation of HSD used here is from `scipy 1.10.1`.

3 Lists of inputs and outputs

3.1 Complete list of inputs

The inputs are tabulated in Table 5.

Table 5: Input parameters

Name	Source	Status	Data type	Dimension	Unit
IDP_MASS_SEISMIC	IDP_124	optional	array	arbitrary	M_{\odot}
IDP_MASS_GRANULATION	IDP_125	optional	array	arbitrary	M_{\odot}
IDP_MASS_GRANULATION_CGBM	IDP_125	optional	array	arbitrary	M_{\odot}
IDP_MASS_RHO_TRANSIT_CGBM	IDP_125	optional	array	arbitrary	M_{\odot}
IDP_RADIUS_SEISMIC	IDP_124	optional	array	arbitrary	R_{\odot}
IDP_RADIUS_GRANULATION_CGBM	IDP_125	optional	array	arbitrary	R_{\odot}
IDP_RADIUS_RHO_TRANSIT	IDP_125	optional	array	arbitrary	R_{\odot}
IDP_RADIUS_RHO_TRANSIT_CGBM	IDP_125	optional	array	arbitrary	R_{\odot}
IDP_AGE_SEISMIC	IDP_124	optional	array	arbitrary	Gyr
IDP_AGE_GYRO	IDP_125	optional	array	arbitrary	Gyr
IDP_AGE_ACTIVITY	IDP_125	optional	array	arbitrary	Gyr
IDP_AGE_GRANULATION_CGBM	IDP_125	optional	array	arbitrary	Gyr
IDP_AGE_RHO_TRANSIT_CGBM	IDP_125	optional	array	arbitrary	Gyr

3.2 Complete list of outputs

Table 6: Output parameters

Name	Status	Data type	Dimension	Unit
M consistency flag	mandatory	boolean	bit	true/false
R consistency flag	mandatory	boolean	bit	true/false
A consistency flag	mandatory	boolean	bit	true/false

4 Processing description

4.1 Type of delivery

Prototype

4.2 Algorithm maturity

Algorithm concept defined, but interfaces (inputs/outputs) unstable. Has been tested with randomly-generated pseudo inputs, but needs to be tested with actual inputs from all of the PLATO modules. The complete list of seismic inputs needs to be added.

4.3 Algorithm source

The implemented algorithm and test cases are shipped directly to WP12 office alongside this document as a compressed archive.

4.4 Pseudo-code

N/A

4.5 Flow diagram

N/A

5 Test case(s)

5.1 Implementation test case(s)

We test four cases using simulated data. The default inputs we adopt are 100 random samples from a truncated normal distribution for each measurement method. We use default mean values corresponding to those of the present Sun: $1 M_{\odot}$, $1 R_{\odot}$, 4.57 Gyr. We adopt default standard deviations of $0.04 M_{\odot}$, $0.01 R_{\odot}$, and 0.5 Gyr. We truncate at $[0, 3] M_{\odot}$, $[0, 3] R_{\odot}$, and $[0, 15] \text{ Gyr}$. These tests are run in `MSAP5-31-consistency.ipynb`.

Case 1

- All consistent measurements.
- Inputs: Defaults
- Outputs: [True, True, True]

Case 2

- One inconsistent mass measurement.
- Inputs: Defaults, except 1 is added to all the samples from the first mass method
- Outputs: [False, True, True]

Case 3

- Two inconsistent radius measurements.
- Inputs: Defaults, except 0.5 is added to all the samples from the first radius method, and 1 is added to all the samples from the second radius method
- Outputs: [True, False, True]

Case 4

- Three inconsistent age measurements.
- Inputs: Defaults, except 2, 4, 6 are added to the first, second, third age methods
- Outputs: [True, True, False]

5.2 Scientific test case(s)

Simulated data would be highly valuable in testing the algorithm.

Bibliography

- John W. Tukey. Comparing individual means in the analysis of variance. *Biometrics*, 5(2):99–114, 1949. ISSN 0006341X, 15410420. URL <http://www.jstor.org/stable/3001913>.
- Pauli Virtanen, Ralf Gommers, Travis E. Oliphant, Matt Haberland, Tyler Reddy, David Cournapeau, Evgeni Burovski, Pearu Peterson, Warren Weckesser, Jonathan Bright, Stéfan J. van der Walt, Matthew Brett, Joshua Wilson, K. Jarrod Millman, Nikolay Mayorov, Andrew R. J. Nelson, Eric Jones, Robert Kern, Eric Larson, C J Carey, İlhan Polat, Yu Feng, Eric W. Moore, Jake VanderPlas, Denis Laxalde, Josef Perktold, Robert Cimrman, Ian Henriksen, E. A. Quintero, Charles R. Harris, Anne M. Archibald, Antônio H. Ribeiro, Fabian Pedregosa, Paul van Mulbregt, and SciPy 1.0 Contributors. SciPy 1.0: Fundamental Algorithms for Scientific Computing in Python. *Nature Methods*, 17:261–272, 2020. doi: 10.1038/s41592-019-0686-2.
- Clyde Young Kramer. Extension of multiple range tests to group means with unequal numbers of replications. *Biometrics*, 12(3):307–310, 1956. ISSN 0006341X, 15410420. URL <http://www.jstor.org/stable/3001469>.