

### Loading a Package

```
library(PACKAGE NAME)
```

### Reading in Data

```
NAME OF DATASET <- read_csv("PATH & NAME OF DATASET.csv")
```

**Note:** The name of the dataset will change, but it will always need to have the .csv at the end of its name!

**Note:** Do not put spaces in the name you give the data set.

### Preview a Dataset

```
glimpse(NAME OF DATASET)
```

```
head(NAME OF DATASET) – shows first 6 rows
```

```
names(NAME OF DATASET) – outputs the names of the columns/variables
```

### Visualizing a One Categorical Variable Bar Plot

```
ggplot(data = NAME OF DATASET,  
       mapping = aes(x = "Observed Results"  
                     fill = NAME OF VARIABLE  
                     )  
       ) +  
geom_bar(stat = "count"  
         position = "stack") +  
labs(y = "TITLE FOR THE Y-AXIS")
```

**Note:** If you want the y-axis to display proportions instead of counts, you need to change position to "fill".

### Creating a Summary Table of Observations of One Categorical Variable

```
NAME OF DATASET |>  
count(NAME OF VARIABLE)
```

### Conducting an Exact Binomial Hypothesis Test for One Proportion

```
binom.test(x = NUMBER OF SUCCESSES, n = SAMPLE SIZE, p = NULL VALUE, alternative = "DIRECTION")
```

**Note:** The alternative direction can be "greater", "less", or "two.sided"

### Performing a Chi-Squared Goodness-of-Fit Test (One Categorical Variable)

```
chisq_test(x = NAME OF DATASET,  
  response = NAME OF VARIABLE,  
  p = c(EXPECTED PROP 1, EXPECTED PROP 2,..., EXPECTED PROP LAST)  
)
```

\*Make sure expected proportions are in alphabetical order!

\*Make sure to check conditions first!

### Plotting a Two Categorical Variable Bar Plot

```
ggplot(data = NAME OF DATASET,  
  mapping = aes(x = EXPLANATORY VARIABLE,  
    fill = RESPONSE VARIABLE)  
  ) +  
  geom_bar(stat = "count",  
    position = "fill") +  
  labs(title = "TITLE FOR GRAPH",  
    x = "TITLE FOR THE X-AXIS",  
    y = "TITLE FOR THE Y-AXIS")
```

**Note:** If you want a side-by-side bar plot you need to change **position** to **"dodge"**. If you want a stacked bar plot, you need change **position** to **"stack"**.

### Creating a Contingency Table of Observed Counts from Two Categorical Variables

```
NAME OF DATASET |>  
  tabyl(RESPONSE VARIABLE, EXPLANATORY VARIABLE) |>  
  adorn_totals(where = c("row", "col"))
```

**Note:** Requires the janitor package to be loaded – library(janitor)

### Creating a Contingency Table of Observed Proportions from Two Categorical Variables

```
NAME OF DATASET |>  
  tabyl(RESPONSE VARIABLE, EXPLANATORY VARIABLE) |>  
  adorn_totals(where = c("row", "col")) |>  
  adorn_percentages(denominator = "col")
```

**Note:** Since your explanatory variable (groups) should be in your rows from above, we want to calculate our proportions in respect to the group totals.

### Performing a Chi-Square Test (Two Categorical Variables)

```
chisq_test(x = NAME OF DATASET,  
  response = RESPONSE VARIABLE,  
  explanatory = EXPLANATORY VARIABLE,  
  correct = FALSE,  
  simulate.p.value = FALSE  
)
```

\*IMPORTANT!!! Make sure to check conditions first! If conditions are not met, must include the `simulate.p.value = TRUE`.

### Calculating Summary Statistics for One Numeric Variable

```
favstats(~ NAME OF VARIABLE, data = NAME OF DATASET)
```

**Note:** The ~ (top left keyboard) **must** be included *before* the variable's name!

### Histogram for One Numeric Variable

```
ggplot(data = NAME OF DATASET,  
  mapping = aes(x = NAME OF VARIABLE)) +  
  geom_histogram(binwidth = WIDTH OF BINS, color = "white") +  
  labs(title = "TITLE FOR GRAPH",  
    x = "TITLE FOR THE X-AXIS",  
    y = "TITLE FOR THE Y-AXIS")
```

**Note:** A histogram **must** have a numeric variable on the x-axis! If your variable has a space in it, you will need to use tick marks.

### Dotplot for One Numeric Variable

```
ggplot(data = NAME OF DATASET,  
  mapping = aes(x = NAME OF VARIABLE)) +  
  geom_dotplot() +  
  labs(title = "TITLE FOR GRAPH",  
    x = "TITLE FOR THE X-AXIS",  
    y = "TITLE FOR THE Y-AXIS")
```

**Note:** A dotplot **must** have the variable on the x-axis!

### Boxplot for One Numeric Variable

```
ggplot(data = NAME OF DATASET,  
  mapping = aes(x = NAME OF VARIABLE)) +  
  geom_boxplot() +  
  labs(title = "TITLE FOR GRAPH",  
    x = "TITLE FOR THE X-AXIS",  
    y = "")
```

**Note:** This boxplot is horizontal. If you want for your boxplot to be vertical, in the mapping aes(), you use **y** = instead of **x** = . Keep in mind you will need to change the location of you axis label, too!

### Performing a t-test for One Mean (and Confidence Interval)

```
t_test(x = NAME OF DATASET,  
  response = NAME OF VARIABLE,  
  mu = VALUE FROM NULL HYPOTHESIS FOR MU,  
  alternative = "two-sided",  
  conf_level = 0.95)
```

**Note:** If you want a 90% confidence interval, you change **conf\_level** to 0.90. If you want a 99% confidence interval, you change **conf\_level** to 0.99

**Note:** If you are doing a one-sided hypothesis test, you change **alternative** to either "greater" or "less"

### Calculating Summary Statistics for One Numerical Variable and One Categorical Variable

```
favstats(NAME OF NUMERICAL VARIABLE ~ NAME OF CATEGORICAL VARIABLE,  
  data = NAME OF DATASET)
```

**Note:** The ~ **must** be included! This is from the mosaic plot.

### Faceted Histograms

```
ggplot(data = NAME OF DATASET,  
  mapping = aes(x = NAME OF NUMERICAL VARIABLE)) +  
  geom_histogram(binwidth = WIDTH OF BINS, color = "white") +  
  facet_wrap(~NAME OF CATEGORICAL VARIABLE) +  
  labs(title = "TITLE FOR GRAPH",  
    x = "TITLE FOR THE X-AXIS",  
    y = "TITLE FOR THE Y-AXIS")
```

**Note:** A histogram **must** have the variable on the x-axis!

### Side-by-Side Boxplots

```
ggplot(data = NAME OF DATASET,  
  mapping = aes(x = NAME OF NUMERICAL VARIABLE,  
    y = NAME OF CATEGORICAL VARIABLE)  
  ) +  
geom_boxplot()+  
labs(title = "TITLE FOR GRAPH",  
  x = "TITLE FOR THE X-AXIS",  
  y = "TITLE FOR THE Y-AXIS")
```

**Note:** For vertically stacked boxplots, the categorical variable should be on the y-axis. For horizontally stacked boxplots, the categorical variable should be on the x-axis.

### Performing a Two-Sample Independent t-test (Difference in Means)

```
t_test(x = NAME OF DATASET,  
  response = NAME OF NUMERICAL VARIABLE,  
  explanatory = NAME OF CATEGORICAL VARIABLE,  
  mu = 0,  
  conf_int = TRUE,  
  conf_level = 0.95,  
  alternative = "two-sided")
```

**Note:** If you want a 90% or 99% confidence interval, you change `conf_level` to 0.90 or 0.99

**Note:** If you are doing a one-sided hypothesis test, you change `alternative` to either "greater" or "less"

### Performing an ANOVA (F-test)

```
model <- aov(NAME OF NUMERICAL VARIABLE ~ NAME OF CATEGORICAL VARIABLE,  
  data = NAME OF DATA SET)
```

```
model |>  
  tidy()
```

**Note:** The ~ is necessary! It has to be there!

**Note:** `tidy()` is from the broom package – `library(broom)`

### Performing an ANOVA (Pairwise Comparisons)

```
library(emmeans)
```

```
emmeans(NAME_OF_MODEL, specs = ~ NAME OF CATEGORICAL VARIABLE) |>  
pairs(adjust = "MULTIPLICITY ADJUSTMENT METHOD")
```

**Note:** The multiplicity adjustment method can be *tukey*, *bonf*, *none*, *sidak*, to name a few.

### Scatterplot between two numeric variables

```
ggplot(data = NAME OF DATASET,  
       mapping = aes(x = NAME OF EXPLANATORY-VARIABLE,  
                     y = NAME OF RESPONSE-VARIABLE)  
       ) +  
geom_point() +  
labs(title = "TITLE FOR GRAPH",  
     x = "TITLE FOR THE X-AXIS",  
     y = "TITLE FOR THE Y-AXIS")
```

### Scatterplot with Regression Line

```
ggplot(data = NAME OF DATASET,  
       mapping = aes(x = NAME OF EXPLANATORY-VARIABLE,  
                     y = NAME OF RESPONSE-VARIABLE)  
       ) +  
geom_point() +  
geom_smooth(method = "lm", se = F) +  
labs(title = "TITLE FOR GRAPH",  
     x = "TITLE FOR THE X-AXIS",  
     y = "TITLE FOR THE Y-AXIS")
```

**Note:** The line is added to the above scatterplot by adding in the *geom\_smooth()* code line.

**Note:** Just because you have added a line to your scatterplot doesn't mean

### Fitting a Linear Regression Model

```
model <- lm(NAME OF RESPONSE-VARIABLE ~ NAME OF EXPLANATORY-VARIABLE,  
            data = NAME OF DATASET)
```

```
model |>
  tidy(conf.int = TRUE,
        conf.level = 0.95)
```

**Note:** The ~ is necessary! It has to be there!

**Note:** If you want a 90% confidence interval, you change `conf.level` to 0.90

**Note:** *tidy()* is from the broom package

### Checking Assumptions for Linear Regression

```
library(easystats)
check_model(model)
```

**Note:** *some of these are checked with the scatterplot, histograms, and critical thinking instead!*

**Note:** *model is the name of the model from fitting the linear regression model.*