



MAXTENA, INC.
ANTENNA INNOVATIONS COMPANY
1715 PRATT DR., SUITE 2800
BLACKSBURG, VA 24060
1-877-MAXTENA (629-8362)
INFO@MAXTENA.COM

MPA1575D184 Compact Microstip Patch Antenna GPS L1 Band



PRODUCT DESCRIPTION

MPA1575D184 is a ceramic microstrip patch antenna with 77% efficiency and antenna peak realized gain of 5.7 dBi. MPA1575D184 has an adhesive tape on the back for easy installation on different surfaces.

SPECIFICATIONS

	Min	Typical	Max	Unit
Frequency	1570.42	1575.42	1580.42	MHz
Polarization		Right-Hand		RHCP
Efficiency (with RadioMax™)		N/A		% (total spherical)
Efficiency		77		% (total spherical)
Gain (with RadioMax™)		N/A		dBi
Realized Gain		6.1		dBi
Beamwidth (3dB) ¹		100		Degrees (both axis)
Bandwidth (-1dB)		23		MHz
Cross Pole Rejection	12			dB
Axial Ratio			3	dB
Front to Back Ratio		25		dB
VSWR		1.3:1		
Impedance (differential)		50		Ohms
Overall Dimensions		18 x 18 x 4		mm
Operating Temperature	-40	20	+85	°C

¹-1dbic realized gain bandwidth

