



中科院计算所
INSTITUTE OF COMPUTING TECHNOLOGY

Aligning Domain-specific Distribution and Classifier for Cross-domain Classification from Multiple Sources



Yongchun Zhu^{1,2}, Fuzhen Zhuang^{1,2}, Deqing Wang³

1.Key Lab of Intelligent Information Processing of Chinese Academy of Sciences (CAS), Institute of Computing Technology, CAS, Beijing 100190, China

2.University of Chinese Academy of Sciences, Beijing 100049, China

3.School of Computer Science, Beihang University, Beijing, China

Single-source domain adaptation




target



source1

Multi-source domain adaptation



source2




source3

- In Single-source Unsupervised Domain Adaptation (SUDA), the distribution of source and target domains cannot be matched very well.
- In Multi-source Unsupervised Domain Adaptation (MUDA), due to the shift between multiple source domains, it is much harder to match distributions of all source domains and target domains.



Two-stage alignment Framework(MFSAN)



Two-stage alignment Framework:

- Common feature extractor
- Domain-specific feature extractor
- Domain-specific classifier

cls loss

$$\mathcal{L}_{cls} = \sum_{j=1}^N \mathbf{E}_{x \sim X_{sj}} J(C_j(H_j(F(\mathbf{x}_i^{sj}))), \mathbf{y}_i^{sj})$$

mmd loss

$$D_{\mathcal{H}}(p, q) \triangleq \|\mathbf{E}_p[\phi(\mathbf{x}^s)] - \mathbf{E}_q[\phi(\mathbf{x}^t)]\|_{\mathcal{H}}^2$$

disc loss

$$\mathcal{L}_{disc} = \frac{2}{N \times (N-1)} \sum_{j=1}^{N-1} \sum_{i=j+1}^N \mathbf{E}_{x \sim X_t} [|C_i(H_i(F(x_k))) - C_j(H_j(F(x_k)))|],$$