In [132…
```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
import sklearn

print("GCI Data Science Environment Ready!")
print("NumPy:", np.__version__)
print("Pandas:", pd.__version__)
print("Scikit-learn:", sklearn.__version__)
```

```
GCI Data Science Environment Ready!
NumPy: 2.5.4
Pandas: 3.1.1
Scikit-learn: 1.9.1
```

In [133…
```
client = pd.read_csv("../data/Client.csv")
record = pd.read_csv("../data/Record.csv")

print("Datasets loaded successfully!")
```

```
Datasets loaded successfully!
```

In [134…
```
print("Client Dataset:", client.shape)
print("Record Dataset:", record.shape)
```

```
Client Dataset: (100000, 50)
Record Dataset: (100000, 51)
```

In [135…
```
display(client.head())
```

	uniqsubs	actvsubs	new_cell	crclscod	asl_flag	totcalls	totmou	totrev	adjrev	
0	2	1	U	A	N	1652	4228.00000	1504.62	1453.44	
1	1	1	N	EA	N	14654	26400.00000	2851.68	2833.88	2
2	1	1	Y	C	N	7903	24385.05333	2155.91	1934.47	2
3	1	1	Y	B	N	1502	3065.00000	2000.90	1941.81	
4	1	1	Y	A	N	4485	14028.00000	2181.12	2166.48	1

5 rows × 50 columns

In [136…
```
display(record.head())
```

	rev_Mean	mou_Mean	totmrc_Mean	da_Mean	ovrmou_Mean	ovrrev_Mean	vceovr_Mean
0	23.9975	219.25	22.500	0.2475	0.00	0.0	0.0
1	57.4925	482.75	37.425	0.2475	22.75	9.1	9.1
2	16.9900	10.25	16.990	0.0000	0.00	0.0	0.0
3	38.0000	7.50	38.000	0.0000	0.00	0.0	0.0
4	55.2300	570.50	71.980	0.0000	0.00	0.0	0.0

5 rows × 51 columns

In [137…

```
client.info()
```

```
<class 'pandas.DataFrame'>
RangeIndex: 100000 entries, 0 to 99999
Data columns (total 50 columns):
 #   Column            Non-Null Count   Dtype  
---  ------            --------------   -----  
 0   uniqsubs          100000 non-null  int64  
 1   actvsubs          100000 non-null  int64  
 2   new_cell          100000 non-null  str    
 3   crclscod          100000 non-null  str    
 4   asl_flag          100000 non-null  str    
 5   totcalls          100000 non-null  int64  
 6   totmou            100000 non-null  float64
 7   totrev            100000 non-null  float64
 8   adjrev            100000 non-null  float64
 9   adjmou            100000 non-null  float64
 10  adjqty            100000 non-null  int64  
 11  avgrev            100000 non-null  float64
 12  avgmou            100000 non-null  float64
 13  avgqty            100000 non-null  float64
 14  avg3mou           100000 non-null  int64  
 15  avg3qty           100000 non-null  int64  
 16  avg3rev           100000 non-null  int64  
 17  avg6mou           97161 non-null   float64
 18  avg6qty           97161 non-null   float64
 19  avg6rev           97161 non-null   float64
 20  prizm_social_one  92612 non-null   str    
 21  area              99960 non-null   str    
 22  dualband          99999 non-null   str    
 23  refurb_new        99999 non-null   str    
 24  hnd_price         99153 non-null   float64
 25  phones            99999 non-null   float64
 26  models            99999 non-null   float64
 27  hnd_webcap        89811 non-null   str    
 28  truck             98268 non-null   float64
 29  rv                98268 non-null   float64
 30  ownrent           66294 non-null   str    
 31  lor               69810 non-null   float64
 32  dwlltype          68091 non-null   str    
 33  marital           98268 non-null   str    
 34  adults            76981 non-null   float64
 35  infobase          77921 non-null   str    
 36  income            74564 non-null   float64
 37  numbcars          50634 non-null   float64
 38  HHstatin          62077 non-null   str    
 39  dwllsize          61692 non-null   str    
 40  forgntvl          98268 non-null   float64
 41  ethnic            98268 non-null   str    
 42  kid0_2            98268 non-null   str    
 43  kid3_5            98268 non-null   str    
 44  kid6_10           98268 non-null   str    
 45  kid11_15          98268 non-null   str    
 46  kid16_17          98268 non-null   str    
 47  creditcd          98268 non-null   str    
 48  eqpdays           99999 non-null   float64
 49  Customer_ID       100000 non-null  int64  
```

```
dtypes: float64(21), int64(8), str(21)
memory usage: 38.1 MB
```

In [138…

```
record.info()
```

```
<class 'pandas.DataFrame'>
RangeIndex: 100000 entries, 0 to 99999
Data columns (total 51 columns):
 #   Column           Non-Null Count   Dtype  
---  ------           --------------   -----  
 0   rev_Mean         99643 non-null   float64
 1   mou_Mean         99643 non-null   float64
 2   totmrc_Mean      99643 non-null   float64
 3   da_Mean          99643 non-null   float64
 4   ovrmou_Mean      99643 non-null   float64
 5   ovrrev_Mean      99643 non-null   float64
 6   vceovr_Mean      99643 non-null   float64
 7   datovr_Mean      99643 non-null   float64
 8   roam_Mean        99643 non-null   float64
 9   change_mou       99109 non-null   float64
 10  change_rev       99109 non-null   float64
 11  drop_vce_Mean    100000 non-null  float64
 12  drop_dat_Mean    100000 non-null  float64
 13  blck_vce_Mean    100000 non-null  float64
 14  blck_dat_Mean    100000 non-null  float64
 15  unan_vce_Mean    100000 non-null  float64
 16  unan_dat_Mean    100000 non-null  float64
 17  plcd_vce_Mean    100000 non-null  float64
 18  plcd_dat_Mean    100000 non-null  float64
 19  recv_vce_Mean    100000 non-null  float64
 20  recv_sms_Mean    100000 non-null  float64
 21  comp_vce_Mean    100000 non-null  float64
 22  comp_dat_Mean    100000 non-null  float64
 23  custcare_Mean    100000 non-null  float64
 24  ccrndmou_Mean    100000 non-null  float64
 25  cc_mou_Mean      100000 non-null  float64
 26  inonemin_Mean    100000 non-null  float64
 27  threeway_Mean    100000 non-null  float64
 28  mou_cvce_Mean    100000 non-null  float64
 29  mou_cdat_Mean    100000 non-null  float64
 30  mou_rvce_Mean    100000 non-null  float64
 31  owylis_vce_Mean  100000 non-null  float64
 32  mouowylisv_Mean  100000 non-null  float64
 33  iwylis_vce_Mean  100000 non-null  float64
 34  mouiwylisv_Mean  100000 non-null  float64
 35  peak_vce_Mean    100000 non-null  float64
 36  peak_dat_Mean    100000 non-null  float64
 37  mou_peav_Mean    100000 non-null  float64
 38  mou_pead_Mean    100000 non-null  float64
 39  opk_vce_Mean     100000 non-null  float64
 40  opk_dat_Mean     100000 non-null  float64
 41  mou_opkv_Mean    100000 non-null  float64
 42  mou_opkd_Mean    100000 non-null  float64
 43  drop_blk_Mean    100000 non-null  float64
 44  attempt_Mean     100000 non-null  float64
 45  complete_Mean    100000 non-null  float64
 46  callfwdv_Mean    100000 non-null  float64
 47  callwait_Mean    100000 non-null  float64
 48  churn            100000 non-null  int64  
 49  months           100000 non-null  int64  
 50  Customer_ID      100000 non-null  int64  
```

```
dtypes: float64(48), int64(3)
memory usage: 38.9 MB
```

In [139…
```
print("CLIENT DATASET COLUMNS")
print(client.columns.tolist())
```

```
CLIENT DATASET COLUMNS
['uniqsubs', 'actvsubs', 'new_cell', 'crclscod', 'asl_flag', 'totcalls', 'totmou',
'totrev', 'adjrev', 'adjmou', 'adjqty', 'avgrev', 'avgmou', 'avgqty', 'avg3mou', 'av
g3qty', 'avg3rev', 'avg6mou', 'avg6qty', 'avg6rev', 'prizm_social_one', 'area', 'dua
lband', 'refurb_new', 'hnd_price', 'phones', 'models', 'hnd_webcap', 'truck', 'rv',
'ownrent', 'lor', 'dwlltype', 'marital', 'adults', 'infobase', 'income', 'numbcars',
'HHstatin', 'dwllsize', 'forgntvl', 'ethnic', 'kid0_2', 'kid3_5', 'kid6_10', 'kid11_
15', 'kid16_17', 'creditcd', 'eqpdays', 'Customer_ID']
```

In [140…
```
print("RECORD DATASET COLUMNS")
print(record.columns.tolist())
```

```
RECORD DATASET COLUMNS
['rev_Mean', 'mou_Mean', 'totmrc_Mean', 'da_Mean', 'ovrmou_Mean', 'ovrrev_Mean', 'vc
eovr_Mean', 'datovr_Mean', 'roam_Mean', 'change_mou', 'change_rev', 'drop_vce_Mean',
'drop_dat_Mean', 'blck_vce_Mean', 'blck_dat_Mean', 'unan_vce_Mean', 'unan_dat_Mean',
'plcd_vce_Mean', 'plcd_dat_Mean', 'recv_vce_Mean', 'recv_sms_Mean', 'comp_vce_Mean',
'comp_dat_Mean', 'custcare_Mean', 'ccrndmou_Mean', 'cc_mou_Mean', 'inonemin_Mean',
'threeway_Mean', 'mou_cvce_Mean', 'mou_cdat_Mean', 'mou_rvce_Mean', 'owylis_vce_Mea
n', 'mouowylisv_Mean', 'iwylis_vce_Mean', 'mouiwylisv_Mean', 'peak_vce_Mean', 'peak_
dat_Mean', 'mou_peav_Mean', 'mou_pead_Mean', 'opk_vce_Mean', 'opk_dat_Mean', 'mou_op
kv_Mean', 'mou_opkd_Mean', 'drop_blk_Mean', 'attempt_Mean', 'complete_Mean', 'callfw
dv_Mean', 'callwait_Mean', 'churn', 'months', 'Customer_ID']
```

In [141…
```
print("Client Unique IDs:",
      client["Customer_ID"].is_unique)

print("Record Unique IDs:",
      record["Customer_ID"].is_unique)
```

```
Client Unique IDs: True
Record Unique IDs: True
```

In [142…
```
client_missing = client.isnull().sum()
record_missing = record.isnull().sum()

print("Missing Values in Client Dataset:")
print(client_missing[client_missing > 0].sort_values(ascending=False))

print("\nMissing Values in Record Dataset:")
print(record_missing[record_missing > 0].sort_values(ascending=False))
```

```
Missing Values in Client Dataset:
numbcars            49366
dwllsize            38308
HHstatin            37923
ownrent             33706
dwlltype            31909
lor                 30190
income              25436
adults              23019
infobase            22079
hnd_webcap          10189
prizm_social_one     7388
avg6mou              2839
avg6qty              2839
avg6rev              2839
truck                1732
rv                   1732
ethnic               1732
kid0_2               1732
kid3_5               1732
kid6_10              1732
kid11_15             1732
kid16_17             1732
marital              1732
forgntvl             1732
creditcd             1732
hnd_price             847
area                   40
refurb_new              1
models                  1
phones                  1
dualband                1
eqpdays                 1
dtype: int64

Missing Values in Record Dataset:
change_mou     891
change_rev     891
rev_Mean       357
totmrc_Mean    357
mou_Mean       357
da_Mean        357
ovrmou_Mean    357
vceovr_Mean    357
ovrrev_Mean    357
roam_Mean      357
datovr_Mean    357
dtype: int64
numbcars            49366
dwllsize            38308
HHstatin            37923
ownrent             33706
dwlltype            31909
lor                 30190
income              25436
adults              23019
```

```
infobase            22079
hnd_webcap          10189
prizm_social_one     7388
avg6mou              2839
avg6qty              2839
avg6rev              2839
truck                1732
rv                   1732
ethnic               1732
kid0_2               1732
kid3_5               1732
kid6_10              1732
kid11_15             1732
kid16_17             1732
marital              1732
forgntvl             1732
creditcd             1732
hnd_price             847
area                   40
refurb_new              1
models                  1
phones                  1
dualband                1
eqpdays                 1
dtype: int64

Missing Values in Record Dataset:
change_mou     891
change_rev     891
rev_Mean       357
totmrc_Mean    357
mou_Mean       357
da_Mean        357
ovrmou_Mean    357
vceovr_Mean    357
ovrrev_Mean    357
roam_Mean      357
datovr_Mean    357
dtype: int64
```

In [143…

```
client_missing_percent = (client.isnull().mean() * 100)

record_missing_percent = (record.isnull().mean() * 100)

print("Client Missing Value Percentage")
print(client_missing_percent[client_missing_percent > 0].sort_values(ascending=Fals

print("\nRecord Missing Value Percentage")
print(record_missing_percent[record_missing_percent > 0].sort_values(ascending=Fals
```

```
Client Missing Value Percentage
numbcars            49.37
dwllsize            38.31
HHstatin            37.92
ownrent             33.71
dwlltype            31.91
lor                 30.19
income              25.44
adults              23.02
infobase            22.08
hnd_webcap          10.19
prizm_social_one     7.39
avg6mou              2.84
avg6qty              2.84
avg6rev              2.84
truck                1.73
rv                   1.73
ethnic               1.73
kid0_2               1.73
kid3_5               1.73
kid6_10              1.73
kid11_15             1.73
kid16_17             1.73
marital              1.73
forgntvl             1.73
creditcd             1.73
hnd_price            0.85
area                 0.04
refurb_new           0.00
models               0.00
phones               0.00
dualband             0.00
eqpdays              0.00
dtype: float64

Record Missing Value Percentage
change_mou     0.89
change_rev     0.89
rev_Mean       0.36
totmrc_Mean    0.36
mou_Mean       0.36
da_Mean        0.36
ovrmou_Mean    0.36
vceovr_Mean    0.36
ovrrev_Mean    0.36
roam_Mean      0.36
datovr_Mean    0.36
dtype: float64
```

In [144…

```
print("Is churn in Client?", "churn" in client.columns)

print("Is churn in Record?", "churn" in record.columns)
```

```
Is churn in Client? False
Is churn in Record? True
```

In [145…
```
common_columns = set(client.columns) & set(record.columns)

print("Common Columns:")
print(sorted(common_columns))
```

```
Common Columns:
['Customer_ID']
```

In [146…
```
# ///churn counts
print(record["churn"].value_counts())
```

```
churn
0    50438
1    49562
Name: count, dtype: int64
```

In [147…
```
# churn parcentage
churn_percentage = (
    record["churn"].value_counts(normalize=True) * 100
)

print(churn_percentage.round(2))
```


```
churn
0    50.44
1    49.56
Name: proportion, dtype: float64
```

In [148…
```
# churn graph
plt.figure(figsize=(7, 5))

sns.countplot(data=record, x="churn")

plt.title("Customer Churn Distribution")
plt.xlabel("Churn Status")
plt.ylabel("Number of Customers")

plt.show()
```



In [149…
```
# ID Matching before merging the datasets
print("Client IDs:", len(client["Customer_ID"]))
print("Record IDs:", len(record["Customer_ID"]))

print("Matching IDs:", client["Customer_ID"].isin(record["Customer_ID"]).sum())
```

```
Client IDs: 100000
Record IDs: 100000
Matching IDs: 100000
```

In [150…
```
#Dataset merging
df = pd.merge(client, record, on="Customer_ID", how="inner",validate="one_to_one")
print("Merged Dataset Successfully!")
print("Merged Dataset Shape:", df.shape)
```

```
Merged Dataset Successfully!
Merged Dataset Shape: (100000, 100)
```

In [151…
```
#Merged Dataset
display(df.head())
```

	uniqsubs	actvsubs	new_cell	crclscod	asl_flag	totcalls	totmou	totrev	adjrev	
0	2	1	U	A	N	1652	4228.00000	1504.62	1453.44	
1	1	1	N	EA	N	14654	26400.00000	2851.68	2833.88	2
2	1	1	Y	C	N	7903	24385.05333	2155.91	1934.47	2
3	1	1	Y	B	N	1502	3065.00000	2000.90	1941.81	
4	1	1	Y	A	N	4485	14028.00000	2181.12	2166.48	1

5 rows × 100 columns

In [152…
```
print("Total Rows in Merged Dataset:", df.shape[0])
print("Total Columns in Merged Dataset:", df.shape[1])
print("Total Missing Values:", df.isnull().sum().sum())
```

```
Total Rows in Merged Dataset: 100000
Total Columns in Merged Dataset: 100
Total Missing Values: 342969
```

In [153…
```
#Missing values Summary
missing_summary = pd.DataFrame({"Missing_Count": df.isnull().sum(), "Missing_Percen

missing_summary = missing_summary.sort_values(by="Missing_Percentage", ascending=Fa
display(missing_summary.head(20).round(2))
```

	Missing_Count	Missing_Percentage
numbcars	49366	49.37
dwllsize	38308	38.31
HHstatin	37923	37.92
ownrent	33706	33.71
dwlltype	31909	31.91
lor	30190	30.19
income	25436	25.44
adults	23019	23.02
infobase	22079	22.08
hnd_webcap	10189	10.19
prizm_social_one	7388	7.39
avg6rev	2839	2.84
avg6qty	2839	2.84
avg6mou	2839	2.84
ethnic	1732	1.73
forgntvl	1732	1.73
marital	1732	1.73
kid0_2	1732	1.73
rv	1732	1.73
truck	1732	1.73


In [154…

```
#Visulaization of missing values  (A horizontal bar chart showing the top 15 column
plt.figure(figsize=(12, 7))

top_missing = missing_summary.head(15)
sns.barplot(x=top_missing["Missing_Percentage"], y=top_missing.index)

plt.title("Top 15 Columns with Missing Values")
plt.xlabel("Missing Percentage(%)")
plt.ylabel("Column Names")

plt.tight_layout()
plt.show()
```



In [155…

```
#Comparison Datasets with Churn
print("Churn Column Exists:", "churn" in df.columns)

print("\nChurn Distribution:")
print(df["churn"].value_counts())

print("\nChurn Percentage:")
print((df["churn"].value_counts(normalize=True) * 100).round(2))
```

```
Churn Column Exists: True

Churn Distribution:
churn
0    50438
1    49562
Name: count, dtype: int64

Churn Percentage:
churn
0    50.44
1    49.56
Name: proportion, dtype: float64
```

In [156…

```
# Compare customer behavior by churn status

features = [
    "rev_Mean", #average revenue
    "mou_Mean", #average minutes of use
    "change_mou", #change in minutes of use
    "change_rev", #change in revenue
    "drop_vce_Mean", #average number of dropped calls
    "custcare_Mean", #average customer care interactions
    "months", #number of months
    "eqpdays" #number of days since equipment installation
```

```
]

# Select only columns available in our dataset
available_features = [col for col in features if col in df.columns]

churn_comparison = df.groupby("churn")[available_features].mean()

display(churn_comparison.T.round(2))
```

churn	0	1
rev_Mean	59.22	58.21
mou_Mean	543.21	483.31
change_mou	-5.34	-22.76
change_rev	-1.41	-0.62
drop_vce_Mean	6.09	5.82
custcare_Mean	1.98	1.60
months	18.63	19.04
eqpdays	363.28	421.09

In [157…

```
#customer usages visualization
fig, axes = plt.subplots(1, 2, figsize=(13, 5))


sns.boxplot(data=df, x="churn", y="rev_Mean",ax=axes[0], showfliers=False) #boxplot

axes[0].set_title("Revenue vs Churn")

sns.boxplot(data=df, x="churn", y="mou_Mean",ax=axes[1], showfliers=False)

axes[1].set_title("Usage vs Churn")

plt.tight_layout()
plt.show()
```



In [158…
```
# Create Usage Change Group

df["usage_group"] = pd.cut(
    df["change_mou"],
    bins=[-float("inf"), -50, -10, 0, float("inf")],
    labels=[
        "High Decrease",
        "Moderate Decrease",
        "Slight Decrease",
        "Increase"
    ]
)

print(df["usage_group"].value_counts())
```

```
usage_group
Increase             43702
High Decrease        32980
Moderate Decrease    14646
Slight Decrease       7781
Name: count, dtype: int64
```

In [159…
```
# Calculate churn rate for each usage group

usage_churn = (
    df.groupby("usage_group", observed=False)["churn"]
    .mean() * 100
)

print("Churn Rate by Usage Group:")
print(usage_churn.round(2))
```


```
Churn Rate by Usage Group:
usage_group
High Decrease        52.29
Moderate Decrease    49.26
Slight Decrease      55.53
Increase             46.00
Name: churn, dtype: float64
```

In [160…
```
#Graphical representation of usage change group
plt.figure(figsize=(10, 5))

usage_churn.plot(kind="bar")

plt.title("Churn Rate by Usage Change")
plt.xlabel("Usage Change Group")
plt.ylabel("Churn Rate (%)")

plt.xticks(rotation=20)
plt.tight_layout()
plt.show()
```



In [161…
```python
# Customer Care Service Group

df["care_group"] = pd.cut(
    df["custcare_Mean"],
    bins=[-float("inf"), 1, 3, float("inf")],
    labels=[
        "Low Interaction",
        "Medium Interaction",
        "High Interaction"
    ]
)

print(df["care_group"].value_counts())
```

```
care_group
Low Interaction       71792
High Interaction      16022
Medium Interaction    12186
Name: count, dtype: int64
```

In [162…
```python
# Calculate churn rate for each customer care group

care_churn = (
    df.groupby("care_group", observed=False)["churn"]
    .mean() * 100
)

print("Churn Rate by Customer Care:")
print(care_churn.round(2))
```


```
Churn Rate by Customer Care:
care_group
Low Interaction       51.23
Medium Interaction    46.18
High Interaction      44.66
Name: churn, dtype: float64
```

In [163…
```
#Visualization by Graphical representation of customer care service group
plt.figure(figsize=(9, 5))

care_churn.plot(kind="bar")

plt.title("Churn Rate by Customer Care Interaction")
plt.xlabel("Customer Care Interaction")
plt.ylabel("Churn Rate (%)")

plt.xticks(rotation=15)
plt.tight_layout()
plt.show()
```



In [164…
```
# Customer Tenure Group

df["tenure_group"] = pd.cut(
    df["months"],
    bins=[-float("inf"), 6, 12, 24, float("inf")],
    labels=[
        "0-6 Months",
        "7-12 Months",
        "13-24 Months",
        "Above 24 Months"
    ]
)

print(df["tenure_group"].value_counts())
```

```
tenure_group
13-24 Months       42868
7-12 Months        31148
Above 24 Months    24689
0-6 Months          1295
Name: count, dtype: int64
```

In [165…
```
# Churn Rate for each customer tenure group

tenure_churn = (
    df.groupby("tenure_group", observed=False)["churn"]
    .mean() * 100
)

print("Churn Rate by Customer Tenure:")
print(tenure_churn.round(2))
```


```
Churn Rate by Customer Tenure:
tenure_group
0-6 Months          38.38
7-12 Months         47.13
13-24 Months        51.78
Above 24 Months     49.37
Name: churn, dtype: float64
```

In [166…
```
#Graphical representation of churn rate by usage group
plt.figure(figsize=(10, 5))

tenure_churn.plot(kind="bar")

plt.title("Churn Rate by Customer Tenure")
plt.xlabel("Customer Tenure")
plt.ylabel("Churn Rate (%)")

plt.xticks(rotation=15)
plt.tight_layout()
plt.show()
```



In [167…
```
#Revenue Group
df["revenue_group"] = pd.qcut(
    df["rev_Mean"],
    q=4,
    labels=[
        "Low Revenue",
```

```
        "Medium Revenue",
        "High Revenue",
        "Very High Revenue"
    ]
)

print(df["revenue_group"].value_counts())
```

```
revenue_group
Low Revenue          24921
High Revenue         24911
Very High Revenue    24910
Medium Revenue       24901
Name: count, dtype: int64
```

In [168…

```
#Churn Rate according to revenue group
revenue_churn = (
    df.groupby("revenue_group", observed=False)["churn"]
    .mean() * 100
)

print("Churn Rate by Revenue:")
print(revenue_churn.round(2))
```

```
Churn Rate by Revenue:
revenue_group
Low Revenue          52.65
Medium Revenue       47.70
High Revenue         49.01
Very High Revenue    48.61
Name: churn, dtype: float64
```


In [169…

```
#Graph
plt.figure(figsize=(10, 5))

revenue_churn.plot(kind="bar")

plt.title("Churn Rate by Average Revenue")
plt.xlabel("Revenue Group")
plt.ylabel("Churn Rate (%)")

plt.xticks(rotation=15)
plt.tight_layout()
plt.show()
```



In [170…
```python
#Equipment Age Group
df["equipment_group"] = pd.cut(
    df["eqpdays"],
    bins=[-float("inf"), 180, 365, 730, float("inf")],
    labels=[
        "New Equipment",
        "1 Year Old",
        "1-2 Years Old",
        "Above 2 Years"
    ]
)

print(df["equipment_group"].value_counts())
```

```
equipment_group
1 Year Old       36356
1-2 Years Old    34505
New Equipment    18327
Above 2 Years    10811
Name: count, dtype: int64
```

In [171…
```python
#Churn Rate
equipment_churn = (
    df.groupby("equipment_group", observed=False)["churn"]
    .mean() * 100
)

print("Churn Rate by Equipment Age:")
print(equipment_churn.round(2))
```

```
Churn Rate by Equipment Age:
equipment_group
New Equipment    41.74
1 Year Old       46.97
1-2 Years Old    53.84
Above 2 Years    57.89
Name: churn, dtype: float64
```


In [172…

```
#Visualization
plt.figure(figsize=(10, 5))

equipment_churn.plot(kind="bar")

plt.title("Churn Rate by Equipment Age")
plt.xlabel("Equipment Age")
plt.ylabel("Churn Rate (%)")

plt.xticks(rotation=15)
plt.tight_layout()
plt.show()
```



In [173…

```
#Customer Demographics vs Churn
print("Available Demographic Columns:")

demographic_cols = [
    "age",
    "marital",
    "adults",
    "kid0_2",
    "kid3_5",
    "kid6_10",
    "kid11_15",
    "kid16_17",
    "ethnic"
]

for col in demographic_cols:
    if col in df.columns:
        print(col, "Available")
```

```
Available Demographic Columns:
marital Available
adults Available
kid0_2 Available
kid3_5 Available
kid6_10 Available
kid11_15 Available
kid16_17 Available
ethnic Available
```

In [174…

```python
# Churn Rate by Marital Status

marital_churn = (
    df.groupby("marital", observed=True)["churn"]
    .agg(["count", "mean"])
)

marital_churn["churn_rate"] = marital_churn["mean"] * 100

print("Churn Rate by Marital Status:")
display(marital_churn[["count", "churn_rate"]].round(2))
```

```
Churn Rate by Marital Status:
```

marital	count	churn_rate
A	5140	48.97
B	7116	49.69
M	31052	48.87
S	17627	47.47
U	37333	51.27

In [175…

```python
# Churn Rate by Number of Adults

adults_churn = (
    df.groupby("adults", observed=True)["churn"]
    .agg(["count", "mean"])
)

adults_churn["churn_rate"] = adults_churn["mean"] * 100

print("Churn Rate by Number of Adults:")
display(adults_churn[["count", "churn_rate"]].round(2))
```

```
Churn Rate by Number of Adults:
```

adults	count	churn_rate
1.0	22299	49.06
2.0	23045	49.49
3.0	13667	48.76
4.0	8803	48.03
5.0	4817	48.56
6.0	4350	47.86

In [176…

```
# Churn Rate by Children Information

kid_columns = [
    "kid0_2",
    "kid3_5",
    "kid6_10",
    "kid11_15",
    "kid16_17"
]

for col in kid_columns:

    print("\nChurn Rate by", col)

    result = (
        df.groupby(col, observed=True)["churn"]
        .agg(["count", "mean"])
    )

    result["churn_rate"] = result["mean"] * 100

    display(result[["count", "churn_rate"]].round(2))
```

```
Churn Rate by kid0_2
```

kid0_2	count	churn_rate
U	94256	49.49
Y	4012	51.94

```
Churn Rate by kid3_5
```

	count	churn_rate
kid3_5		
U	93572	49.54
Y	4696	50.64

Churn Rate by kid6_10

	count	churn_rate
kid6_10		
U	90195	49.62
Y	8073	49.24

Churn Rate by kid11_15

	count	churn_rate
kid11_15		
U	89454	49.65
Y	8814	49.04

Churn Rate by kid16_17

	count	churn_rate
kid16_17		
U	88304	49.52
Y	9964	50.22

In [177…

```
# Demographic Churn Analysis

demographic_features = [
    "marital",
    "adults",
    "kid0_2",
    "kid3_5",
    "kid6_10",
    "kid11_15",
    "kid16_17"
]

fig, axes = plt.subplots(2, 2, figsize=(14, 10))


for ax, col in zip(axes.flat, demographic_features[:4]):

    sns.barplot(
        data=df,
        x=col,
        y="churn",
        ax=ax,
```

```
        errorbar=None
    )

    ax.set_title(f"Churn Rate by {col}")
    ax.set_ylabel("Churn Rate")

plt.tight_layout()
plt.show()
```



In [178…

```
# Remaining Demographic Features

remaining_features = [
    "kid6_10",
    "kid11_15",
    "kid16_17"
]

fig, axes = plt.subplots(1, 3, figsize=(15, 5))


for ax, col in zip(axes, remaining_features):

    sns.barplot(
        data=df,
        x=col,
        y="churn",
        ax=ax,
        errorbar=None
    )

    ax.set_title(f"Churn Rate by {col}")
```

```
    ax.set_ylabel("Churn Rate")

plt.tight_layout()
plt.show()
```



In [179…

```
# Correlation Analysis

numerical_df = df.select_dtypes(include=["int64", "float64"])

correlation = numerical_df.corr()

churn_correlation = (
    correlation["churn"]
    .drop("churn")
    .sort_values(ascending=False)
)

print("Top Positive Correlations with Churn:")
display(churn_correlation.head(15).round(3))

print("\nTop Negative Correlations with Churn:")
display(churn_correlation.tail(15).round(3))
```

```
Top Positive Correlations with Churn:
eqpdays          0.113
uniqsubs         0.040
vceovr_Mean      0.024
ovrrev_Mean      0.024
months           0.021
ovrmou_Mean      0.020
actvsubs         0.020
roam_Mean        0.009
change_rev       0.008
income           0.005
numbcars         0.002
rv               0.000
recv_sms_Mean   -0.001
datovr_Mean     -0.001
callfwdv_Mean   -0.002
Name: churn, dtype: float64
Top Negative Correlations with Churn:
```

```
models          -0.045
mou_rvce_Mean   -0.047
mou_peav_Mean   -0.047
opk_vce_Mean    -0.048
peak_vce_Mean   -0.048
plcd_vce_Mean   -0.048
attempt_Mean    -0.049
mou_opkv_Mean   -0.049
avg3mou         -0.050
comp_vce_Mean   -0.052
complete_Mean   -0.052
mou_cvce_Mean   -0.052
mou_Mean        -0.057
totmrc_Mean     -0.069
hnd_price       -0.103
Name: churn, dtype: float64
```


In [180…

```
# Correlation Heatmap

plt.figure(figsize=(12, 8))

sns.heatmap(
    correlation[["churn"]].sort_values(
        by="churn",
        ascending=False
    ),
    annot=True,
    cmap="coolwarm",
    center=0
)

plt.title("Feature Correlation with Customer Churn")
plt.tight_layout()
plt.show()
```



In [181…

```
# Top 15 Features Correlation with Churn

top_features = pd.concat([
    churn_correlation.head(15),
    churn_correlation.tail(15)
])


plt.figure(figsize=(10, 9))

sns.barplot(
    x=top_features.values,
    y=top_features.index
)

plt.title("Top Features Correlation with Churn")
plt.xlabel("Correlation Coefficient")
plt.ylabel("Features")

plt.axvline(x=0, color="black", linewidth=1)

plt.tight_layout()
plt.show()
```



In [182…

```
# Equipment Age vs Customer Churn

equipment_analysis = (
    df.groupby("equipment_group", observed=True)["churn"]
    .agg(
        total_customers="count",
        churned_customers="sum",
        churn_rate="mean"
    )
)

equipment_analysis["churn_rate"] *= 100

display(equipment_analysis.round(2))
```

equipment_group	total_customers	churned_customers	churn_rate
New Equipment	18327	7649	41.74
1 Year Old	36356	17077	46.97
1-2 Years Old	34505	18577	53.84
Above 2 Years	10811	6259	57.89


In [183…

```
# Equipment Age and Churn Comparison

equipment_analysis["churn_rate"].plot(
    kind="bar",
    figsize=(10, 5)
)

plt.title("Customer Churn by Equipment Age")
plt.xlabel("Equipment Age")
plt.ylabel("Churn Rate (%)")

plt.xticks(rotation=15)
plt.tight_layout()
plt.show()
```



In [184…

```
from scipy.stats import chi2_contingency

# Create contingency table
equipment_churn_table = pd.crosstab(
    df["equipment_group"],
    df["churn"]
)

print("Equipment Age vs Churn:")
display(equipment_churn_table)
```

```
# Chi-Square Test
chi2, p_value, dof, expected = chi2_contingency(
    equipment_churn_table
)

print("Chi-Square Statistic:", chi2)
print("P-value:", p_value)
print("Degrees of Freedom:", dof)

if p_value < 0.05:
    print("Result: Statistically Significant Association")
else:
    print("Result: No Statistically Significant Association")
```

Equipment Age vs Churn:

churn	0	1
equipment_group		
New Equipment	10678	7649
1 Year Old	19279	17077
1-2 Years Old	15928	18577
Above 2 Years	4552	6259

```
Chi-Square Statistic: 1099.3107452465624
P-value: 5.135698765860835e-238
Degrees of Freedom: 3
Result: Statistically Significant Association
```

In [185…

```
import numpy as np

# Calculate Cramer's V

n = equipment_churn_table.to_numpy().sum()

min_dimension = min(
    equipment_churn_table.shape[0] - 1,
    equipment_churn_table.shape[1] - 1
)

cramers_v = np.sqrt(
    chi2 / (n * min_dimension)
)

print("Cramer's V:", round(cramers_v, 4))

if cramers_v < 0.1:
    print("Association Strength: Very Weak")
elif cramers_v < 0.3:
    print("Association Strength: Weak")
elif cramers_v < 0.5:
    print("Association Strength: Moderate")
```

```
else:
    print("Association Strength: Strong")
```

```
Cramer's V: 0.1048
Association Strength: Weak
```

In [186…

```
# Revenue Group Analysis

revenue_analysis = (
    df.groupby("revenue_group", observed=True)["churn"]
    .agg(
        total_customers="count",
        churned_customers="sum",
        churn_rate="mean"
    )
)

revenue_analysis["churn_rate"] *= 100

display(revenue_analysis.round(2))
```

revenue_group	total_customers	churned_customers	churn_rate
Low Revenue	24921	13122	52.65
Medium Revenue	24901	11877	47.70
High Revenue	24911	12210	49.01
Very High Revenue	24910	12108	48.61

In [187…

```
# Chi-Square Test for Revenue and Churn

revenue_table = pd.crosstab(
    df["revenue_group"],
    df["churn"]
)

chi2_rev, p_rev, dof_rev, expected_rev = chi2_contingency(
    revenue_table
)

print("Chi-Square:", chi2_rev)
print("P-value:", p_rev)
print("Degrees of Freedom:", dof_rev)
```

```
Chi-Square: 141.87868503502918
P-value: 1.4871779473090141e-30
Degrees of Freedom: 3
```

In [188…

```
# Cramer's V for Revenue and Churn

n_rev = revenue_table.to_numpy().sum()

min_dim_rev = min(
```

```
    revenue_table.shape[0] - 1,
    revenue_table.shape[1] - 1
)

cramers_v_rev = np.sqrt(
    chi2_rev / (n_rev * min_dim_rev)
)

print("Revenue Cramer's V:", round(cramers_v_rev, 4))
```

```
Revenue Cramer's V: 0.0377
```

In [189…

```
# Tenure Group Analysis

tenure_analysis = (
    df.groupby("tenure_group", observed=True)["churn"]
    .agg(
        total_customers="count",
        churned_customers="sum",
        churn_rate="mean"
    )
)

tenure_analysis["churn_rate"] *= 100

display(tenure_analysis.round(2))
```

tenure_group	total_customers	churned_customers	churn_rate
0-6 Months	1295	497	38.38
7-12 Months	31148	14679	47.13
13-24 Months	42868	22197	51.78
Above 24 Months	24689	12189	49.37

In [190…

```
# Chi-Square Test

tenure_table = pd.crosstab(
    df["tenure_group"],
    df["churn"]
)

chi2_tenure, p_tenure, dof_tenure, expected_tenure = (
    chi2_contingency(tenure_table)
)

print("Chi-Square:", chi2_tenure)
print("P-value:", p_tenure)
print("Degrees of Freedom:", dof_tenure)
```

```
Chi-Square: 223.4120904052857
P-value: 3.673714490918242e-48
Degrees of Freedom: 3
```

In [191…

```python
# Cramer's V

n_tenure = tenure_table.to_numpy().sum()

min_dim_tenure = min(
    tenure_table.shape[0] - 1,
    tenure_table.shape[1] - 1
)

cramers_v_tenure = np.sqrt(
    chi2_tenure / (n_tenure * min_dim_tenure)
)

print("Tenure Cramer's V:", round(cramers_v_tenure, 4))
```

```
Tenure Cramer's V: 0.0473
```

In [192…

```python
# Final Comparative Analysis

comparison = pd.DataFrame({
    "Factor": [
        "Equipment Age",
        "Revenue Group",
        "Customer Tenure"
    ],

    "Chi_Square": [
        chi2,
        chi2_rev,
        chi2_tenure
    ],

    "P_Value": [
        p_value,
        p_rev,
        p_tenure
    ],

    "Cramers_V": [
        cramers_v,
        cramers_v_rev,
        cramers_v_tenure
    ]
})

# Association Strength
def association_strength(v):
    if v < 0.1:
        return "Very Weak"
    elif v < 0.3:
        return "Weak"
    elif v < 0.5:
```

```
        return "Moderate"
    else:
        return "Strong"

comparison["Association"] = (
    comparison["Cramers_V"].apply(association_strength)
)

# Statistical Significance
comparison["Significance"] = comparison["P_Value"].apply(
    lambda p: "Significant" if p < 0.05 else "Not Significant"
)

# Format P-values in Scientific Notation
comparison["P_Value"] = comparison["P_Value"].apply(
    lambda p: f"{p:.3e}"
)

# Display Final Comparison
display(comparison.round(4))
```

	Factor	Chi_Square	P_Value	Cramers_V	Association	Significance
0	Equipment Age	1099.3107	5.136e-238	0.1048	Weak	Significant
1	Revenue Group	141.8787	1.487e-30	0.0377	Very Weak	Significant
2	Customer Tenure	223.4121	3.674e-48	0.0473	Very Weak	Significant


In [193…

```
plt.figure(figsize=(9, 5))

sns.barplot(
    data=comparison,
    x="Factor",
    y="Cramers_V"
)

plt.title("Comparative Association with Customer Churn")
plt.xlabel("Factors")
plt.ylabel("Cramer's V")

plt.tight_layout()
plt.show()
```



Key Findings

The analysis of customer churn reveals several important insights:

1. **Equipment Age:** Customers using older equipment show higher churn rates. Customers with equipment older than two years have the highest churn rate (57.89%).
2. **Revenue Group:** Low-revenue customers have the highest churn rate (52.65%).
3. **Customer Tenure:** Customers with 13–24 months of tenure have the highest churn rate (51.78%).
4. **Statistical Association:** Equipment Age, Revenue Group, and Customer Tenure all show statistically significant associations with customer churn.
5. **Comparative Analysis:** Equipment Age has the strongest association with churn among the three examined factors.

Conclusion

This project analyzed customer churn patterns using exploratory data analysis, data visualization, and statistical techniques.

The findings indicate that customer churn is associated with several factors, including equipment age, revenue group, and customer tenure.

Among these factors, equipment age demonstrates the strongest association with churn.

These findings can help businesses identify customer segments that may require additional attention and develop targeted customer retention strategies.

However, statistical association does not necessarily imply causation. Further predictive modeling would be required to identify the underlying causes of customer churn.

Business Recommendations

1. **Equipment Upgrade:** Encourage customers using older equipment to upgrade their devices.
2. **Affordable Packages:** Introduce suitable packages for low-revenue customers.
3. **Customer Retention:** Develop targeted retention campaigns for customers with 13–24 months of tenure.
4. **Customer Monitoring:** Regularly monitor customer usage patterns and service interactions.
5. **Data-Driven Decisions:** Use customer data and predictive analytics to identify potential churn risks.

In [194…

```
# Create output directories

import os

os.makedirs("../outputs/figures", exist_ok=True)
os.makedirs("../outputs/results", exist_ok=True)

print("Output directories are ready!")
```

```
Output directories are ready!
```

In [195…

```
# Save Important Visualizations

# 1. Customer Churn Distribution
plt.figure(figsize=(7, 5))
sns.countplot(data=df, x="churn")
plt.title("Customer Churn Distribution")
plt.savefig("../outputs/figures/churn_distribution.png",
            dpi=300, bbox_inches="tight")
plt.close()


# 2. Equipment Age vs Churn
equipment_analysis["churn_rate"].plot(
    kind="bar", figsize=(8, 5)
)
plt.title("Customer Churn by Equipment Age")
```

```
plt.ylabel("Churn Rate (%)")
plt.savefig("../outputs/figures/equipment_churn.png",
            dpi=300, bbox_inches="tight")
plt.close()


# 3. Revenue vs Churn
revenue_analysis["churn_rate"].plot(
    kind="bar", figsize=(8, 5)
)
plt.title("Customer Churn by Revenue")
plt.ylabel("Churn Rate (%)")
plt.savefig("../outputs/figures/revenue_churn.png",
            dpi=300, bbox_inches="tight")
plt.close()


# 4. Tenure vs Churn
tenure_analysis["churn_rate"].plot(
    kind="bar", figsize=(8, 5)
)
plt.title("Customer Churn by Tenure")
plt.ylabel("Churn Rate (%)")
plt.savefig("../outputs/figures/tenure_churn.png",
            dpi=300, bbox_inches="tight")
plt.close()


# 5. Comparative Analysis
plt.figure(figsize=(9, 5))
sns.barplot(
    data=comparison,
    x="Factor",
    y="Cramers_V"
)
plt.title("Comparative Association with Customer Churn")
plt.savefig("../outputs/figures/comparative_analysis.png",
            dpi=300, bbox_inches="tight")
plt.close()

print("All important graphs saved successfully!")
```

```
All important graphs saved successfully!
```

In [196…

```
# Save Important Analysis Results

# 1. Comparative Analysis
comparison.to_csv(
    "../outputs/results/comparative_analysis.csv",
    index=False
)

# 2. Equipment Age Analysis
equipment_analysis.to_csv(
    "../outputs/results/equipment_analysis.csv"
)
```

```
# 3. Revenue Analysis
revenue_analysis.to_csv(
    "../outputs/results/revenue_analysis.csv"
)

# 4. Customer Tenure Analysis
tenure_analysis.to_csv(
    "../outputs/results/tenure_analysis.csv"
)

# 5. Missing Values Summary
missing_summary.to_csv(
    "../outputs/results/missing_values_summary.csv"
)

print("All analysis results saved successfully!")
```

```
All analysis results saved successfully!
```

In [197…

```
# Verify Saved Files

for folder in ["../outputs/figures", "../outputs/results"]:
    print(f"\nFiles in {folder}:")
    for file in sorted(os.listdir(folder)):
        print("-", file)
```

```
Files in ../outputs/figures:
- churn_distribution.png
- comparative_analysis.png
- equipment_churn.png
- revenue_churn.png
- tenure_churn.png

Files in ../outputs/results:
- comparative_analysis.csv
- equipment_analysis.csv
- missing_values_summary.csv
- revenue_analysis.csv
- tenure_analysis.csv
```

In [ ]: