

Exam page 3

Janis Hodorjonoks

May 30, 2019

434 Elementary Queueing Theory

To determine performance measures, we first compute

$$\begin{aligned} L_q &= \sum_{n=c}^K (n-c)p_n = p_0 \frac{(\lambda/\mu)^c \lambda/c\mu}{c!(1-\lambda/c\mu)^2} \left[1 - \left(\frac{\lambda}{c\mu} \right)^{K-c+1} - \left(1 - \frac{\lambda}{c\mu} \right) (K-c+1) \left(\frac{\lambda}{c\mu} \right)^{K-c} \right] \\ &= p_0 \frac{(c\rho)^c \rho}{c!(1-\rho)^2} [1 - \rho^{K-c+1} - (1-\rho)(K-c+1)\rho^{K-c}], \end{aligned}$$

where we have defined $\rho = \lambda/(c\mu)$. This allows us to obtain the average number of customers in the system (see also Exercise 11.6.1):

$$L = L_q + \left(c - \sum_{n=0}^{c-1} (c-n)p_n \right) = L_q + c - \sum_{n=0}^{c-1} (c-n) \frac{(\lambda/\mu)^n}{n!} p_0, \quad (11.12)$$

which is the number waiting in the queue plus the average number of busy servers. In the special case of $c = 1$, this reduces to

$$L = L_q + (1 - p_0) = L_q + \frac{\lambda'}{\mu},$$

where $\lambda' = \lambda(1 - p_K)$ is the effective arrival rate. The time spent in the system can now be obtained from $W = L/\lambda'$. Finally, the mean time spent in the queue waiting for service to begin is found from $W_q = W - 1/\mu$ or $W_q = L_q/\lambda'$.

Erlang's Loss Formula

For the special case when $K = c$, i.e., the $M/M/c/c$ queue, the so-called "blocked calls cleared with c servers" system, these results lead to another well-known formula associated with the name Erlang. The probability that there are n customers in the $M/M/c/c$ queue is given as

$$p_n = \frac{(\lambda/\mu)^n / n!}{\sum_{i=0}^c (\lambda/\mu)^i / i!} = p_0 \frac{(\lambda/\mu)^n}{n!}.$$

The formula for p_c is called "Erlang's loss formula" and is the fraction of time that all c servers are busy. It is written as $B(c, \lambda/\mu)$ and called "Erlang's B formula":

$$B(c, \lambda/\mu) = \frac{(\lambda/\mu)^c / c!}{\sum_{i=0}^c (\lambda/\mu)^i / i!} = p_0 \frac{(\lambda/\mu)^c}{c!}.$$

Notice that the probability that an arrival is lost is equal to the probability that all channels are busy. Erlang's loss formula is also valid for the $M/G/c/c$ queue. In other words, the steady-state probabilities are a function only of the mean service time, and not of the complete underlying cumulative distribution function. An efficient recursive algorithm for computing $B(c, \lambda/\mu)$ is given by

$$B(0, \lambda/\mu) = 1, \quad B(c, \lambda/\mu) = \frac{(\lambda/\mu)B(c-1, \lambda/\mu)}{c + (\lambda/\mu)B(c-1, \lambda/\mu)}.$$

We leave its proof as an exercise. It is also possible to express Erlang's C formula in terms of $B(c, \lambda/\mu)$ and again, we leave this as an exercise.

11.7 Finite-Source Systems—The $M/M/c/M$ Queue

The $M/M/c/M$ queue is a c -server system with a finite customer population. No longer do we have a Poisson input process with an infinite user population. There is a total of M customers and a customer is either in the system, or else is outside the system and is in some sense "arriving." When

To determine performance measures, we first compute

$$\begin{aligned} L_q &= \sum_{n=c}^K (n-c)p_n = p_0 \frac{(\lambda/\mu)^c \lambda/c\mu}{c!(1-\lambda/c\mu)^2} \left[1 - \left(\frac{\lambda}{c\mu} \right)^{K-c+1} - \left(1 - \frac{\lambda}{c\mu} \right) (K-c+1) \left(\frac{\lambda}{c\mu} \right)^{K-c} \right] \\ &= p_0 \frac{(cp)^c \lambda/c\mu}{c!(1-\lambda/c\mu)^2} [1 - \rho^{K-c+1} - (1-\rho)(K-c+1)\rho^{K-c}], \end{aligned}$$

where we have defined $\rho = \lambda/(c\mu)$. This allows us to obtain the average number of customers in the system (see also Exercise 11.6.1):

$$L = L_q + \left(c - \sum_{n=0}^{c-1} (c-n)p_n \right) = L_q + c - \sum_{n=0}^{c-1} (c-n) \frac{(\lambda/\mu)^n}{n!} p_0, \quad (11.12)$$

which is the number waiting in the queue plus the average number of busy servers. In the special case of $c = 1$, it reduces to

$$L = L_q + (1 - p_0) = L_q + \frac{\lambda'}{\mu'}$$

where $\lambda' = \lambda(1 - p_K)$ is the effective arrival rate. The time spent in the system can now be obtained from $W = L/\lambda'$. Finally, the mean time spent in the queue waiting for service to begin is found from $W_q = W - 1/\mu$ or $W_q = L_q/\lambda'$.

Erlang's Loss Formula

For the special case $K = c$, i.e., the $M/M/c/c$ queue, the so-called “blocked calls cleared with c servers” system, the results lead to another well-known formula associated with the name of Erlang. The probability that there are n customers in the $M/M/c/c$ queue is given as

$$p_n = \frac{(\lambda/\mu)^c / n!}{\sum_{i=0}^c (\lambda/\mu)^i / i!} = p_0 \frac{(\lambda/\mu)^n}{n!}.$$

The formula for p_c is called “Erlang’s loss formula” and is the fraction of time that all c servers are busy. It is written as $B(c, \lambda/\mu)$ and called “Erlang’s B formula”:

$$B(c, \lambda/\mu) = \frac{(\lambda/\mu)^c / c!}{\sum_{i=0}^c (\lambda/\mu)^i / i!} = p_0 \frac{(\lambda/\mu)^c}{c!}.$$

Notice that the probability that an arrival is lost is equal to the probability that all channels are busy. Erlang’s loss formula is also valid for the $M/G/c/c$ queue. In other words, the steady-state probabilities are a function only of the mean service time, and not of the complete underlying cumulative distribution function. An efficient recursive algorithm for computing $B(c, \lambda/\mu)$ is given by

$$B(0, \lambda/\mu) = 1, \quad B(c, \lambda/\mu) = \frac{(\lambda/\mu)B(c-1, \lambda/\mu)}{c + (\lambda/\mu)B(c-1, \lambda/\mu)}.$$

We leave its proof as an exercise. It is also possible to express Erlang’s C formula in terms of $B(c, \lambda/\mu)$ and again, we leave this as an exercise.

11.7 Finite-Source Systems—The $M/M/c//M$ Queue

The $M/M/c//M$ queue is a c -server system with a finite customer population. No longer do we have a Poisson input process with an infinite user population. There is a total of M customers and a customer is either in the system, or else is outside the system and is in some sense “arriving.” When

```

\documentclass[11pt]{book}
\usepackage{geometry}
\usepackage{fancyhdr}
\usepackage{amsmath}
\usepackage{tcolorbox}
\usepackage{xcolor}
\usepackage{times}
\usepackage{amssymb}
\usepackage{ragged2e}
\usepackage{parskip}
\usepackage{fancyhdr}
\usepackage{graphicx}
\usepackage{textcomp}
\fontfamily{cmtt}\selectfont
\geometry{a4paper,
total={212mm,305mm},
left=29mm,
top=33mm,
right=29mm,
bottom=40mm}
\pagestyle{fancy}
\fancyhead[L]{\textbf{434 \hspace{5mm} \small{Elementary Queueing Theory}}}
\fancyfoot{}
\usepackage{xcolor}
\pagecolor{yellow!5}
\author{Janis Hodorjonoks}
\title{Exam page 3}
\setlength{\parskip}{2em}
\parindent=1cm
\renewcommand{\headrulewidth}{0.7pt}
\renewcommand{\baselinestretch}{0.8}
\begin{document}
\maketitle
\pagebreak

\parindent=0.5cm To determine performance measures, we first compute

$$\begin{aligned}
L_q &= \sum_{n=c}^K (n-c)p_n = p_0 \\
&\frac{(\lambda/\mu)^c \lambda/\mu}{c!(1-\lambda/\mu)^2} \left[ 1 - \left( \frac{\lambda}{c\mu} \right)^{K-c+1} - \left( 1 - \frac{\lambda}{c\mu} \right)^{K-c+1} \right. \\
&\quad \left. \left( \frac{\lambda}{c\mu} \right)^{K-c} \right] \\
L &= p_0 \frac{(c\mu)^c \lambda/\mu}{(\lambda/\mu)^2} \left[ 1 - \rho^{K-c+1} - (1-\rho)(K-c+1)\rho^{K-c} \right]
\end{aligned}$$

where we have defined  $\rho = \lambda/(c\mu)$ . This allows us to obtain the average number of customers in the system (see also Exercise 11.6.1):

$$L = L_q + \left( c - \sum_{n=0}^{c-1} (c-n)p_n \right) = L_q + c - \sum_{n=0}^{c-1} (c-n) \frac{(\lambda/\mu)^n}{n!} p_0,$$

which is the number waiting in the queue plus the average number of busy servers. In the special case of  $c = 1$ , it reduces to

$$L = L_q + (1 - p_0) = L_q + \frac{\lambda'}{\mu}$$

where  $\lambda' = \lambda(1 - p_K)$  is the effective arrival rate. The time spent in the system can now be obtained from  $W = L/\lambda$ . Finally, the mean time spent in the queue waiting for service to begin is found

```

from $W_{\{q\}} = W - 1/\mu$ or
 $W_{\{q\}} = L_{\{q\}}/\lambda$. \square

Erlang's Loss Formula
 For the special case $K = c$, i.e., the $M/M/c/c$ queue, the so-called blocked calls cleared with c servers system, the results lead to another well-known formula associated with the name of Erlang.
 The probability that are n customers in the $M/M/c/c$ queue is given as

$$p_n = \frac{(\lambda/\mu)^n/n!}{\sum_{i=0}^c (\lambda/\mu)^i/i!} = p_0 \frac{(\lambda/\mu)^n/n!}{\sum_{i=0}^c (\lambda/\mu)^i/i!}.$$

The formula for p_c is called Erlang's loss formula and is the fraction of time that all c servers are busy. It is written as $B(c, \lambda/\mu)$ and called Erlang's B formula:

$$B(c, \lambda/\mu) = \frac{(\lambda/\mu)^c/c!}{\sum_{i=0}^c (\lambda/\mu)^i/i!} = p_0 \frac{(\lambda/\mu)^c/c!}{\sum_{i=0}^c (\lambda/\mu)^i/i!}.$$

Notice that the probability that an arrival is lost is equal to the probability that all channels are busy. Erlang's loss formula is also valid for the $M/G/c/c$ queue.

In other words, the steady-state probabilities are a function only of the mean service time, and not of the complete underlying cumulative distribution function. An efficient recursive algorithm for computing $B(c, \lambda/\mu)$ is given by

$$B(0, \lambda/\mu) = 1, \quad B(c, \lambda/\mu) = \frac{(\lambda/\mu)B(c-1, \lambda/\mu)}{(\lambda/\mu)B(c-1, \lambda/\mu) + 1}.$$

We leave its proof as an exercise. It is also possible to express Erlang's C formula in terms of $B(c, \lambda/\mu)$ and again, we leave this as an exercise. \square

Finite-Source Systems
 The $M/M/c/M$ Queue \square

The $M/M/c/M$ queue is a c -server system with a finite customer population. No longer do we have a Poisson input process with an infinite user population. There is a total of M customers and a customer is either in the system, or else is outside the system and is in some sense arriving. When