


SURFACE MOUNT MICRO HEADER

(1.27 mm) .050" PITCH • FTSH SERIES



FTSH

Board Mates:

CLP, FLE

Cable Mates:

FFSD, FFTP

SPECIFICATIONS

Insulator Material:

Black Liquid Crystal Polymer

Terminal Material:

Phosphor Bronze

Plating:

Sn or Au over

50 μ " (1.27 μ m) Ni

Current Rating (FTSH/CLP):

3.4 A per pin

(2 pins powered)

Operating Temp Range:

-55 °C to +125 °C

PROCESSING

Lead-Free Solderable:

Yes

SMT Lead Coplanarity:

-MT & -DV Tail Option:

(0.10 mm) .004" max (02-25)

-MT & -DH Tail Option:

(0.15 mm) .006" max (26-50)*

*(.004" stencil solution

may be available; contact

IPG@samtec.com)

ALSO AVAILABLE

MOQ Required

Molded Pick & Place pads

Latches

Other platings

FTSH	1	NO. PINS PER ROW	LEAD STYLE	PLATING OPTION	TAIL OPTION	OPTION	FLEX SHROUD OPTIONS	OTHER OPTIONS
------	---	------------------	------------	----------------	-------------	--------	---------------------	---------------

02
thru
50

-01
= (3.05 mm)
.120" Post
(Mates with
FFSD)

-02
= (1.91 mm)
.075" Post
(Mates with
FLE)

-03
= (1.65 mm)
.065" Post
(Mates with
CLP-D)

-04
= (3.81 mm)
.150" Post
(Mates with
CLP-DH)

-05
= (4.32 mm)
.170" Post
(Mates with
CLP-BE)

-F
= Gold flash
on post,
Matte Tin
on tail

-L
= 10 μ "
(0.25 μ m)
Gold
on post,
Matte Tin
on tail

-DV
= Double
Vertical

-DH
= Double
Horizontal
(Styles
-01, -02 &
-04 only)

-MT
= Mixed
Technology
(Styles
-01, -02 &
-04 only)

Leave Blank
for -DH &
-MT

"XXX"
= Polarized
Position
(Specify
position
of
omitted
pin)
(Not
available
with -EX
options)

(Style -02 & -03
only, -DH & -MT
not available)
9 pins/row
minimum
(Other positions
available. Call
Samtec.)

-ES
= End Shroud

-EC
= End Shroud
with Locking Clip
(Manual
placement
required)

-EP
= End Shroud
with Guide Post

-EL
= End Shroud with
Board Lock
(Boards are
positively locked
and cannot be
unmated)

-EJ
= Ejector Shroud
(Style -01 only)
-DH & -MT
not available
10 pins/row
minimum
25 pins/row
maximum

-K
= Keying
Shroud
(For mating
with FFSD
Style -01 only
and 05, 08, 10,
13, 15, 17,
20 & 25
pins/row only.
13, 17, 20 & 25
pins/row only
with -EJ option)
(-DV only)

-A
= Alignment
Pin
(-DV 3 positions
minimum)
(-DH 5 positions
minimum)
(Metal or
plastic at
Samtec
discretion)


-C
= (5.00 mm)
.197" DIA
Polyimide film
Pick & Place Pad
(-DH only)

-P
= Pick &
Place Pad
(-DV 4 positions
minimum)
(-DH & -MT
not available)


-TR
= Tape & Reel
(Flex Shroud
options
not available
except -ES
& -EJ)

-FR
= Full Reel
Tape & Reel
(must order
maximum
quantity
per reel;
contact
Samtec for
quantity breaks)


OPTION	Z
-ES	(2.57) .101
-EJ	(15.77) .621
-EC	(3.33) .131
-EP	(5.87) .231
-EL	(6.53) .257




-EX OPTION SHOWN



-EJ OPTION SHOWN




-MT
(Styles -01, -02 & -04 only)



-DH
(Styles -01, -02, -04 only)

LEAD STYLE	A
-01	(3.05) .120
-02	(1.91) .075
-03	(1.65) .065
-04	(3.81) .150
-05	(4.32) .170



Notes:

Some sizes, styles and options are non-standard, non-returnable.

See SFM/TFM for positive alignment feature.



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Samtec:

[FTSH-120-01-L-MT](#) [FTSH-107-01-F-MT](#) [FTSH-118-01-L-MT](#) [FTSH-105-01-F-MT](#) [FTSH-107-01-L-MT](#) [FTSH-110-01-F-MT](#) [FTSH-132-01-F-MT](#) [FTSH-113-01-F-MT](#) [FTSH-122-01-F-MT](#) [FTSH-105-01-L-MT](#) [FTSH-110-01-L-MT](#) [FTSH-120-01-F-MT](#) [FTSH-130-01-F-MT](#) [FTSH-105-04-F-MT](#) [FTSH-104-01-L-MT-TR](#) [FTSH-104-02-F-MT-TR](#) [FTSH-120-04-F-MT](#) [FTSH-109-04-F-MT](#) [FTSH-112-01-F-MT](#) [FTSH-105-01-F-MT-TR](#) [FTSH-130-01-L-MT](#) [FTSH-135-01-F-MT](#) [FTSH-144-01-L-MT](#) [FTSH-125-02-L-MT](#) [FTSH-116-01-L-MT](#) [FTSH-115-01-L-MT](#) [FTSH-120-02-L-MT](#) [FTSH-125-01-F-MT](#) [FTSH-134-01-L-MT](#) [FTSH-116-01-F-MT](#) [FTSH-136-01-L-MT](#) [FTSH-140-01-L-MT](#) [FTSH-130-02-L-MT](#) [FTSH-129-01-F-MT](#) [FTSH-140-01-F-MT](#) [FTSH-135-01-L-MT](#) [FTSH-132-01-L-MT](#) [FTSH-134-01-F-MT](#) [FTSH-125-01-L-MT](#) [FTSH-120-02-F-MT](#) [FTSH-114-01-L-MT](#) [FTSH-113-01-L-MT](#) [FTSH-115-01-F-MT](#) [FTSH-111-02-L-MT](#) [FTSH-106-01-L-MT](#) [FTSH-106-02-F-MT](#) [FTSH-108-01-L-MT](#) [FTSH-111-01-L-MT](#) [FTSH-108-04-L-MT-TR](#) [FTSH-110-02-L-MT](#) [FTSH-108-02-L-MT](#) [FTSH-108-02-F-MT](#) [FTSH-115-02-L-MT](#) [FTSH-124-02-LM-MT](#) [FTSH-124-02-L-MT](#) [FTSH-140-04-F-MT](#) [FTSH-117-01-F-MT](#) [FTSH-125-01-LM-MT](#) [FTSH-125-01-LM-MT-TR](#) [FTSH-127-04-L-MT](#) [FTSH-134-04-F-MT](#) [FTSH-132-04-L-MT](#) [FTSH-107-04-L-MT](#) [FTSH-112-02-F-MT](#) [FTSH-123-04-L-MT](#) [FTSH-120-01-LM-MT](#) [FTSH-116-04-L-MT](#) [FTSH-110-04-F-MT](#) [FTSH-125-04-L-MT](#) [FTSH-120-04-L-MT](#) [FTSH-109-02-L-MT](#) [FTSH-125-04-F-MT](#) [FTSH-107-02-F-MT](#) [FTSH-110-02-F-MT](#) [FTSH-112-01-L-MT](#) [FTSH-122-01-L-MT](#) [FTSH-136-02-L-MT](#) [FTSH-112-04-L-MT](#) [FTSH-112-04-F-MT](#) [FTSH-114-04-L-MT](#) [FTSH-115-04-F-MT](#) [FTSH-109-01-F-MT](#) [FTSH-125-01-L-MT-TR](#) [FTSH-107-02-L-MT](#) [FTSH-108-01-F-MT](#) [FTSH-117-01-L-MT](#) [FTSH-116-02-L-MT](#) [FTSH-115-04-L-MT](#) [FTSH-106-01-F-MT](#) [FTSH-106-02-L-MT](#) [FTSH-109-01-L-MT](#) [FTSH-108-04-L-MT](#) [FTSH-135-02-F-MT](#) [FTSH-110-01-LM-MT](#) [FTSH-111-01-F-MT](#) [FTSH-113-02-L-MT](#) [FTSH-110-04-L-MT](#) [FTSH-112-01-FM-MT](#) [FTSH-103-02-L-MT-TR](#) [FTSH-104-04-F-MT](#)