

Parallel Algorithm for Closest Pair Problem

Ge Wu | July 22, 2013

INSTITUTE FOR THEORETICAL INFORMATICS



Closest Pair Problem

- Given n **different** unordered points $P = \{p_1, p_2, \dots, p_n\}$ in **unit square**:

$$p_i = (x_i, y_i) \in (0, 1) \times (0, 1) \subset \mathbb{R}^2$$

- Find a pair of points with closest euclidean distance between them
- Find any pair if there's a tie.

- $O(n \log n)$ lower bound in comparison tree model
- 1976 Rabin proves that + floor function + randomness = $\hat{=}$ $O(n)$ expected time
- 1979 Steven Fortune and John E. Hopcroft + floor function but no randomness = $\hat{=}$ $O(n \log \log n)$
- 1995 Samir Khuller and Yossi Matias Another $O(n)$ algorithm that uses the floor function and randomization

- Compute all pair of distances: $O((n^{\frac{2}{3}})^2) = O(n^{\frac{4}{3}})$
- Divide & Conquer: $O(n^{\frac{2}{3}} \log n^{\frac{2}{3}}) = O(n^{\frac{2}{3}} \log n) \subset O(n)$
More samples possible: $O(\frac{n}{\log n} \log \frac{n}{\log n}) \subset O(n)$
- Other approach?

- Map points to the cells
- Divide the coordinates by cell length and truncate them to integer
- Partition $\mathbb{G} = \{G_1, G_2, \dots, G_k\}$ with:

$$\bigcup_{i=1}^k G_i = P, G_i \cap G_j = \emptyset, k \leq n$$

- $O(n)$ with hashing

- Compute distances of all pairs
- Running time: $O(n^2)$

Theorem

Let $f_i = |G_i|$ with $1 \leq i \leq k$ be the number of points in i -th non-empty cell and c, d some positive constants, then:

$$\sum_{i=1}^k f_i \leq c \cdot n \text{ with probability } 1 - \frac{1}{2^{n^d}}$$

Alternative for Sampling

```
0 Cell list  $C = \emptyset$ , Hash table  $H = \emptyset$ , Result  $rst = \infty$   
   Number of non-empty cells  $k = 0$   
  
1 Choose set  $S$  of  $n^{\frac{2}{3}}$  samples  $O(n^{\frac{8}{9}})$   
    $\delta = \min_{x,y \in S, x \neq y} (dist(x, y))$   
2 for  $i = 1$  to  $n$  do  $O(n)$   
    $c = cell(p_i)$   
   if not  $H.find(c)$  then  
        $H.add(\{c, idx = ++k\})$   
        $L[H.find(c).idx].add(p_i)$   
3 for  $i = 1$  to  $k$  do  $O(n)$   
   foreach  $j$  in  $\{i\} \cup neighbor\_idx(cell_i)$  do  
       foreach  $\{p_i, p_j\}$  in  $L_i \times L_j$   
            $rst = \min(rst, dist(p_i, p_j))$ 
```



```
1 Choose set  $S$  of  $n^{\frac{2}{3}}$  samples  
    $\delta = \min_{x,y \in S, x \neq y} (dist(x, y))$   $O(n^{\frac{8}{9}})$   
2 for  $i = 1$  to  $n$  do  
    $c = cell(p_i)$   $O(n)$   
   if not  $H.find(c)$  then  
      $H.add(\{c, idx = ++k\})$   
      $L[H.find(c).idx].add(p_i)$   
3 for  $i = 1$  to  $k$  do  
   foreach  $j$  in  $neighbor\_idx(cell_i)$  do  $O(n)$   
     foreach  $\{p_i, p_j\}$  in  $L_i \times L_j$   
        $rst = \min(rst, dist(p_i, p_j))$ 
```

Theorem

Let $f_i = |G_i|$ with $1 \leq i \leq k$ be the number of points in i -th non-empty cell and c, d some positive constants, then:

$$\sum_{i=1}^k f_i \leq c \cdot n \text{ with probability } 1 - \frac{1}{2^{n^d}}$$

Sampling Lemma

fa

Lemma 2

fa

Lemma 3

fa

- [BS76] Jon Louis Bentley and Michael Ian Shamos.
“Divide-and-conquer in multidimensional space”. In:
Proceedings of the eighth annual ACM symposium on Theory of computing. STOC '76. Hershey, Pennsylvania, USA: ACM, 1976, pp. 220–230. DOI: 10.1145/800113.803652. URL: <http://doi.acm.org/10.1145/800113.803652>.
- [CG89] Benny Chor and Oded Goldreich. “On the power of two-point based sampling”. In: *Journal of Complexity* 5.1 (1989), pp. 96–106.
- [Die+97] Martin Dietzfelbinger et al. “A reliable randomized algorithm for the closest-pair problem”. In: *Journal of Algorithms* 25.1 (1997), pp. 19–51.

- [FH78] Steven Fortune and John E Hopcroft. *A note on Rabin's nearest-neighbor algorithm*. Tech. rep. Cornell University, 1978.
- [KM95] Samir Khuller and Yossi Matias. “A simple randomized sieve algorithm for the closest-pair problem”. In: *Information and Computation* 118.1 (1995), pp. 34–37.
- [KT06] J. Kleinberg and E. Tardos. “Algorithm Design”. In: Pearson Education, 2006. Chap. 13 Randomized Algorithms.
- [Lip09] Richard J. Lipton. *Rabin Flips a Coin*. 2009. URL: <http://rjlipton.wordpress.com/2009/03/01/rabin-flips-a-coin/> (visited on 07/15/2013).
- [Rab76] Michael Oser Rabin. “Probabilistic algorithms”. In: *Algorithms and Complexity: New Directions and Recent Results*. Ed. by Joseph Frederick Traub. Academic Press, 1976, pp. 21–39.

[Web] URL: `http://www.cse.ust.hk/tcsc/comp670r/Class_1_Notes.ppt/`.

Load Balancing in Step 3

testc

Implementation of Hashing