

---

# **easyInterface**

***Release 0.0.5***

**Simon Ward**

**Feb 20, 2020**



## EXAMPLE GALLERIES

<b>1</b>	<b>Features of easyInterface</b>	<b>3</b>
<b>2</b>	<b>Projects using easyInterface</b>	<b>5</b>
<b>3</b>	<b>Installation</b>	<b>7</b>
3.1	Install via <code>pip</code> . . . . .	7
3.2	Install as an easyInterface developer . . . . .	7
3.3	Main Contents . . . . .	7
<b>4</b>	<b>Indices and tables</b>	<b>23</b>
	<b>Python Module Index</b>	<b>25</b>
	<b>Index</b>	<b>27</b>





easyInterface is a library to interface crystallographic calculators to front end applications, JuPyter notebooks and scripting interfaces.

The code of the project is on Github: [easyInterface](#)



## FEATURES OF EASYINTERFACE

Boom!





## PROJECTS USING EASYINTERFACE

easyInterface is currently being used in the following projects:

- [easyDiffraction](#) - A scientific software for modelling and analysis of the neutron diffraction data



## INSTALLATION

### 3.1 Install via pip

You can do a direct install via pip by using:

```
$ pip install easyInterface
```

### 3.2 Install as an easyInterface developer

You can get the latest development source from our [Github repository](#). You need `setuptools` installed in your system to install `easyInterface`. For example, you can do:

```
$ git clone https://github.com/easyDiffraction/easyInterface
$ cd easyInterface
$ pip install -r requirements.txt
$ pip install -e .
```

### 3.3 Main Contents

#### 3.3.1 Introduction to easyInterface

Here we can see some examples of `easyInterface` in action

#### 3.3.2 Scripted Examples

This section gathers examples which don't produce any figures. These examples show the basic features of `easyInterface`.

---

**Note:** Click [here](#) to download the full example code or to run this example in your browser via Binder

---

#### Creating a interface

This demonstrates an example of how to load an example and create a interface to a `crispy` calculator. Information about the project is then displayed.

```
import os
from easyInterface.Utils.Helpers import getExamplesDir
from easyInterface.Diffraction.Calculators import CryspyCalculator
from easyInterface.Diffraction.Interface import CalculatorInterface

data_dir = getExamplesDir()
main_rcif = os.path.join(data_dir, 'Fe304_powder-1d_neutrons-pol_5C1(LLB)', 'main.cif
↪')
calculator = CryspyCalculator(main_rcif)

interface = CalculatorInterface(calculator)

print(interface.project_dict)

print(interface.phasesIds())

print(interface.getPhase(interface.phasesIds()[0]))
```

**Total running time of the script:** ( 0 minutes 0.000 seconds)

---

**Note:** Click [here](#) to download the full example code or to run this example in your browser via Binder

---

### Creating a QT interface

This demonstrates an example of how to load an example and create a QT interface to a cryspy calculator. Information about the project is then displayed.

```
import os

from easyInterface.Utils.Helpers import getExamplesDir
from easyInterface.Diffraction.Calculators import CryspyCalculator
from easyInterface.Diffraction.QtInterface import QtCalculatorInterface

data_dir = getExamplesDir()
main_rcif = os.path.join(data_dir, 'Fe304_powder-1d_neutrons-pol_5C1(LLB)', 'main.cif
↪')
calculator = CryspyCalculator(main_rcif)

interface = QtCalculatorInterface(calculator, None)

print(interface.project_dict)

print(interface.phasesIds())

print(interface.getPhase(interface.phasesIds()[0]))
```

**Total running time of the script:** ( 0 minutes 0.000 seconds)

---

**Note:** Click [here](#) to download the full example code or to run this example in your browser via Binder

---

## Performing a fit

This demonstrates an example of how to load an example and create an interface to a crspsy calculator and then fit a value.

```
import os
from easyInterface.Utils.Helpers import getExamplesDir
from easyInterface.Diffraction.Calculators import CrspsyCalculator
from easyInterface.Diffraction.Interface import CalculatorInterface

data_dir = getExamplesDir()
main_rcif = os.path.join(data_dir, 'PbSO4_powder-1d_neutrons-unpol_D1A(ILL)', 'main.
↪cif')

calculator = CrspsyCalculator(main_rcif)

interface = CalculatorInterface(calculator)

print(interface.project_dict)

phase_ids = interface.phasesIds()

print(phase_ids)

phase = interface.getPhase(phase_ids[0])
phase['phasename'] = 'PbSO5'
interface.addPhase(phase)
interface.removePhase('PbSO5')

phase = interface.getPhase(phase_ids[0])
interface.setPhaseValue(phase_ids[0], ['atoms', 'Pb', 'fract_x'], 0.18)
interface.setPhases(phase)
print(phase)

interface.setPhaseRefine(phase_ids[0], ['atoms', 'Pb', 'fract_x'], True)

calc = interface.getCalculations()
print(calc)

res = interface.refine()

print(res)
```

Total running time of the script: ( 0 minutes 0.000 seconds)

## 3.3.3 Interface and Calculators

### easyInterface Interface

**class** easyInterface.Diffraction.Interface.CalculatorInterface (*calculator*)

Interface to calculators in the *easyInterface.Diffraction.Calculator* class.

**addExperiment** (*experiment*)

Add an experiment to the list of experiments in both the project dict and the calculator.

**Parameters** **experiment** (*Experiment*) – Experiment object to be added to the system.

**addExperimentDefinition** (*exp\_path*)

Add an experiment to be simulated from a cif file. Note that this will not have any crystallographic phases associated with it.

**Parameters** **exp\_path** (*str*) – Path to a experiment file (*.cif*)

**addPhase** (*phase*)

Add a new phases from a phase object to the list of existing crystal phases.

**Parameters** **phase** (*Phase*) – New phase to be added to the phase list.

**addPhaseDefinition** (*phase\_path*)

Add a new phases from a cif file to the list of existing crystal phases.

**Parameters** **phase\_path** (*str*) – Path to a phase definition file (*.cif*)

Example:

```
interface = CalculatorInterface(calculator)
phase_path = '~/Experiments/new_phase.cif'
interface.addPhaseDefinition(phase_path)
```

**addPhaseToExp** (*exp\_name, phase\_name, scale=0.0*)

Link a phase in the project dictionary to an experiment in the project dictionary. Links in the calculator will also be made.

**Parameters**

- **exp\_name** (*str*) – The name of the experiment
- **phase\_name** (*str*) – The name of the phase to be associated with the experiment
- **scale** (*float*) – The scale of the crystallographic phase in the experimental system.

**Raises** **KeyError** – If the *exp\_name* or *phase\_name* are unknown

**asCifDict** ()

Converts the project dictionary into a *cif* structure.

**Return type** *str*

**Returns** Project dictionary as a string encoded to the cif specification.

**asDict** ()

Converts the project dictionary into a standard python dictionary. If there is an error then an empty dictionary is returned.

**Return type** *dict*

**Returns** Python dictionary of the project dictionary.

**canRedo** ()

Informs on if the project dictionary can have redo() called. Typically called after an undo function call.

**Return type** *bool*

**Returns** Can or Can't redo the project dictionary.

**canUndo** ()

Informs on if the project dictionary can have undo() called.

**Return type** *bool*

**Returns** Can or Can't undo the project dictionary.

**clearUndoStack()**

Resets the Undo/Redo stack of the project dictionary.

ALL PREVIOUS UNDO/REDO EDITS WILL BE LOST

**experimentsCount()**

Returns number of experiments in the project dictionary.

**Return type** `int`

**experimentsIds()**

Returns labels of the experiments in the project dictionary.

**Return type** `List[str]`

**property final\_chi\_square**

Calculates the final chi squared of the simulation. Where the final chi squared is the chi squared divided by the number of data points.

**Return type** `float`

**Returns** Final chi squared

**getCalculation(*calculation\_name*)**

Returns a specified calculation from the project dictionary.

**Parameters** **calculation\_name** (`str`) – Name of the calculation to be returned.

**Raises** **KeyError** – If the calculation\_name is not known.

**Return type** `Calculation`

**Returns** Calculation requested.

**getCalculations()**

Returns all calculations in the project dictionary. Calculations will be updated if members of the phases or experiments section of the project dictionary has been modified.

**Return type** `Calculations`

**Returns** Calculations object containing all calculations.

**getDictByPath(*keys*)**

Returns an object in the project dictionary by the path to the object.

**Parameters** **keys** (`List[str]`) – Path to the object in the project dictionary

**Raises** **KeyError** – The supplied keys do not return an object in the project dictionary

**Return type** `Any`

**Returns** Object from the project dictionary.

**getExperiment(*experiment\_name*)**

Returns a experiment from the project dictionary by name if one is supplied. If the experiment name is none then all experiments are returned. If the experiment name does not exist **KeyError** is thrown.

**Parameters** **experiment\_name** (`Optional[str]`) – Name of the experiment to be returned or None for all experiments

**Return type** `Experiment`

**Returns** Copy of the project dictionaries phase object with name `experiment_name`

**Raises** **KeyError** – The supplied key is not a valid experiment name

**getPhase** (*phase\_name*)

Returns a phase from the project dictionary by name if one is supplied. If the phase name is none then all phases are returned. If the phase name does not exist **KeyError** is thrown.

**Parameters** **phase\_name** (`Optional[str]`) – Name of the phase to be returned or None for all phases

**Return type** *Phase*

**Returns** Copy of the project dictionaries phase object with name *phase\_name*

**Raises** **KeyError** – The supplied key is not a valid phase name

**name** ()

Returns the name of the current project.

**Return type** `str`

**Returns** Name of the current project

**phasesCount** ()

Returns number of phases in the project dictionary.

**Return type** `int`

**phasesIds** ()

Returns labels of the phases in the project dictionary.

**Return type** `List[str]`

**redo** ()

Perform an redo operation on the project dictionary.

**refine** ()

Perform a refinement on parameters which are marked in the project dictionary. If the refinement fails then only the “refinement\_message” will be returned in the results dictionary with an explanation of the error.

**Return type** `dict`

**Returns** Refinement results of the following fields: “num\_refined\_parameters”, “refinement\_message”, “nfev”, “nit”, “njev”, “final\_chi\_sq”

**removeExperiment** (*experiment\_name*)

Remove a experiment from both the project dictionary and the calculator.

**Parameters** **experiment\_name** (`str`) – Name of the experiment to be removed.

**removePhase** (*phase\_name*)

Remove a phase of a given name from the dictionary and the calculator object.

**Parameters** **phase\_name** (`str`) – name of the phase to be removed.

**removePhaseFromExp** (*exp\_name*, *phase\_name*)

Remove the link between an experiment and a crystallographic phase. Links in the calculator will also be removed.

**Parameters**

- **exp\_name** (`str`) – The name of the experiment.
- **phase\_name** (`str`) – The name of the phase to be removed.

**Raises** **KeyError** – If the *exp\_name* or *phase\_name* are unknown



**saveCifs** (*save\_dir*)

Write project cif files (*main.cif*, *experiments.cif* and *phases.cif*) to a user supplied directory. This contains all information needed to recreate the project dictionary.

**Parameters** **save\_dir** (*str*) – Directory to where the project cif files should be saved.

**setCalculatorFromProject** ()

Resets the project phases and experiments fields of the project dictionary from the calculator.

**Return type** *None*

**setDictByPath** (*keys*, *value*)

Set an object in the project dictionary by a key path.

**Parameters**

- **keys** (*List[str]*) – Path to the object to be modified/created
- **value** (*Any*) – Value to be set at the key path

**Return type** *None*

**setExperiment** (*experiment*)

Set phases (sample model tab in GUI)

**setExperimentDefinition** (*exp\_path*)

Set an experiment/s to be simulated from a cif file. Note that this will not have any crystallographic phases associated with it.

**Parameters** **exp\_path** (*str*) – Path to a experiment file (*.cif*)

**setExperiments** (*experiments*)

Set experiments (Experimental data tab in GUI)

**setPhase** (*phase*)

Set phases (sample model tab in GUI)

**setPhaseDefinition** (*phase\_path*)

Parse a phases cif file and replace existing crystal phases

**Parameters** **phase\_path** (*str*) – Path to new phase definition file (*.cif*)

Example:

```
interface = CalculatorInterface(calculator)
phase_path = '~/Experiments/phases.cif'
interface.setPhaseDefinition(phase_path)
```

**setPhases** (*phases=None*)

Set phases (sample model tab in GUI)

**setProjectFromCalculator** ()

Sets the project dictionary from the calculator given on initialisation. Calling this function will regenerate the project dictionary and changes may be lost.

**undo** ()

Perform an undo operation on the project dictionary.

**updateCalculations** ()

Calculate all experiments and populate the calculations field in the project dictionary. Note that this will only occur if a member of the phases or experiments section of the project dictionary has been modified since the last call to *updateCalculations*.

**updateExperiments ()**

Synchronise the project dictionary from the calculator.

**updatePhases ()**

Synchronise the phases in project dictionary by queering the calculator object.

**writeExpCif (save\_dir)**

Write the *experiments.cif* where all experiments in the project dictionary are saved to file. This includes the instrumental parameters and which phases are in the experiment/s

**Parameters** **save\_dir** (str) – Directory to where the experiment cif file should be saved.

**writeMainCif (save\_dir)**

Write the *main.cif* where links to the experiments and phases are stored and other generalised project information.

**Parameters** **save\_dir** (str) – Directory to where the main cif file should be saved.

**writePhaseCif (save\_dir)**

Write the *phases.cif* where all phases in the project dictionary are saved to file. This cif file should be compatible with other crystallographic software.

**Parameters** **save\_dir** (str) – Directory to where the phases cif file should be saved.

## easyInterfaces Project Dictionary

```
class easyInterface.Diffraction.Interface.ProjectDict (interface, app, calculator,
                                                    info, phases, experiments,
                                                    calculations)
```

This class deals with the creation and modification of the main project dictionary.

**classmethod default ()**

Create a default and empty project dictionary

**Return type** *ProjectDict*

**Returns** Default project dictionary with undo/redo functionality

**classmethod fromPars (experiments, phases, calculations={})**

Create a main project dictionary from phases and experiments.

**Parameters**

- **calculations** (Union[*Calculations*, *Calculation*, List[*Calculation*], None]) –
- **experiments** (Union[*Experiments*, *Experiment*, List[*Experiment*]]) – A collection of experiments to be compared to calculations
- **phases** (Union[*Phases*, *Phase*, List[*Phase*]]) – A Collection of crystallographic phases to be calculated

**Return type** *ProjectDict*

**Returns** Project dictionary with undo/redo

## easyInterface Crspsy Calculator

```
class easyInterface.Diffraction.Calculators.CrspsyCalculator (main_rcif_path=None)
```

```

asCifDict ()
    ...
    Return type dict

getPhases ()
    Set phases (sample model tab in GUI)
    Return type Phases

refine ()
    refinement ...

setExperiments (experiments)
    Set experiments (Experimental data tab in GUI)

setObjFromProjectDicts (phases, experiments)
    Set all the cryspy parameters from project dictionary

setPhases (phases)
    Set phases (sample model tab in GUI)

```

### 3.3.4 Container Classes

#### Phase Classes

```

class easyInterface.Diffraction.DataClasses.PhaseObj.Atom.ADP (u_11, u_22,
                                                                u_33, u_12, u_13,
                                                                u_23)
    Data store for Atom site anisotropic displacement parameters

class easyInterface.Diffraction.DataClasses.PhaseObj.Atom.Atom (atom_site_label,
                                                                type_symbol,
                                                                scat_length_neutron,
                                                                fract_x, fract_y,
                                                                fract_z, oc-
                                                                cupancy,
                                                                adp_type,
                                                                U_iso_or_equiv,
                                                                ADp, MSp)
    Storage for details about an atom

classmethod default (atom_site_label)
    Default constructor for an atom given a unique name in the phase
    Parameters atom_site_label (str) – The atoms unique name in the phase
    Return type Atom
    Returns Default atom with a given name

classmethod fromPars (atom_site_label, type_symbol, scat_length_neutron, fract_x, fract_y,
                                                                fract_z, occupancy, adp_type, U_iso_or_equiv, ADp=None, MSp=None)
    Atom constructor from parameters
    Parameters
    • atom_site_label (str) – The unique name of the atom in the phase
    • type_symbol (str) – The type of atom
    • scat_length_neutron (float) – Neutron scattering length

```

- **fract\_x** (float) – X position
- **fract\_y** (float) – Y position
- **fract\_z** (float) – Z position
- **occupancy** (float) – Site occupancy
- **adp\_type** (str) – ADP type code
- **U\_iso\_or\_equiv** (float) – Isotropic atomic displacement parameter

**Return type** *Atom*

**Returns** Fully formed atom data store

**classmethod** **fromXYZ** (*atom\_site\_label*, *type\_symbol*, *x*, *y*, *z*)

Construct an atom from name, type and position

**Parameters**

- **atom\_site\_label** (str) – The atoms unique name in the phase
- **type\_symbol** (str) – The type of atom
- **x** (float) – X position
- **y** (float) – Y position
- **z** (float) – Z position

**Return type** *Atom*

**Returns** Atom with name type and position filled in

**class** `easyInterface.Diffraction.DataClasses.PhaseObj.Atom`.**Atoms** (*atoms*)

Container for multiple atoms

**class** `easyInterface.Diffraction.DataClasses.PhaseObj.Atom`.**MSP** (*MSPtype*, *chi\_11*,  
*chi\_22*, *chi\_33*,  
*chi\_12*, *chi\_13*,  
*chi\_23*)

Data store for Atom site magnetic susceptibility parameters

**class** `easyInterface.Diffraction.DataClasses.PhaseObj.Cell`.**Cell** (*length\_a*,  
*length\_b*,  
*length\_c*, *angle\_alpha*,  
*angle\_beta*,  
*angle\_gamma*)

Container for crysolographic unit cell parameters

**classmethod** **default** ()

Default constructor for a crystallographic unit cell

**Return type** *Cell*

**Returns** Default crystallographic unit cell container

**classmethod** **fromPars** (*length\_a*, *length\_b*, *length\_c*, *angle\_alpha*, *angle\_beta*, *angle\_gamma*)

Constructor of a crystallographic unit cell when parameters are known

**Parameters**

- **length\_a** (float) – Unit cell length a
- **length\_b** (float) – Unit cell length b

- **length\_c** (float) – Unit cell length c
- **angle\_alpha** (float) – Unit cell angle alpha
- **angle\_beta** (float) – Unit cell angle beta
- **angle\_gamma** (float) – Unit cell angle gamma

**Return type** *Cell*

**Returns**

**class** easyInterface.Diffraction.DataClasses.PhaseObj.Phase.**Phase** (*name, space-group, cell, atoms, sites*)

Container for crysolographic phase information

**classmethod default** (*name*)

Default constructor for a crystallographic phase with a given name

**Return type** *Phase*

**Returns** Default empty phase with a name

**class** easyInterface.Diffraction.DataClasses.PhaseObj.Phase.**Phases** (*phases*)

Container for multiple phases

**renamePhase** (*old\_phase\_name, new\_phase\_name*)

Easy method of renaming a phase

**Parameters**

- **old\_phase\_name** (str) – phase name to be changed
- **new\_phase\_name** (str) – new phase name

**Return type** NoReturn

**class** easyInterface.Diffraction.DataClasses.PhaseObj.SpaceGroup.**SpaceGroup** (*crystal\_system, space\_group\_name\_H, space\_group\_IT\_number, origin\_choice*)

## Data Classes

**class** easyInterface.Diffraction.DataClasses.DataObj.Calculation.**BraggPeaks** (*bragg\_peaks*)

Container for multiple calculations

**class** easyInterface.Diffraction.DataClasses.DataObj.Calculation.**CalculatedPattern** (*x, y\_calc, y\_diff\_lower, y\_diff\_upper*)

Storage container for a calculated pattern

**class** easyInterface.Diffraction.DataClasses.DataObj.Calculation.**Calculation** (*name, bragg\_peaks, calculated\_pattern, limits*)

Storage container for calculations

```
class easyInterface.Diffraction.DataClasses.DataObj.Calculation.Calculations (calculations)
    Container for multiple calculations

class easyInterface.Diffraction.DataClasses.DataObj.Calculation.CrystalBraggPeaks (name,
                                                                                   h,
                                                                                   k,
                                                                                   l,
                                                                                   ttheta)

    Generator for HKL reflections and corresponding two theta.

class easyInterface.Diffraction.DataClasses.DataObj.Calculation.Limits (y_obs_lower=-
                                                                                   inf,
                                                                                   y_obs_upper=inf,
                                                                                   y_diff_upper=inf,
                                                                                   y_diff_lower=-
                                                                                   inf,
                                                                                   x_calc=None,
                                                                                   y_calc=None)

    Generator for limits of a dataset

class easyInterface.Diffraction.DataClasses.DataObj.Experiment.Background (ttheta,
                                                                                   in-
                                                                                   ten-
                                                                                   sity)

    Data store for the background data parameters

classmethod default ()
    Default constructor for a background point

    Return type Background

    Returns Default background data object

classmethod fromPars (ttheta, intensity)
    Constructor for background when two theta and intensity are known

    Parameters

    • ttheta (float) – Two Theta angle in degrees

    • intensity (float) – Value for intensity

    Return type Background

    Returns Background data dict

class easyInterface.Diffraction.DataClasses.DataObj.Experiment.Backgrounds (backgrounds)
    Store for a collection of background points
```

```

class easyInterface.Diffraction.DataClasses.DataObj.Experiment.Experiment (name,
                                                                    wave-
                                                                    length,
                                                                    off-
                                                                    set,
                                                                    phase,
                                                                    back-
                                                                    ground,
                                                                    res-
                                                                    o-
                                                                    lu-
                                                                    tion,
                                                                    mea-
                                                                    sured_pattern)
Experimental details data container

classmethod default (name)
    Default constructor for an Experiment

    Parameters name (str) – What the experiment should be called

    Return type Experiment

    Returns Default empty experiment

classmethod fromPars (name, wavelength, offset, scale, background, resolution, mea-
                        sured_pattern)
    Constructor of experiment from parameters

    Parameters
        • name (str) – What the experiment should be called
        • wavelength (float) – Experimental wavelength
        • offset (float) – Experimental offset
        • scale (float) – Scale parameter
        • background (Backgrounds) – Background model
        • resolution (Resolution) – Resolution model
        • measured_pattern (MeasuredPattern) – The Measured data

    Return type Experiment

    Returns Experiment from parameters

class easyInterface.Diffraction.DataClasses.DataObj.Experiment.ExperimentPhase (name,
                                                                    scale)
Storage container for the Experimental Phase details

classmethod default (name)
    Default experimental phase data container

    Return type ExperimentPhase

    Returns Default experimental phase data container

classmethod fromPars (name, scale)
    Parameter initialised experimental phase data container

    Return type ExperimentPhase

```

**Returns** Set experimental phase data container

**class** easyInterface.Diffraction.DataClasses.DataObj.Experiment.**ExperimentPhases** (*experiment\_phases*)  
Storage of multiple phase markers associated with experiments

**class** easyInterface.Diffraction.DataClasses.DataObj.Experiment.**Experiments** (*experiments*)  
Container for multiple experiments

**class** easyInterface.Diffraction.DataClasses.DataObj.Experiment.**MeasuredPattern** (*x*,  
*y\_obs*,  
*sy\_obs*,  
*y\_obs\_up=None*,  
*sy\_obs\_up=None*,  
*y\_obs\_down=None*,  
*sy\_obs\_down=None*)

Storage container for measured patterns

**classmethod default** (*polarised=False*)  
Default constructor for measured data container.

**Parameters** **polarised** (*bool*) – Should the container be initialised as a polarised data container?

**Returns** Empty data container

**property isPolarised**  
Is the measured data of a polarised type?

**Return type** *bool*

**Returns** True if it is from a polarised measurement, false otherwise

**property y\_obs\_lower**  
Lower data confidence bound.

**Return type** *list*

**Returns** value of lower confidence bound

**property y\_obs\_upper**  
Upper data confidence bound.

**Return type** *list*

**Returns** value of upper confidence bound

**class** easyInterface.Diffraction.DataClasses.DataObj.Experiment.**Resolution** (*u*,  
*v*,  
*w*,  
*x*,  
*y*)

Data store for the resolution parameters

**classmethod default** ()  
Default constructor for the resolution dict

**Return type** *Resolution*

**Returns** Default resolution dict

**classmethod fromPars** (*u, v, w, x, y*)  
Constructor when resolution parameters are known

**Parameters**



- **u** (float) – resolution parameter u
- **v** (float) – resolution parameter v
- **w** (float) – resolution parameter w
- **x** (float) – resolution parameter x
- **y** (float) – resolution parameter y

**Return type** *Resolution*

**Returns** Resolution dictionary with values set



## INDICES AND TABLES

- `genindex`
- `modindex`
- `search`



## PYTHON MODULE INDEX

### e

`easyInterface.Diffraction.DataClasses.DataObj.Calculation,`  
17  
`easyInterface.Diffraction.DataClasses.DataObj.Experiment,`  
18  
`easyInterface.Diffraction.DataClasses.PhaseObj.Atom,`  
15  
`easyInterface.Diffraction.DataClasses.PhaseObj.Cell,`  
16  
`easyInterface.Diffraction.DataClasses.PhaseObj.Phase,`  
17  
`easyInterface.Diffraction.DataClasses.PhaseObj.SpaceGroup,`  
17



# INDEX

## A

addExperiment () (easyInterface.Diffraction.Interface.CalculatorInterface method), 9

addExperimentDefinition () (easyInterface.Diffraction.Interface.CalculatorInterface method), 9

addPhase () (easyInterface.Diffraction.Interface.CalculatorInterface method), 10

addPhaseDefinition () (easyInterface.Diffraction.Interface.CalculatorInterface method), 10

addPhaseToExp () (easyInterface.Diffraction.Interface.CalculatorInterface method), 10

ADP (class in easyInterface.Diffraction.DataClasses.PhaseObj.Atom), 15

asCifDict () (easyInterface.Diffraction.Calculators.CrspyCalculator method), 14

asCifDict () (easyInterface.Diffraction.Interface.CalculatorInterface method), 10

asDict () (easyInterface.Diffraction.Interface.CalculatorInterface method), 10

Atom (class in easyInterface.Diffraction.DataClasses.PhaseObj.Atom), 15

Atoms (class in easyInterface.Diffraction.DataClasses.PhaseObj.Atom), 16

## B

Background (class in easyInterface.Diffraction.DataClasses.DataObj.Experiment), 18

Backgrounds (class in easyInterface.Diffraction.DataClasses.DataObj.Experiment), 18

BraggPeaks (class in easyInterface.Diffraction.DataClasses.DataObj.Calculation), 17

## C

CalculatedPattern (class in easyInterface.Diffraction.DataClasses.DataObj.Calculation), 17

Calculation (class in easyInterface.Diffraction.DataClasses.DataObj.Calculation), 17

Calculations (class in easyInterface.Diffraction.DataClasses.DataObj.Calculation), 17

CalculatorInterface (class in easyInterface.Diffraction.Interface), 9

canRedo () (easyInterface.Diffraction.Interface.CalculatorInterface method), 10

canUndo () (easyInterface.Diffraction.Interface.CalculatorInterface method), 10

Cell (class in easyInterface.Diffraction.DataClasses.PhaseObj.Cell), 16

clearUndoStack () (easyInterface.Diffraction.Interface.CalculatorInterface method), 10

CrspyCalculator (class in easyInterface.Diffraction.Calculators), 14

CrystalBraggPeaks (class in easyInterface.Diffraction.DataClasses.DataObj.Calculation), 18

## D

default () (easyInterface.Diffraction.DataClasses.DataObj.Experiment.Background class method), 18

default () (easyInterface.Diffraction.DataClasses.DataObj.Experiment.Experiment class method), 19

default () (easyInter- **F**  
 face.Diffraction.DataClasses.DataObj.ExperimentExperimentPhase  
 class method), 19 final\_chi\_square () (easyInter-  
 default () (easyInter- face.Diffraction.Interface.CalculatorInterface  
 face.Diffraction.DataClasses.DataObj.ExperimentMeasuredPattern property), 11  
 class method), 20 fromPars () (easyInter-  
 default () (easyInter- face.Diffraction.DataClasses.DataObj.Experiment.Background  
 face.Diffraction.DataClasses.DataObj.ExperimentResolution class method), 18  
 class method), 20 fromPars () (easyInter-  
 default () (easyInter- face.Diffraction.DataClasses.DataObj.Experiment.Experiment  
 face.Diffraction.DataClasses.PhaseObj.Atom.Atom fromPars () (easyInter-  
 class method), 15 class method), 19  
 default () (easyInter- face.Diffraction.DataClasses.DataObj.Experiment.ExperimentPh  
 face.Diffraction.DataClasses.PhaseObj.Cell.Cell fromPars () (easyInter-  
 class method), 16 class method), 19  
 default () (easyInter- face.Diffraction.DataClasses.DataObj.Experiment.Resolution  
 face.Diffraction.DataClasses.PhaseObj.Phase.Phase fromPars () (easyInter-  
 class method), 17 class method), 20  
 default () (easyInter- face.Diffraction.DataClasses.PhaseObj.Atom.Atom  
 face.Diffraction.Interface.ProjectDict class fromPars () (easyInter-  
 method), 14 class method), 15  
 class method), 16  
**E** fromPars () (easyInter-  
 easyInterface.Diffraction.DataClasses.DataObj.CalcDiffraction face.Diffraction.Interface.ProjectDict class  
 (module), 17 method), 14  
 easyInterface.Diffraction.DataClasses.DataObj.Experiment (easyInter-  
 (module), 18 face.Diffraction.DataClasses.PhaseObj.Atom.Atom  
 easyInterface.Diffraction.DataClasses.PhaseObj.Atom class method), 16  
 (module), 15  
 easyInterface.Diffraction.DataClasses.PhaseObj.Cell **G**  
 (module), 16 getCalculation () (easyInter-  
 easyInterface.Diffraction.DataClasses.PhaseObj.Phase face.Diffraction.Interface.CalculatorInterface  
 (module), 17 method), 11  
 easyInterface.Diffraction.DataClasses.PhaseObj.SpaceGroup (easyInter-  
 (module), 17 getCalculations () (easyInter-  
 Experiment (class in easyInter- face.Diffraction.Interface.CalculatorInterface  
 face.Diffraction.DataClasses.DataObj.Experiment) method), 11  
 18 getDictByPath () (easyInter-  
 ExperimentPhase (class in easyInter- face.Diffraction.Interface.CalculatorInterface  
 face.Diffraction.DataClasses.DataObj.Experiment) method), 11  
 19 getExperiment () (easyInter-  
 ExperimentPhases (class in easyInter- face.Diffraction.Interface.CalculatorInterface  
 face.Diffraction.DataClasses.DataObj.Experiment) method), 11  
 20 getPhase () (easyInter-  
 Experiments (class in easyInter- face.Diffraction.Interface.CalculatorInterface  
 face.Diffraction.DataClasses.DataObj.Experiment) method), 11  
 20 getPhases () (easyInter-  
 experimentsCount () (easyInter- face.Diffraction.Calculators.CrspyCalculator  
 face.Diffraction.Interface.CalculatorInterface method), 15  
 method), 11  
 experimentsIds () (easyInter- **I**  
 face.Diffraction.Interface.CalculatorInterface isPolarised () (easyInter-  
 method), 11 face.Diffraction.DataClasses.DataObj.Experiment.MeasuredPatt  
 property), 20



<b>L</b>			
Limits	(class in easyInterface.Diffraction.DataClasses.DataObj.Calculation), 18	Resolution	(class in easyInterface.Diffraction.DataClasses.DataObj.Experiment), 20
<b>M</b>		<b>S</b>	
MeasuredPattern	(class in easyInterface.Diffraction.DataClasses.DataObj.Experiment), 20	saveCifs()	(easyInterface.Diffraction.Interface.CalculatorInterface method), 12
MSP	(class in easyInterface.Diffraction.DataClasses.PhaseObj.Atom), 16	setCalculatorFromProject()	(easyInterface.Diffraction.Interface.CalculatorInterface method), 13
<b>N</b>		setDictByPath()	(easyInterface.Diffraction.Interface.CalculatorInterface method), 13
name()	(easyInterface.Diffraction.Interface.CalculatorInterface method), 12	setExperiment()	(easyInterface.Diffraction.Interface.CalculatorInterface method), 13
<b>P</b>		setExperimentDefinition()	(easyInterface.Diffraction.Interface.CalculatorInterface method), 13
Phase	(class in easyInterface.Diffraction.DataClasses.PhaseObj.Phase), 17	setExperiments()	(easyInterface.Diffraction.Calculators.CrspyCalculator method), 15
Phases	(class in easyInterface.Diffraction.DataClasses.PhaseObj.Phase), 17	setExperiments()	(easyInterface.Diffraction.Interface.CalculatorInterface method), 13
phasesCount()	(easyInterface.Diffraction.Interface.CalculatorInterface method), 12	setObjFromProjectDicts()	(easyInterface.Diffraction.Calculators.CrspyCalculator method), 15
phasesIds()	(easyInterface.Diffraction.Interface.CalculatorInterface method), 12	setPhase()	(easyInterface.Diffraction.Interface.CalculatorInterface method), 13
ProjectDict	(class in easyInterface.Diffraction.Interface), 14	setPhaseDefinition()	(easyInterface.Diffraction.Interface.CalculatorInterface method), 13
<b>R</b>		setPhases()	(easyInterface.Diffraction.Calculators.CrspyCalculator method), 15
redo()	(easyInterface.Diffraction.Interface.CalculatorInterface method), 12	setPhases()	(easyInterface.Diffraction.Interface.CalculatorInterface method), 13
refine()	(easyInterface.Diffraction.Calculators.CrspyCalculator method), 15	setProjectFromCalculator()	(easyInterface.Diffraction.Interface.CalculatorInterface method), 13
refine()	(easyInterface.Diffraction.Interface.CalculatorInterface method), 12	SpaceGroup	(class in easyInterface.Diffraction.DataClasses.PhaseObj.SpaceGroup), 17
removeExperiment()	(easyInterface.Diffraction.Interface.CalculatorInterface method), 12	<b>U</b>	
removePhase()	(easyInterface.Diffraction.Interface.CalculatorInterface method), 12	undo()	(easyInterface.Diffraction.Interface.CalculatorInterface method), 13
removePhaseFromExp()	(easyInterface.Diffraction.Interface.CalculatorInterface method), 12	updateCalculations()	(easyInterface.Diffraction.Interface.CalculatorInterface method), 13
renamePhase()	(easyInterface.Diffraction.DataClasses.PhaseObj.Phase.Phases method), 17		

`updateExperiments()` (*easyInterface.Diffraction.Interface.CalculatorInterface*  
*method*), 13

`updatePhases()` (*easyInterface.Diffraction.Interface.CalculatorInterface*  
*method*), 14

## W

`writeExpCif()` (*easyInterface.Diffraction.Interface.CalculatorInterface*  
*method*), 14

`writeMainCif()` (*easyInterface.Diffraction.Interface.CalculatorInterface*  
*method*), 14

`writePhaseCif()` (*easyInterface.Diffraction.Interface.CalculatorInterface*  
*method*), 14

## Y

`y_obs_lower()` (*easyInterface.Diffraction.DataClasses.DataObj.Experiment.MeasuredPattern*  
*property*), 20

`y_obs_upper()` (*easyInterface.Diffraction.DataClasses.DataObj.Experiment.MeasuredPattern*  
*property*), 20