

Differential Geometry of Curves and Surfaces

Manfredo P. do Carmo

May 11, 2026

解答 直观理解：当两条直母线 L_{t_1} 和 L_{t_2} 靠得很近时，公垂线段的长度趋于零，但其方向在极限时趋向于曲面的某个切方向。这个极限给出了中心点的几何定义。

解答：

设两直母线的方向分别为 $w(t_1)$ 和 $w(t_2)$ ，其公垂线为 $\mathbf{x}(t_1, v_1)\mathbf{x}(t_2, v_2)$ 。

(a) 设公垂线方向的单位向量为 $u(t_1, t_2)$ ，则

$$u(t_1, t_2) = \frac{\mathbf{x}(t_2, v_2) - \mathbf{x}(t_1, v_1)}{|\mathbf{x}(t_2, v_2) - \mathbf{x}(t_1, v_1)|}.$$

当 $t_2 \rightarrow t_1$ 时， L_{t_2} 趋近于 L_{t_1} ，公垂线段退化为曲面上某条切向量。这个极限方向就是曲面的切平面中的某个方向。

在 $v = \bar{v}$ 处，母线的切向量为 $\mathbf{x}_t = \alpha' + \bar{v}w'$ ，而 $\mathbf{x}_v = w$ 。公垂线同时正交于两条母线，在极限情况下它必正交于 $w(t_1)$ ，且与 $\alpha' + \bar{v}w'$ 共面。

由直纹面法向量的表达式 $N = \frac{w \wedge (\alpha' + \bar{v}w')}{|w \wedge (\alpha' + \bar{v}w')|}$ ，在极限点有 u 趋于与 N 正交的方向，即 u 在切平面内。而 $\langle w' \wedge w, N \rangle = 0$ 正是 $w' \wedge w$ 与 N 正交的条件。

(b) 为求 $\bar{v}$ ，设公垂线段中点为

$$\mathbf{m}(t_1, t_2) = \frac{1}{2}[\alpha(t_1) + v_1 w(t_1) + \alpha(t_2) + v_2 w(t_2)].$$

公垂线的方向向量为 $\mathbf{d} = \alpha(t_2) + v_2 w(t_2) - \alpha(t_1) - v_1 w(t_1)$ 。公垂条件： $\langle \mathbf{d}, w(t_1) \rangle = 0$ 且 $\langle \mathbf{d}, w(t_2) \rangle = 0$ 。

令 $t_2 = t_1 + \Delta t$ ， $v_2 = v_1 + \Delta v$ ，展开并取极限 $\Delta t \rightarrow 0$ ，可得

$$\Delta v \approx -\frac{\langle \alpha', w' \rangle}{\langle w', w' \rangle} \Delta t,$$

于是

$$\bar{v} = \lim_{t_2 \rightarrow t_1} v_1 = -\frac{\langle \alpha', w' \rangle}{\langle w', w' \rangle}.$$

这正是中心点的公式，故 $(t_1, \bar{v})$ 是母线 L_{t_1} 的中心点，所有这样的中心点构成的曲线就是线限制。

结论：当 $t_2 \rightarrow t_1$ 时，公垂线退化为切平面内的向量；中心点由 $\bar{v} = -\frac{\langle \alpha', w' \rangle}{\langle w', w' \rangle}$ 给出，这提供了线限制的另一种几何解释。□

练习 3-5, 5* —do Carmo, Exercise 3-5, 5 A right conoid is a ruled surface whose rulings L_t intersect perpendicularly at fixed axis r which does not meet the directrix $\alpha: I \rightarrow R^3$.

- Find a parametrization for the right conoid and determine a condition that implies it to be noncylindrical.
- Given a noncylindrical right conoid, find the line of striction and the distribution parameter.

练习 3-5, 6 —do Carmo, Exercise 3-5, 6 Let $\mathbf{x}(t, v) = \alpha(t) + vw(t)$ be a developable surface. Prove that at a regular point we have $\langle N_v, \mathbf{x}_v \rangle = \langle N_v, \mathbf{x}_t \rangle = 0$. Conclude that the tangent plane of a developable surface is constant along (the regular points of) a fixed ruling.

练习 3-5, 7 —do Carmo, Exercise 3-5, 7 Let S be a regular surface and let $C \subset S$ be a regular curve on S , nowhere tangent to an asymptotic direction. Consider the envelope of the family of tangent planes of S along C . Prove that the direction of the ruling that passes through a point $p \in C$ is conjugate to the tangent direction of C at p .

练习 3-5, 8 —do Carmo, Exercise 3-5, 8 Show that if $C \subset S^2$ is a parallel of unit sphere S^2 , then the envelope of tangent planes of S^2 along C is either a cylinder, if C is an equator, or a cone, if C is not an equator.

练习 3-5, 9* —do Carmo, Exercise 3-5, 9 (Focal Surfaces.) Let S be a regular surface without parabolic or umbilical points. Let $\mathbf{x}: U \rightarrow S$ be a parametrization of S such that the coordinate curves are lines of curvature. The parametrized surfaces $\mathbf{y}(u, v) = \mathbf{x}(u, v) + \rho_1 N(u, v)$ and $\mathbf{z}(u, v) = \mathbf{x}(u, v) + \rho_2 N(u, v)$, where $\rho_1 = 1/k_1$, $\rho_2 = 1/k_2$, are called focal surfaces of $\mathbf{x}(U)$. Prove that

- If $(k_1)_u$ and $(k_2)_v$ are nowhere zero, then $\mathbf{y}$ and $\mathbf{z}$ are regular parametrized surfaces.
- At the regular points, the directions on a focal surface corresponding to the principal directions on $\mathbf{x}(U)$ are conjugate.
- A focal surface, say $\mathbf{y}$, can be constructed as follows: Consider the line of curvature $\mathbf{x}(u, \text{const.})$ on $\mathbf{x}(U)$, and construct the developable surface generated by the normals of $\mathbf{x}(U)$ along the curve $\mathbf{x}(u, \text{const.})$. The line of striction of such a developable lies on $\mathbf{y}(U)$, and as $\mathbf{x}(u, \text{const.})$ describes $\mathbf{x}(U)$, this line describes $\mathbf{y}(U)$.

练习 3-5, 10* —do Carmo, Exercise 3-5, 10 Example 4 can be generalized as follows. A one-parameter differentiable family of planes $\{\alpha(t), N(t)\}$ is a correspondence which assigns to each $t \in I$ a point $\alpha(t) \in R^3$ and a unit vector $N(t) \in R^3$ in such a way that both α , and N are differentiable maps. A family $\{\alpha(t), N(t)\}$, $t \in I$, is said to be a family of tangent planes if $\alpha'(t) \neq 0$, $N'(t) \neq 0$, and $\langle \alpha'(t), N(t) \rangle = 0$ for all $t \in I$.

- Give a proof that a differentiable one-parameter family of tangent planes $\{\alpha(t), N(t)\}$ determines a differentiable one-parameter family of lines $\{\alpha(t), (N \wedge N')/|N'|\}$ which generates a developable surface $\mathbf{x}(t, v) = \alpha(t) + v \frac{N \wedge N'}{|N'|}$.
- Prove that if $\alpha'(t) \wedge (N(t) \wedge N'(t)) \neq 0$ for all $t \in I$, then the envelope is regular in a neighborhood of $v = 0$, and the unit normal vector of $\mathbf{x}$ at $(t, 0)$ is $N(t)$.
- Let $\alpha = \alpha(s)$ be a curve in R^3 parametrized by arc length. Assume that the curvature $k(s)$ and the torsion $\tau(s)$ of α are nowhere zero. Prove that the family of osculating planes $\{\alpha(s), b\{s\}\}$ is a one-parameter differentiable family of tangent planes and that the envelope of this family is the tangent surface to $\alpha(s)$.

练习 3-5, 11* —do Carmo, Exercise 3-5, 11 Let $\mathbf{x} = \mathbf{x}(u, v)$ be a regular parametrized surface. A parallel surface to $\mathbf{x}$ is a parametrized surface $\mathbf{y}(u, v) = \mathbf{x}(u, v) + aN(u, v)$, where a is a constant.

- Prove that $y_u \wedge y_v = (1 - 2Ha + Ka^2)(\mathbf{x}_u \wedge \mathbf{x}_v)$, where K and H are the Gaussian and mean curvatures of $\mathbf{x}$, respectively.
- Prove that at the regular points, the Gaussian curvature of $\mathbf{y}$ is $\frac{K}{1-2Ha+Ka^2}$ and the mean curvature of $\mathbf{y}$ is $\frac{H-Ka}{1-2Ha+Ka^2}$.
- Let a surface $\mathbf{x}$ have constant mean curvature equal to $c \neq 0$ and consider the parallel surface to $\mathbf{x}$ at a distance $1/2c$. Prove that this parallel surface has constant Gaussian curvature equal to $4c^2$.

练习 3-5, 12* —do Carmo, Exercise 3-5, 12 Prove that there are no compact (i.e., bounded and closed in R^3) minimal surfaces.

练习 3-5, 13* —do Carmo, Exercise 3-5, 13 a. Let S be a regular surface without umbilical points. Prove that S is a minimal surface if and only if the Gauss map $N: S \rightarrow S^2$ satisfies, for all $p \in S$ and all $w_1, w_2 \in T_p(S)$, $\langle dN_p(w_1), dN_p(w_2) \rangle_{N(p)} = \lambda(p) \langle w_1, w_2 \rangle_p$, where $\lambda(p) \neq 0$ is a number which depends only on p .

- Let $\mathbf{x}: U \rightarrow S^2$ be a parametrization of the unit sphere S^2 by stereographic projection. Consider a neighborhood V of a point p of the minimal surface S in part a such that $N: S \rightarrow S^2$ restricted to V is a diffeomorphism. Prove that the parametrization $y = N^{-1} \circ \mathbf{x}: U \rightarrow S$ is isothermal.

练习 3-5, 14* —do Carmo, Exercise 3-5, 14 When two differentiable functions $f, g: U \subset R^2 \rightarrow R$ satisfy the Cauchy-Riemann equations $\frac{\partial f}{\partial u} = \frac{\partial g}{\partial v}$, $\frac{\partial f}{\partial v} = -\frac{\partial g}{\partial u}$, they are easily seen to be harmonic; in this situation, f and g are said to be harmonic conjugate. Let $\mathbf{x}$ and $\mathbf{y}$ be isothermal parametrizations of minimal surfaces such that their component functions are pairwise harmonic conjugate; then $\mathbf{x}$ and $\mathbf{y}$ are called conjugate minimal surfaces. Prove that

- The helicoid and the catenoid are conjugate minimal surfaces.
- Given two conjugate minimal surfaces, $\mathbf{x}$ and $\mathbf{y}$, the surface $\mathbf{z} = (\cos t)\mathbf{x} + (\sin t)\mathbf{y}$ is again minimal for all $t \in R$.
- All surfaces of the one-parameter family have the same fundamental form: $E = \langle \mathbf{x}_u, \mathbf{x}_u \rangle = \langle \mathbf{y}_v, \mathbf{y}_v \rangle$, $F = 0$, $G = \langle \mathbf{x}_v, \mathbf{x}_v \rangle = \langle \mathbf{y}_u, \mathbf{y}_u \rangle$.

附录：详细推导

球面的第二基本形式推导

考虑单位球面在地理坐标下的参数化：

$$\mathbf{x}(\theta, \varphi) = (\sin \theta \cos \varphi, \sin \theta \sin \varphi, \cos \theta).$$

步骤 1：计算一阶偏导数

$$\mathbf{x}_\theta = (\cos \theta \cos \varphi, \cos \theta \sin \varphi, -\sin \theta), \quad \mathbf{x}_\varphi = (-\sin \theta \sin \varphi, \sin \theta \cos \varphi, 0).$$

步骤 2: 计算单位法向量

$$\mathbf{x}_\theta \times \mathbf{x}_\varphi = (\sin^2 \theta \cos \varphi, \sin^2 \theta \sin \varphi, \sin \theta \cos \theta).$$

取模长 $\|\mathbf{x}_\theta \times \mathbf{x}_\varphi\| = \sin \theta$, 得

$$N = (\sin \theta \cos \varphi, \sin \theta \sin \varphi, \cos \theta). \quad (\text{A3-1})$$

注意这里 $N = \mathbf{x}$ ——球面上每一点的法向量恰好等于该点的位置向量。

步骤 3: 计算二阶偏导数

$$\mathbf{x}_{\theta\theta} = (-\sin \theta \cos \varphi, -\sin \theta \sin \varphi, -\cos \theta), \quad \mathbf{x}_{\theta\varphi} = (-\cos \theta \sin \varphi, \cos \theta \cos \varphi, 0), \quad \mathbf{x}_{\varphi\varphi} = (-\sin \theta \cos \varphi, -$$

步骤 4: 计算第二基本形式系数

$$\begin{aligned} L = \langle \mathbf{x}_{\theta\theta}, N \rangle &= (-\sin \theta \cos \varphi)(\sin \theta \cos \varphi) + (-\sin \theta \sin \varphi)(\sin \theta \sin \varphi) + (-\cos \theta)(\cos \theta) \\ &= -\sin^2 \theta - \cos^2 \theta = -1, \end{aligned}$$

$$M = \langle \mathbf{x}_{\theta\varphi}, N \rangle = 0, \quad N_{\text{coeff}} = \langle \mathbf{x}_{\varphi\varphi}, N \rangle = -\sin^2 \theta. \quad (\text{A3-2})$$

结论: 球面的第二基本形式系数为 $L = -1$, $M = 0$, $N_{\text{coeff}} = -\sin^2 \theta$. 结合第一基本形式 $E = 1$, $F = 0$, $G = \sin^2 \theta$, 可得 $S_p = I$ (恒等变换), 因此 $\kappa_1 = \kappa_2 = 1$ 。

注意在很多教材中, 球面的 Weingarten 映射定义为 $S_p = -dN_p$, 此时 $dN_p(v) = -v$, $S_p(v) = v$ (恒等变换), 与我们的定义一致。但在法曲率计算 $\kappa_n = \langle S_p(v), v \rangle$ 中, 法曲率为正值。这与球面“向法向量方向弯曲”的直觉一致。

旋转抛物面的第二基本形式推导

考虑旋转抛物面 $z = x^2 + y^2$, 参数化为

$$\mathbf{x}(u, v) = (u, v, u^2 + v^2).$$

步骤 1: 一阶偏导数

$$\mathbf{x}_u = (1, 0, 2u), \quad \mathbf{x}_v = (0, 1, 2v).$$

步骤 2: 单位法向量

$$\mathbf{x}_u \times \mathbf{x}_v = (-2u, -2v, 1), \quad \|\mathbf{x}_u \times \mathbf{x}_v\| = \sqrt{1 + 4u^2 + 4v^2}.$$

$$N = \frac{(-2u, -2v, 1)}{\sqrt{1 + 4u^2 + 4v^2}}. \quad (\text{A3-3})$$

步骤 3: 二阶偏导数

$$\mathbf{x}_{uu} = (0, 0, 2), \quad \mathbf{x}_{uv} = (0, 0, 0), \quad \mathbf{x}_{vv} = (0, 0, 2).$$

步骤 4: 第二基本形式系数

$$L = \langle \mathbf{x}_{uu}, N \rangle = \frac{2}{\sqrt{1 + 4u^2 + 4v^2}}, \quad M = \langle \mathbf{x}_{uv}, N \rangle = 0, \quad N_{\text{coeff}} = \langle \mathbf{x}_{vv}, N \rangle = \frac{2}{\sqrt{1 + 4u^2 + 4v^2}}. \quad (\text{A3-4})$$

在原点 $(0,0)$ 处, $L = N_{\text{coeff}} = 2$, $M = 0$ 。

此时第一基本形式为 $E = 1$, $F = 0$, $G = 1$, 因此

$$S_p = \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix}^{-1} \begin{pmatrix} 2 & 0 \\ 0 & 2 \end{pmatrix} = \begin{pmatrix} 2 & 0 \\ 0 & 2 \end{pmatrix} = 2I.$$

所以 $\kappa_1 = \kappa_2 = 2$, $K = 4 > 0$ (椭圆点), $H = 2$ 。

旋转抛物面在原点的 Dupin 指示线是一个椭圆, 因为 $K > 0$, 所有方向的法曲率同号。

Christoffel 符号与 Codazzi-Mainardi 方程

Christoffel 符号 Γ_{ij}^k 由第一基本形式的系数定义为:

$$\Gamma_{ij}^k = \frac{1}{2} \sum_{m=1}^2 g^{km} \left(\frac{\partial g_{im}}{\partial j} + \frac{\partial g_{jm}}{\partial i} - \frac{\partial g_{ij}}{\partial m} \right), \quad (\text{A3-5})$$

其中 $(g_{ij}) = \begin{pmatrix} E & F \\ F & G \end{pmatrix}$, (g^{ij}) 是其逆矩阵。

Codazzi-Mainardi 方程的直观含义是: 第二基本形式的”协变导数”必须对称。具体形式为:

$$\begin{aligned} \frac{\partial L}{\partial v} - \frac{\partial M}{\partial u} &= L\Gamma_{12}^1 + M(\Gamma_{12}^2 - \Gamma_{11}^1) - N_{\text{coeff}}\Gamma_{11}^2, \\ \frac{\partial N_{\text{coeff}}}{\partial u} - \frac{\partial M}{\partial v} &= L\Gamma_{22}^1 + M(\Gamma_{22}^2 - \Gamma_{21}^1) - N_{\text{coeff}}\Gamma_{21}^2. \end{aligned} \quad (\text{A3-6})$$

这些方程的深层含义是: 第一基本形式和第二基本形式不是独立的——它们必须协调一致, 才能描述一个真实嵌入 $\mathbb{R}^3$ 的曲面。这种协调性正是可积性条件的本质。

附录：问答记录

本节记录学习 Do Carmo 《曲线与曲面的微分几何》过程中的问答与思考。

待记录问题

本节将随学习进度逐步填充以下问题：

- 曲率与挠率的直观几何意义
- Frenet-Serret 公式的推导细节
- 局部标准形式的系数解释
- 全曲率定理的证明思路
- 等周不等式的证明

历史悠久的问答

曲率的直观理解

问：曲率 $k(s) = \|\alpha''(s)\|$ 的直观几何意义是什么？

答：对于单位速度曲线 $\alpha(s)$ ，速度向量 $\alpha'(s)$ 是单位切向量，其模长恒为 1。加速度向量 $\alpha''(s)$ 描述速度向量方向的变化率。 $\|\alpha''(s)\|$ 正是这种方向变化的速率——即曲线在每一点的弯曲程度。直线速度方向不变， $\alpha''(s) = 0$ ；圆周速度方向匀速变化， $\|\alpha''(s)\| = 1/a$ (a 为半径)。

挠率与扭曲

问：挠率 $\tau(s)$ 描述的是什么？

答：挠率描述曲线在空间中的“扭曲”程度。曲率只告诉我们曲线在密切平面内如何弯曲，但曲线可能“偏离”密切平面——这种偏离的速度由挠率度量。对于平面曲线， $\alpha', \alpha'', \alpha'''$ 始终共面， $\det(\alpha', \alpha'', \alpha''') = 0$ ，故挠率为零。螺旋线的挠率为常数，描述其均匀扭曲的特性。

曲率另一个表达式的推导

背景：命题 1-5, 2 给出了曲率在一般参数化下的表达式：

$$k(t) = \frac{\|\alpha'(t) \times \alpha''(t)\|}{\|\alpha'(t)\|^3}.$$

目标：从单位速度曲率的定义 $k(s) = \|\alpha''(s)\|$ 推导出一般参数下的表达式。

推导步骤：

设 $\alpha(t)$ 是正则曲线， $s = s(t)$ 是弧长参数。回忆弧长公式：

$$s(t) = \int_{t_0}^t \|\alpha'(u)\| du, \quad \frac{ds}{dt} = \|\alpha'(t)\|.$$

由链式法则， $\alpha'(s) = \frac{\alpha'(t)}{ds/dt} = \frac{\alpha'(t)}{\|\alpha'(t)\|}$ 。

进一步，

$$\alpha''(s) = \frac{d}{ds} \alpha'(s) = \frac{d}{dt} \left(\frac{\alpha'(t)}{\|\alpha'(t)\|} \right) \cdot \frac{dt}{ds}.$$

经过计算（利用向量积的模长公式 $\|u \times v\| = \|u\| \|v\| \sin \theta$ ），可得：

$$\|\alpha''(s)\| = \frac{\|\alpha'(t) \times \alpha''(t)\|}{\|\alpha'(t)\|^3}.$$

因此在参数 t 下，曲率为 $k(t) = \frac{\|\alpha'(t) \times \alpha''(t)\|}{\|\alpha'(t)\|^3}$ 。

挠率另一个表达式的推导

背景：命题 1-5, 4 给出了挠率的另一个表达式：

$$\tau(s) = -\langle \mathbf{b}'(s), \mathbf{n}(s) \rangle.$$

目标：从挠率的行列式定义 $\tau = \frac{\det(\alpha', \alpha'', \alpha''')}{k^2}$ 推导出 $\tau = -\langle \mathbf{b}', \mathbf{n} \rangle$ 。

推导步骤：

由 Frenet 标架的定义： $\mathbf{t} = \alpha'$ ， $\mathbf{n} = \frac{\alpha''}{k}$ ， $\mathbf{b} = \mathbf{t} \times \mathbf{n}$ 。

对 $\mathbf{b} = \mathbf{t} \times \mathbf{n}$ 求导：

$$\mathbf{b}' = \mathbf{t}' \times \mathbf{n} + \mathbf{t} \times \mathbf{n}' = (k\mathbf{n}) \times \mathbf{n} + \mathbf{t} \times \mathbf{n}' = \mathbf{t} \times \mathbf{n}'.$$

由于 $\mathbf{n}'$ 可以分解为 $A\mathbf{t} + B\mathbf{n} + C\mathbf{b}$ （由正交性），且 $\|\mathbf{n}\| = 1$ 蕴含 $\langle \mathbf{n}', \mathbf{n} \rangle = 0$ ，故 $\mathbf{n}' = -k\mathbf{t} + \tau\mathbf{b}$ （这正是 Frenet-Serret 公式的第二式）。

于是

$$\mathbf{b}' = \mathbf{t} \times (-k\mathbf{t} + \tau\mathbf{b}) = \mathbf{t} \times \tau\mathbf{b} = \tau(\mathbf{t} \times \mathbf{b}) = -\tau\mathbf{n},$$

因为 $\mathbf{t} \times \mathbf{b} = -\mathbf{b} \times \mathbf{t} = -\mathbf{n}$ 。

因此 $\mathbf{b}' = -\tau\mathbf{n}$ ，取与 $\mathbf{n}$ 的内积即得

$$\tau = -\langle \mathbf{b}', \mathbf{n} \rangle.$$

Frenet-Serret 公式的直观解释与推导思路

背景：Frenet-Serret 公式是曲线局部理论的核心：

$$\begin{cases} \mathbf{t}' = k\mathbf{n}, \\ \mathbf{n}' = -k\mathbf{t} + \tau\mathbf{b}, \\ \mathbf{b}' = -\tau\mathbf{n}. \end{cases}$$

直观解释：

可以将 Frenet 标架 $\{\mathbf{t}, \mathbf{n}, \mathbf{b}\}$ 想象为沿曲线运动的“观察者”的坐标系。这个坐标系随着曲线在空间中移动而转动和摆动。

- $\mathbf{t}' = k\mathbf{n}$ ：切向量的变化完全由法向分量决定，系数 k 正是弯曲程度—— k 越大，切向量转动得越快。
- $\mathbf{n}' = -k\mathbf{t} + \tau\mathbf{b}$ ：主法向量的变化涉及两个方面： $-k\mathbf{t}$ 部分反映了主法向量试图“追回”切向量方向变化（与 $\mathbf{t}' = k\mathbf{n}$ 相呼应），而 $\tau\mathbf{b}$ 部分则反映了曲线在空间中的扭曲。
- $\mathbf{b}' = -\tau\mathbf{n}$ ：副法向量的变化只与挠率有关——它描述了密切平面的旋转。

几何图像：想象一个骑自行车的人沿着曲线运动。人的朝向就是 $\mathbf{t}$ 方向，车把的指向是 $\mathbf{n}$ ，而 $\mathbf{b}$ 则垂直于前两者。曲率 k 决定了人在转弯时需要倾斜多少（这对应 $\mathbf{t}' = k\mathbf{n}$ ），而挠率 τ 则描述了车子在转弯的同时是否还在上下颠簸（对应 $\mathbf{b}' = -\tau\mathbf{n}$ ）。

推导思路（简述）：

Frenet-Serret 公式可从正交性条件出发推导。由于 $\{\mathbf{t}, \mathbf{n}, \mathbf{b}\}$ 是标准正交基，有 $\langle \mathbf{t}, \mathbf{n} \rangle = 0$, $\langle \mathbf{t}, \mathbf{b} \rangle = 0$, $\langle \mathbf{n}, \mathbf{b} \rangle = 0$ ，以及 $\|\mathbf{t}\| = \|\mathbf{n}\| = \|\mathbf{b}\| = 1$ 。

对正交性条件求导，并利用 $\mathbf{b} = \mathbf{t} \times \mathbf{n}$ ，可以逐步得到三个公式。例如：

1. 由 $\langle \mathbf{t}, \mathbf{n} \rangle = 0$ 求导： $\langle \mathbf{t}', \mathbf{n} \rangle + \langle \mathbf{t}, \mathbf{n}' \rangle = 0$ 。
2. 由于 $\mathbf{t}' = \alpha''$ 与 $\mathbf{n}$ 平行（定义 $\mathbf{n} = \mathbf{t}'/|\mathbf{t}'|$ ），得 $\langle \mathbf{t}', \mathbf{n} \rangle = |\mathbf{t}'| = k$ 。
3. 结合 $\|\mathbf{n}'\|$ 的计算，可得 $\mathbf{t}' = k\mathbf{n}$ 和 $\mathbf{n}' = -k\mathbf{t} + \tau\mathbf{b}$ 。

详细证明见 do Carmo, Proposition 1-5, 4。