



Indian AI – 70

The Indian AI 70 is an advanced AI-based biometric access control and time attendance device designed for secure and touchless authentication. Equipped with high-speed facial recognition, in-glass fingerprint technology, card and password authentication, the device ensures accurate and reliable identification in less than a second. With its 7-inch touch display, IP65-rated rugged design, multiple communication options, and seamless integration with access control and attendance software, the Indian AI 70 is an ideal solution for offices, industries, factories, corporate buildings, and high-security environments.

Specification	Details
Model	Indian AI 70
Display	7" TFT Color Touch LED Screen (600 × 1024)
Camera	WDR Binocular Camera @ 1MP
Operating System	Linux
CPU	Dual Core @ 1GHz
Memory	RAM: 512MB, ROM: 8GB
Speaker	8 ohm @ 1W
Supplement Light	No
Fingerprint Sensor	In-Glass Fingerprint (Z-ID)
Authentication Methods	Fingerprint / Face / Card / Password (Virtual Keypad)
Fingerprint Capacity	10,000 Templates (1:N)
Face Capacity	10,000 Templates (1:N)
Card Capacity	50,000 Cards (1:N)
User Capacity	50,000 Users (1:N)
Transaction Capacity	300,000 Logs
Password Length	Maximum 8 Digits
Authentication Speed	Fingerprint: < 0.5 sec, Face: < 0.35 sec
Facial Recognition Distance	30 cm to 200 cm
FAR (False Acceptance Rate)	Face ≤ 0.01%, Fingerprint ≤ 0.0001%
FRR (False Rejection Rate)	Face ≤ 0.02%, Fingerprint ≤ 0.01%
Card Type	ID Card @ 125 kHz (Standard), IC Card @ 13.56 MHz (Optional)
Communication	TCP/IP ×1
Wi-Fi	IEEE802.11 b/g/n/ax @ 2.4 GHz (Optional)
Wiegand	Input or Output ×1
USB Port	USB Type-A (USB Drive Only) ×1
Auxiliary Inputs	Aux Input ×1, Electric Lock ×1, Door Sensor ×1, Exit Button ×1, 12V Output ×1
Standard Functions	ADMS, DST, Photo Capture, Event Photo Capture, 14-digit User ID, Access Levels, Groups, Holidays, Anti-Passback, Record Query, Schedule Bell, Tamper Switch Alarm, Automatic Status Switch, Multiple Authentication Methods, SIP Client (v2.0), ONVIF Support, AC Push & TA Push Protocol Switch, HTTPS/SSH Backend Access, T9 Keyboard
Access Control Interface	RS485 (RS485 Card Reader / Biometric Reader)
Power Supply	DC 12V 3A (Optional)
Operating Temperature	-5°C to 45°C
Operating Humidity	10% to 90% RH (Non-condensing)
Dimensions	238 mm × 115 mm × 22.3 mm (L × W × H)
Net Weight	0.622 Kg
Ingress Protection	IP65 (Waterproof & Dustproof)
Certifications	ISO14001, ISO9001, CE, FCC, RoHS