Coldstone Web data warehouse

Data dictionary for the Nigeria and Kenya schemas

Database	coldstone_web
Platform	Amazon Redshift Serverless, workgroup eatngo-analytics (us-east-1)
Nigeria tables	coldstone_web_ng_analytics
Kenya tables	coldstone_web_ke_analytics
Source	Coldstone Creamery online ordering platform (API), Nigeria and Kenya
Refreshed	Daily, with the previous day's data (D-1); history from each country's first order
Tables	24 per country, identical in both schemas

This document explains what each table and column in the Coldstone warehouse contains, how the tables connect, and the conventions to keep in mind when querying them. It is written for anyone building reports or answering questions with this data.

1. The two schemas

Nigeria and Kenya have their own copy of the same 24 tables. Column names, types and meanings are identical; only the data and the currency differ. To compare countries, query both schemas and combine the results (for example with UNION ALL), adding a country column of your own.

Schema	Country	Currency	Use it for
`coldstone_web_ng_analytics`	Nigeria	Naira (NGN), stored in kobo	Reports and analysis
`coldstone_web_ke_analytics`	Kenya	Kenyan shilling (KES), stored in cents	Reports and analysis
`coldstone_web_ng_staging`	Nigeria	-	Internal to the load. Do not query: emptied and refilled every run.
`coldstone_web_ke_staging`	Kenya	-	Internal to the load. Do not query.

2. Things to know before querying

Topic	What it means
Money is in minor units	All amounts (prices, totals, balances) are whole numbers of kobo (Nigeria) or cents (Kenya). Divide by 100 to get naira or shillings: `total_price / 100.0`. Kenya amounts are in KES and are never converted to naira.
Times are in UTC	Every timestamp is stored in UTC. Business days follow local time: Lagos is UTC+1 and Nairobi is UTC+3. Convert before grouping by day: `CONVERT_TIMEZONE('UTC', 'Africa/Lagos', created_at)` (use 'Africa/Nairobi' for Kenya). An order at 00:30 in Lagos is stored as 23:30 the previous day.
IDs	Every record has a 24-character ID from the source platform. In each table it is called `external_id`; in other tables the same ID appears as `<thing>_external_id` (e.g. `orders.branch_external_id` = `branches.external_id`).
Latest state, no duplicates	Each order, customer and so on appears once, showing its latest known state. When an order's status changes, its row is updated rather than a new row being added. Line tables (order items, options, timeline) are replaced together with their order.
Daily refresh (D-1)	Each morning the pipeline loads everything created on the previous day (00:00-24:00 local time), plus older records that changed. Today's activity appears tomorrow. Reference tables (branches, menu, staff, roles, wallets, discounts) are reloaded in full every day.
loaded_at	Every table has a `loaded_at` column: when the pipeline last wrote that row (UTC). It is not a business date; use `created_at` for when something happened.
Personal data	Columns marked *(personal data)* hold names, emails, phone numbers or bank details. Only use them where you have a legitimate need, and keep them out of widely shared reports.
Not included	Chowdeck orders (handled by a separate pipeline) and customer messages (not available from the source).

3. Tables at a glance

Grouped by subject. 'Incremental' tables grow day by day; 'full snapshot' tables are reloaded in full every day; line tables are replaced together with the record they belong to.

Table	Subject	One row per	What it holds
orders	Sales	customer order	Every online order placed with Coldstone: who ordered, from which branch, how it was paid and delivered, its current status and its value.
order_items	Sales	product line within an order	The products in each order, with the price and quantity of each line.
order_item_modifiers	Sales	option chosen on an order line	Customisations picked for each product in an order, such as toppings, flavours and add-ons.
order_timeline	Sales	step in an order's progress	The milestones each order goes through, for measuring preparation and delivery times.
customers	Customers	registered customer	People who have registered or ordered on the Coldstone website.
wallet_transactions	Wallet & settlement	money movement in a branch wallet	Money coming into and out of each branch's wallet: sales credited, settlements paid out.
wallets	Wallet & settlement	branch wallet	Each branch's wallet balance and the bank account its settlements are paid to.
menu_items	Menu	product	Everything that can be sold: menu products and the products used as options (toppings, flavours, add-ons).
menu_categories	Menu	menu category	Headings that group products on the menu.
menu_modifiers	Menu	option group on a product	The choices offered on a product, e.g. 'pick a flavour' or 'add toppings', and the rules for how many can be picked.
modifier_items	Menu	product available in an option group	Which products can be picked in each option group.
discounts	Promotions	discount / promo code	Promotions set up in the platform and their rules. (Kenya has none at the time of writing.)
discount_applicable_items	Promotions	product a discount applies to	Products a discount can be used on.
discount_combo_items	Promotions	product in a combo discount	Products that together make up a combo deal.
branches	Branches & staff	branch (store)	Every Coldstone branch: name, location and settings.
members	Branches & staff	staff user	Staff who use the Coldstone dashboard (store staff, admins, customer support).
branch_members	Branches & staff	staff user and home branch	Links each staff user to their home branch.
member_additional_branches	Branches & staff	staff user and extra branch	Extra branches a staff user can work in, besides their home branch.
member_roles	Branches & staff	staff user and role	Roles assigned to each staff user.
roles	Branches & staff	role	Staff roles, e.g. Stores, Super Admin, Customer Support.
permissions	Branches & staff	permission	Areas of the dashboard a role can be given access to.
sub_permissions	Branches & staff	detailed permission	Finer-grained actions within a permission.

Table	Subject	One row per	What it holds
activity_logs	Activity (audit trail)	action taken in the platform	An audit trail of actions: logins, menu changes such as marking items out of stock, and customer actions.
activity_initiators	Activity (audit trail)	person behind an action	The person who performed each action in activity_logs.

4. How the tables connect

The main joins. Every arrow is 'many rows on the left belong to one row on the right'.

From	Column	To
order_items, order_item_modifiers, order_timeline	order_external_id	orders.external_id
order_item_modifiers	order_external_id, line_no	order_items (same two columns)
orders, customers, wallets, wallet_transactions, menu_items, members, activity_logs	branch_external_id	branches.external_id
orders	customer_external_id	customers.external_id
order_items	product_external_id	menu_items.external_id
menu_items	category_external_id	menu_categories.external_id
menu_modifiers	menu_item_external_id	menu_items.external_id
modifier_items	modifier_external_id / menu_item_external_id	menu_modifiers / menu_items
discount_applicable_items, discount_combo_items	discount_external_id / item_external_id	discounts / menu_items
branch_members, member_additional_branches, member_roles	member_external_id	members.external_id
member_roles	role_external_id	roles.external_id
sub_permissions	permission_external_id	permissions.external_id
activity_initiators	activity_external_id	activity_logs.external_id

5. Table reference

Each table below exists in both `coldstone_web_ng_analytics` and `coldstone_web_ke_analytics`. 'Key' marks the columns that uniquely identify a row.

5.1 orders

Sales. Every online order placed with Coldstone: who ordered, from which branch, how it was paid and delivered, its current status and its value.

One row per	customer order
Unique key	external_id
Refresh	Incremental. New and updated orders are added every day (D-1). Orders whose status changes later are updated in place, so each order always shows its latest state.
Joins to	order_items, order_item_modifiers, order_timeline on order_external_id = orders.external_id branches on branch_external_id = branches.external_id customers on customer_external_id = customers.external_id
Storage	distributed by (external_id) sorted by (created_at, branch_external_id)

Column	Type	Description
`external_id` Key	`VARCHAR(24)`	Order ID (unique).
`reference`	`VARCHAR(64)`	Human-readable order reference shown to customers and staff.
`payment_method`	`VARCHAR(64)`	How the order was paid. Values seen: card, wallet (website); Bank transfer, Cash, Card (call-centre orders). Note the mixed capitals.
`payment_status`	`VARCHAR(32)`	Payment state. Values seen: paid, pending. Pending orders are call-centre (cca) orders not yet confirmed as paid in the platform; many are paid by bank transfer.
`status`	`VARCHAR(32)`	Where the order is in its lifecycle. Values seen: preparing, ready, picked, delivered, rejected.
`channel`	`VARCHAR(32)`	Where the order was placed. Values seen: website, cca (call-centre orders, Nigeria only).
`subtotal`	`BIGINT`	Value of the items before delivery, in minor units (kobo / cents). Divide by 100 for naira / shillings.
`delivery_fee`	`BIGINT`	Delivery charge, in minor units.
`total_price`	`BIGINT`	Total charged (subtotal + delivery fee), in minor units.
`phone_number`	`VARCHAR(32)`	Contact phone number on the order. *(personal data)*
`branch_external_id` links to branches	`VARCHAR(24)`	Branch that fulfilled the order.
`branch_name`	`VARCHAR(256)`	Branch name as recorded on the order.
`created_at`	`TIMESTAMP (UTC)`	When the order was placed (UTC).
`updated_at`	`TIMESTAMP (UTC)`	When the order last changed, e.g. a status update (UTC).
`customer_external_id`	`VARCHAR(24)`	Customer who placed the order.
`customer_name`	`VARCHAR(256)`	Customer's name as recorded on the order. *(personal data)*
`delivery_type`	`VARCHAR(32)`	How the order reached the customer. Values seen: delivery, pickup.
`loaded_at`	`TIMESTAMP (UTC)`	When this row was last written by the daily load (UTC). Set by the pipeline, not the source system.

5.2 order_items

Sales. The products in each order, with the price and quantity of each line.

One row per	product line within an order
Unique key	order_external_id, line_no
Refresh	Replaced with its order: when an order is loaded, all of its lines are deleted and re-inserted, so removed lines never linger.
Joins to	orders on order_external_id = orders.external_id menu_items on product_external_id = menu_items.external_id order_item_modifiers on (order_external_id, line_no)
Storage	distributed by (order_external_id) sorted by (order_external_id)

Column	Type	Description
`order_external_id` **Key** · links to orders	`VARCHAR(24)`	The order this line belongs to.
`line_no` **Key**	`SMALLINT`	Position of the line within the order (1, 2, 3...).
`product_external_id`	`VARCHAR(24)`	Product ordered (a menu item).
`product_name`	`VARCHAR(512)`	Product name as recorded on the order.
`price`	`BIGINT`	Price recorded on the line, in minor units.
`quantity`	`INTEGER`	Number of units ordered.
`loaded_at`	`TIMESTAMP (UTC)`	When this row was last written by the daily load (UTC). Set by the pipeline, not the source system.

5.3 order_item_modifiers

Sales. Customisations picked for each product in an order, such as toppings, flavours and add-ons.

One row per	option chosen on an order line
Unique key	order_external_id, line_no, modifier_no
Refresh	Replaced with its order, like order_items.
Joins to	order_items on (order_external_id, line_no) orders on order_external_id = orders.external_id
Storage	distributed by (order_external_id) sorted by (order_external_id)

Column	Type	Description
`order_external_id` **Key** · links to orders	`VARCHAR(24)`	The order.
`line_no` **Key**	`SMALLINT`	The order line the option belongs to.
`modifier_no` **Key**	`SMALLINT`	Position of the option on that line (1, 2, 3...).
`product_external_id`	`VARCHAR(24)`	Product on the line.
`modifier_external_id`	`VARCHAR(24)`	ID of the chosen option.
`modifier_name`	`VARCHAR(512)`	Name of the chosen option.
`price`	`BIGINT`	Extra charge for the option, in minor units (0 if free).
`loaded_at`	`TIMESTAMP (UTC)`	When this row was last written by the daily load (UTC). Set by the pipeline, not the source system.

5.4 order_timeline

Sales. The milestones each order goes through, for measuring preparation and delivery times.

One row per	step in an order's progress
Unique key	order_external_id, step_no
Refresh	Replaced with its order, like order_items.
Joins to	orders on order_external_id = orders.external_id
Storage	distributed by (order_external_id) sorted by (order_external_id)

Column	Type	Description
`order_external_id` `Key · links to orders`	`VARCHAR(24)`	The order.
`step_no` `Key`	`SMALLINT`	Position of the step (1 = first).
`title`	`VARCHAR(64)`	Step name. Values seen: accepted, preparing, ready, shipped, delivered, picked.
`description`	`VARCHAR(1024)`	Text describing the step.
`status`	`BOOLEAN`	True when the step has been reached; false when it hasn't (yet).
`created_at`	`TIMESTAMP (UTC)`	When the step was created (UTC).
`updated_at`	`TIMESTAMP (UTC)`	When the step last changed, e.g. was completed (UTC).
`loaded_at`	`TIMESTAMP (UTC)`	When this row was last written by the daily load (UTC). Set by the pipeline, not the source system.

5.5 customers

Customers. People who have registered or ordered on the Coldstone website.

One row per	registered customer
Unique key	external_id
Refresh	Incremental. New and updated customers are added every day.
Joins to	orders on orders.customer_external_id = customers.external_id branches on branch_external_id = branches.external_id
Storage	distribution chosen by Redshift sorted by (created_at)

Column	Type	Description
`external_id` `Key`	`VARCHAR(24)`	Customer ID (unique).
`first_name`	`VARCHAR(256)`	First name. *(personal data)*
`last_name`	`VARCHAR(256)`	Last name. *(personal data)*
`email`	`VARCHAR(256)`	Email address. *(personal data)*
`phone_number`	`VARCHAR(32)`	Phone number. *(personal data)*
`customer_external_id`	`VARCHAR(24)`	ID of the Coldstone platform account that owns this record (the business account, not a shopper).
`branch_external_id`	`VARCHAR(24)`	Branch the customer is registered with, if any.
`active`	`BOOLEAN`	True if the account is active.
`unsubscribed`	`BOOLEAN`	True if the customer has opted out of marketing messages.
`channel`	`VARCHAR(32)`	Where they signed up. Value seen: website.
`created_at`	`TIMESTAMP (UTC)`	When the customer registered (UTC).
`updated_at`	`TIMESTAMP (UTC)`	When their details last changed (UTC).

Column	Type	Description
loaded_at	TIMESTAMP (UTC)	When this row was last written by the daily load (UTC). Set by the pipeline, not the source system.

5.6 wallet_transactions

Wallet & settlement. Money coming into and out of each branch's wallet: sales credited, settlements paid out.

One row per	money movement in a branch wallet
Unique key	external_id
Refresh	Incremental. New and updated transactions are added every day.
Joins to	wallets on branch_external_id = wallets.branch_external_id branches on branch_external_id = branches.external_id
Storage	distribution chosen by Redshift sorted by (created_at, branch_external_id)

Column	Type	Description
external_id Key	VARCHAR(24)	Transaction ID (unique).
reference	VARCHAR(64)	Transaction reference.
amount	BIGINT	Amount moved, in minor units.
type	VARCHAR(32)	Direction. Values seen: credit (money in), debit (money out).
status	VARCHAR(32)	Transaction state. Value seen: successful.
customer_external_id	VARCHAR(24)	ID of the Coldstone platform account that owns this record (the business account, not a shopper).
branch_external_id links to branches	VARCHAR(24)	Branch whose wallet moved.
description	VARCHAR(1024)	What the movement was for. Values seen: Sales, Settlement.
created_at	TIMESTAMP (UTC)	When the transaction happened (UTC).
updated_at	TIMESTAMP (UTC)	When it last changed (UTC).
loaded_at	TIMESTAMP (UTC)	When this row was last written by the daily load (UTC). Set by the pipeline, not the source system.

5.7 wallets

Wallet & settlement. Each branch's wallet balance and the bank account its settlements are paid to.

One row per	branch wallet
Unique key	external_id
Refresh	Full snapshot. Reloaded in full every day, so balances are as at the latest run.
Joins to	branches on branch_external_id = branches.external_id wallet_transactions on branch_external_id
Storage	copied to every node (DISTSTYLE ALL) sorted by (branch_external_id)

Column	Type	Description
external_id Key	VARCHAR(24)	Wallet ID (unique).
reference	VARCHAR(64)	Wallet reference.
customer_external_id	VARCHAR(24)	ID of the Coldstone platform account that owns this record (the business account, not a shopper).
account_external_id	VARCHAR(24)	ID of the linked account record in the platform.
branch_external_id links to branches	VARCHAR(24)	Branch that owns the wallet.

Column	Type	Description
balance	BIGINT	Wallet balance, in minor units.
current_balance	BIGINT	Current balance as reported by the platform, in minor units.
temp_balance	BIGINT	Temporary / pending balance as reported by the platform, in minor units.
active	BOOLEAN	True if the wallet is active.
account_name	VARCHAR(256)	Settlement bank account name. *(personal data)*
account_number	VARCHAR(32)	Settlement bank account number. *(personal data)*
bank_name	VARCHAR(128)	Settlement bank.
created_at	TIMESTAMP (UTC)	When the wallet was created (UTC).
updated_at	TIMESTAMP (UTC)	When it last changed (UTC).
loaded_at	TIMESTAMP (UTC)	When this row was last written by the daily load (UTC). Set by the pipeline, not the source system.

5.8 menu_items

Menu. Everything that can be sold: menu products and the products used as options (toppings, flavours, add-ons).

One row per	product
Unique key	external_id
Refresh	Full snapshot. Reloaded in full every day for every branch.
Joins to	menu_categories on category_external_id = menu_categories.external_id branches on branch_external_id = branches.external_id menu_modifiers on menu_modifiers.menu_item_external_id = menu_items.external_id order_items on order_items.product_external_id = menu_items.external_id
Storage	copied to every node (DISTSTYLE ALL) sorted by (external_id)

Column	Type	Description
external_id Key	VARCHAR(24)	Product ID (unique).
slug	VARCHAR(512)	URL-friendly product name.
name	VARCHAR(512)	Product name.
description	VARCHAR(4096)	Product description.
price	BIGINT	Selling price, in minor units.
original_price	BIGINT	Price before any reduction, in minor units.
lagos_price	BIGINT	Lagos-specific price, in minor units (Nigeria only; empty when not used).
regional_price	BIGINT	Price outside Lagos, in minor units (Nigeria only; empty when not used).
quantity	INTEGER	Stock quantity, when stock is tracked.
track_quantity	BOOLEAN	True if stock levels are tracked.
is_cup_size	BOOLEAN	True if the product is a cup size option.
cup_size	VARCHAR(64)	Cold Stone size name, for size options. Values seen: like_it, love_it, gotta_have_it, ours, mine, everybody.
has_sku	BOOLEAN	True if the product has a stock-keeping unit code.
sku	VARCHAR(128)	Stock-keeping unit code.
low_stock_threshold	INTEGER	Stock level at which the product counts as running low.
image	VARCHAR(2048)	Product image URL.
channel	VARCHAR(32)	Where the product is offered. Value seen: all.
active	BOOLEAN	True if the product is enabled.
out_of_stock	BOOLEAN	True if the product is currently marked out of stock.

Column	Type	Description
customer_external_id	VARCHAR(24)	ID of the Coldstone platform account that owns this record (the business account, not a shopper).
branch_external_id links to branches	VARCHAR(24)	Branch whose menu the product belongs to.
category_external_id links to menu_categories	VARCHAR(24)	Menu category.
created_at	TIMESTAMP (UTC)	When the product was created (UTC).
updated_at	TIMESTAMP (UTC)	When it last changed (UTC).
loaded_at	TIMESTAMP (UTC)	When this row was last written by the daily load (UTC). Set by the pipeline, not the source system.

5.9 menu_categories

Menu. Headings that group products on the menu.

One row per	menu category
Unique key	external_id
Refresh	Full snapshot. Reloaded in full every day.
Joins to	menu_items on menu_items.category_external_id = menu_categories.external_id
Storage	copied to every node (DISTSTYLE ALL) sorted by (external_id)

Column	Type	Description
external_id Key	VARCHAR(24)	Category ID (unique).
name	VARCHAR(256)	Category name.
loaded_at	TIMESTAMP (UTC)	When this row was last written by the daily load (UTC). Set by the pipeline, not the source system.

5.10 menu_modifiers

Menu. The choices offered on a product, e.g. 'pick a flavour' or 'add toppings', and the rules for how many can be picked.

One row per	option group on a product
Unique key	external_id
Refresh	Full snapshot. Reloaded in full every day.
Joins to	menu_items on menu_item_external_id = menu_items.external_id modifier_items on modifier_items.modifier_external_id = menu_modifiers.external_id
Storage	copied to every node (DISTSTYLE ALL) sorted by (menu_item_external_id)

Column	Type	Description
external_id Key	VARCHAR(24)	Option group ID (unique).
menu_item_external_id links to menu_items	VARCHAR(24)	Product the option group belongs to.
title	VARCHAR(512)	Option group title shown to customers.
position	INTEGER	Display order on the product.
quantity	INTEGER	Number of options the rule refers to (see unit).
unit	VARCHAR(32)	How 'quantity' applies. Values seen: exactly (pick exactly N), most (pick up to N), all.
modifier_type	VARCHAR(32)	Kind of option group. Values seen: addon, type, flavour.

Column	Type	Description
channel	VARCHAR(32)	Where it is offered. Value seen: all.
loaded_at	TIMESTAMP (UTC)	When this row was last written by the daily load (UTC). Set by the pipeline, not the source system.

5.11 modifier_items

Menu. Which products can be picked in each option group.

One row per	product available in an option group
Unique key	modifier_external_id, menu_item_external_id
Refresh	Replaced with its option group on every load.
Joins to	menu_modifiers on modifier_external_id = menu_modifiers.external_id menu_items on menu_item_external_id = menu_items.external_id
Storage	copied to every node (DISTSTYLE ALL) sorted by (modifier_external_id)

Column	Type	Description
modifier_external_id Key · links to menu_modifiers	VARCHAR(24)	Option group.
menu_item_external_id Key · links to menu_items	VARCHAR(24)	Product that can be picked in it.
loaded_at	TIMESTAMP (UTC)	When this row was last written by the daily load (UTC). Set by the pipeline, not the source system.

5.12 discounts

Promotions. Promotions set up in the platform and their rules. (Kenya has none at the time of writing.)

One row per	discount / promo code
Unique key	external_id
Refresh	Full snapshot. Reloaded in full every day.
Joins to	discount_applicable_items, discount_combo_items on discount_external_id = discounts.external_id branches on branch_external_id = branches.external_id
Storage	copied to every node (DISTSTYLE ALL) sorted by (external_id)

Column	Type	Description
external_id Key	VARCHAR(24)	Discount ID (unique).
code	VARCHAR(64)	Promo code customers enter.
type	VARCHAR(64)	Kind of discount, e.g. fixed amount or percentage.
target	VARCHAR(64)	What the discount applies to.
channel	VARCHAR(32)	Where it can be used.
category	VARCHAR(64)	Discount category.
value	BIGINT	Discount value; an amount in minor units or a percentage, depending on type.
start_date	TIMESTAMP (UTC)	When the discount starts (UTC).
end_date	TIMESTAMP (UTC)	When it ends (UTC).
is_first_time_user_only	BOOLEAN	True if only first-time customers can use it.
minimum_order_amount	BIGINT	Minimum order value to qualify, in minor units.
min_quantity_per_item	INTEGER	Minimum quantity per item to qualify.
partial_combo_threshold	DECIMAL(5,	Share of a combo that must be bought for a partial combo discount.

Column	Type	Description
usage_limit	INTEGER	Maximum number of uses.
usage_count	INTEGER	Number of times used so far.
active	BOOLEAN	True if the discount is active.
partial_combo_allowed	BOOLEAN	True if a partial combo still qualifies.
customer_external_id	VARCHAR(24)	ID of the Coldstone platform account that owns this record (the business account, not a shopper).
branch_external_id links to branches	VARCHAR(24)	Branch the discount belongs to, if branch-specific.
created_at	TIMESTAMP (UTC)	When the discount was created (UTC).
updated_at	TIMESTAMP (UTC)	When it last changed (UTC).
loaded_at	TIMESTAMP (UTC)	When this row was last written by the daily load (UTC). Set by the pipeline, not the source system.

5.13 discount_applicable_items

Promotions. Products a discount can be used on.

One row per	product a discount applies to
Unique key	discount_external_id, item_external_id
Refresh	Replaced with its discount on every load.
Joins to	discounts on discount_external_id = discounts.external_id menu_items on item_external_id = menu_items.external_id
Storage	copied to every node (DISTSTYLE ALL) sorted by (discount_external_id)

Column	Type	Description
discount_external_id Key · links to discounts	VARCHAR(24)	Discount.
item_external_id Key	VARCHAR(24)	Product it applies to.
loaded_at	TIMESTAMP (UTC)	When this row was last written by the daily load (UTC). Set by the pipeline, not the source system.

5.14 discount_combo_items

Promotions. Products that together make up a combo deal.

One row per	product in a combo discount
Unique key	discount_external_id, item_external_id
Refresh	Replaced with its discount on every load.
Joins to	discounts on discount_external_id = discounts.external_id menu_items on item_external_id = menu_items.external_id
Storage	copied to every node (DISTSTYLE ALL) sorted by (discount_external_id)

Column	Type	Description
discount_external_id Key · links to discounts	VARCHAR(24)	Discount.
item_external_id Key	VARCHAR(24)	Product in the combo.
loaded_at	TIMESTAMP (UTC)	When this row was last written by the daily load (UTC). Set by the pipeline, not the source system.

5.15 branches

Branches & staff. Every Coldstone branch: name, location and settings.

One row per	branch (store)
Unique key	external_id
Refresh	Full snapshot. Reloaded in full every day.
Joins to	Most tables link here through branch_external_id = branches.external_id
Storage	copied to every node (DISTSTYLE ALL) sorted by (external_id)

Column	Type	Description
`external_id` Key	`VARCHAR(24)`	Branch ID (unique).
`branch_code`	`VARCHAR(16)`	Short branch code, where set.
`name`	`VARCHAR(256)`	Branch name (lower case, e.g. 'westlands').
`address`	`VARCHAR(1024)`	Street address.
`latitude`	`DOUBLE PRECISION`	Latitude of the branch.
`longitude`	`DOUBLE PRECISION`	Longitude of the branch.
`is_active`	`BOOLEAN`	True if the branch is active.
`is_headquarters`	`BOOLEAN`	True for the head-office branch.
`is_private`	`BOOLEAN`	True if the branch is not publicly listed.
`longest_distance`	`INTEGER`	Furthest delivery distance configured for the branch.
`customer_external_id`	`VARCHAR(24)`	ID of the Coldstone platform account that owns this record (the business account, not a shopper).
`created_at`	`TIMESTAMP (UTC)`	When the branch was created (UTC).
`updated_at`	`TIMESTAMP (UTC)`	When it last changed (UTC).
`loaded_at`	`TIMESTAMP (UTC)`	When this row was last written by the daily load (UTC). Set by the pipeline, not the source system.

5.16 members

Branches & staff. Staff who use the Coldstone dashboard (store staff, admins, customer support).

One row per	staff user
Unique key	external_id
Refresh	Full snapshot. Reloaded in full every day.
Joins to	branches on branch_external_id = branches.external_id branch_members, member_additional_branches, member_roles on member_external_id activity_initiators on initiator_external_id = members.external_id
Storage	copied to every node (DISTSTYLE ALL) sorted by (external_id)

Column	Type	Description
`external_id` Key	`VARCHAR(24)`	Staff user ID (unique).
`email`	`VARCHAR(256)`	Email address. *(personal data)*
`username`	`VARCHAR(256)`	Login name.
`first_name`	`VARCHAR(256)`	First name. *(personal data)*
`last_name`	`VARCHAR(256)`	Last name. *(personal data)*
`role_name`	`VARCHAR(256)`	Main role. Values seen: Stores, Super Admin, Customer Support.
`is_deactivated`	`BOOLEAN`	True if the user has been deactivated.

Column	Type	Description
verified	BOOLEAN	True if the user has verified their account.
phone_number	VARCHAR(32)	Phone number. *(personal data)*
customer_external_id	VARCHAR(24)	ID of the Coldstone platform account that owns this record (the business account, not a shopper).
branch_external_id links to branches	VARCHAR(24)	Home branch.
created_at	TIMESTAMP (UTC)	When the user was created (UTC).
updated_at	TIMESTAMP (UTC)	When it last changed (UTC).
loaded_at	TIMESTAMP (UTC)	When this row was last written by the daily load (UTC). Set by the pipeline, not the source system.

5.17 branch_members

Branches & staff. Links each staff user to their home branch.

One row per	staff user and home branch
Unique key	branch_external_id, member_external_id
Refresh	Replaced with its staff user on every load.
Joins to	branches on branch_external_id members on member_external_id
Storage	copied to every node (DISTSTYLE ALL) sorted by (member_external_id)

Column	Type	Description
branch_external_id Key · links to branches	VARCHAR(24)	Branch.
member_external_id Key · links to members	VARCHAR(24)	Staff user.
loaded_at	TIMESTAMP (UTC)	When this row was last written by the daily load (UTC). Set by the pipeline, not the source system.

5.18 member_additional_branches

Branches & staff. Extra branches a staff user can work in, besides their home branch.

One row per	staff user and extra branch
Unique key	member_external_id, branch_external_id
Refresh	Replaced with its staff user on every load.
Joins to	members on member_external_id branches on branch_external_id
Storage	copied to every node (DISTSTYLE ALL) sorted by (member_external_id)

Column	Type	Description
member_external_id Key · links to members	VARCHAR(24)	Staff user.
branch_external_id Key · links to branches	VARCHAR(24)	Extra branch they can access.
loaded_at	TIMESTAMP (UTC)	When this row was last written by the daily load (UTC). Set by the pipeline, not the source system.

5.19 member_roles

Branches & staff. Roles assigned to each staff user.

One row per	staff user and role
Unique key	member_external_id, role_external_id
Refresh	Replaced with its staff user on every load.
Joins to	members on member_external_id roles on role_external_id = roles.external_id
Storage	copied to every node (DISTSTYLE ALL) sorted by (member_external_id)

Column	Type	Description
`member_external_id` `Key · links to members`	`VARCHAR(24)`	Staff user.
`role_external_id` `Key · links to roles`	`VARCHAR(24)`	Role.
`loaded_at`	`TIMESTAMP (UTC)`	When this row was last written by the daily load (UTC). Set by the pipeline, not the source system.

5.20 roles

Branches & staff. Staff roles, e.g. Stores, Super Admin, Customer Support.

One row per	role
Unique key	external_id
Refresh	Full snapshot. Reloaded in full every day.
Joins to	member_roles on role_external_id = roles.external_id
Storage	copied to every node (DISTSTYLE ALL) sorted by (external_id)

Column	Type	Description
`external_id` `Key`	`VARCHAR(24)`	Role ID (unique).
`name`	`VARCHAR(256)`	Role name.
`description`	`VARCHAR(1024)`	What the role is for.
`created_at`	`TIMESTAMP (UTC)`	When the role was created (UTC).
`updated_at`	`TIMESTAMP (UTC)`	When it last changed (UTC).
`loaded_at`	`TIMESTAMP (UTC)`	When this row was last written by the daily load (UTC). Set by the pipeline, not the source system.

5.21 permissions

Branches & staff. Areas of the dashboard a role can be given access to.

One row per	permission
Unique key	external_id
Refresh	Full snapshot. Reloaded in full every day.
Joins to	sub_permissions on permission_external_id = permissions.external_id
Storage	copied to every node (DISTSTYLE ALL) sorted by (external_id)

Column	Type	Description
`external_id` `Key`	`VARCHAR(24)`	Permission ID (unique).
`name`	`VARCHAR(256)`	Permission name.

Column	Type	Description
description	VARCHAR(1024)	What it allows.
created_at	TIMESTAMP (UTC)	When it was created (UTC).
updated_at	TIMESTAMP (UTC)	When it last changed (UTC).
loaded_at	TIMESTAMP (UTC)	When this row was last written by the daily load (UTC). Set by the pipeline, not the source system.

5.22 sub_permissions

Branches & staff. Finer-grained actions within a permission.

One row per	detailed permission
Unique key	external_id
Refresh	Full snapshot. Reloaded in full every day.
Joins to	permissions on permission_external_id = permissions.external_id
Storage	copied to every node (DISTSTYLE ALL) sorted by (permission_external_id)

Column	Type	Description
external_id Key	VARCHAR(24)	Sub-permission ID (unique).
name	VARCHAR(256)	Name.
description	VARCHAR(1024)	What it allows.
permission_external_id links to permissions	VARCHAR(24)	Parent permission.
is_enabled	BOOLEAN	True if enabled.
created_at	TIMESTAMP (UTC)	When it was created (UTC).
updated_at	TIMESTAMP (UTC)	When it last changed (UTC).
loaded_at	TIMESTAMP (UTC)	When this row was last written by the daily load (UTC). Set by the pipeline, not the source system.

5.23 activity_logs

Activity (audit trail). An audit trail of actions: logins, menu changes such as marking items out of stock, and customer actions.

One row per	action taken in the platform
Unique key	external_id
Refresh	Incremental. New actions are added every day.
Joins to	activity_initiators on activity_external_id = activity_logs.external_id branches on branch_external_id = branches.external_id
Storage	distributed by (external_id) sorted by (created_at)

Column	Type	Description
external_id Key	VARCHAR(24)	Action ID (unique).
description	VARCHAR(4096)	What happened, e.g. 'Logged in to Cold Stone Creamery'.
customer_external_id	VARCHAR(24)	ID of the Coldstone platform account that owns this record (the business account, not a shopper).
branch_external_id	VARCHAR(24)	Branch the action relates to.
initiator_type	VARCHAR(32)	Who did it. Values seen: Member (staff), Customer.
created_at	TIMESTAMP (UTC)	When the action happened (UTC).

Column	Type	Description
updated_at	TIMESTAMP (UTC)	When the record last changed (UTC).
loaded_at	TIMESTAMP (UTC)	When this row was last written by the daily load (UTC). Set by the pipeline, not the source system.

5.24 activity_initiators

Activity (audit trail). The person who performed each action in activity_logs.

One row per	person behind an action
Unique key	activity_external_id, initiator_external_id
Refresh	Replaced with its action on every load.
Joins to	activity_logs on activity_external_id = activity_logs.external_id members on initiator_external_id = members.external_id (staff)
Storage	distributed by (activity_external_id) sorted by (activity_external_id)

Column	Type	Description
activity_external_id Key · links to activity_logs	VARCHAR(24)	The action.
initiator_external_id Key	VARCHAR(24)	Person who did it (staff user or customer ID).
first_name	VARCHAR(256)	First name. *(personal data)*
last_name	VARCHAR(256)	Last name. *(personal data)*
username	VARCHAR(256)	Login name.
email	VARCHAR(256)	Email address. *(personal data)*
role_name	VARCHAR(256)	Their role at the time. Values seen: Stores, Super Admin, Customer Support.
initiator_type	VARCHAR(32)	Member (staff) or Customer.
loaded_at	TIMESTAMP (UTC)	When this row was last written by the daily load (UTC). Set by the pipeline, not the source system.

6. Example queries

Daily sales in Nigeria, by Lagos business day

```
SELECT CAST(CONVERT_TIMEZONE('UTC', 'Africa/Lagos', created_at) AS DATE) AS business_date,
       COUNT(*)                     AS orders,
       SUM(total_price) / 100.0     AS sales_ngn
FROM coldstone_web_ng_analytics.orders
WHERE payment_status = 'paid'
GROUP BY 1
ORDER BY 1 DESC;
```

Top 10 Kenya branches by sales in a month (amounts in KES)

```
SELECT b.name AS branch, COUNT(*) AS orders, SUM(o.total_price) / 100.0 AS sales_kes
FROM coldstone_web_ke_analytics.orders o
JOIN coldstone_web_ke_analytics.branches b ON b.external_id = o.branch_external_id
WHERE o.payment_status = 'paid'
  AND o.created_at >= '2026-08-31 21:00'   -- 1 Sep 00:00 Nairobi, in UTC
  AND o.created_at <  '2026-09-30 21:00'   -- 1 Oct 00:00 Nairobi, in UTC
GROUP BY 1
ORDER BY 3 DESC
LIMIT 10;
```

Best-selling products in Nigeria

```
SELECT i.product_name, SUM(i.quantity) AS units
FROM coldstone_web_ng_analytics.order_items i
JOIN coldstone_web_ng_analytics.orders o ON o.external_id = i.order_external_id
WHERE o.payment_status = 'paid'
GROUP BY 1
ORDER BY 2 DESC
LIMIT 20;
```

Average time from order to delivery (Kenya, minutes)

```
SELECT AVG(DATEDIFF(minute, o.created_at, t.updated_at)) AS minutes_to_deliver
FROM coldstone_web_ke_analytics.orders o
JOIN coldstone_web_ke_analytics.order_timeline t ON t.order_external_id = o.external_id
WHERE t.title = 'delivered' AND t.status;
```

Both countries side by side (each in its own currency)

```
SELECT 'NG' AS country, COUNT(*) AS orders, SUM(total_price) / 100.0 AS sales_local
FROM coldstone_web_ng_analytics.orders WHERE payment_status = 'paid'
UNION ALL
SELECT 'KE', COUNT(*), SUM(total_price) / 100.0
FROM coldstone_web_ke_analytics.orders WHERE payment_status = 'paid';
```

Where a description says 'values seen', the list comes from the data loaded so far and may grow as the platform adds new statuses or options.