Course Name: Operating systems

LAB: 08

Submitted By: Ebaad Khan

Roll: DT-22045

```
PROGRAM:
#include <stdio.h>
int max[100][100], alloc[100][100], need[100][100];
int avail[100];
int n, r;
void input();
void show();
void cal();
int main() {
  printf("******* Deadlock Detection Algorithm *********\n");
 input();
 show();
 cal();
 return 0;
}
```

```
void input() {
  int i, j;
  printf("Enter the number of Processes: ");
  scanf("%d", &n);
  printf("Enter the number of Resource Instances: ");
  scanf("%d", &r);
  printf("Enter the Max Matrix:\n");
  for(i = 0; i < n; i++) {
    for(j = 0; j < r; j++) {
      scanf("%d", &max[i][j]);
    }
  }
  printf("Enter the Allocation Matrix:\n");
  for(i = 0; i < n; i++) {
    for(j = 0; j < r; j++) {
      scanf("%d", &alloc[i][j]);
    }
  }
  printf("Enter the Available Resources:\n");
  for(j = 0; j < r; j++) {
    scanf("%d", &avail[j]);
  }
}
```

```
void show() {
  int i, j;
  printf("\nProcess\tAllocation\tMax\t\tAvailable\n");
  for(i = 0; i < n; i++) {
    printf("P%d\t", i + 1);
    for(j = 0; j < r; j++) {
      printf("%d ", alloc[i][j]);
    }
    printf("\t");
    for(j = 0; j < r; j++) {
      printf("%d ", max[i][j]);
    }
    printf("\t");
    if(i == 0) {
      for(j = 0; j < r; j++) {
        printf("%d ", avail[j]);
      }
    }
    printf("\n");
  }
}
void cal() {
  int finish[100], dead[100];
  int i, j, k, flag = 1, c1 = 0;
```

```
// Calculate need matrix
for(i = 0; i < n; i++) {
  finish[i] = 0;
  for(j = 0; j < r; j++) {
    need[i][j] = max[i][j] - alloc[i][j];
  }
}
while(flag) {
  flag = 0;
  for(i = 0; i < n; i++) {
    int canExecute = 1;
    if(finish[i] == 0) {
      for(j = 0; j < r; j++) {
         if(need[i][j] > avail[j]) {
           canExecute = 0;
           break;
         }
      }
      if(canExecute) {
         for(j = 0; j < r; j++) {
           avail[j] += alloc[i][j];
         }
         finish[i] = 1;
```

```
flag = 1;
       }
     }
   }
 }
 int deadlock = 0;
 printf("\nDeadlocked Processes:\n");
 for(i = 0; i < n; i++) {
   if(finish[i] == 0) {
      printf("P%d ", i + 1);
      deadlock = 1;
   }
 }
 if(deadlock == 0) {
   printf("No Deadlock Detected. System is in Safe State.\n");
 } else {
   printf("\nSystem is in Deadlock.\n");
 }
OUTPUT:
```

}

```
© C:\Users\Ebaad Khan\Docum€ ×
****** Deadlock Detection Algorithm ********
Enter the number of Processes: 3
Enter the number of Resource Instances: 2
Enter the Max Matrix:
2 2
1 2
1 2
Enter the Allocation Matrix:
1 0
1 1
0 1
Enter the Available Resources:
0 0
Process Allocation
                        Max
                                        Available
        1 0
                2 2
                        0 0
P1
P2
        1 1
                1 2
        0 1
Р3
                1 2
Deadlocked Processes:
P1 P2 P3
System is in Deadlock.
Process exited after 34.09 seconds with return value 0
Press any key to continue . . .
```