Too Normal to Be Human: Probing a Behavioral Foundation Model for LLM-Agent Detection

Anonymous Authors

Abstract

LLM agents now browse and buy on behalf of people. Whether a platform can tell them from their owners matters for fraud, account takeover, and in sensitive settings for insider-risk monitoring. A natural candidate is a *behavioral foundation model*: a sequence model pretrained on billions of user actions whose next-action likelihood should flag anything that is not human. We test this with BehaviorGPT (12.5B parameters, 150B e-commerce actions), using its public API and its vendor's own anomaly-scoring method. In a WebShop pilot, agents look *less* surprising than humans, but we show that this is entirely a search-engine confound. Once the shown list is controlled, AUROC falls from 0.57 to 0.50. We then introduce *counterfactual replay* on OPeRA, a dataset of real Amazon sessions from 45 users. At each human click, an LLM agent acting for that user chooses from the identical result list with the identical history, so engine, query and context are fixed by construction. Agents from two model families, with and without the user's persona, consistently choose items that BehaviorGPT ranks *higher* than the human's choice (paired $p \leq 0.014$ in all three conditions): they are *too normal*, not anomalous. The signal is weak, however (step AUROC 0.54–0.58), and adds nothing to a five-feature logistic regression over the shown list (sponsored, position, rating, price, query overlap), which reaches 0.62–0.80. Behavioral foundation models therefore need to be evaluated against cheap, context-matched baselines and under controlled engines, and anomaly-style detectors aimed at agents are pointed in the wrong direction.

1 Introduction

Web agents built on large language models (LLMs) can now search, compare and purchase on real sites [1, 8, 10]. Increasingly they do so *inside a human's account*, with the human's history, preferences and payment methods. For a platform, this raises a question that classic bot detection was not built for: given a real user's session, did the user or an agent acting for them make this choice? The same question arises wherever delegated agents operate on accounts that carry trust, from fraud and account takeover in commerce to insider-risk monitoring on government and defense networks.

Behavioral foundation models offer an attractive answer. Pretrained on very large logs of user actions, they assign a likelihood to every next action given a user's history, much as sequential recommenders do [2]. The vendor-recommended way to turn such a model into a detector is anomaly scoring: convert next-action scores into probabilities, compute excess surprisal, and accumulate it with a CUSUM statistic [3, 5]. This assumes that non-human behavior is *surprising*. LLM agents, however, are trained on human text and pick sensible, popular options. They may instead be *too predictable*.

We test this assumption on BehaviorGPT [6] through its public API, at a total compute cost below US$10. Our contributions are:

1. **A confound.** In a WebShop pilot [8], agents appear less surprising than humans (AUROC 0.57), but the effect comes entirely from the search engine that produced each class's result lists. Measured within the shown list, it disappears (0.50; §3).

2. **A protocol.** *Counterfactual replay* on real human sessions (OPeRA [7]): at every human click an agent chooses from the identical list with the identical history. Engine, query and context are held fixed by construction, and the setting matches delegated agents acting inside an account (§4).

3. **A finding.** Across two model families and with or without the user's persona, agents are *too normal*: BehaviorGPT ranks their choices higher than the human's ($p \leq 0.014$). The signal is weak (AUROC 0.54–0.58) and redundant with five cheap list features, which reach 0.62–0.80 on their own (§5).

All code, prompts and cached API responses are released.

Related work. LLM agents for web shopping are usually evaluated for task success [1, 8–10]. A parallel line uses LLMs to *simulate* human behavior [4], and OPeRA [7] was built to measure how well they imitate individual shoppers. We ask the converse, security-oriented question: can a model of human behavior tell them apart? The vendor's anomaly toolkit [5] evaluates detection only on simulated perturbations. To our knowledge, this is the first evaluation of a behavioral foundation model against real LLM agents under a controlled engine.

2 Setup

The model. BehaviorGPT-v4 is a 12.5B-parameter sequence model trained on 150B e-commerce actions [6]. Its API takes a user history (search, view, add-to-cart and order events) and, optionally, a query. It returns raw similarity scores for catalog items, not probabilities. A filter by item id scores any chosen set of items. We uploaded a private catalog of 74,347 products containing every item shown to or chosen by any human or agent in our data. In preliminary checks the API was deterministic, the history changed the ranking, and the model ignored timing below the hour. Because the API terms let the vendor train on uploaded content, we used only public data.

Scoring a choice in context. For a choice c made from a shown list L (with $|L| = n$) after history h and query q, one API call with the id filter set to L gives scores $s_i(h, q)$ for all $i \in L$. We use:

- the **within-list percentile** of s_c in L (1 means the model's top pick);
- the **conditional logit** $s_c/\tau - \log \sum_{i \in L} e^{s_i/\tau} + \log n$, with τ fit by maximum likelihood on human choices from the other half of the users (2-fold by user);
- the **history gain**: the percentile with h minus the percentile with an empty history.

All three compare the choice only with what the chooser actually saw, so they are invariant to the engine that produced L. The vendor's original statistic instead compares c against the whole catalog.

Baselines. Five features of the chosen item within L, computed without BehaviorGPT: log list position, sponsored flag, price percentile, star rating, and query–title word-overlap percentile. Detectors are logistic regressions on baselines, on BehaviorGPT features, or on both, evaluated with 5-fold cross-validation grouped by user. We report AUROC with the agent as the positive class, with 95% intervals from a bootstrap over users.

3 Pilot: an engine confound

WebShop [8] provides 1,643 human sessions on a 1.18M-product store. We took 150 test humans, plus 300 others to calibrate the vendor's statistic. We ran Claude Haiku 5.5 and DeepSeek V4 Flash on the same 150 instructions in a re-implementation of the store with BM25 search. With the




Figure 1: Counterfactual replay. At each human click, an agent acting for the same user chooses from the identical list with the identical history. Engine, query and context are held fixed, so any difference between the two choices comes from the chooser.

vendor's method [5], agents look *less* surprising (AUROC 0.57 for predictability, paired by instruction $p \approx 0.001$, same sign for both models).

The effect is not behavioral. Our engine's lists were themselves more aligned with BehaviorGPT: 63% of their top-10 items fall in the model's top 100, against 56% for the original engine. Scored within the list each chooser actually saw, the gap vanishes (AUROC 0.50 [0.44, 0.55], paired $p = 0.59$; Fig. 2a). WebShop has two further problems: a median of one scored step per session, and instructed crowd workers who behave like agents by design. It is the wrong testbed.

4 Counterfactual replay

Human data. OPeRA [7] logs real users shopping on Amazon with a browser plug-in, along with their self-reported personas. From the full release (54 users, 692 sessions) we build one time-ordered event stream per user across all of that user's sessions. We extract every click on a product in a search-result list where the logged page contains the full list. This gives 384 steps from 45 users, with a median list size of 55 and a median of 13 history events per API call.

Agents. At each step, an LLM receives the user's survey persona, their last 12 events, the query and the full list in page order (title, price, rating, sponsored flag), and returns the item it would open (Fig. 1). There are three conditions: Claude Haiku 5.5 with persona, the same without persona, and DeepSeek V4 Flash with persona (temperature 0.7). Haiku answered every step. DeepSeek answered 247 of 384 validly; the remaining responses were empty or malformed. Agents chose the same item as the human in 10%, 14% and 19% of steps, respectively.

Why this design. It removes the two confounds that undermine naive comparisons: the engine (both choices come from one list) and the intent (both act on the same query and history). It also matches the threat model of a delegated agent operating within a legitimate account. The cost is that each decision is judged in isolation; we return to this in §6.

5 Results

Agents are too normal. With engine and context fixed, all three agent conditions choose items that BehaviorGPT ranks higher than the human's choice (Fig. 3; Table 1). The mean within-list percentile rises from 0.59 to 0.64–0.67. The effect is significant in every condition (paired Wilcoxon $p = 0.014$, 3.3×10^{-5} and 2.6×10^{-4}) and holds for the conditional logit. This is the opposite of the assumption behind anomaly scoring: an agent operating inside an account makes the account look *more* typical, not less, so a CUSUM on excess surprisal would drift away from an alarm.

But the signal is weak and redundant. On its own, BehaviorGPT reaches a step AUROC of 0.54–0.58, and 0.61–0.65 when averaged per user (Fig. 2b). The five list features alone reach 0.80 (Haiku with persona), 0.74 (Haiku without persona) and 0.62 (DeepSeek). Adding BehaviorGPT




Figure 2: Detection performance with 95% user-cluster bootstrap intervals. (a) In the WebShop pilot, the apparent signal (agents less surprising) disappears once choices are scored within the list each chooser saw. (b) In counterfactual replay, BehaviorGPT alone detects agents only weakly. Five list features detect them far better, and adding BehaviorGPT to them changes AUROC by at most 0.015.




Figure 3: Agents pick what the model expects. Cumulative distribution of the BehaviorGPT within-list percentile of the chosen item. Curves further to the right mean more model-typical choices. Human and agent choices are paired by step; p from a paired Wilcoxon test.

changes these by $+0.001$, $+0.005$ and $+0.015$, all well inside the confidence intervals. The ROC curves for baselines and baselines + BehaviorGPT overlap almost everywhere (Fig. 5).

What gives agents away. The cheap tells are behavioral, not semantic (Fig. 4). Humans click a sponsored result in 34% of steps, against 5% for Haiku with persona and 23% for DeepSeek. Haiku also reads deeper into the list (mean rank 18 vs. 8). All agents pick items with higher star ratings and more literal query matches. The last tell partly explains the BehaviorGPT effect: given a query, the model favors on-topic, popular items, and so do agents.

History and persona. Conditioning on the user's history raises the percentile of human choices only from 0.569 to 0.590. In other words, the user's past actions add little predictive power for which listed item a person opens. For agents, history helps *more* (history gain 0.03–0.05 vs. 0.00–0.02), probably because agents see the recent events in their prompt and stay consistent with them. Giving the agent the user's persona does not make it harder for BehaviorGPT to detect (step AUROC 0.54 vs. 0.58 without persona; the intervals overlap). It does change its style: without the persona Haiku

Table 1: BehaviorGPT statistics, human vs. agent on identical context. Means, paired Wilcoxon p, and AUROC at the step level (user-cluster bootstrap CI) and at the user level (per-user means, 45 vs. 45).

Agent	Statistic	Human / Agent	Paired p	Step AUROC	User AUROC
Haiku 5.5 + persona	percentile	0.590 / 0.635	0.014	0.54 [0.51, 0.58]	0.61
	logit	0.068 / 0.111	0.032	0.54 [0.50, 0.57]	0.59
	history gain	0.021 / 0.043	0.012	0.55 [0.51, 0.59]	0.58
Haiku 5.5, no pers.	percentile	0.590 / 0.670	3.3×10^{-5}	0.58 [0.54, 0.61]	0.65
	logit	0.068 / 0.156	1.5×10^{-4}	0.57 [0.54, 0.61]	0.64
	history gain	0.021 / 0.048	0.004	0.54 [0.50, 0.59]	0.59
DeepSeek V4 Flash	percentile	0.578 / 0.665	2.6×10^{-4}	0.58 [0.52, 0.63]	0.62
	logit	0.048 / 0.151	8.1×10^{-4}	0.57 [0.53, 0.63]	0.61
	history gain	0.001 / 0.029	0.019	0.55 [0.50, 0.59]	0.58




Figure 4: Cheap tells. Properties of the chosen item for humans and agents on the same 384 steps (247 for DeepSeek). Means with 95% user-cluster bootstrap intervals. Agents avoid ads, prefer highly rated and literally matching items, and Haiku scrolls further down the list.

clicks more ads and stays higher in the list, which lowers the baseline detector from 0.80 to 0.74. The model family matters more than the persona: DeepSeek is the hardest agent to detect by any method.

6 Discussion

Implications for detection. The vendor's anomaly pipeline flags behavior the model finds surprising. Against LLM agents this points the wrong way: at the level of single choices, agents are slightly *more* typical than the humans they act for. A detector built on a behavioral foundation model would need a two-sided or "too-typical" test. Even then it would add nothing over a handful of list features that any platform already logs. Advertising engagement in particular is a strong, cheap and so far overlooked signal of a human chooser.

Implications for evaluation. Our pilot shows how easily a spurious effect appears: a different search engine alone produced a significant, model-consistent difference between humans and agents. Any comparison of humans and agents across environments, including agent benchmarks that reuse human demonstrations [8, 9], should score choices relative to what each chooser was shown. Counterfactual replay on logged human sessions does this by construction and is cheap: about 1,000 LLM calls and 768 API calls here.

Limitations. We judge single decisions, not whole agent sessions, so query formulation, navigation, timing and dwell, plausibly the strongest agent tells, are out of scope. BehaviorGPT cannot read them anyway, since it ignores time below the hour. OPeRA products enter the catalog with title and




Figure 5: ROC curves for the three detectors (5-fold CV grouped by user; AUROC in parentheses). Adding BehaviorGPT to the list baselines (solid colored line) barely moves the baseline curve (gray).

price only, which may weaken the model's item representations. DeepSeek's 36% invalid responses may select easier steps. Our sample of 45 users is small for user-level claims. We test one behavioral foundation model through its public interface, without access to its weights.

Broader impact. Detection of delegated agents can protect users and platforms. It can also be used to block legitimate assistive agents, and our findings suggest that crude heuristics (ad avoidance) would do so with many false positives. For sensitive deployments such as defense or government networks, current hosted behavioral models are unsuitable regardless of accuracy, because their terms allow training on uploaded data. We used only public datasets.

7 Conclusion

A behavioral foundation model can tell LLM agents from the humans they act for, but only weakly, in the opposite direction to the one anomaly detection assumes, and not beyond what five cheap features already provide. Engine-controlled, context-matched evaluation, here through counterfactual replay, is necessary to see this; without it, a search-engine confound produces a convincing but spurious effect.

References

[1] Xiang Deng, Yu Gu, Boyuan Zheng, Shijie Chen, Samuel Stevens, Boshi Wang, Huan Sun, and Yu Su. Mind2Web: Towards a generalist agent for the web. *arXiv preprint arXiv:2306.06070*, 2023.

[2] Wang-Cheng Kang and Julian McAuley. Self-attentive sequential recommendation. *arXiv preprint arXiv:1808.09781*, 2018.

[3] E. S. Page. Continuous inspection schemes. *Biometrika*, 41(1–2):100–115, 1954. doi: 10.1093/biomet/41.1-2.100.

[4] Joon Sung Park, Joseph C. O'Brien, Carrie J. Cai, Meredith Ringel Morris, Percy Liang, and Michael S. Bernstein. Generative agents: Interactive simulacra of human behavior. *arXiv preprint arXiv:2304.03442*, 2023.

[5] Unbox AI. behaviorgpt-anomaly: anomaly scoring with BehaviorGPT. `https://github.com/Unbox-AI/behaviorgpt-anomaly`, 2026. MIT licence. Accessed 2026-11-08.

[6] Unbox AI. BehaviorGPT API documentation. `https://portal.unboxai.com/docs/`, 2026. Accessed 2026-11-08.

[7] Ziyi Wang, Yuxuan Lu, Wenbo Li, Amirali Amini, Bo Sun, Yakov Bart, Weimin Lyu, Jiri Gesi, Tian Wang, Jing Huang, Yu Su, Upol Ehsan, Malihe Alikhani, Toby Jia-Jun Li, Lydia Chilton, and Dakuo Wang. OPeRA: A dataset of observation, persona, rationale, and action for evaluating LLMs on human online shopping behavior simulation. *arXiv preprint arXiv:2506.05606*, 2025.

[8] Shunyu Yao, Howard Chen, John Yang, and Karthik Narasimhan. WebShop: Towards scalable real-world web interaction with grounded language agents. *arXiv preprint arXiv:2207.01206*, 2022.

[9] Aohan Zeng, Mingdao Liu, Rui Lu, Bowen Wang, Xiao Liu, Yuxiao Dong, and Jie Tang. AgentTuning: Enabling generalized agent abilities for LLMs. *arXiv preprint arXiv:2310.12823*, 2023.

[10] Shuyan Zhou, Frank F. Xu, Hao Zhu, Xuhui Zhou, Robert Lo, Abishek Sridhar, Xianyi Cheng, Tianyue Ou, Yonatan Bisk, Daniel Fried, Uri Alon, and Graham Neubig. WebArena: A realistic web environment for building autonomous agents. *arXiv preprint arXiv:2307.13854*, 2023.