

智慧充电系列部署文档

编译服务器

编译服务器准备

```
1  # Maven部署
2  [root@services ~]# yum clean all; yum repoinfo
3  [root@services ~]# yum -y install java-1.8.0-openjdk-devel.x86_64
4  [root@services ~]# ln -s /usr/lib/jvm/java-1.8.0-openjdk-1.8.0.332.b09-
  1.e18_5.x86_64/ /usr/lib/jvm/jdk
5  [root@services ~]# java -version
6  openjdk version "1.8.0_332"
7  OpenJDK Runtime Environment (build 1.8.0_332-b09)
8  OpenJDK 64-Bit Server VM (build 25.332-b09, mixed mode)
9  [root@services ~]# unzip Charging.zip
10 [root@services ~]# cd Charging
11 [root@services Charging]# ls
12 apache-maven-3.6.3-bin.tar.gz  install_redis.sh          redis
13 charge                          node-v16.17.0-linux-x64.tar.gz  redis-6.2.6.tar.gz
14
15
16 [root@services Charging]# tar -xf apache-maven-3.6.3-bin.tar.gz
17 [root@services Charging]# mv apache-maven-3.6.3 /usr/local/maven
18 [root@services Charging]# ls /usr/local/maven/
19 bin boot conf lib LICENSE NOTICE README.txt
20
21 [root@services ~]# vim /etc/bashrc
22 [root@services ~]# tail -3 /etc/bashrc
23 export JAVA_HOME="/usr/lib/jvm/jdk/"
24 export MAVEN_HOME="/usr/local/maven/"
25 export PATH=${MAVEN_HOME}/bin/${JAVA_HOME}/bin:$PATH
26 [root@services ~]# source /etc/bashrc
27
28 [root@services ~]# mvn -v
29 Apache Maven 3.6.3 (cecedd343002696d0abb50b32b541b8a6ba2883f)
30 Maven home: /usr/local/maven
31 Java version: 1.8.0_332, vendor: Red Hat, Inc., runtime: /usr/lib/jvm/java-1.8.0-
  openjdk-1.8.0.332.b09-1.e18_5.x86_64/jre
32 Default locale: en_US, platform encoding: UTF-8
33 OS name: "linux", version: "4.18.0-372.9.1.el8.x86_64", arch: "amd64", family:
  "unix"
34 [root@services ~]#
35
36 [root@services ~]# mkdir /usr/local/maven/repo
37 [root@services ~]# vim /usr/local/maven/conf/settings.xml
38 [root@services ~]# sed -rn '56p;147p;160,166p' /usr/local/maven/conf/settings.xml
39 <localRepository>/usr/local/maven/repo</localRepository>
40 <mirrors>
```

```
41     <mirror>
42         <id>alimaven</id>
43         <name>阿里云公共仓库</name>
44         <url>https://maven.aliyun.com/repository/public</url>
45         <mirrorOf>central</mirrorOf>
46     </mirror>
47 </mirrors>
48
49
50 # NPM部署
51 [root@services ~]# ls node-v16.17.0-linux-x64.tar.gz
52 node-v16.17.0-linux-x64.tar.gz
53 [root@services ~]# tar -xf node-v16.17.0-linux-x64.tar.gz
54 [root@services ~]# mv node-v16.17.0-linux-x64 /usr/local/node
55 [root@services ~]# ls /usr/local/node/
56 bin CHANGELOG.md include lib LICENSE README.md share
57
58 [root@services ~]# vim /etc/bashrc
59 [root@services ~]# tail -4 /etc/bashrc
60 export JAVA_HOME="/usr/lib/jvm/jdk/"
61 export MAVEN_HOME="/usr/local/maven/"
62 export NODE_HOME="/usr/local/node/"
63 export PATH=${MAVEN_HOME}/bin:${JAVA_HOME}/bin:${NODE_HOME}/bin:$PATH
64 [root@services ~]# source /etc/bashrc
65
66 [root@services ~]# node -v
67 v16.17.0
68 [root@services ~]# npm -v
69 8.15.0
70 [root@services ~]#
71
72 [root@services ~]# npm config set cache "/usr/local/node/node_cache"
73 [root@services ~]# npm config set registry "http://mirrors.cloud.tencent.com/npm/"
74 [root@services ~]# npm config list
75 ; "user" config from /root/.npmrc
76
77 cache = "/usr/local/node/node_cache"
78 prefix = "/usr/local/node/node_global"
79 registry = "http://mirrors.cloud.tencent.com/npm/"
80
81 ; node bin location = /usr/local/node/bin/node
82 ; node version = v16.17.0
83 ; npm local prefix = /root
84 ; npm version = 8.15.0
85 ; cwd = /root
86 ; HOME = /root
87 ; Run `npm config ls -l` to show all defaults.
88 [root@services ~]#
```

服务部署

MySQL部署

```

1 [root@services ~]# yum -y install mysql mysql-server
2 [root@services ~]# systemctl enable mysqld --now
3 [root@services ~]# mysql
4
5 mysql> create user prouser@'%' identified by '123456';
6 Query OK, 0 rows affected (0.10 sec)
7
8 mysql> grant all on *.* to prouser@'%';
9 Query OK, 0 rows affected (0.83 sec)
10
11 mysql> flush privileges;
12 Query OK, 0 rows affected (0.02 sec)
13
14 mysql> exit
15 Bye
16 [root@services ~]#

```

Redis部署

```

1 [root@services ~]# ls
2 install_redis.sh  redis-6.2.6.tar.gz  redis.service redis
3 [root@services ~]# bash install_redis.sh
4 [root@services ~]# ls /usr/local/redis/
5 bin  conf  data  logs
6 [root@services ~]# vim /usr/local/redis/conf/redis.conf
7 [root@services ~]# sed -rn '901p' /usr/local/redis/conf/redis.conf
8 requirepass 123456
9 [root@services ~]# mv redis /etc/init.d/
10 [root@services ~]# chmod +x /etc/init.d/redis
11 [root@services ~]# /etc/init.d/redis start
12 [root@services ~]# /usr/local/redis/bin/redis-cli -a '123456' ping
13 warning: Using a password with '-a' or '-u' option on the command line interface
    may not be safe.
14 PONG
15 [root@services ~]#

```

智慧充电单体

代码配置

```

1 [root@services Charging]# ls charge/
2 BACKEND-ADMIN  BACKEND-SERVICE  FRONTEND-APP
3 [root@services Charging]# cd charge/BACKEND-SERVICE/RuoYi-Vue-master/
4 [root@services RuoYi-Vue-master]# ls
5 admin-deploy  pom.xml          ruoyi-framework  ruoyi-system
6 bin           README.md        ruoyi-generator  ry.bat
7 doc           ruoyi-admin     ruoyi.iml        ry.sh
8 LICENSE       ruoyi-common    ruoyi-quartz     sql
9 [root@services RuoYi-Vue-master]# cd ../../BACKEND-SERVICE/RuoYi-Vue-master/ruoyi-
    admin/src/main/resources
10 [root@services resources]# ls

```

```

11 application-codeboy.yml application-web-tech.yml i18n META-INF
12 application-druid.yml application.yml logback.xml mybatis
13 application-vm.yml banner.txt mapper static
14 [root@services resources]# sed -rn '/192.168.88/p' application-vm.yml
15 url: jdbc:mysql://127.0.0.1:3306/charging_deploy?
useUnicode=true&characterEncoding=utf8&zeroDateTimeBehavior=convertToNull&useSSL=true&serverTimezone=GMT%2B8
16 host: 127.0.0.1

```

代码编译

```

1 # 后端编译
2 [root@services resources]# cd
3 [root@services ~]# cd Charging/charge/BACKEND-SERVICE/RuoYi-Vue-master/
4 [root@services RuoYi-Vue-master]# ls
5 admin-deploy LICENSE ruoyi-admin ruoyi-generator ruoyi-system sql
6 bin pom.xml ruoyi-common ruoyi.iml ry.bat
7 doc README.md ruoyi-framework ruoyi-quartz ry.sh
8 [root@services RuoYi-Vue-master]# mvn clean package -D'maven.test.skip=true'
9 [root@services RuoYi-Vue-master]# ls ruoyi-admin/target/ruoyi-admin.jar
10 ruoyi-admin/target/ruoyi-admin.jar
11
12 # 管理端编译
13 [root@services RuoYi-Vue-master]# cd ../../BACKEND-ADMIN/ruoyi-ui/
14 [root@services ruoyi-ui]# npm install
15 [root@services ruoyi-ui]# npm run build:prod
16 [root@services ruoyi-ui]# ls dist/
17 favicon.ico html index.html index.html.gz robots.txt static
18 [root@services ruoyi-ui]#
19
20 # h5编译(HBuild完成)

```

单体项目部署

```

1 # 数据库恢复
2 [root@services ruoyi-ui]# cd ../../BACKEND-SERVICE/RuoYi-Vue-master/sql/
3 [root@services sql]# ls
4 charging-deploy.sql quartz.sql ry_20220822.sql
5 [root@services sql]# mysql < charging-deploy.sql
6 [root@services sql]# mysql -e "SHOW DATABASES;"
7 +-----+
8 | Database |
9 +-----+
10 | charging_deploy |
11 | information_schema |
12 | mysql |
13 | performance_schema |
14 | sys |
15 +-----+
16 [root@services sql]#cd
17

```

```

18 # 后端
19 [root@services ~]# mkdir -p /usr/local/project/charge/
20 [root@services ~]# mv Charging/charge/BACKEND-SERVICE/RuoYi-Vue-master/ruoyi-
admin/target/ruoyi-admin.jar /usr/local/project/charge/
21 [root@services ~]# cd /usr/local/project/charge/
22 [root@services charge]# java -jar ruoyi-admin.jar --spring.profile.active=vm
23
24 #另开终端
25 [root@services ~]# cat /usr/local/project/charge/run.sh
26 #!/bin/bash
27 start_project(){
28 nohup java -Dfile.encoding=utf-8 \
29 -jar /usr/local/project/charge/ruoyi-admin.jar \
30 -Xmx256M \
31 -Xms128M \
32 -XX:MaxMetaspaceSize=256M \
33 -XX:MetaspaceSize=128M \
34 --server.port=8080 \
35 --spring.profiles.active=vm >/usr/local/project/charge/ruoyi-admin.log 2>&1 &
36 }
37
38 stop_project(){
39     jps | grep "ruoyi-admin.jar" | awk '{print $1}' | xargs kill
40 }
41
42 case $1 in
43 start)
44     start_project;;
45 stop)
46     stop_project;;
47 *)
48     echo "Usage: $0 {start|stop}"
49 esac
50 [root@services ~]# chmod +x /usr/local/project/charge/run.sh
51 [root@services ~]# /usr/local/project/charge/run.sh start
52 [root@services ~]# ss -antpu | grep java
53 tcp    LISTEN 0      128          *:8080      *:.*      users:
54 (("java",pid=1904,fd=36))
55 [root@services ~]#
56 [root@services ~]# curl http://localhost:8080/charge/station/1
57 {"msg":"操作成功","code":200,"data":
{"searchValue":null,"createBy":null,"createTime":null,"updateBy":null,"updateTime":
null,"remark":null,"params":{"id":1,"stationCode":"001","stationName":"方恒时尚中
心充电
站","deviceNumber":2,"acGunNumber":2,"dcGunNumber":2,"acRatePower":70,"dcRatePower
":60,"province":"01010000","city":"01010000","address":"北京市海淀区北三环西辅路方恒时尚
中心方
恒","stationLng":116.342130,"stationLat":39.968092,"devicePower":150,"stationModel
":3,"stationStatus":0,"stationType":1,"stationModified":"2018-08-
09","stationCreate":"2018-08-09","operatorId":1,"parkFee":3}}[root@charge ~]#
58
59 # 管理端

```

```

60 [root@services ~]# yum -y install nginx
61 [root@services ~]# mv Charging/charge/BACKEND-ADMIN/ruoyi-ui/dist/
   /usr/local/project/charge/
62 [root@services ~]# vim /etc/nginx/conf.d/charge.conf
63 [root@services ~]# cat /etc/nginx/conf.d/charge.conf
64 server {
65     listen 8000;
66     server_name __;
67
68     location / {
69         root "/usr/local/project/charge/dist/";
70         index index.html;
71     }
72
73     location /prod-api/ {
74         proxy_pass http://127.0.0.1:8080/;
75     }
76 }
77 [root@services ~]# systemctl enable nginx --now
78 [root@services ~]# ss -antpu | grep nginx
79 tcp LISTEN 0      128          0.0.0.0:8000  0.0.0.0:*    users:
   (("nginx",pid=4660,fd=6),("nginx",pid=4659,fd=6),("nginx",pid=4658,fd=6))
80 tcp LISTEN 0      128          0.0.0.0:80   0.0.0.0:*    users:
   (("nginx",pid=4660,fd=7),("nginx",pid=4659,fd=7),("nginx",pid=4658,fd=7))
81 tcp LISTEN 0      128          [::]:80      [::]:*       users:
   (("nginx",pid=4660,fd=8),("nginx",pid=4659,fd=8),("nginx",pid=4658,fd=8))
82
83 [root@services ~]# cd /root/Charging/charge/FRONTEND-
   APP/chargingDeploy/chargingDeploy/unpackage/dist/build
84 [root@services build]# ls
85 h5.zip
86 [root@services build]# unzip -q h5.zip
87 [root@services build]# ls
88 h5 h5.zip
89 [root@services build]# mv h5 /usr/local/project/charge/
90 [root@services build]# ls /usr/local/project/charge/
91 dist h5 run.sh ruoyi-admin.jar ruoyi-admin.log
92 [root@services ~]# vim /etc/nginx/conf.d/charge.conf
93 [root@services ~]# sed -rn '15,$p' /etc/nginx/conf.d/charge.conf
94 server {
95     listen 80;
96     server_name __;
97
98     location / {
99         root "/usr/local/project/charge/h5/";
100        index index.html;
101    }
102
103    location /prod-api/ {
104        proxy_pass http://127.0.0.1:8080/;
105    }
106 }
107 [root@services ~]# vim /etc/nginx/nginx.conf

```

```
108 [root@services ~]# sed -rn '39,40p' /etc/nginx/nginx.conf
109     #listen      80 default_server;
110     #listen      [::]:80 default_server;
111 [root@services ~]# systemctl restart nginx
112 [root@services ~]# ss -antpu | grep nginx
113 tcp    LISTEN 0      128          0.0.0.0:8000    0.0.0.0:*      users:
114      ((("nginx",pid=5680,fd=6),("nginx",pid=5679,fd=6),("nginx",pid=5678,fd=6))
115 tcp    LISTEN 0      128          0.0.0.0:80     0.0.0.0:*      users:
116      ((("nginx",pid=5680,fd=7),("nginx",pid=5679,fd=7),("nginx",pid=5678,fd=7))
117 [root@services ~]#
118 公网IP访问测试
```

49.232.54.116/#/pages/nearbyStation/nearbyStation

Kimi.ai - 帮你看看更大... 云计算VIP笔记地址 达 top审批列表 - 教研讲... NSDVN2312 Dev NSDVN2310 登录直播系统 Dev

附近电桩



