

See discussions, stats, and author profiles for this publication at: <https://www.researchgate.net/publication/336982801>

RASP 4: ancestral state reconstruction tool for multiple genes and characters

Article in *Molecular Biology and Evolution* · October 2019

DOI: 10.1093/molbev/msz257

CITATION

1

READS

225

3 authors, including:



Yan Yu

Sichuan University

80 PUBLICATIONS 1,543 CITATIONS

[SEE PROFILE](#)



Xing-Jin He

Sichuan University

220 PUBLICATIONS 2,595 CITATIONS

[SEE PROFILE](#)

Some of the authors of this publication are also working on these related projects:



Molecular phylogeny; Evolutionary History; Floral Genome Project; Taxionamy [View project](#)

RASP 4: Ancestral State Reconstruction Tool for Multiple Genes and Characters

Yan Yu,^{1,2,*} Christopher Blair,^{3,4} and Xingjin He^{*,1}

¹Key Laboratory of Bio-Resources and Eco-Environment of Ministry of Education, College of Life Sciences, Sichuan University, Chengdu, Sichuan, P.R. China

²Bioinformatics Core, College of Life Sciences, Sichuan University, Chengdu, Sichuan, P. R. China

³Department of Biological Sciences, New York City College of Technology, The City University of New York, Brooklyn, NY

⁴Biology PhD Program, CUNY Graduate Center, New York, NY

*Corresponding authors: E-mails: yyu@scu.edu.cn; xjhe@scu.edu.cn.

Associate editor: Anne Yoder

Abstract

With the continual progress of sequencing techniques, genome-scale data are increasingly used in phylogenetic studies. With more data from throughout the genome, the relationship between genes and different kinds of characters is receiving more attention. Here, we present version 4 of RASP, a software to reconstruct ancestral states through phylogenetic trees. RASP can apply generalized statistical ancestral reconstruction methods to phylogenies, explore the phylogenetic signal of characters to particular trees, calculate distances between trees, and cluster trees into groups. RASP 4 has an improved graphic user interface and is freely available from <http://mnh.scu.edu.cn/soft/blog/RASP> (program) and <https://github.com/sculab/RASP> (source code).

Key words: ancestral state reconstruction, genome, phylogeny, phylogenetic signal.

RASP (Reconstruct Ancestral State in Phylogenies) is a software to reconstruct ancestral states through phylogenetic trees. To date, the program has been used to infer biogeographic history in numerous groups of animals, plants, fungi, and bacteria (Blair et al. 2015; Yu et al. 2015; Stucki et al. 2016; Bourguignon et al. 2018; Navaud et al. 2018; Yan et al. 2018). With the continual progress of sequencing techniques, the data from genomes, transcriptomes, and proteomes have been increasingly used in phylogenetic studies (Choi and Kim 2017). Additionally, morphology, ecology, and distribution data are increasingly integrated into research (Soltis and Soltis 2016). This motivated us to add more functionality into RASP to implement additional algorithms and tools.

The new version of RASP can analyze phylogenomic data (and other types of data), make inference on our generalized statistical method for ancestral state reconstruction (Fig. 1A) and summarize results under a graphical user interface (Fig. 1B). Users are also allowed to quantify phylogenetic signal of different morphological or ecological characters to particular trees (Fig. 1C), inferring ancestral states for traits (Fig. 1D), and compute a distance matrix to cluster trees (Fig. 1E).

Methods to reconstruct ancestral geographical distributions using a combination of phylogenetic and distributional information are increasing rapidly. In RASP 4, we implement a generalized statistical method for models implemented in the R package “BioGeoBEARS” (Matzke 2014) and “APE” (Paradis and Schliep 2019); namely our method summarizes ancestral reconstructions across all input trees. The probability (p) of an ancestral range x at node n on the final species tree is

calculated as $p(x_n) = \sum_{t \in T} [w(x_n)_t] / g_n$ where T is the set of trees, $w(x_n)_t$ is the weight of ancestral range x at node n for tree t , and g_n is the number of times node n occurs in T (see supplementary material, Supplementary Material online for details). To reduce computational burden, RASP applies parallel computing to all models both by taking advantage of multiple threads and splitting trees into small groups. See supplementary table S1, Supplementary Material online for a full comparison of the methods of ancestral reconstruction implemented in RASP.

Phylogenetic signal is the tendency of related species to resemble each other in a specific character more than species drawn at random from the same tree (Münkemüller et al. 2012). To test for phylogenetic signal for continuous states, RASP calculates Moran's I (Moran 1948, 1950), Abouheif's C_{mean} (Abouheif 1999), Pagel's λ (Pagel 1999), and Blomberg's K (Blomberg et al. 2003) using the R package “ade4phylo” (Jombart et al. 2010). For discrete states, RASP fits models of trait evolution using a likelihood ratio test and calculates Pagel's λ using the R package “geiger” (Pennell et al. 2014; Fig. 1C). If some species have more than one state, RASP will convert them to all possible combinations of single states and calculate Pagel's λ for each of them. The largest Pagel's λ is used in the final result.

Tree distances are often used as a formal way to quantify the differences of trees inferred from different genes and reconstruction methods (Sand et al. 2014). In RASP, users can compute trees distances using different methods: KC distance (Kendall and Colijn 2016), triplet distance implemented in mp-est (Liu et al. 2010), RF distance (Robinson and Foulds




FIG. 1. Screenshots from RASP 4. The sample data and tutorials can be found on the RASP website. (A) The main screen of RASP. The expanded menu shows the ancestral state reconstruction methods implemented in RASP. (B) The tree view interface of RASP. The graphic shows the results of using the DIVALike model in BioGeoBEARS. The expanded menu shows the operations that can be performed on the results. (C) The Trees and States tool. The list shows the results of phylogenetic signal for three states. (D) Graphical interface showing ancestral state reconstruction results from BayesTraits (Meade and Pagel 2018). (E) The Trees versus Trees tool. The expanded menu shows the supported distance methods.

1981), KF distance (Kuhner and Felsenstein 1994), path differences (Steel and Penny 1993), and SPR distance (de Oliveira Martins et al. 2008; De Oliveira Martins et al. 2016) implemented in the R package “phangorn” (Schliep 2011; supplementary table S2, Supplementary Material online). Having the distance matrix, values can be normalized using min–max normalization (Han et al. 2006). Next, trees are clustered into groups using the R package “adeget” (Jombart 2008) according to the distance matrix. The end result may provide insight into the sources of heterogeneity among gene/species histories. For example, distinct clusters of genes may indicate unique phylogenetic signatures (Kendall and Colijn 2016). Additionally, the tree distance matrix and groups could be used to provide a candidate species tree under the coalescent model (Liu et al. 2010).

In summary, the new version of RASP 4 implements several tools for multiple gene and species trees and characters while simultaneously making it easier to process trees generated from different sources. We provide six tutorials to help users select appropriate methods for different research questions

on the our website (<http://mnh.scu.edu.cn/soft/blog/RASP/>; last accessed October 31, 2019) and GitHub (<https://github.com/sculab/RASP/tree/master/Tutorials>; last accessed October 31, 2019). We will continue to develop RASP with a focus on implementing new algorithms and integrating more tools. RASP for Windows and macOS are available freely from <http://mnh.scu.edu.cn/soft/blog/RASP> (program) and <https://github.com/sculab/RASP> (source code), and licensed under the terms of the MIT license.

Supplementary Material

Supplementary data are available at *Molecular Biology and Evolution* online.

Acknowledgments

We thank Liang Liu, Jianquan Liu, and Kangshan Mao for discussion. This study was supported by the National Natural Science Foundation of China (Grant No. 31500188), the Specimen Platform of Sichuan Nature Reserve (Grant No.

18PTDJ0114), and the Specimen Platform of China, Teaching Specimen's sub-platform, the Science and Technology Basic Work (Grant No. 2013FY112100).

References

- Abouheif E. 1999. A method for testing the assumption of phylogenetic independence in comparative data. *Evol Ecol Res.* 1:895–909.
- Blair C, Noonan B, Brown J, Raselimanana A, Vences M, Yoder A. 2015. Multilocus phylogenetic and geospatial analyses illuminate diversification patterns and the biogeographic history of Malagasy endemic plated lizards (Gerrhosauridae: Zonosaurinae). *J Evol Biol.* 28(2):481–492.
- Blomberg SP, Garland T Jr, Ives AR. 2003. Testing for phylogenetic signal in comparative data: behavioral traits are more labile. *Evolution* 57(4):717–745.
- Bourguignon T, Tang Q, Ho SYW, Juna F, Wang Z, Arab DA, Cameron SL, Walker J, Rentz D, Evans TA, et al. 2018. Transoceanic dispersal and plate tectonics shaped global cockroach distributions: evidence from mitochondrial phylogenomics. *Mol Biol Evol.* 35(4):970–983.
- Choi J, Kim S-H. 2017. A genome tree of life for the fungi kingdom. *Proc Natl Acad Sci U S A.* 114(35):9391–9396.
- de Oliveira Martins L, Leal E, Kishino H. 2008. Phylogenetic detection of recombination with a Bayesian prior on the distance between trees. *PLoS One* 3(7):e2651.
- De Oliveira Martins L, Mallo D, Posada D. 2016. A Bayesian supertree model for genome-wide species tree reconstruction. *Syst Biol.* 65(3):397–416.
- Han J, Jian P, Michelin K. 2006. Data mining, Southeast Asia edition. San Francisco (CA): Elsevier Inc.
- Jombart T. 2008. adegenet: a R package for the multivariate analysis of genetic markers. *Bioinformatics* 24(11):1403–1405.
- Jombart T, Balloux F, Dray S. 2010. Adephylo: new tools for investigating the phylogenetic signal in biological traits. *Bioinformatics* 26(15):1907–1909.
- Kendall M, Colijn C. 2016. Mapping phylogenetic trees to reveal distinct patterns of evolution. *Mol Biol Evol.* 33(10):2735–2743.
- Kuhner MK, Felsenstein J. 1994. A simulation comparison of phylogeny algorithms under equal and unequal evolutionary rates. *Mol Biol Evol.* 11(3):459–468.
- Liu L, Yu L, Edwards SV. 2010. A maximum pseudo-likelihood approach for estimating species trees under the coalescent model. *BMC Evol Biol.* 10(1):302.
- Matzke NJ. 2014. Model selection in historical biogeography reveals that founder-event speciation is a crucial process in island clades. *Syst Biol.* 63(6):951–970.
- Meade A, Pagel M. 2017. BayesTraits: a computer package for analyses of trait evolution. Version 3. Available from: <http://www.evolution.rdg.ac.uk/BayesTraits.html>.
- Moran PA. 1948. The interpretation of statistical maps. *J R Stat Soc Ser B (Methodol).* 10(2):243–251.
- Moran PA. 1950. Notes on continuous stochastic phenomena. *Biometrika* 37(1–2):17–23.
- Münkemüller T, Lavergne S, Bzeznik B, Dray S, Jombart T, Schiffrers K, Thuiller W. 2012. How to measure and test phylogenetic signal. *Methods Ecol Evol.* 3(4):743–756.
- Navaud O, Barbacci A, Taylor A, Clarkson JP, Raffaele S. 2018. Shifts in diversification rates and host jump frequencies shaped the diversity of host range among Sclerotiniaceae fungal plant pathogens. *Mol Ecol.* 27(5):1309–1323.
- Pagel M. 1999. Inferring the historical patterns of biological evolution. *Nature* 401(6756):877.
- Paradis E, Schliep K. 2019. ape 5.0: an environment for modern phylogenetics and evolutionary analyses in R. *Bioinformatics* 35(3):526–528.
- Pennell MW, Eastman JM, Slater GJ, Brown JW, Uyeda JC, FitzJohn RG, Alfaro ME, Harmon LJ. 2014. geiger v2. 0: an expanded suite of methods for fitting macroevolutionary models to phylogenetic trees. *Bioinformatics* 30(15):2216–2218.
- Robinson DF, Foulds LR. 1981. Comparison of phylogenetic trees. *Math Biosci.* 53(1–2):131–147.
- Sand A, Holt MK, Johansen J, Brodal GS, Mailund T, Pedersen CN. 2014. tqDist: a library for computing the quartet and triplet distances between binary or general trees. *Bioinformatics* 30(14):2079–2080.
- Schliep KP. 2011. phangorn: phylogenetic analysis in R. *Bioinformatics* 27(4):592–593.
- Soltis DE, Soltis PS. 2016. Mobilizing and integrating big data in studies of spatial and phylogenetic patterns of biodiversity. *Plant Divers.* 38(6):264–270.
- Steel MA, Penny D. 1993. Distributions of tree comparison metrics—some new results. *Syst Biol.* 42:126–141.
- Stucki D, Brites D, Jeljeli L, Coscolla M, Liu Q, Trauner A, Fenner L, Rutaihua L, Borrell S, Luo T, et al. 2016. Mycobacterium tuberculosis lineage 4 comprises globally distributed and geographically restricted sublineages. *Nat Genet.* 48(12):1535–1543.
- Yan H-F, Zhang C-Y, Anderberg AA, Hao G, Ge X-J, Wiens JJ. 2018. What explains high plant richness in East Asia? Time and diversification in the tribe Lysimachieae (Primulaceae). *New Phytol.* 219(1):436–448.
- Yu Y, Harris AJ, Blair C, He X. 2015. RASP (Reconstruct Ancestral State in Phylogenies): a tool for historical biogeography. *Mol Phylogenet Evol.* 87:46–49.