



search

Home

+=1

Support the Content

Community

Log in

Sign up

Converting Tkinter application to .exe and installer with cx_Freeze

Converting tkinter to exe tutorial with cx_Freeze - Python 3.4 part 29



setup.py code:

```
import cx_Freeze
import sys
import matplotlib

base = None

if sys.platform == 'win32':
    base = "Win32GUI"

executables = [cx_Freeze.Executable("tkinterVid28.py", base=base, icon="cli
```



```
options = {"build_exe": {"packages": ["tkinter", "matplotlib"], "include_
version = "0.01",
description = "Sea of BTC trading application",
executables = executables
)
```

The icon if you don't have it:



Saved as tkinterVid28.py:

```
# The code for changing pages was derived from: http://stackoverflow.com/qu
# License: http://creativecommons.org/licenses/by-sa/3.0/
```

```
import matplotlib
matplotlib.use('TkAgg')
import matplotlib.animation as animation
from numpy import arange, sin, pi
from matplotlib.backends.backend_tkagg import FigureCanvasTkAgg, Navigation
from matplotlib.figure import Figure
import matplotlib.dates as mdates
import matplotlib.ticker as mticker
from matplotlib.finance import candlestick_ohlc

import tkinter as tk
from tkinter import ttk
from matplotlib import style

import urllib
import json
import pandas as pd
import numpy as np
from matplotlib import pyplot as plt

style.use('ggplot')
```



LARGE_FONT = ("Verdana", 12)
 NORM_FONT = ("Helvetica", 10) Home +=1 Support the Content Community
 SMALL_FONT = ("Helvetica", 8)

Log in Sign up

```
f = plt.figure()
a = f.add_subplot(111)
```

```
exchange = "BTC-e"
DatCounter = 9000
programName = "btce"
```

```
resampleSize = "15Min"
```

```
#####
```

```
## set this to 1day.
```

```
DataPace = "1d"
```

```
#####
```

```
paneCount = 1
```

```
candleWidth = 0.008
```

```
topIndicator = "none"
```

```
bottomIndicator = "none"
```

```
middleIndicator = "none"
```

```
chartLoad = True
```

```
EMAs = []
```

```
SMAs = []
```

```
darkColor = '#183A54'
```

```
lightColor = '#00A3E0'
```

```
def tutorial():
    def leavemini(what):
```



```
def page2():
    leavemini(tut)
    tut2 = tk.Tk()
    def leavemini2(what):
        what.destroy()

    def page3():

        leavemini2(tut2)
        tut3 = tk.Tk()
        tut3.wm_title("part 3!")

        label = ttk.Label(tut3, text="Part 3", font=NORM_FONT)
        label.pack(side="top", fill="x", pady=10)
        B1 = ttk.Button(tut3, text = "Done!", command = tut3.destroy)
        B1.pack()
        tut3.mainloop()

    tut2.wm_title("part 2!")

    label = ttk.Label(tut2, text="Part 2", font=NORM_FONT)
    label.pack(side="top", fill="x", pady=10)
    B1 = ttk.Button(tut2, text = "next!", command = page3)
    B1.pack()

    tut.mainloop()

tut = tk.Tk()
tut.wm_title("Tutorial")
label = ttk.Label(tut, text="What do you need help with?", font=NORM_FONT)
label.pack(side="top", fill="x", pady=10)
B1 = ttk.Button(tut, text = "Overview of the application", command = page2)
B1.pack()

B2 = ttk.Button(tut, text = "How do I trade here?", command=lambda: pop)
B2.pack()

B3 = ttk.Button(tut, text = "Indicator questions/help", command=lambda: pop)
B3.pack()
```

[Home](#)[+=1](#)[Support the Content](#)[Community](#)

```
def loadChart(run):  
    global chartLoad
```

[Log in](#)[Sign up](#)

```
    if run == 'start':  
        chartLoad = True  
    elif run == 'stop':  
        chartLoad = False
```

```
def addTopIndicator(what):  
    global topIndicator  
    global DatCounter
```

```
    if DataPace == "tick":  
        popupmsg("Indicators in Tick Data not available, choose 1 minute tf
```

```
    if what == "none":  
        topIndicator = what  
        DatCounter = 9000
```

```
    elif what == "rsi":  
        rsiQ = tk.Tk()  
        rsiQ.wm_title("Periods?")  
        label = ttk.Label(rsiQ, text="Choose how many periods you want each  
        label.pack(side="top", fill="x", pady=10)
```

```
        e = ttk.Entry(rsiQ)  
        e.insert(0,14)  
        e.pack()  
        e.focus_set()
```

```
    def callback():
```



```
periods = (e.get())
```

```
group = []
```

```
group.append("rsi")
```

```
group.append(periods)
```

```
topIndicator = group
```

```
DatCounter = 9000
```

```
print("set top indicator to",group)
```

```
rsiQ.destroy()
```

```
b = ttk.Button(rsiQ, text="Submit", width=10, command=callback)
```

```
b.pack()
```

```
tk.mainloop()
```

```
elif what == "macd":
```

```
global topIndicator
```

```
global DatCounter
```

```
topIndicator = "macd"
```

```
DatCounter = 9000
```

```
def addMiddleIndicator(what):
```

```
global middleIndicator
```

```
global DatCounter
```

```
if DataPace == "tick":
```

```
    popupmsg("Indicators in Tick Data not available, choose 1 minute tf")
```

```
if what != "none":
```

```
    if middleIndicator == "none":
```

```
        if what == "sma":
```

```
            midIQ = tk.Tk()
```

```
            midIQ.wm_title("Periods?")
```

```
            label = ttk.Label(midIQ, text="Choose how many periods you")
```

```
            label.pack(side="top", fill="x", pady=10)
```

```
            e = ttk.Entry(midIQ)
```

```
            e.insert(0,10)
```

```
            e.pack()
```

```
            e.focus_set()
```

```
            def callback():
```



```

middleIndicator = []
periods = (e.get())
group = []
group.append("sma")
group.append(int(periods))
middleIndicator.append(group)
DatCounter = 9000
print("mid indicator",middleIndicator)
midIQ.destroy()
b = ttk.Button(midIQ, text="Submit", width=10, command=call
b.pack()
tk.mainloop()

if what == "ema":
    midIQ = tk.Tk()
    midIQ.wm_title("Periods?")
    label = ttk.Label(midIQ, text="Choose how many periods you
    label.pack(side="top", fill="x", pady=10)
    e = ttk.Entry(midIQ)
    e.insert(0,10)
    e.pack()
    e.focus_set()
    def callback():
        global middleIndicator
        global DatCounter
        middleIndicator = []
        periods = (e.get())
        group = []
        group.append("ema")
        group.append(int(periods))
        middleIndicator.append(group)
        DatCounter = 9000
        print("mid indicator",middleIndicator)
        midIQ.destroy()
    b = ttk.Button(midIQ, text="Submit", width=10, command=call
    b.pack()
    tk.mainloop()

else:
    if what == "sma":
        midIQ = tk.Tk()

```



```
label.pack(side="top", fill="x", pady=10)
e = ttk.Entry(midIQ)
e.insert(0,10)
e.pack()
e.focus_set()
def callback():
    global middleIndicator
    global DatCounter
    periods = (e.get())
    group = []
    group.append("sma")
    group.append(int(periods))
    middleIndicator.append(group)
    DatCounter = 9000
    print("mid indicator",middleIndicator)
    midIQ.destroy()
b = ttk.Button(midIQ, text="Submit", width=10, command=call
b.pack()
tk.mainloop()
```

```
if what == "ema":
    midIQ = tk.Tk()
    midIQ.wm_title("Periods?")
    label = ttk.Label(midIQ, text="Choose how many periods you
label.pack(side="top", fill="x", pady=10)
e = ttk.Entry(midIQ)
e.insert(0,10)
e.pack()
e.focus_set()
def callback():
    global middleIndicator
    global DatCounter
    periods = (e.get())
    group = []
    group.append("ema")
    group.append(int(periods))
    middleIndicator.append(group)
    DatCounter = 9000
    print("mid indicator",middleIndicator)
    midIQ.destroy()
b = ttk.Button(midIQ, text="Submit", width=10, command=call
b.pack()
```




middleIndicator = "none"

Home

+=1

Support the Content

Community

Log in

Sign up

```

def addBottomIndicator(what):
    global bottomIndicator
    global DatCounter

    if DataPace == "tick":
        popupmsg("Indicators in Tick Data not available, choose 1 minute tf

    if what == "none":
        bottomIndicator = what
        DatCounter = 9000

    elif what == "rsi":
        rsiQ = tk.Tk()
        rsiQ.wm_title("Periods?")
        label = ttk.Label(rsiQ, text="Choose how many periods you want each
        label.pack(side="top", fill="x", pady=10)

        e = ttk.Entry(rsiQ)
        e.insert(0,14)
        e.pack()
        e.focus_set()

    def callback():
        global bottomIndicator
        global DatCounter
        periods = (e.get())
        group = []
        group.append("rsi")
        group.append(periods)
        bottomIndicator = group
        DatCounter = 9000
        print("set top indicator to",group)
        rsiQ.destroy()

    b = ttk.Button(rsiQ, text="Submit", width=10, command=callback)
    b.pack()

```



```
elif what == "macd":
```

```
    global bottomIndicator
```

```
    global DatCounter
```

```
    bottomIndicator = "macd"
```

```
    DatCounter = 9000
```

```
def changeTimeFrame(tf):
```

```
    global DataPace
```

```
    global DatCounter
```

```
    if tf == '7d' and resampleSize == '1Min':
```

```
        popupmsg("Too much data chosen, choose a smaller data time frame or
```

```
    else:
```

```
        DataPace = tf
```

```
        DatCounter = 9000
```

```
def changeSampleSize(size,width):
```

```
    global resampleSize
```

```
    global DatCounter
```

```
    global candleWidth
```

```
    if DataPace == '7d' and size == '1Min':
```

```
        popupmsg("Too much data chosen, choose a smaller Data Time Frame or
```

```
    if DataPace == 'tick':
```

```
        popupmsg("You are currently viewing tick data, not OHLC. Choose a l
```

```
    else:
```

```
        resampleSize = size
```

```
        DatCounter = 9000
```

```
        candleWidth = width
```

```
def popupmsg(msg):
```

```
    popup = tk.Tk()
```

```
    def leavemini():
```

```
        popup.destroy()
```

```
    popup.wm_title("!")
```



```

label.pack(side="top", fill="x", pady=10)
B1 = ttk.Button(popup, text = "Okay", command = leaveMini)
B1.pack()

popup.mainloop()

def changeExchange(toWhat,pn):
    global exchange
    global DatCounter
    global programName
    exchange = toWhat
    programName = pn
    DatCounter = 9000

def animate(i):
    global refreshRate
    global DatCounter

#####
#####

def computeMACD(x, slow=26, fast=12,location="bottom"):
    """
    compute the MACD (Moving Average Convergence/Divergence) using a fa
    return value is emaslow, emafast, macd which are len(x) arrays
    """
    values = {'key': 1,'prices':x}

    url = "http://seaofbtc.com/api/indicator/macd"
    data = urllib.parse.urlencode(values)
    data = data.encode('utf-8')
    req = urllib.request.Request(url, data)
    resp = urllib.request.urlopen(req)
    respData = resp.read()
    newData = str(respData).replace("b","").replace('[','').replace(']')

    #print(newData)

    split = newData.split('::')

    macd = split[0]

```



```
macd = macd.split("Home")
ema9 = ema9.split(", ")
hist = hist.split(", ")
```

+=1

Support the Content

Community

Log in

Sign up

```
try:
    macd = [float(i) for i in macd]
except Exception as e:
    print(str(e)+" macd")
try:
    ema9 = [float(i) for i in ema9]
except Exception as e:
    print(str(e)+" ema9")
try:
    hist = [float(i) for i in hist]
except Exception as e:
    print(str(e)+" hist")
```

```
print("call!!!")
```

```
if location == "top":
    try:
        a0.plot(OHLC['MPLDates'][fast:], macd[fast:], color=darkCol
        a0.plot(OHLC['MPLDates'][fast:], ema9[fast:], color=lightCo
        a0.fill_between(OHLC['MPLDates'][fast:], hist[fast:], 0, al
        datLabel = "MACD"
        a0.set_ylabel(datLabel)
    except Exception as e:
        print(str(e))
        topIndicator = "none"

elif location == "bottom":
    try:
```



```

a3.fill_between(OHLC['MPLDates'], [fast:], hist[fast:], 0, al
datLabel = "MACD" +=1
a3.set_ylabel(datLabel)
except Exception as e:
    print(str(e))
    bottomIndicator = "none"

```

```

#####
#####

```

```

def rsiIndicator(priceData, location="top"):

    if location == "top":
        values = {'key': 1, 'prices': priceData, 'periods': topIndicator[1]}

    elif location == "bottom":
        values = {'key': 1, 'prices': priceData, 'periods': bottomIndicator[1]}

    url = "http://seaofbtc.com/api/indicator/rsi"
    data = urllib.parse.urlencode(values)
    data = data.encode('utf-8')
    req = urllib.request.Request(url, data)
    resp = urllib.request.urlopen(req)
    respData = resp.read()
    newData = str(respData).replace("b", "").replace('[', '').replace(']')
    priceList = newData.split(',')
    rsiData = [float(i) for i in priceList]

    print("call!!!")

    if location == "top":
        a0.plot_date(OHLC['MPLDates'], rsiData, lightColor, label = "RSI")
        datLabel = "RSI(" + str(topIndicator[1]) + ")"
        a0.set_ylabel(datLabel)

    elif location == "bottom":
        a3.plot_date(OHLC['MPLDates'], rsiData, lightColor, label = "RSI")
        datLabel = "RSI(" + str(bottomIndicator[1]) + ")"
        a3.set_ylabel(datLabel)

```



def moving_average(x, n, type='simple'):

```
x = np.asarray(x)
if type=='simple':
    weights = np.ones(n)
else:
    weights = np.exp(np.linspace(-1, 0, n))

weights /= weights.sum()

a = np.convolve(x, weights, mode='full')[:len(x)]
return a
```

if chartLoad:

```
if paneCount == 1:
    if DataPace == "tick":
        try:
            if exchange == "BTC-e":
                a = plt.subplot2grid((6,4), (0,0), rowspan=5, colsp
                a2 = plt.subplot2grid((6,4), (5,0), rowspan=1, colsp

                dataLink = 'https://btc-e.com/api/3/trades/btc_usd?
                data = urllib.request.urlopen(dataLink)
                data = data.readall().decode('utf-8')
                data = json.loads(data)
                data = data["btc_usd"]
                data = pd.DataFrame(data)

                data["datestamp"] = np.array(data['timestamp']).ast
                allDates = data["datestamp"].tolist()

                buys = data[(data['type']=='bid')]
                buyDates = (buys["datestamp"]).tolist()

                sells = data[(data['type']=='ask')]
                sellDates = (sells["datestamp"]).tolist()
```



```
a.clear()
```

Home +=1 Support the Content Community

```
a.plot_date(buyDates,buys["price"], lightColor, lab
```

Log in Sign up

```
a.plot_date(sellDates,sells["price"], darkColor, la
```

```
a2.fill_between(allDates,0, volume, facecolor='#183
```

```
a.xaxis.set_major_locator(mticker.MaxNLocator(5))
```

```
a.xaxis.set_major_formatter(mdates.DateFormatter('%
```

```
plt.setp(a.get_xticklabels(), visible=False)
```

```
a.legend(bbox_to_anchor=(0., 1.02, 1., .102), loc=3
         ncol=2, borderaxespad=0.)
```

```
title = 'Last Price: '+str(data["price"][1999])
```

```
a.set_title(title)
```

```
if exchange == 'Bitstamp':
```

```
    a = plt.subplot2grid((6,4), (0,0), rowspan=5, colsp
```

```
    a2 = plt.subplot2grid((6,4), (5,0), rowspan=1, cols
```

```
    dataLink = 'https://www.bitstamp.net/api/transactio
```

```
    data = urllib.request.urlopen(dataLink)
```

```
    data = data.readall().decode('utf-8')
```

```
    data = json.loads(data)
```

```
    data = pd.DataFrame(data)
```

```
    data["datestamp"] = np.array(data['date'].apply(int
```

```
    datestamps = data["datestamp"].tolist()
```

```
    volume = data["amount"].apply(float).tolist()
```

```
    a.clear()
```

```
    a.plot_date(datestamps,data["price"], '#183A54')
```

```
    a2.fill_between(datestamps,0, volume, facecolor='#1
```



```

plt.setp(a.get_xticklabels(), visible=False)
    Home    +=1    Support the Content    Community
title = exchange+' Tick Data\nLast Price: '+str(dat
a.set_title(title)
    Log in    Sign up
priceData = data["price"].apply(float).tolist()

if exchange == 'Bitfinex':
    a = plt.subplot2grid((6,4), (0,0), rowspan=5, colsp
    a2 = plt.subplot2grid((6,4), (5,0), rowspan=1, cols

    dataLink = 'https://api.bitfinex.com/v1/trades/btcu

    data = urllib.request.urlopen(dataLink)
    data = data.readall().decode('utf-8')
    data = json.loads(data)
    data = pd.DataFrame(data)

    volume = data["amount"].apply(float).tolist()

    data["datestamp"] = np.array(data['timestamp']).ast
    allDates = data["datestamp"].tolist()

    buys = data[(data['type']=='buy')]
    buyDates = (buys["datestamp"]).tolist()

    sells = data[(data['type']=='sell')]
    sellDates = (sells["datestamp"]).tolist()

    a.clear()

    a.plot_date(buyDates,buys["price"], lightColor, lab
    a.plot_date(sellDates,sells["price"], darkColor, la
    a2.fill_between(allDates,0, volume, facecolor='#183

    a.xaxis.set_major_locator(mticker.MaxNLocator(5))
    a.xaxis.set_major_formatter(mdates.DateFormatter('%
plt.setp(a.get_xticklabels(), visible=False)
    a.legend(bbox_to_anchor=(0., 1.02, 1., .102), loc=3

```




```

title = exchange+' Tick Data\nLast Price: '+str(data[0])
a.set_title(title)
priceData = data["price"].apply(float).tolist()

Log in Sign up
if exchange == 'Huobi':
    try:
        a = plt.subplot2grid((6,4), (0,0), rowspan=6, colspan=4)

        data = urllib.request.urlopen('http://seaofbtc.com/api/v1/ticker?symbol=BTCUSD')

        data = str(data).replace('b', '').replace("'", '')
        data = json.loads(data)

        dateStamp = np.array(data[0]).astype('datetime64[ns]')
        dateStamp = dateStamp.tolist()
        print('here')

        df = pd.DataFrame({'Datetime':dateStamp})

        df['Price'] = data[1]

        df['Volume'] = data[2]
        df['Symbol'] = "BTCUSD"
        df['MPLDate'] = df['Datetime'].apply(lambda date: date.strftime('%Y-%m-%d %H:%M:%S'))
        df = df.set_index('Datetime')
        lastPrice = df['Price'][-1]

        a.plot_date(df['MPLDate'][-4500:], df['Price'][-4500:], 'b-', lw=2)

        a.xaxis.set_major_locator(mticker.MaxNLocator(5))
        a.xaxis.set_major_formatter(mdates.DateFormatter('%Y-%m-%d %H:%M:%S'))

        title = exchange+' Tick Data\nLast Price: '+str(data[0])
        a.set_title(title)
        priceData = df['Price'].apply(float).tolist()
    except Exception as e:

```



Home

+=1

Support the Content

Community

```
except Exception as e:
    print("failed",str(e))
    DatCounter = 9000
```

```
##### ALL OTHER, NON-TICK, DATA. #####
```

```
else:
```

```
    if DatCounter > 12:
```

```
        try:
```

```
            if exchange == 'Huobi':
```

```
                if topIndicator != "none":
```

```
                    a = plt.subplot2grid((6,4), (1,0), rowspan=
```

```
                    a0 = plt.subplot2grid((6,4), (0,0), sharex=
```

```
                else:
```

```
                    a = plt.subplot2grid((6,4), (0,0), rowspan=
```

```
            else:
```

```
                if topIndicator != "none" and bottomIndicator !=
                    # actual price chart.
```

```
                    a = plt.subplot2grid((6,4), (1,0), rowspan=
```

```
                    # volume!
```

```
                    a2 = plt.subplot2grid((6,4), (4,0), sharex=
```

```
                    # top indicator
```

```
                    a0 = plt.subplot2grid((6,4), (0,0), sharex=
```

```
                    # bottom indicator
```

```
                    a3 = plt.subplot2grid((6,4), (5,0), sharex=
```

```
                elif topIndicator != "none":
```

```
                    a = plt.subplot2grid((6,4), (1,0), rowspan=
```

```
                    a2 = plt.subplot2grid((6,4), (5,0), sharex=
```

```
                    a0 = plt.subplot2grid((6,4), (0,0), sharex=
```

```
                elif bottomIndicator != "none":
```

```
                    a = plt.subplot2grid((6,4), (0,0), rowspan=
```

```
                    a2 = plt.subplot2grid((6,4), (4,0), sharex=
```

```
                    #a0 = plt.subplot2grid((6,4), (0,0), sharex=
```

```
                    a3 = plt.subplot2grid((6,4), (5,0), sharex=
```

```
            else:
```


[Home](#)
[+=1](#)
[Support the Content](#)
[Community](#)

```
print('http://seaofbtc.com/api/basic/price?key=1&tf
data = urllib.request.urlopen('http://seaofbtc.com/
```

```
data = str(data).replace('b', '').replace("'", '')
data = json.loads(data)
```

```
dateStamp = np.array(data[0]).astype('datetime64[s]')
dateStamp = dateStamp.tolist()
```

```
df = pd.DataFrame({'Datetime':dateStamp})
df['Price'] = data[1]
df['Volume'] = data[2]
df['Symbol'] = "BTCUSD"
df['MPLDate'] = df['Datetime'].apply(lambda date: m
df = df.set_index('Datetime')
```

```
OHLC = df['Price'].resample(resampleSize, how='ohl
OHLC = OHLC.dropna()
```

```
volumeData = df['Volume'].resample(resampleSize, ho
```

```
OHLC['dateCopy'] = OHLC.index
OHLC['MPLDates'] = OHLC['dateCopy'].apply(lambda da
del OHLC['dateCopy']
```

```
volumeData['dateCopy'] = volumeData.index
volumeData['MPLDates'] = volumeData['dateCopy'].app
del volumeData['dateCopy']
```

```
priceData = OHLC['close'].apply(float).tolist()
```

```
a.clear()
if middleIndicator != "none":
```



Home [+1 Support the content](#) [Community](#)

Log in [Sign up](#)

```

if eachMA[0] == "sma":
    sma = pd.rolling_mean(OHLC["close"], eachMA[1])
    label = str(eachMA[1]) + " SMA"
    a.plot(OHLC['MPLDates'], sma, label=label)
if eachMA[0] == "ema":
    ewma = pd.stats.moments.ewma
    label = str(eachMA[1]) + " EMA"
    a.plot(OHLC['MPLDates'], ewma(OHLC["close"], eachMA[1]), label=label)

```

```

a.legend(loc=0)

```

```


if topIndicator[0] == "rsi":
    rsiIndicator(priceData, "top")
elif topIndicator == "macd":
    try:
        computeMACD(priceData, location="top")
    except:
        print("failed macd")

```

```

if bottomIndicator[0] == "rsi":
    rsiIndicator(priceData, "bottom")
elif bottomIndicator == "macd":
    try:
        computeMACD(priceData, location="bottom")
    except:
        print("failed macd")

```



```

if exchange != 'Huobi':
    Home2.fill_between(volumeData['MPLDates'], 0, volume
    a2.set_ylabel("volume")

    Log in    Sign up

a.xaxis.set_major_locator(mticker.MaxNLocator(3))
a.xaxis.set_major_formatter(mdates.DateFormatter('%

plt.setp(a.get_xticklabels(), visible=False)

if topIndicator != "none":
    plt.setp(a0.get_xticklabels(), visible=False)

if bottomIndicator != "none":
    plt.setp(a2.get_xticklabels(), visible=False)

x = (len(OHLC['close']))-1

if DataPace == '1d':
    title = exchange+' 1 Day Data with '+resampleSi
if DataPace == '3d':
    title = exchange+' 3 Day Data with '+resampleSi
if DataPace == '7d':
    title = exchange+' 7 Day Data with '+resampleSi

if topIndicator != "none":
    a0.set_title(title)
else:
    a.set_title(title)
print('NewGraph!')

DatCounter = 0

```



DatCounter = 9000

Home

+=1

Support the Content

Community

else:

DatCounter += 1

Log in

Sign up

```
class SeaofBTCCapp(tk.Tk):
```

```
    def __init__(self, *args, **kwargs):
```

```
        tk.Tk.__init__(self, *args, **kwargs)
```

```
        tk.Tk.wm_title(self, "Sea of BTC Client")
```

```
        container = tk.Frame(self)
```

```
        container.pack(side="top", fill="both", expand = True)
```

```
        container.grid_rowconfigure(0, weight=1)
```

```
        container.grid_columnconfigure(0, weight=1)
```

```
        menubar = tk.Menu(container)
```

```
        filemenu = tk.Menu(menubar, tearoff=0)
```

```
        filemenu.add_command(label="Save settings", command=lambda: popups
```

```
        filemenu.add_separator()
```

```
        filemenu.add_command(label="Exit", command=quit)
```

```
        menubar.add_cascade(label="File", menu=filemenu)
```

```
        exchangeChoice = tk.Menu(menubar, tearoff=1)
```

```
        exchangeChoice.add_command ( label="BTC-e",
```

```
                                     command=lambda: changeExchange('BTC-e','b
```

```
        exchangeChoice.add_command ( label="Bitfinex",
```

```
                                     command=lambda: changeExchange('Bitfinex'
```

```
        exchangeChoice.add_command ( label="Bitstamp",
```

```
                                     command=lambda: changeExchange('Bitstamp'
```

```
        exchangeChoice.add_command ( label="Huobi",
```


[Home](#)
[+=1](#)
[Support the Content](#)
[Community](#)

```

dataTF = tk.Menu(menubar, tearoff=1)
dataTF.add_command ( label="Tick",
                     command=lambda: changeTimeFrame('tick') )
dataTF.add_command ( label="1 day",
                     command=lambda: changeTimeFrame('1d') )
dataTF.add_command ( label="3 day",
                     command=lambda: changeTimeFrame('3d') )
dataTF.add_command ( label="1 Week",
                     command=lambda: changeTimeFrame('7d') )
menubar.add_cascade(label = "Data Time Frame", menu = dataTF)

OHLCI = tk.Menu(menubar, tearoff=1)

OHLCI.add_command ( label="Tick",
                   command=lambda: changeTimeFrame('tick') )
OHLCI.add_command ( label="1 minute",
                   command=lambda: changeSampleSize('1Min',0
OHLCI.add_command ( label="5 minute",
                   command=lambda: changeSampleSize('5Min',0
OHLCI.add_command ( label="15 minute",
                   command=lambda: changeSampleSize('15Min',
OHLCI.add_command ( label="30 minute",
                   command=lambda: changeSampleSize('30Min',
OHLCI.add_command ( label="1 Hour",
                   command=lambda: changeSampleSize('1H',0.0
OHLCI.add_command ( label="3 Hour",
                   command=lambda: changeSampleSize('3H',0.0
menubar.add_cascade(label = "OHLC Interval", menu = OHLCI)

topIndi = tk.Menu(menubar, tearoff=1)
topIndi.add_command(label="None",
                   command=lambda: addTopIndicator('none'))
topIndi.add_separator()
topIndi.add_command ( label="RSI",
                   command=lambda: addTopIndicator('rsi'))
topIndi.add_command ( label="MACD",
                   command=lambda: addTopIndicator('macd'))

```


[Home](#)
[+=1](#)
[Support the Content](#)
[Community](#)

```

mainI = tk.Menu(menubar, tearoff=1)
mainI.add_command ( label="None",
                    command=lambda: addMiddleIndicator('none')

mainI.add_separator()
mainI.add_command ( label="SMA",
                    command=lambda: addMiddleIndicator('sma')
mainI.add_command ( label="EMA",
                    command=lambda: addMiddleIndicator('ema')
menubar.add_cascade(label = "Main Graph Indicator", menu = mainI)


bottomI = tk.Menu(menubar, tearoff=1)
bottomI.add_command ( label="None",
                     command=lambda: addBottomIndicator('none')

bottomI.add_separator()
bottomI.add_command ( label="RSI",
                     command=lambda: addBottomIndicator('rsi')
bottomI.add_command ( label="MACD",
                     command=lambda: addBottomIndicator('macd')
menubar.add_cascade(label = "Bottom Indicator", menu = bottomI)


tradeButton = tk.Menu(menubar, tearoff=1)
tradeButton.add_command ( label="Manual Trading",
                         command=lambda: print('NOT live yet'))

tradeButton.add_separator()
tradeButton.add_command ( label="Automated Trading",
                         command=lambda: print('NOT live yet'))


tradeButton.add_separator()
tradeButton.add_command ( label="Quick Buy",
                         command=lambda: print('quick buy!'))#, ac
tradeButton.add_command ( label="Quick Sell",
                         command=lambda: print('quick sell!'))#, ac
tradeButton.add_separator()
tradeButton.add_command ( label="Set-up Quick Buy/Sell",
                         command=lambda: print('quick buy!'))

```



[Home](#)
[+=1](#)
[Support the Content](#)
[Community](#)
[Log in](#)
[Sign up](#)

```
startStop = tk.Menu(menubar, tearoff=1)
startStop.add_command ( label="Resume",
                        command=lambda: loadChart('start'))
startStop.add_command ( label="Pause",
                        command=lambda: loadChart('stop'))
menubar.add_cascade(label = "Resume/Pause Client", menu = startStop
```

```
helpmenu = tk.Menu(menubar, tearoff=0)
helpmenu.add_command(label="Tutorial", command=tutorial)
menubar.add_cascade(label="Help", menu=helpmenu)
```

```
tk.Tk.config(self, menu=menubar)
```

```
self.frames = {}
for F in (StartPage, BTCE_Page):
```

```
    frame = F(container, self)
    self.frames[F] = frame
    frame.grid(row=0, column=0, sticky="nsew")
```

```
self.show_frame(StartPage)
```

```
tk.Tk.iconbitmap(self,default='clienticon.ico')
```

```
def show_frame(self, cont):
```

```
    frame = self.frames[cont]
    frame.tkraise()
```

```
class StartPage(tk.Frame):
```

```
    def __init__(self, parent, controller):
        tk.Frame.__init__(self,parent)
```



your API keys into the program. We, as in Sea of BTC, never see your API information. The program may save them locally, however to make things easier on you. Keep in mind that it is a fantastic idea to enable 'IP Whitelisting' if your exchange supports it, and only trading via your specific IP address. On most exchanges, even if so was to acquire your API key, withdrawals are not possible. Some still give the option, so make sure this is turned OFF if your exchange a

Sea of BTC makes no promise of warranty, satisfaction, performance, anything else. Understand that your use of this client is completely at your own risk.""", font=LARGE_FONT)

```
label.pack(side="top", fill="x", pady=10)
```

```
button1 = ttk.Button(self, text="Agree",
                     command=lambda: controller.show_frame(BTCe_Page))
button2 = ttk.Button(self, text="Disagree",
                     command=quit)
```

```
button1.pack()
button2.pack()
```

```
class BTCe_Page(tk.Frame):
```

```
    def __init__(self, parent, controller):
```

```
        tk.Frame.__init__(self, parent)
```

```
        label = ttk.Label(self, text="BTC-e Exchange Page", font=LARGE_FONT)
        label.pack(pady=10, padx=10)
```

```
        canvas = FigureCanvasTkAgg(f, self)
```

```
        canvas.show()
```

```
        canvas.get_tk_widget().pack(side=tk.TOP, fill=tk.BOTH, expand=1)
```

```
        toolbar = NavigationToolbar2TkAgg(canvas, self)
```

```
        toolbar.update()
```

```
        canvas._tkcanvas.pack(side=tk.TOP, fill=tk.BOTH, expand=1)
```



```
ani = animation.FuncAnimation(t, animate, interval=5000)
app.mainloop()
```



[Home](#) [+=1](#) [Support the Content](#) [Community](#)

[Log in](#) [Sign up](#)

There exists 1 **challenge(s)** for this tutorial. [Sign Up To +=1](#) for access to these, video downloads, and no ads.

There exists 2 **quiz/question(s)** for this tutorial. [Sign Up To +=1](#) for access to these, video downloads, and no ads.

That's it for this series. For more tutorials, head to the [Home Page](#)



Programming GUIs and windows with Tkinter and Python Introduction

Object Oriented Programming Crash Course with Tkinter

Passing functions with Parameters in Tkinter using Lambda

How to change and show a new window in Tkinter

Styling your GUI a bit using TTK

How to embed a Matplotlib graph to your Tkinter GUI

How to make the Matplotlib graph live in your application

Organizing our GUI

Plotting Live Updating Data in Matplotlib and our Tkinter GUI

Customizing an embedded Matplotlib Graph in Tkinter

Creating our Main Menu in Tkinter

Building a pop-up message window

Exchange Choice Option

Time-frame and sample size option



Trading option, start/stop, and help menu options

Home

+1

Support the Content

Community

Tutorial on adding a tutorial

Log in

Sign up

Allowing the exchange choice option to affect actual shown exchange

Adding exchange choice cont'd

Adding exchange choices part 3

Indicator Support

Pulling data from the Sea of BTC API

Setting up sub plots within our Tkinter GUI

Graphing an OHLC candlestick graph embedded in our Tkinter GUI

Acquiring RSI data from Sea of BTC API

Acquiring MACD data from Sea of BTC API

Converting Tkinter application to .exe and installer with cx_Freeze



You've reached the end!



Consulting and Contracting

Facebook

Twitter

Instagram

Home

$+=1$

Support the Content

Community

Log in

Sign up

Legal stuff:

Terms and Conditions

Privacy Policy

© OVER 9000! PythonProgramming.net

Programming is a superpower.