



Allowing the exchange choice option to affect actual shown exchange

Exchange choice change - Tkinter tutorial Python 3.4 part 20



*# The code for changing pages was derived from: <http://stackoverflow.com/questions/7546050/switch-between-two->
License: <http://creativecommons.org/licenses/by-sa/3.0/>*

```
import matplotlib
matplotlib.use("TkAgg")
from matplotlib.backends.backend_tkagg import FigureCanvasTkAgg, NavigationToolbar2TkAgg
#from matplotlib.figure import Figure
import matplotlib.animation as animation
from matplotlib import style
from matplotlib import pyplot as plt
```

```
import matplotlib.dates as mdates
import matplotlib.ticker as mticker
```

```
import tkinter as tk
from tkinter import ttk
```

```
import urllib
import json
```

```
import pandas as pd
import numpy as np
```

```
LARGE_FONT= ("Verdana", 12)
NORM_FONT= ("Verdana", 10)
```



```
style.use("ggplot")

f = plt.figure()

#a = f.add_subplot(111)

exchange = "BTC-e"
DatCounter = 9000
programName = "btce"
resampleSize = "15Min"
DataPace = "tick"
candleWidth = 0.008

paneCount = 1

topIndicator = "none"
bottomIndicator = "none"
middleIndicator = "none"
chartLoad = True

EMAs = []
SMAs = []

def tutorial():

    ## def Leavemini(what):
    ##     what.destroy()

    def page2():
        tut.destroy()
        tut2 = tk.Tk()

        def page3():
            tut2.destroy()
            tut3 = tk.Tk()

            tut3.wm_title("Part 3!")

            label = ttk.Label(tut3, text="Part 3", font=NORM_FONT)
            label.pack(side="top", fill="x", pady=10)
            B1 = ttk.Button(tut3, text="Done!", command= tut3.destroy)
            B1.pack()
            tut3.mainloop()

            tut2.wm_title("Part 2!")
            label = ttk.Label(tut2, text="Part 2", font=NORM_FONT)
            label.pack(side="top", fill="x", pady=10)
            B1 = ttk.Button(tut2, text="Next", command= page3)
            B1.pack()
            tut2.mainloop()

        tut = tk.Tk()
        tut.wm_title("Tutorial")
        label = ttk.Label(tut, text="What do you need help with?", font=NORM_FONT)
        label.pack(side="top", fill="x", pady=10)

        B1 = ttk.Button(tut, text = "Overview of the application", command=page2)
```



```

B2 = ttk.Button(tut, text = "How do I trade with this client?", command=lambda:popupmsg("Not yet completed"))
B2.pack()

B3 = ttk.Button(tut, text = "Indicator Questions/Help", command=lambda:popupmsg("Not yet completed"))
B3.pack()

tut.mainloop()

def loadChart(run):
    global chartLoad

    if run == "start":
        chartLoad = True

    elif run == "stop":
        chartLoad = False

def addMiddleIndicator(what):
    global middleIndicator
    global DatCounter

    if DataPace == "tick":
        popupmsg("Indicators in Tick Data not available.")

    if what != "none":
        if middleIndicator == "none":
            if what == "sma":
                midIQ = tk.Tk()
                midIQ.wm_title("Periods?")
                label = ttk.Label(midIQ, text="Choose how many periods you want your SMA to be.")
                label.pack(side="top", fill="x", pady=10)
                e = ttk.Entry(midIQ)
                e.insert(0,10)
                e.pack()
                e.focus_set()

            def callback():
                global middleIndicator
                global DatCounter

                middleIndicator = []
                periods = (e.get())
                group = []
                group.append("sma")
                group.append(int(periods))
                middleIndicator.append(group)
                DatCounter = 9000
                print("middle indicator set to:",middleIndicator)
                midIQ.destroy()

```



```
b.pack()
tk.mainloop()

if what == "ema":
    midIQ = tk.Tk()
    #midIQ.wm_title("Periods?")
    label = ttk.Label(midIQ, text="Choose how many periods you want your EMA to be.")
    label.pack(side="top", fill="x", pady=10)
    e = ttk.Entry(midIQ)
    e.insert(0,10)
    e.pack()
    e.focus_set()

    def callback():
        global middleIndicator
        global DatCounter

        middleIndicator = []
        periods = (e.get())
        group = []
        group.append("ema")
        group.append(int(periods))
        middleIndicator.append(group)
        DatCounter = 9000
        print("middle indicator set to:",middleIndicator)
        midIQ.destroy()

    b = ttk.Button(midIQ, text="Submit", width=10, command=callback)
    b.pack()
    tk.mainloop()

else:
    if what == "sma":
        midIQ = tk.Tk()
        midIQ.wm_title("Periods?")
        label = ttk.Label(midIQ, text="Choose how many periods you want your SMA to be.")
        label.pack(side="top", fill="x", pady=10)
        e = ttk.Entry(midIQ)
        e.insert(0,10)
        e.pack()
        e.focus_set()

        def callback():
            global middleIndicator
            global DatCounter

            #middleIndicator = []
            periods = (e.get())
            group = []
            group.append("sma")
            group.append(int(periods))
            middleIndicator.append(group)
            DatCounter = 9000
            print("middle indicator set to:",middleIndicator)
            midIQ.destroy()

        b = ttk.Button(midIQ, text="Submit", width=10, command=callback)
        b.pack()
        tk.mainloop()
```



```

midIQ.wm_title("Periods?")
label = ttk.Label(midIQ, text="Choose how many periods you want your EMA to be.")
label.pack(side="top", fill="x", pady=10)
e = ttk.Entry(midIQ)
e.insert(0,10)
e.pack()
e.focus_set()

def callback():
    global middleIndicator
    global DatCounter

    #middleIndicator = []
    periods = (e.get())
    group = []
    group.append("ema")
    group.append(int(periods))
    middleIndicator.append(group)
    DatCounter = 9000
    print("middle indicator set to:",middleIndicator)
    midIQ.destroy()

b = ttk.Button(midIQ, text="Submit", width=10, command=callback)
b.pack()
tk.mainloop()

else:
    middleIndicator = "none"

def addTopIndicator(what):
    global topIndicator
    global DatCounter

    if DataPace == "tick":
        popupmsg("Indicators in Tick Data not available.")

    elif what == "none":
        topIndicator = what
        DatCounter = 9000

    elif what == "rsi":
        rsiQ = tk.Tk()
        rsiQ.wm_title("Periods?")
        label = ttk.Label(rsiQ, text = "Choose how many periods you want each RSI calculation to consider.")
        label.pack(side="top", fill="x", pady=10)

        e = ttk.Entry(rsiQ)
        e.insert(0,14)
        e.pack()
        e.focus_set()

    def callback():
        global topIndicator
        global DatCounter

        periods = (e.get())
        group = []
        group.append("rsi")
        group.append(periods)

```



```

    DatCounter = 9000
    print("Set top indicator to",group)
    rsiQ.destroy()

    b = ttk.Button(rsiQ, text="Submit", width=10, command=callback)
    b.pack()
    tk.mainloop()

elif what == "macd":
    global topIndicator
    global DatCounter
    topIndicator = "macd"
    DatCounter = 9000

def addBottomIndicator(what):
    global bottomIndicator
    global DatCounter

    if DataPace == "tick":
        popupmsg("Indicators in Tick Data not available.")

    elif what == "none":
        bottomIndicator = what
        DatCounter = 9000

    elif what == "rsi":
        rsiQ = tk.Tk()
        rsiQ.wm_title("Periods?")
        label = ttk.Label(rsiQ, text = "Choose how many periods you want each RSI calculation to consider.")
        label.pack(side="top", fill="x", pady=10)

        e = ttk.Entry(rsiQ)
        e.insert(0,14)
        e.pack()
        e.focus_set()

    def callback():
        global bottomIndicator
        global DatCounter

        periods = (e.get())
        group = []
        group.append("rsi")
        group.append(periods)

        bottomIndicator = group
        DatCounter = 9000
        print("Set bottom indicator to",group)
        rsiQ.destroy()

    b = ttk.Button(rsiQ, text="Submit", width=10, command=callback)
    b.pack()
    tk.mainloop()

elif what == "macd":
    global bottomIndicator
    global DatCounter
    bottomIndicator = "macd"
    DatCounter = 9000

```



```

def changeTimeFrame(tf):
    global DataPace
    global DatCounter
    if tf == "7d" and resampleSize == "1Min":
        popupmsg("Too much data chosen, choose a smaller time frame or higher OHLC interval")
    else:
        DataPace = tf
        DatCounter = 9000

def changeSampleSize(size,width):
    global resampleSize
    global DatCounter
    global candleWidth
    if DataPace == "7d" and resampleSize == "1Min":
        popupmsg("Too much data chosen, choose a smaller time frame or higher OHLC interval")

    elif DataPace == "tick":
        popupmsg("You're currently viewing tick data, not OHLC.")

    else:
        resampleSize = size
        DatCounter = 9000
        candleWidth = width

def changeExchange(towhat,pn):
    global exchange
    global DatCounter
    global programName

    exchange = towhat
    programName = pn
    DatCounter = 9000

def popupmsg(msg):
    popup = tk.Tk()
    popup.wm_title("!")
    label = ttk.Label(popup, text=msg, font=NORM_FONT)
    label.pack(side="top", fill="x", pady=10)
    B1 = ttk.Button(popup, text="Okay", command = popup.destroy)
    B1.pack()
    popup.mainloop()

def animate(i):
    global refreshRate
    global DatCounter

    if chartLoad:
        if paneCount == 1:
            if DataPace == "tick":
                try:

                    a = plt.subplot2grid((6,4), (0,0), rowspan = 5, colspan = 4)
                    a2 = plt.subplot2grid((6,4), (5,0), rowspan = 1, colspan = 4, sharex = a)

                    dataLink = 'https://btc-e.com/api/3/trades/btc_usd?limit=2000'
                    data = urllib.request.urlopen(dataLink)

```



```

data = data["btc_usd"]
data = pd.DataFrame(data)

data["datestamp"] = np.array(data['timestamp']).astype("datetime64[s]")
allDates = data["datestamp"].tolist()

buys = data[(data['type']=="bid")]
#buys["datestamp"] = np.array(buys["timestamp"]).astype("datetime64[s]")
buyDates = (buys["datestamp"]).tolist()

sells = data[(data['type']=="ask")]
#sells["datestamp"] = np.array(sells["timestamp"]).astype("datetime64[s]")
sellDates = (sells["datestamp"]).tolist()

volume = data["amount"]

a.clear()

a.plot_date(buyDates, buys["price"], "#00A3E0", label="buys")
a.plot_date(sellDates, sells["price"], "#183A54", label="sells")

a2.fill_between(allDates, 0, volume, facecolor = "#183A54")

a.xaxis.set_major_locator(mticker.MaxNLocator(5))
a.xaxis.set_major_formatter(mdates.DateFormatter("%Y-%m-%d %H:M:S"))

a.legend(bbox_to_anchor=(0, 1.02, 1, .102), loc=3,
        ncol=2, borderaxespad=0)

title = "BTC-e BTCUSD Prices\nLast Price: "+str(data["price"][1999])
a.set_title(title)

print("here")

except Exception as e:
    print("Failed because of:",e)

```

```
class SeaofBTCapp(tk.Tk):
```

```

    def __init__(self, *args, **kwargs):

        tk.Tk.__init__(self, *args, **kwargs)

        tk.Tk.iconbitmap(self, default="clienticon.ico")
        tk.Tk.wm_title(self, "Sea of BTC client")

        container = tk.Frame(self)
        container.pack(side="top", fill="both", expand = True)

```




```

menubar = tk.Menu(container)
filemenu = tk.Menu(menubar, tearoff=0)
filemenu.add_command(label="Save settings", command = lambda: popupmsg("Not supported just yet!"))
filemenu.add_separator()
filemenu.add_command(label="Exit", command=quit)
menubar.add_cascade(label="File", menu=filemenu)

exchangeChoice = tk.Menu(menubar, tearoff=1)
exchangeChoice.add_command(label="BTC-e",
                           command=lambda: changeExchange("BTC-e", "btce"))
exchangeChoice.add_command(label="Bitfinex",
                           command=lambda: changeExchange("Bitfinex", "bitfinex"))
exchangeChoice.add_command(label="Bitstamp",
                           command=lambda: changeExchange("Bitstamp", "bitstamp"))
exchangeChoice.add_command(label="Huobi",
                           command=lambda: changeExchange("Huobi", "huobi"))

menubar.add_cascade(label="Exchange", menu=exchangeChoice)

dataTF = tk.Menu(menubar, tearoff=1)
dataTF.add_command(label = "Tick",
                   command=lambda: changeTimeFrame('tick'))
dataTF.add_command(label = "1 Day",
                   command=lambda: changeTimeFrame('1d'))
dataTF.add_command(label = "3 Day",
                   command=lambda: changeTimeFrame('3d'))
dataTF.add_command(label = "1 Week",
                   command=lambda: changeTimeFrame('7d'))
menubar.add_cascade(label = "Data Time Frame", menu = dataTF)

OHLCI = tk.Menu(menubar, tearoff=1)
OHLCI.add_command(label = "Tick",
                  command=lambda: changeTimeFrame('tick'))
OHLCI.add_command(label = "1 minute",
                  command=lambda: changeSampleSize('1Min', 0.0005))
OHLCI.add_command(label = "5 minute",
                  command=lambda: changeSampleSize('5Min', 0.003))
OHLCI.add_command(label = "15 minute",
                  command=lambda: changeSampleSize('15Min', 0.008))
OHLCI.add_command(label = "30 minute",
                  command=lambda: changeSampleSize('30Min', 0.016))
OHLCI.add_command(label = "1 Hour",
                  command=lambda: changeSampleSize('1H', 0.032))
OHLCI.add_command(label = "3 Hour",
                  command=lambda: changeSampleSize('3H', 0.096))

menubar.add_cascade(label="OHLC Interval", menu=OHLCI)

topIndi = tk.Menu(menubar, tearoff=1)
topIndi.add_command(label="None",
                    command = lambda: addTopIndicator('none'))
topIndi.add_command(label="RSI",
                    command = lambda: addTopIndicator('rsi'))
topIndi.add_command(label="MACD",
                    command = lambda: addTopIndicator('macd'))

menubar.add_cascade(label="Top Indicator", menu=topIndi)

```



```

        command = lambda: addMiddleIndicator('none'))
mainI.add_command(label="SMA",
                  command = lambda: addMiddleIndicator('sma'))
mainI.add_command(label="EMA",
                  command = lambda: addMiddleIndicator('ema'))

menubar.add_cascade(label="Main/middle Indicator", menu=mainI)


bottomI = tk.Menu(menubar, tearoff=1)
bottomI.add_command(label="None",
                    command = lambda: addBottomIndicator('none'))
bottomI.add_command(label="RSI",
                    command = lambda: addBottomIndicator('rsi'))
bottomI.add_command(label="MACD",
                    command = lambda: addBottomIndicator('macd'))

menubar.add_cascade(label="Bottom Indicator", menu=bottomI)


tradeButton = tk.Menu(menubar, tearoff=1)
tradeButton.add_command(label = "Manual Trading",
                        command=lambda: popupmsg("This is not live yet"))
tradeButton.add_command(label = "Automated Trading",
                        command=lambda: popupmsg("This is not live yet"))

tradeButton.add_separator()
tradeButton.add_command(label = "Quick Buy",
                        command=lambda: popupmsg("This is not live yet"))
tradeButton.add_command(label = "Quick Sell",
                        command=lambda: popupmsg("This is not live yet"))

tradeButton.add_separator()
tradeButton.add_command(label = "Set-up Quick Buy/Sell",
                        command=lambda: popupmsg("This is not live yet"))

menubar.add_cascade(label="Trading", menu=tradeButton)


startStop = tk.Menu(menubar, tearoff = 1)
startStop.add_command( label="Resume",
                       command = lambda: loadChart('start'))
startStop.add_command( label="Pause",
                       command = lambda: loadChart('stop'))
menubar.add_cascade(label = "Resume/Pause client", menu = startStop)


helpmenu = tk.Menu(menubar, tearoff=0)
helpmenu.add_command(label="Tutorial", command=tutorial)

menubar.add_cascade(label="Help", menu=helpmenu)


tk.Tk.config(self, menu=menubar)

```



```
for F in (StartPage, BTce_Page):

    frame = F(container, self)

    self.frames[F] = frame

    frame.grid(row=0, column=0, sticky="nsew")

self.show_frame(StartPage)

def show_frame(self, cont):

    frame = self.frames[cont]
    frame.tkraise()

class StartPage(tk.Frame):

    def __init__(self, parent, controller):
        tk.Frame.__init__(self, parent)
        label = tk.Label(self, text=("""ALPHA Bitcoin trading application
use at your own risk. There is no promise
of warranty."""), font=LARGE_FONT)
        label.pack(pady=10, padx=10)

        button1 = ttk.Button(self, text="Agree",
                              command=lambda: controller.show_frame(BTce_Page))
        button1.pack()

        button2 = ttk.Button(self, text="Disagree",
                              command=quit)
        button2.pack()

class PageOne(tk.Frame):

    def __init__(self, parent, controller):
        tk.Frame.__init__(self, parent)
        label = tk.Label(self, text="Page One!!!", font=LARGE_FONT)
        label.pack(pady=10, padx=10)

        button1 = ttk.Button(self, text="Back to Home",
                              command=lambda: controller.show_frame(StartPage))
        button1.pack()

class BTce_Page(tk.Frame):

    def __init__(self, parent, controller):
        tk.Frame.__init__(self, parent)
        label = tk.Label(self, text="Graph Page!", font=LARGE_FONT)
        label.pack(pady=10, padx=10)

        button1 = ttk.Button(self, text="Back to Home",
                              command=lambda: controller.show_frame(StartPage))
        button1.pack()
```



```

canvas.show()
canvas.get_tk_widget().pack(side=tk.BOTTOM, fill=tk.BOTH, expand=True)

toolbar = NavigationToolbar2TkAgg(canvas, self)
toolbar.update()
canvas._tkcanvas.pack(side=tk.TOP, fill=tk.BOTH, expand=True)


```

```

app = SeaofBTCapp()
app.geometry("1280x720")
ani = animation.FuncAnimation(f, animate, interval=5000)
app.mainloop()

```

The next tutorial: [Adding Exchange Choice Cont'd](#)



Programming GUIs and windows with Tkinter and Python Introduction

Object Oriented Programming Crash Course with Tkinter

Passing functions with Parameters in Tkinter using Lambda

How to change and show a new window in Tkinter

Styling your GUI a bit using TTK

How to embed a Matplotlib graph to your Tkinter GUI

How to make the Matplotlib graph live in your application

Organizing our GUI

Plotting Live Updating Data in Matplotlib and our Tkinter GUI

Customizing an embedded Matplotlib Graph in Tkinter

Creating our Main Menu in Tkinter


Building a pop-up message window



Time-frame and sample size option
Adding indicator Menus (3 videos)
Trading option, start/stop, and help menu options
Tutorial on adding a tutorial

Allowing the exchange choice option to affect actual shown exchange

Adding exchange choice cont'd
Adding exchange choices part 3
Indicator Support
Pulling data from the Sea of BTC API
Setting up sub plots within our Tkinter GUI
Graphing an OHLC candlestick graph embedded in our Tkinter GUI
Acquiring RSI data from Sea of BTC API
Acquiring MACD data from Sea of BTC API
Converting Tkinter application to .exe and installer with cx_Freeze



You've reached the end!

Contact: Harrison@pythonprogramming.net.

Support this Website!
Consulting and Contracting



Instagram

Legal stuff:

[Terms and Conditions](#)

[Privacy Policy](#)