INSTITUT TEKNOLOGI DEL

MATERI PRAKTIKUM

4233201 – Kecerdasan Buatan

Semester Ganjil Tahun Ajaran 2026/2027

Session Date	**:** 12 Oktober 2026
Week/Session	**:** 6/2
Topic	**:** Text Classification
Practicum Goals	**:** Mahasiswa mampu melakukan semua tahap dalam proses klasifikasi teks
Duration	**:** 2 x 50 minutes
Place of Submission	**:** ecourse
Submission Deadline	**:** Akhir Sesi

Klasifkasi teks digunakan untuk mengelompokkan teks ke dalam kategori tertentu. Dalam praktikum ini, akan dipelajari bagaimana melakukan klasifikasi teks mulai dari preprocessing teks, ekstraksi fitur, hingga pelatihan model Naïve Bayes untuk mendeteksi pesan spam/bukan spam.

In [1]:
```
import pandas as pd

df = pd.read_csv('/content/Text_classification.csv')
print(df.head())
```

```
  Category                                            Message
0      ham  Go until jurong point, crazy.. Available only ...
1      ham                      Ok lar... Joking wif u oni...
2     spam  Free entry in 2 a wkly comp to win FA Cup fina...
3      ham  U dun say so early hor... U c already then say...
4      ham  Nah I don't think he goes to usf, he lives aro...
```

NLTK (Natural Language Toolkit) adalah pustaka Python yang digunakan untuk membantu komputer dalam menganalisis, memproses, dan memahami teks tertulis. NLTK menyediakan alat untuk tokenisasi, stemming, lemmatization, stopword removal, dan analisis teks lainnya.

In [2]:
```
# Download resource NLTK yang diperlukan
import nltk
nltk.download('punkt_tab')
nltk.download('punkt')
nltk.download('stopwords')
nltk.download('wordnet')

# Import library untuk preprocessing
import re
import string
from nltk.corpus import stopwords
from nltk.tokenize import word_tokenize
from nltk.stem import WordNetLemmatizer

# Inisialisasi lemmatizer
lemmatizer = WordNetLemmatizer()

# Fungsi preprocessing teks
def clean_text(text):
    text = text.lower()  # Ubah menjadi lowercase
    text = re.sub(r'\d+', '', text)  # Hapus angka
    text = text.translate(str.maketrans('', '', string.punctuation))  # Hapus tanda baca
    words = word_tokenize(text)  # Tokenisasi
    words = [word for word in words if word not in stopwords.words('english')]  # Hapus stopwords
    words = [lemmatizer.lemmatize(word) for word in words]  # Lemmatization
    return ' '.join(words)

# Terapkan preprocessing ke teks
df['clean_text'] = df['Message'].apply(clean_text)

# Cek hasil preprocessing
print("\nHasil Preprocessing:\n", df[['Message', 'clean_text']].head())
```

```
[nltk_data] Downloading package punkt_tab to /root/nltk_data...
[nltk_data]   Package punkt_tab is already up-to-date!
[nltk_data] Downloading package punkt to /root/nltk_data...
[nltk_data]   Package punkt is already up-to-date!
[nltk_data] Downloading package stopwords to /root/nltk_data...
[nltk_data]   Package stopwords is already up-to-date!
[nltk_data] Downloading package wordnet to /root/nltk_data...
[nltk_data]   Package wordnet is already up-to-date!
Hasil Preprocessing:
                                              Message  \
0  Go until jurong point, crazy.. Available only ...
1                      Ok lar... Joking wif u oni...
2  Free entry in 2 a wkly comp to win FA Cup fina...
3  U dun say so early hor... U c already then say...
4  Nah I don't think he goes to usf, he lives aro...

                                          clean_text
0  go jurong point crazy available bugis n great ...
1                            ok lar joking wif u oni
2  free entry wkly comp win fa cup final tkts st ...
3                u dun say early hor u c already say
4           nah dont think go usf life around though
```

In [3]:
```
# Ubah Label dari 'ham'/'spam' menjadi 0/1
df['Category'] = df['Category'].map({'ham': 0, 'spam': 1})

# Cek jumlah masing-masing kelas
print(df['Category'].value_counts())
```

```
Category
0    4825
1     747
Name: count, dtype: int64
```

In [4]:
```python
from sklearn.model_selection import train_test_split

# Pisahkan fitur dan label
X = df['clean_text']
y = df['Category']

# Split data (80% training, 20% testing)
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42, stratify=y)
```

In [5]:
```python
from sklearn.feature_extraction.text import TfidfVectorizer

# Konversi teks menjadi fitur numerik menggunakan TF-IDF
vectorizer = TfidfVectorizer(ngram_range=(1,2), max_features=5000)  # Menggunakan bigram
X_train_tfidf = vectorizer.fit_transform(X_train)
X_test_tfidf = vectorizer.transform(X_test)

print("\nTF-IDF Shape (Train):", X_train_tfidf.shape)
```

```
TF-IDF Shape (Train): (4457, 5000)
```

In [6]:
```python
from sklearn.naive_bayes import MultinomialNB

# Inisialisasi model Naïve Bayes
model = MultinomialNB(alpha=0.1)


# Train model
model.fit(X_train_tfidf, y_train)

# Prediksi hasil
y_pred = model.predict(X_test_tfidf)
```

In [7]:
```python
from sklearn.metrics import accuracy_score, classification_report, confusion_matrix

# Akurasi
accuracy = accuracy_score(y_test, y_pred)
print("\nAccuracy:", accuracy)

# Classification Report
print("\nClassification Report:\n", classification_report(y_test, y_pred))
```

```
Accuracy: 0.979372197309417

Classification Report:
               precision    recall  f1-score   support

           0       0.98      1.00      0.99       966
           1       0.98      0.86      0.92       149

    accuracy                           0.98      1115
   macro avg       0.98      0.93      0.95      1115
weighted avg       0.98      0.98      0.98      1115
```

Confusion matrix adalah tabel evaluasi yang menunjukkan bagaimana model klasifikasi bekerja dalam memprediksi kelas data.

- True Positive (TP): Model benar memprediksi spam sebagai spam.
- True Negative (TN): Model benar memprediksi ham sebagai ham.
- False Positive (FP): Model salah memprediksi ham sebagai spam.
- False Negative (FN): Model salah memprediksi spam sebagai ham.

In [8]:
```python
# Confusion Matrix
import seaborn as sns
import matplotlib.pyplot as plt
import numpy as np
import pandas as pd
from sklearn.metrics import confusion_matrix

# Hitung confusion matrix
conf_matrix = confusion_matrix(y_test, y_pred)


# Definisi elemen dalam confusion matrix
TN, FP, FN, TP = conf_matrix.ravel()

# Buat dataframe confusion matrix
df_conf_matrix = pd.DataFrame(conf_matrix, index=['Actual Ham', 'Actual Spam'], columns=['Predicted Ham', 'Predicted Spa

# Label untuk TP, FP, FN, TN
labels = np.array([["TN = {}\n(True Negative)".format(TN), "FP = {}\n(False Positive)".format(FP)],
                   ["FN = {}\n(False Negative)".format(FN), "TP = {}\n(True Positive)".format(TP)]])
```

```
# Plot heatmap dengan keterangan
plt.figure(figsize=(6,5))
ax = sns.heatmap(df_conf_matrix, annot=labels, fmt='', cmap='Blues', linewidths=0.5, cbar=True)

# Tambahkan label
plt.xlabel('Predicted')
plt.ylabel('Actual')
plt.title('Confusion Matrix with TP, FP, FN, TN')
plt.show()
```



In [9]:
```
# Contoh teks baru
new_texts = ["Congratulations! You won a free trip to Bali.",
             "Hey, are you coming to the party tonight?"]

# Preprocess teks baru
new_texts_clean = [clean_text(text) for text in new_texts]

# Transformasi dengan TF-IDF
new_texts_tfidf = vectorizer.transform(new_texts_clean)

# Prediksi
predictions = model.predict(new_texts_tfidf)

# Output hasil prediksi
for text, label in zip(new_texts, predictions):
    print(f"\nMessage: {text} \nPredicted: {'Spam' if label == 1 else 'Ham'}")
```

```
Message: Congratulations! You won a free trip to Bali.
Predicted: Spam

Message: Hey, are you coming to the party tonight?
Predicted: Ham
```