

#01

MariaDB [(none)]> show databases;

Database
dbspr
information_schema
mysql
performance_schema
phpmyadmin
sports_event
test

7 rows in set (0.064 sec)

#02

MariaDB [(none)]> select database();

database()
NULL

1 row in set (0.001 sec)

#03

MariaDB [(none)]> create database if not exists tbspr;

Query OK, 1 row affected (0.005 sec)

#04

MariaDB [dbspr]> show warnings;

Empty set (0.004 sec)

#05

MariaDB [dbspr]> use dbspr;

Database changed

#06

MariaDB [dbspr]> select database();

database()
dbspr

1 row in set (0.001 sec)

#07

MariaDB [dbspr]> show tables;

Tables_in_dbspr
tbltest

1 row in set (0.004 sec)

#08

MariaDB [dbspr]> drop table if exists tbl1er;

Query OK, 0 rows affected, 1 warning (0.159 sec)

#09

MariaDB [dbspr]> show warnings;

Level	Code	Message
Note	1051	Unknown table 'dbspr.tbl1er'

1 row in set (0.001 sec)

#10

```

MariaDB [dbspr]> create table if not exists tbl1er
-> (
-> rno int primary key auto_increment,
-> sname text not null,
-> m1 decimal (5,2) unsigned not null,
-> m2 decimal (5,2) unsigned not null,
-> total decimal (6,2) unsigned not null default 0,
-> average decimal (5,2) unsigned not null default 0,
-> result enum('Fail', 'Pass') not null default 'Fail' check(result = 'Fail' or result =
'pass')
-> ) auto_increment = 1001;
Query OK, 0 rows affected (0.116 sec)

```

```

#11
MariaDB [dbspr]> show tables;
+-----+
| Tables_in_dbspr |
+-----+
| tbl1er           |
| tblest           |
+-----+
2 rows in set (0.002 sec)

```

```

#12
MariaDB [dbspr]> select * from tbl1er;
Empty set (0.007 sec)

```

```

#13
MariaDB [dbspr]> select count(*) from tbl1er;
+-----+
| count(*) |
+-----+
|         0 |
+-----+
1 row in set (0.005 sec)

```

```

#14
MariaDB [dbspr]> drop trigger if exists trginster;
Query OK, 0 rows affected, 1 warning (0.003 sec)

```

```

#15
MariaDB [dbspr]> show warnings;
+-----+-----+-----+
| Level | Code | Message                                |
+-----+-----+-----+
| Note  | 1360 | Trigger does not exist                |
+-----+-----+-----+
1 row in set (0.000 sec)

```

```

#16
MariaDB [dbspr]> drop trigger if exists trgupd1er;
Query OK, 0 rows affected, 1 warning (0.001 sec)

```

```

#17
MariaDB [dbspr]> show warnings;
+-----+-----+-----+
| Level | Code | Message                                |
+-----+-----+-----+
| Note  | 1360 | Trigger does not exist                |
+-----+-----+-----+
1 row in set (0.001 sec)

```

```

#18
MariaDB [dbspr]> drop trigger if exists trgdell1er;
Query OK, 0 rows affected, 1 warning (0.001 sec)

```

```

#19
MariaDB [dbspr]> show warnings;
+-----+-----+-----+

```

```
| Level | Code | Message |
+-----+-----+-----+
| Note | 1360 | Trigger does not exist |
+-----+-----+-----+
1 row in set (0.000 sec)
```

```
#20
MariaDB [dbspr]> delimiter //
```

```
#21
MariaDB [dbspr]> create or replace trigger trgins1er
-> before insert on tbl1er
-> for each row
-> begin
->
-> set new.total = new.m1 + new.m2;
-> set new.average = new.total/2;
-> set new.result = if (new.m1 > 34.4 and new.m2 > 34.4, 'Pass', 'Fail');
->
-> end
-> //
```

Query OK, 0 rows affected (0.011 sec)

```
#22
MariaDB [dbspr]> delimiter ;
```

```
#23
MariaDB [dbspr]> delimiter //
```

```
#24
MariaDB [dbspr]> create or replace trigger trgupd1er
-> before update on tbl1er
-> for each row
-> begin
->
-> set new.total = new.m1 + new.m2;
-> set new.average = new.total/2;
-> set new.result = if(new.m1 > 34.4 and new.m2 > 34.4, 'Pass' , 'Fail');
->
-> end
-> //
```

Query OK, 0 rows affected (0.019 sec)

```
#25
MariaDB [dbspr]> delimiter ;
```

```
#26
MariaDB [dbspr]> delimiter //
```

```
#27
MariaDB [dbspr]> create or replace trigger trgdell1er
-> before update on tbl1er
-> for each row
-> begin
->
-> signal sqlstate '12345'
-> set message_text = 'Denied delete a row permission';
->
-> end
-> //
```

Query OK, 0 rows affected (0.013 sec)

```
#28
MariaDB [dbspr]> delimiter ;
MariaDB [dbspr]>
```

```
#29
MariaDB [dbspr]> select trigger_name, event_manipulation from information_schema.triggers where
trigger_schema=database();
```

trigger_name	event_manipulation
trgins1er	INSERT
trgupd1er	UPDATE
trgdell1er	UPDATE
trginsest	INSERT
trgupdest	UPDATE

5 rows in set (0.123 sec)

#30

MariaDB [dbspr]> insert into tbl1er

-> (sname,m1,m2)

-> value

-> ('x5',56.5,63),

-> ('x3' , 45.5, 52),

-> ('x1' , 47.5 ,54),

-> ('x2' ,98 ,20),

-> ('x4', 61 , 63.5);

Query OK, 5 rows affected (0.011 sec)

Records: 5 Duplicates: 0 Warnings: 0

#31

MariaDB [dbspr]> select \* from tbl1er;

rno	sname	m1	m2	total	average	result
1001	x5	56.50	63.00	119.50	59.75	Pass
1002	x3	45.50	52.00	97.50	48.75	Pass
1003	x1	47.50	54.00	101.50	50.75	Pass
1004	x2	98.00	20.00	118.00	59.00	Fail
1005	x4	61.00	63.50	124.50	62.25	Pass

5 rows in set (0.001 sec)