

#01

MariaDB [(none)]> select user, host, password from mysql.user;

User	Host	Password
root	localhost	
usrspr	localhost	
root	127.0.0.1	
root	::1	
pma	localhost	

5 rows in set (0.003 sec)

#02

MariaDB [(none)]> drop user if exists usrcmr;

Query OK, 0 rows affected, 1 warning (0.001 sec)

#03

MariaDB [(none)]> drop user if exists `usrcmr`@`%`;

Query OK, 0 rows affected, 1 warning (0.001 sec)

#04

MariaDB [(none)]> show warnings;

Level	Code	Message
Note	1974	Can't drop user 'usrcmr'@'%'; it doesn't exist

1 row in set (0.000 sec)

#05

MariaDB [(none)]> drop user if exists `usrcmr`@`127.0.0.1`;

Query OK, 0 rows affected, 1 warning (0.001 sec)

#06

MariaDB [(none)]> show warnings;

Level	Code	Message
Note	1974	Can't drop user 'usrcmr'@'127.0.0.1'; it doesn't exist

1 row in set (0.000 sec)

#07

MariaDB [(none)]> drop user if exists `usrcmr`@`127.0.0.1`;

Query OK, 0 rows affected, 1 warning (0.001 sec)

#08

MariaDB [(none)]> show warnings;

Level	Code	Message
Note	1974	Can't drop user 'usrcmr'@'127.0.0.1'; it doesn't exist

1 row in set (0.000 sec)

#09

MariaDB [(none)]> delete from mysql.user where user='usrcmr';

Query OK, 0 rows affected (0.002 sec)

#10

MariaDB [(none)]> select user, host, password from mysql.user;

User	Host	Password
root	localhost	
usrspr	localhost	
root	127.0.0.1	
root	::1	

```
| pma      | localhost |      |
+-----+-----+-----+
5 rows in set (0.002 sec)
```

```
#11
MariaDB [(none)]> create user if not exists `usrcmr`@`localhost` identified by 'pwdcmr';
Query OK, 0 rows affected (0.004 sec)
```

```
#12
MariaDB [(none)]> select password('pwdcmr');
+-----+
| password('pwdcmr') |
+-----+
| *E0C41F296C4E41BC7F426763F56FE60A3E0E1CBE |
+-----+
1 row in set (0.005 sec)
```