

Title: How to develop Inner Join feature(way: 02)?

#01

```
MariaDB [dbspr]> select * from stdtbl s1
-> inner join usttbl u1
-> on s1.pid=u1.pid;
```

```
+-----+-----+-----+-----+-----+
| pid  | pname | edu  | pid  | prole |
+-----+-----+-----+-----+-----+
| 1001 | x1    | UG   | 1001 | Tutor |
| 1004 | x4    | UG   | 1004 | HM     |
| 1007 | x7    | UG   | 1007 | Tutor |
+-----+-----+-----+-----+-----+
3 rows in set (0.001 sec)
```

#02

```
MariaDB [dbspr]> select * from stdtbl s1
-> inner join psttbl p1
-> on s1.pid=p1.pid;
```

```
+-----+-----+-----+-----+-----+
| pid  | pname | edu  | pid  | prole |
+-----+-----+-----+-----+-----+
| 1001 | x1    | UG   | 1001 | Coach |
| 1002 | x2    | PG   | 1002 | HOD    |
| 1005 | x5    | PG   | 1005 | Coach |
| 1008 | x8    | PG   | 1008 | HOD    |
+-----+-----+-----+-----+-----+
4 rows in set (0.001 sec)
```

#03

```
MariaDB [dbspr]> select * from stdtbl s1
-> inner join usttbl u1
-> on s1.pid=u1.pid
-> inner join psttbl p1
-> on s1.pid=p1.pid;
```

```
+-----+-----+-----+-----+-----+-----+
| pid  | pname | edu  | pid  | prole | pid  | prole |
+-----+-----+-----+-----+-----+-----+
| 1001 | x1    | UG   | 1001 | Tutor | 1001 | Coach |
+-----+-----+-----+-----+-----+-----+
1 row in set (0.001 sec)
```