الجهاز الوطني للإيرادات
National Bureau for Revenue

E-INVOICING API SPECIFICATIONS AND SWAGGER GUIDE

Version 1.0

May 2026

© Kingdom of Bahrain | National Bureau for Revenue

Table of Contents

1. E-Invoicing APIs Specifications 3
1.1. Compliance CSID API 3
1.2. Compliance Check API 4
1.3. Production CSID API 5
1.4. CSID Renewal API 5
1.5. Clearance API 6
1.6. Reporting API 7
2. E-Invoicing Swagger File Overview 8

CONFIDENTIAL

1. E-Invoicing APIs Specifications

The e-invoicing platform provides a comprehensive set of REST APIs designed to enable the technical user to integrate their EGS devices with the NBR's system. The APIs follow modern REST principles, use JSON as the primary data format, and are served over HTTPS.

They allow to programmatically perform all operations required by NBR to be compliant, covering all processes (Compliance CSID, Compliance Check, Production CSID, CSID Renewal, Clearance, Reporting).

In order to be able to successfully consume the e-invoicing APIs, request authentication headers and request body shall be provided in the expected format and structure as demonstrated on the swagger and highlighted below.

For each API, there are two endpoints, one for sandbox and another for production. The APIs are listed and explained below.

1.1. Compliance CSID API

- Description:
  An initial device onboarding request for an e-invoicing solution by providing an OTP code and CSR information for each device onboarding or renewal request.
- Request Type:
  POST
- Endpoints:
  - /v1/sandbox/devices/compliance
  - /v1/core/devices/compliance
- Request Headers:
  - Header Name: otp
    Header Value: otp number can be obtained from e-invoice portal as illustrated in the user manual. For Sandbox, use the OTP mentioned in the swagger.
- Request Body:
  - Parameter Name: csr
    Parameter Value: CSR (PKCS#10) encoded in base64 which can be obtained using the SDK.
- Response:
  - Parameter Name: requestID
    Parameter Value: ID that will be used in making requests to compliance check API and production CSID API
  - Parameter Name: dispositionMessage
    Parameter Value: indicates whether CSID generation is successful or unsuccessful

CONFIDENTIAL

- Parameter Name: binarySecurityToken
  Parameter Value: generated CSID (X.509 certificate) encoded in base64 that will used as username in making requests to compliance check API
- Parameter Name: secret
  Parameter Value: generated secret encoded in base64 that will be used as password in making requests to compliance check API
- Parameter Name: errors
  Parameter Value: indicates errors in the submitted request

1.2. Compliance Check API

- **Description:**
  A request to complete the compliance checks for different type of e-invoices enabling the e-invoicing Solution Developers to be able to test compliance of their e-invoicing solutions.
  - Note: This API can be called multiple times to submit all the required types of invoices based on what is indicated in the CSR.
- **Request Type:**
  POST
- **Endpoints:**
  - /v1/sandbox/invoices/compliance
  - /v1/core/invoices/compliance
- **Request Headers:**
  - Header Name: Authorization
    Header Value: basic auth base64 username and password received upon successful call to the Compliance CSID API.
- **Request Body:**
  - Parameter Name: invoiceHash
    Parameter Value: invoice hash (sha-256) in base64 for the included invoice in the request
  - Parameter Name: uuid
    Parameter Value: uuid for the included invoice in the request
  - Parameter Name: invoice
    Parameter Value: xml invoice in base64 included invoice in the request
- **Response:**
  - Parameter Name: validationResults
    Parameter Value: an object that includes the status of the submission along with arrays for infoMessages, errorMessages, warningMessages.
  - Parameter Name: reportingStatus
    Parameter Value: indicates whether reporting invoice validation is successful or unsuccessful

CONFIDENTIAL

- Parameter Name: clearanceStatus
  Parameter Value: indicates whether clearance invoice validation is successful or unsuccessful

1.3. Production CSID API

- Description:
  A final request to obtain the Production CSID for the e-invoicing solution linked to the authorized VAT payer to commence submitting e-invoices for Clearance and Reporting.
- Request Type:
  POST
- Endpoints:
  - /v1/sandbox/devices/production
  - /v1/core/devices/production
- Request Headers:
  - Header Name: Authorization
    Header Value: basic auth base64 username and password received upon successful call to the Compliance CSID API.
- Request Body:
  - Parameter Name: compliance_request_id
    Parameter Value: ID received upon successful call to the Compliance CSID API.
- Response:
  - Parameter Name: requestID
    Parameter Value: ID that will be used in making requests to CSID renewal API.
  - Parameter Name: dispositionMessage
    Parameter Value: indicates whether CSID generation is successful or unsuccessful
  - Parameter Name: binarySecurityToken
    Parameter Value: generated CSID (X.509 certificate) encoded in base64 that will used as username in making requests clearance and reporting APIs
  - Parameter Name: secret
    Parameter Value: generated secret encoded in base64 that will be used as password in making requests clearance and reporting APIs
  - Parameter Name: errors
    Parameter Value: indicates errors in the submitted request

1.4. CSID Renewal API

- Description:
  A request for device CSID renewal for an e-invoicing solution by submitting an existing production CSID and CSR. The request is accompanied with the OTP generated by the VAT Payer linked to the device.

CONFIDENTIAL

- Note: This API generates a compliance CSID and revokes the current production CSID. The user is required to undergo the compliance check API.

- **Request Type:**
  PATCH
- **Endpoints:**
  - /v1/sandbox/devices/renew
    /v1/core/devices/renew
- **Request Headers:**
  - Header Name: otp
    Header Value: otp number can be obtained from e-invoice portal as illustrated in the user manual.
  - Header Name: Authorization
    Header Value: basic auth base64 username and password received upon successful call to the Production CSID API.
- **Request Body:**
  - Parameter Name: csr
    Parameter Value: CSR (PKCS#10) encoded in base64 which can be obtained using the SDK.
- **Response:**
  - Parameter Name: requestID
    Parameter Value: ID that will be used in making requests to compliance check API, renewal CSID and Production CSID API
  - Parameter Name: dispositionMessage
    Parameter Value: indicates whether CSID generation is successful or unsuccessful
  - Parameter Name: binarySecurityToken
    Parameter Value: generated CSID (X.509 certificate) encoded in base64 that will used as username in making requests to compliance check API
  - Parameter Name: secret
    Parameter Value: generated secret encoded in base64 that will be used as password in making requests to compliance check API
  - Parameter Name: errors
    Parameter Value: indicates errors in the submitted request

1.5. Clearance API

- **Description:**
  The process of validating and signing the standard e-invoice document and associated credit and debit notes and simulates the validation checks applied to the Clearance process.

CONFIDENTIAL

- **Request Type:**
  POST
- **Endpoints:**
  - /v1/sandbox/invoices/clearance
    /v1/core/invoices/clearance
- **Request Headers:**
  - Header Name: Authorization
    Header Value: basic auth base64 username and password received upon successful call to the Production CSID API.
- **Request Body:**
  - Parameter Name: invoiceHash
    Parameter Value: invoice hash (sha-256) in base64 for the included invoice in the request
  - Parameter Name: uuid
    Parameter Value: uuid for the included invoice in the request
  - Parameter Name: invoice
    Parameter Value: xml invoice in base64 included invoice in the request
- **Response:**
  - Parameter Name: validationResults
    Parameter Value: an object that includes the status of the submission along with arrays for infoMessages, errorMessages, warningMessages.
  - Parameter Name: clearanceStatus
    Parameter Value: indicates whether reporting invoice validation is successful or unsuccessful
  - Parameter Name: clearedInvoice
    Parameter Value: cleared xml invoice in base64 signed by NBR
  - Parameter Name: qrCode
    Parameter Value: invoice QR code (TLV) in base64
  - Parameter Name: timestamp
    Parameter Value: clearing invoice timestamp in UTC (Zulu) format

1.6. Reporting API

- **Description:**
  The process of validating the simplified e-invoices and associated credit notes and debit notes and simulates the validation checks applies to the Reporting process.
- **Request Type:**
  POST
- **Endpoints:**
  - /v1/sandbox/invoices/reporting
  - /v1/core/invoices/reporting

CONFIDENTIAL

- Request Headers:
  - Header Name: Authorization
    Header Value: basic auth base64 username and password received upon successful call to the Production CSID API.
- Request Body:
  - Parameter Name: invoiceHash
    Parameter Value: invoice hash (sha-256) in base64 for the included invoice in the request
  - Parameter Name: uuid
    Parameter Value: uuid for the included invoice in the request
  - Parameter Name: invoice
    Parameter Value: xml invoice in base64 included invoice in the request
- Response:
  - Parameter Name: validationResults
    Parameter Value: an object that includes the status of the submission along with arrays for infoMessages, errorMessages, warningMessages.
  - Parameter Name: reportingStatus
    Parameter Value: indicates whether reporting invoice validation is successful or unsuccessful
  - Parameter Name: timestamp
    Parameter Value: clearing invoice timestamp in UTC (Zulu) format

2. E-Invoicing Swagger File Overview

The swagger file is a tool that is commonly used to help technical users to develop their integration with other systems. It provides an interactive interface where they can explore the available API endpoints, understand request and response structure.

Note that currently the swagger file doesn't have the e-invoice URLs defined which will be shared at a later stage to enable users from trying out API calls and further explore the API behavior.

The swagger file can be viewed using any swagger viewer compatible tool such as online Swagger UI and Swagger Editor that are available publicly or other offline IDE plugins.

CONFIDENTIAL