

Annual Service Review

Network Planning Directorate

Published under the transparency requirement

Contents

1. Introduction.....	1
2. Method.....	2
2.1 Data sources.....	2
2.2 Adjustments.....	2
3. Results.....	3
3.1 Ridership.....	3
3.2 Punctuality.....	3
4. Conclusions.....	4
Appendix A. Counter calibration.....	4

1. Introduction

The depot replacement programme was approved on the understanding that service levels would be maintained throughout construction. That assumption has not survived contact with the schedule: the temporary layover facility is smaller than the site it replaces, and peak-hour vehicle circulation is now the binding constraint. Mitigation is available but unglamorous. Two additional relief runs, shifted twelve minutes earlier, absorb most of the shortfall at a cost well inside the contingency already held for this phase. The remainder is best handled by publishing the revised layover times rather than by adding vehicles.

2. Method

Members should note that the figures below are drawn from the automatic passenger counters, which under-report boardings at the two rear doors by a margin the vendor states as three per cent. No adjustment has been applied; the raw counts are reported so that later revisions remain traceable to their source.

2.1 Data sources

Members should note that the figures below are drawn from the automatic passenger counters, which under-report boardings at the two rear doors by a margin the vendor states as three per cent. No adjustment has been applied; the raw counts are reported so that later revisions remain traceable to their source. The depot replacement programme was approved on the understanding that service levels would be maintained throughout construction. That assumption has not survived contact with the schedule: the temporary layover facility is smaller than the site it replaces, and peak-hour vehicle circulation is now the binding constraint.

2.2 Adjustments

Mitigation is available but unglamorous. Two additional relief runs, shifted twelve minutes earlier, absorb most of the shortfall at a cost well inside the contingency already held for this phase. The remainder is best handled by publishing the revised layover times rather than by adding vehicles.

3. Results

The depot replacement programme was approved on the understanding that service levels would be maintained throughout construction. That assumption has not survived contact with the schedule: the temporary layover facility is smaller than the site it replaces, and peak-hour vehicle circulation is now the binding constraint. Members should note that the figures below are drawn from the automatic passenger counters, which under-report boardings at the two rear doors by a margin the vendor states as three per cent. No adjustment has been applied; the raw counts are reported so that later revisions remain traceable to their source.

3.1 Ridership

Mitigation is available but unglamorous. Two additional relief runs, shifted twelve minutes earlier, absorb most of the shortfall at a cost well inside the contingency already held for this phase. The remainder is best handled by publishing the revised layover times rather than by adding vehicles. The recommendation is therefore to proceed, with the reporting requirement attached, and to bring a further report in the autumn once a full quarter of post-occupancy data is available for comparison.

3.2 Punctuality

Members should note that the figures below are drawn from the automatic passenger counters, which under-report boardings at the two rear doors by a margin the vendor states as three per cent. No adjustment has been applied; the raw counts are reported so that later revisions remain traceable to their source.

4. Conclusions

The recommendation is therefore to proceed, with the reporting requirement attached, and to bring a further report in the autumn once a full quarter of post-occupancy data is available for comparison. The depot replacement programme was approved on the understanding that service levels would be maintained throughout construction. That assumption has not survived contact with the schedule: the temporary layover facility is smaller than the site it replaces, and peak-hour vehicle circulation is now the binding constraint.

Appendix A. Counter calibration

Members should note that the figures below are drawn from the automatic passenger counters, which under-report boardings at the two rear doors by a margin the vendor states as three per cent. No adjustment has been applied; the raw counts are reported so that later revisions remain traceable to their source. The recommendation is therefore to proceed, with the reporting requirement attached, and to bring a further report in the autumn once a full quarter of post-occupancy data is available for comparison.