

Annual Service Review

The depot replacement programme was approved on the understanding that service levels would be maintained throughout construction. That assumption has not survived contact with the schedule: the temporary layover facility is smaller than the site it replaces, and peak-hour vehicle circulation is now the binding constraint.

Contents

1. Introduction	1
2. Method	1
2.1 Data sources	2
2.2 Adjustments	2
3. Results	2
3.1 Ridership	3
4. Conclusions	3

1. Introduction

Mitigation is available but unglamorous. Two additional relief runs, shifted twelve minutes earlier, absorb most of the shortfall at a cost well inside the contingency already held for this phase. The remainder is best handled by publishing the revised layover times rather than by adding vehicles.

The statutory basis is set out in [the passenger transport regulations](#); the counter specification is published [separately](#).

2. Method

Members should note that the figures below are drawn from the automatic passenger counters, which under-report boardings at the two rear doors by a margin the vendor states as three per cent. No adjustment has been applied; the raw counts are reported so that later revisions remain traceable to their source.

2.1 Data sources

The depot replacement programme was approved on the understanding that service levels would be maintained throughout construction. That assumption has not survived contact with the schedule: the temporary layover facility is smaller than the site it replaces, and peak-hour vehicle circulation is now the binding constraint.

2.1.1 Automatic passenger counters

Mitigation is available but unglamorous. Two additional relief runs, shifted twelve minutes earlier, absorb most of the shortfall at a cost well inside the contingency already held for this phase. The remainder is

best handled by publishing the revised layover times rather than by adding vehicles.

2.1.2 Manual verification

Members should note that the figures below are drawn from the automatic passenger counters, which under-report boardings at the two rear doors by a margin the vendor states as three per cent. No adjustment has been applied; the raw counts are reported so that later revisions remain traceable to their source.

2.2 Adjustments

The recommendation is therefore to proceed, with the reporting requirement attached, and to bring a further report in the autumn once a full quarter of post-occupancy data is available for comparison.

No adjustment has been applied; the raw counts are reported so that later revisions remain traceable to their source.

3. Results

The depot replacement programme was approved on the understanding that service levels would be maintained throughout construction. That assumption has not survived contact with the schedule: the temporary layover facility is smaller than the site it replaces, and peak-hour vehicle circulation is now the binding constraint.

3.1 Ridership

Mitigation is available but unglamorous. Two additional relief runs, shifted twelve minutes earlier, absorb most of the shortfall at a cost well inside the contingency already held for this phase. The remainder is best handled by publishing the revised layover times rather than by adding vehicles.

4. Conclusions

The recommendation is therefore to proceed, with the reporting requirement attached, and to bring a further report in the autumn once a full quarter of post-occupancy data is available for comparison.

Return to [the introduction](#), or write to planning@example.org.

¹ Counter under-reporting is stated by the vendor as three per cent at the rear doors.

² Punctuality is measured at the timing points only.