

Depot Replacement: Interim Service Report

The depot replacement programme was approved on the understanding that service levels would be maintained throughout construction. That assumption has not survived contact with the schedule: the temporary layover facility is smaller than the site it replaces, and peak-hour vehicle circulation is now the binding constraint. Mitigation is available but unglamorous. Two additional relief runs, shifted twelve minutes earlier, absorb most of the shortfall at a cost well inside the contingency already held for this phase. The remainder is best handled by publishing the revised layover times rather than by adding vehicles.

1. Purpose

The depot replacement programme was approved on the understanding that service levels would be maintained throughout construction. That assumption has not survived contact with the schedule: the temporary layover facility is smaller than the site it replaces, and peak-hour vehicle circulation is now the binding constraint.

Mitigation is available but unglamorous. Two additional relief runs, shifted twelve minutes earlier, absorb most of the shortfall at a cost well inside the contingency already held for this phase. The remainder is best handled by publishing the revised layover times rather than by adding vehicles.

2. Background

Members should note that the figures below are drawn from the automatic passenger counters, which under-report boardings at the two rear doors by a margin the vendor states as three per cent. No adjustment has been applied; the raw counts are reported so that later revisions remain traceable to their source.

The recommendation is therefore to proceed, with the reporting requirement attached, and to bring a further report in the autumn once a full quarter of post-occupancy data is available for comparison.

3. Site constraints

The depot replacement programme was approved on the understanding that service levels would be maintained throughout construction. That assumption has not survived contact with the schedule: the temporary layover facility is smaller than the site it replaces, and peak-hour vehicle circulation is now the binding constraint.

Mitigation is available but unglamorous. Two additional relief runs, shifted twelve minutes earlier, absorb most of the shortfall at a cost well inside the contingency already held for this phase. The remainder is best handled by publishing the revised layover times rather than by adding vehicles.

4. Circulation

Members should note that the figures below are drawn from the automatic passenger counters, which under-report boardings at the two rear doors by a margin the vendor states as three per cent. No adjustment has been applied; the raw counts are reported so that later revisions remain traceable to their source.

The recommendation is therefore to proceed, with the reporting requirement attached, and to bring a further report in the autumn once a full quarter of post-occupancy data is available for comparison.

5. Layover capacity

The depot replacement programme was approved on the understanding that service levels would be maintained throughout construction. That assumption has not survived contact with the schedule: the temporary layover facility is smaller than the site it replaces, and peak-hour vehicle circulation is now the binding constraint.

Mitigation is available but unglamorous. Two additional relief runs, shifted twelve minutes earlier, absorb most of the shortfall at a cost well inside the contingency already held for this phase. The remainder is best handled by publishing the revised layover times rather than by adding vehicles.

6. Cost

Members should note that the figures below are drawn from the automatic passenger counters, which under-report boardings at the two rear doors by a margin the vendor states as three per cent. No adjustment has been applied; the raw counts are reported so that later revisions remain traceable to their source.

The recommendation is therefore to proceed, with the reporting requirement attached, and to bring a further report in the autumn once a full quarter of post-occupancy data is available for comparison.

7. Consultation

The depot replacement programme was approved on the understanding that service levels would be maintained throughout construction. That assumption has not survived contact with the schedule: the temporary layover facility is smaller than the site it replaces, and peak-hour vehicle circulation is now the binding constraint.

Mitigation is available but unglamorous. Two additional relief runs, shifted twelve minutes earlier, absorb most of the shortfall at a cost well inside the contingency already held for this phase. The remainder is best handled by publishing the revised layover times rather than by adding vehicles.

8. Recommendation

Members should note that the figures below are drawn from the automatic passenger counters, which under-report boardings at the two rear doors by a margin the vendor states as three per cent. No adjustment has been applied; the raw counts are reported so that later revisions remain traceable to their source.

The recommendation is therefore to proceed, with the reporting requirement attached, and to bring a further report in the autumn once a full quarter of post-occupancy data is available for comparison.

Network Planning

Not for onward circulation