

Layover Handbook

Network Planning Directorate

Contents

- 1. Scope 1
- 2. Definitions 1
 - 2.1 Layover 2
 - 2.2 Relief run 2
- 3. Standards 2
 - 3.1 Swept path 3
 - 3.2 Reversing 3
- 4. Records 3

1. Scope

The depot replacement programme was approved on the understanding that service levels would be maintained throughout construction. That assumption has not survived contact with the schedule: the temporary layover facility is smaller than the site it replaces, and peak-hour vehicle circulation is now the binding constraint.

2. Definitions

Mitigation is available but unglamorous. Two additional relief runs, shifted twelve minutes earlier, absorb most of the shortfall at a cost well inside the contingency already held for this phase. The remainder is best handled by publishing the revised layover times rather than by adding vehicles.

2.1 Layover

Members should note that the figures below are drawn from the automatic passenger counters, which under-report boardings at the two rear doors by a margin the vendor states as three per cent. No adjustment has been applied; the raw counts are reported so that later revisions remain traceable to their source.

2.2 Relief run

The depot replacement programme was approved on the understanding that service levels would be maintained throughout construction. That assumption has not survived contact with the schedule: the temporary layover facility is smaller than the site it replaces, and peak-hour vehicle circulation is now the binding constraint.

3. Standards

Mitigation is available but unglamorous. Two additional relief runs, shifted twelve minutes earlier, absorb most of the shortfall at a cost well inside the contingency already held for this phase. The remainder is best handled by publishing the revised layover times rather than by adding vehicles. Members should note that the figures below are drawn from the automatic passenger counters, which under-report boardings at the two rear doors by a margin the vendor states as three per cent. No adjustment has been applied; the raw counts are reported so that later revisions remain traceable to their source.

3.1 Swept path

The depot replacement programme was approved on the understanding that service levels would be maintained throughout construction. That assumption has not survived contact with the schedule: the temporary layover facility is smaller than the site it replaces, and peak-hour vehicle circulation is now the binding constraint.

3.2 Reversing

The recommendation is therefore to proceed, with the reporting requirement attached, and to bring a further report in the autumn once a full quarter of post-occupancy data is available for comparison.

Where a reversing manoeuvre is unavoidable, a banksman shall be provided for every movement, without exception.¹

4. Records

The recommendation is therefore to proceed, with the reporting requirement attached, and to bring a further report in the autumn once a full quarter of post-occupancy data is available for comparison. Mitigation is available but unglamorous. Two additional relief runs, shifted twelve minutes earlier, absorb most of the shortfall at a cost well inside the contingency already held for this phase. The remainder is best handled by publishing the revised layover times rather than by adding vehicles.

¹ The operator's own standard already requires this on all sites, so no additional cost is anticipated.

² Counter under-reporting is stated by the vendor as three per cent at the rear doors.