

Built-in Scan

1 Overview

1.1 Location \$<AMDAPPSDKSamplesInstallPath>\samples\opencl\c1\2.0

1.2 How to Run

See the *Getting Started* guide for how to build samples. You first must compile the sample.

Use the command line to change to the directory where the executable is located. The precompiled sample executable is at

\$<AMDAPPSDKSamplesInstallPath>\samples\opencl\bin\x86 64\ for 64-bit builds.

Ensure that the OpenCL 2.0 environment is installed.

Type the following command(s).

- BuiltInScan
 This runs the program with the default options.
- BuiltInScan -hThis prints the help file.

1.3 Command Line Options

Table 1 lists, and briefly describes, the command line options.

Table 1 Command Line Options

Short Form	Long Form	Description
-h	help	Shows all command options and their respective meanings.
	device	Devices on which the program is to be run. Acceptable values are cpu or gpu.
-q	quiet	Quiet mode. Suppresses most text output.
-e	verify	Verify results against reference implementation.
-t	timing	Print timing related statistics.
	dump	Dump binary image for all devices.
	load	Load binary image and execute on device.
	flags	Specify compiler flags to build the kernel.
- p	platformId	Select platformId to be used (0 to N-1, where N is the number of available platforms).
-d	deviceId	Select deviceld to be used (0 to N-1, where N is the number of available devices).
- ∇	version	AMD APP SDK version string.
-i	iterations	Number of iterations for kernel execution.

Built-in Scan 1 of 2

2 Introduction

This sample demonstrates the work group level scan and work group level broadcast features introduced in OpenCL 2.0. Work-group level scan lets the programmer perform a prefix scan on an array at the work-group level. The scan could be done using three types of operations: add, min, and max. A work-group level broadcast lets one work-item broadcast a variable value to all the other work-items in the work-group.

This sample must be run in the OpenCL 2.0 environment.

3 Implementation Details

This sample implements a parallel prefix sum using work-group level scan and broadcast. Global prefix sum is performed by first using work-group level prefix sum. Each work-group then acquires result of previous scan to perform global prefix sum.

4 References

- 1. The OpenCL Specification, version 2.0, rev 22 document (page 34).
- 2. The OpenCL C Programming Language (ver 2.0, rev 22) document (page 38).

Contact

Advanced Micro Devices, Inc. One AMD Place P.O. Box 3453 Sunnyvale, CA, 94088-3453 Phone: +1.408.749.4000 For AMD Accelerated Parallel Processing:

URL: developer.amd.com/appsdk Developing: developer.amd.com/



The contents of this document are provided in connection with Advanced Micro Devices, Inc. ("AMD") products. AMD makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. The information contained herein may be of a preliminary or advance nature and is subject to change without notice. No license, whether express, implied, arising by estoppel or otherwise, to any intellectual property rights is granted by this publication. Except as set forth in AMD's Standard Terms and Conditions of Sale, AMD assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including, but not limited to, the implied warranty of merchantability, fitness for a particular purpose, or infringement of any intellectual property right.

AMD's products are not designed, intended, authorized or warranted for use as components in systems intended for surgical implant into the body, or in other applications intended to support or sustain life, or in any other application in which the failure of AMD's product could create a situation where personal injury, death, or severe property or environmental damage may occur. AMD reserves the right to discontinue or make changes to its products at any time without notice.

Copyright and Trademarks

© 2015 Advanced Micro Devices, Inc. All rights reserved. AMD, the AMD Arrow logo, ATI, the ATI logo, Radeon, FireStream, and combinations thereof are trademarks of Advanced Micro Devices, Inc. OpenCL and the OpenCL logo are trademarks of Apple Inc. used by permission by Khronos. Other names are for informational purposes only and may be trademarks of their respective owners.