

# The l3charts package

Éric BURGHARD

2023/01/04

<https://git.itsufficient.me/latex/l3charts>

## Abstract

This package defines a few simple TikZ charts that can be drawn using  $\LaTeX$  environments. This has mainly been developed as an experimentation of `expl3` for checking what  $\LaTeX$ 3 really brought to facilitate package development (`expansion control`, `seq`, `prop`, `keys`, `int`, `bool`, `fp`, `dimmsg`, ...).

## Contents

<b>1</b>	<b>About this documentation</b>	<b>3</b>
<b>2</b>	<b>Motivation</b>	<b>3</b>
<b>3</b>	<b>Kiviat chart</b>	<b>3</b>
3.1	Usage	3
3.1.1	Dimensions	3
3.1.2	Set	4
3.2	Examples	5
3.2.1	Simple	5
3.2.2	Rounded	6
3.2.3	Multi-set	7
3.3	To do	8
<b>4</b>	<b>Ball chart</b>	<b>8</b>
4.1	Usage	8
4.2	Examples	9
4.2.1	Simple	9
4.2.2	Delimited	9
<b>5</b>	<b>Bar chart</b>	<b>9</b>
5.1	Usage	9
5.2	Examples	10
5.2.1	Simple	11
5.2.2	Gauge	11
<b>6</b>	<b>Bubble chart</b>	<b>11</b>
6.1	Usage	12
6.2	Examples	12
6.2.1	Horizontal	13
6.2.2	Vertical	14
<b>7</b>	<b>Radial chart</b>	<b>14</b>
7.1	Usage	14
7.2	Examples	15
7.2.1	Horizontal	15
7.2.2	Vertical	15
<b>8</b>	<b>Arc chart</b>	<b>15</b>
8.1	Usage	16
8.2	Examples	16
8.2.1	Simple	16
8.2.2	Colorful	17

---

<b>9</b>	<b>Macros</b>	<b>17</b>
9.1	Package . . . . .	17
9.2	Examples . . . . .	17
<b>10</b>	<b>Index</b>	<b>18</b>
<b>11</b>	<b>Changes</b>	<b>19</b>

# 1 About this documentation

I doubt that  $\LaTeX$  will have one day a modern documentation system as powerful as **cargo doc** due to its typeless and syntaxless nature. In my opinion  $\LaTeX$  literate programming with **docstrip** is just an ugly hack that turns the code and the documentation unmaintainable, and it's probably the component of  $\LaTeX$  which aged the most.

So I chose to write the documentation separately and borrowed much of the style from the **microtype** package which by the way (if you are still curious about it), pushes the **docstrip** mastery to a *black magic* level.

# 2 Motivation

This package has been developed mainly to typeset a fancy résumé but perhaps it could be used in other contexts too. I didn't want to write *TikZ* charts directly in the document as it would have turned a simple typesetting file into an unreadable document, and I would have forgotten every details after just a few months.

I wouldn't have the patience to develop this with  $\LaTeX$  or  $\TeX$  either, but I was curious enough about **expl3** to try an implementation. You should probably take this package as a rough tutorial on how to develop with **expl3** because it uses nearly all the types defined in the reference documentation (expansion control, **seq**, **prop**, **keys**, **int**, **bool**, **fp**, **dim**, **msg**, ...) in straightforward ways.

$\TeX$  will always be that dusty tech you can't ignore because but there are so many (unmatched) packages coming from academic circles, but **expl3** gives a touch of modernity and facilitates a lot package development by allowing to easily bridge  $\TeX$  packages (here  $\LaTeX$  and *TikZ*).

# 3 Kiviat chart

## 3.1 Usage

The **kiviat chart** or *radar chart* allows to represent one or several set along several dimensions.

<code>\begin{kiviatchart}</code>	Environment that hold a kiviat chart. Accepts an optional argument [ <i>&lt;clist&gt;</i> ] which is comma separated list of keywords and values :	
<code>\end{kiviatchart}</code>		
<b>radius</b>	<i>&lt;dim&gt;</i>	3.5cm
	Maximal diagram radius	
<b>units</b>	<i>&lt;int&gt;</i>	5
	Set the scale of units from 0 to the given number	
<b>rounded</b>	<i>&lt;bool&gt;</i>	false
	Use circles for the scale and curves for the sets instead of polygons	
*	<i>&lt;keyval&gt;</i>	
	All other options are passed to <b>tikzpicture</b> ( <i>env</i> )	
	A <b>kiviatchart</b> ( <i>env</i> ) should begin with a <b>dims</b> ( <i>env</i> ), followed by one or several <b>set</b> ( <i>env</i> ).	

### 3.1.1 Dimensions

<code>\begin{dims}</code>	Environment that hold the definition of all dimensions. Accepts an optional argument [ <i>&lt;clist&gt;</i> ] which is comma separated list of keywords and values :	
<code>\end{dims}</code>		
<b>radius</b>	<i>&lt;dim&gt;</i>	kiviatchart ( <i>env</i> ) radius
	Radius to put dimension labels on	
<b>label-on</b>	<i>&lt;int&gt;</i>	1
	Dimension axis index (between 1 and number of dimensions) to put the labels on. In case of invalid value (0), the units labels are hidden.	


<b>dim-options</b>	$\langle prop \rangle$	<code>{opacity=0.8}</code>
	TikZ options for drawing dimensions axis with	
<b>unit-options</b>	$\langle prop \rangle$	<code>{opacity=0.3}</code>
	TikZ options for drawing unit polygons with	
<b>label-options</b>	$\langle prop \rangle$	<code>{opacity=0.5,above,xshift=1.5mm}</code>
	TikZ options drawing for unit labels	
<b>label-cs</b>	$\langle str \rangle$	<code>identity</code>
	Name of the cs used to format labels	
<b>unit-cs</b>	$\langle str \rangle$	<code>tinytt</code>
	Name of the cs used to format unit scale	
<b>angle</b>	$\langle fp \rangle$	<code>90</code>
	Angle of the first dimension	
<b>\value</b>	$\backslash value[\langle clist \rangle]{\langle label \rangle}$ is used to add a dimension to the kiviart chart. [ $\langle clist \rangle$ ] is passed to TikZ to draw the nodes corresponding to the labels.	

### 3.1.2 Set

$\backslash begin{\text{set}}$	<b>set</b> ( <i>env</i> ) is used to add a new set to the kiviart chart. Accepts an optional argument [ $\langle clist \rangle$ ] which is comma separated list of keywords and values :	
$\backslash end{\text{set}}$		
<b>dot-options</b>	$\langle prop \rangle$	<code>{fill,circle,inner sep=1pt}</code>
	Options for polygon node	
<b>*</b>	$\langle keyval \rangle$	<code>color=black,line width=1.5pt,opacity=1,fill opacity=0.3,fill=gray</code>
	All other options are passed to $\backslash draw$ cs which draws the polygon	
<b>\value</b>	$\backslash value\{\langle int \rangle\}$ is used to add a value to the set.	
	There must be the same number of $\backslash value$ inside <b>set</b> ( <i>env</i> ) and <b>dims</b> ( <i>env</i> ), and each $\backslash value$ corresponds to the dimension in <b>dims</b> ( <i>env</i> ) at the same index.	

## 3.2 Examples


### 3.2.1 Simple



```
% scale is passed to tikzpicture
\begin{kiviatchart}[scale=0.75]
% Define the dimensions
\begin{dims}[
% inverted labels
label-cs=textinv,
% value scale on dim2 axis
label-on=2]
% Specify placement of each
% labels
\value[above]{Dim 1}
\value[right]{Dim 2}
\value[below]{Dim 3}
\value[below]{Dim 4}
\value[left]{Dim 5}
\end{dims}

% Add least one set should
% be defined.
\begin{set}
\value{4} % Dim 1
\value{3} % Dim 2
\value{4} % Dim 3
\value{5} % Dim 4
\value{3} % Dim 5
\end{set}
\end{kiviatchart}
```


### 3.2.2 Rounded



```
% rounded replace polygons by circles
% curves
\begin{kiviatchart}[
  scale=0.75,
  rounded]
% Define the dimensions
\begin{dims}[
  % inverted labels
  label-cs=textinv,
  % value scale on dim2 axis
  label-on=2]
% Specify placement of each
% labels
\value[above]{Dim 1}
\value[right]{Dim 2}
\value[below]{Dim 3}
\value[below left]{Dim 4}
\value[left]{Dim 5}
\end{dims}

% Add least one set should
% be defined.
\begin{set}
\value{4} % Dim 1
\value{3} % Dim 2
\value{4} % Dim 3
\value{5} % Dim 4
\value{3} % Dim 5
\end{set}
\end{kiviatchart}
```

### 3.2.3 Multi-set



```
\begin{kiviatchart}[
  scale=0.75,
  rounded]
\begin{dims}[
  % bigger radius for labels
  radius=3.7cm,
  % hide unit labels
  label-on=0]
  \value[above]{Dim 1}
  \value[right]{Dim 2}
  \value[below]{Dim 3}
  \value[below]{Dim 4}
  \value[left]{Dim 5}
\end{dims}

\begin{set}[% red set
  fill=red,
  % big rectangle dots
  dot-options={
    fill,rectangle,
    inner sep=2pt
  }]
  \value{4} % Dim 1
  \value{3} % Dim 2
  \value{4} % Dim 3
  \value{5} % Dim 4
  \value{2} % Dim 5
\end{set}

\begin{set}[% green set
  fill=green,
  % big diamond dots
  dot-options={
    fill,diamond,
    inner sep=2pt
  }]
  \value{2} % Dim 1
  \value{4} % Dim 2
  \value{3} % Dim 3
  \value{4} % Dim 4
  \value{5} % Dim 5
\end{set}

\begin{set}[% blue set
  fill=blue,
  % big semicircle dots
  dot-options={
    fill,semicircle,
    inner sep=2pt
  }]
  \value{5} % Dim 1
  \value{2} % Dim 2
  \value{4} % Dim 3
  \value{3} % Dim 4
  \value{4} % Dim 5
\end{set}
\end{kiviatchart}
```

### 3.3 To do

At the moment the environments are not user friendly. We could provide basic sanity checks, with error messages when theses rules are violated :

- one and only one `dims (env)` declared before any `set (env)`
- at least 3 dimensions are declared
- all `set (env)` have the same number of `\value` than the `dims (env)`
- `\value` in `set (env)` is between 0 and `units`

## 4 Ball chart

### 4.1 Usage


`\begin{ballchart}` Environment that hold a ball chart. Accepts an optional argument [`\clist`] which is comma separated list of keywords and values :

<code>n</code>	<code>\langle int \rangle</code>	5
	The number of circles per bar	
<code>gap</code>	<code>\langle dim \rangle</code>	1ex
	Gap between bars	
<code>cgap</code>	<code>\langle dim \rangle</code>	1pt
	Gap between circles	
<code>radius</code>	<code>\langle dim \rangle</code>	2.5mm
	Radius of the circles	
<code>label-cs</code>	<code>\langle str \rangle</code>	identity
	Macro name to format labels	
<code>fill-options</code>	<code>\langle prop \rangle</code>	{fill=black}
	TikZ options to fill the balls with	
<code>draw-options</code>	<code>\langle prop \rangle</code>	{draw=none}
	TikZ options to draw the balls with	
<code>label-options</code>	<code>\langle prop \rangle</code>	{left}
	TikZ options for dimensions axis	
<code>label-cs</code>	<code>\langle str \rangle</code>	identity
	Macro name to format labels	
<code>label-pos</code>	<code>\langle str \rangle</code>	left
	Position of the label. Possible values :	
	<ul style="list-style-type: none"> <li>• <code>left, right</code></li> <li>• <code>above, below</code></li> <li>• <code>above right, above left</code></li> <li>• <code>below right, below left</code></li> </ul>	
<code>value-cs</code>	<code>\langle str \rangle</code>	nop
	cs name to format values with	
<code>*</code>	<code>\langle keyval \rangle</code>	
	All other options are passed to <code>tikzpicture (env)</code>	
<code>\value</code>	<code>\value{\langle label \rangle}{\langle percent \rangle}</code> is used to add a new bar.	




## 4.2 Examples

### 4.2.1 Simple




```
\begin{ballchart}
  \value{Dim 1}{95}
  \value{Dim 2}{80}
  \value{Dim 3}{80}
  \value{Dim 4}{20}
\end{ballchart}
```



```
\begin{ballchart}[
  % inverted labels
  label-cs=textinv,
  % to the right
  label-pos=right,
  % closer to the bar
  label-options={xshift=-8mm},
  % show circle
  draw-options={draw=black!30}]
  \value{Dim 1}{95}
  \value{Dim 2}{80}
  \value{Dim 3}{80}
  \value{Dim 4}{20}
\end{ballchart}
```

### 4.2.2 Delimited



```
\begin{ballchart}[
  % 6 circles per bar
  n=6,
  % red labels
  label-cs=redbf,
  % closer to bar
  label-options={xshift=4mm},
  % bigger gap
  gap=1.5ex,
  cgap=3pt,
  % fill in red
  fill-options={fill=red!50},
  % black circle
  draw-options={draw=black}]
  \value{Dim 1}{95}
  \value{Dim 2}{80}
  \value{Dim 3}{80}
  \value{Dim 4}{20}
\end{ballchart}
```

## 5 Bar chart


### 5.1 Usage

<code>\begin{barchart}</code>	Environment that hold a bar chart. Accepts an optional argument [ <i>&lt;clist&gt;</i> ] which is comma separated list of keywords and values :
<code>\end{barchart}</code>	
<code>width</code>	<i>&lt;dim&gt;</i> Maximum width

<b>height</b>	$\langle dim \rangle$	3.5mm
	Bar height	
<b>gap</b>	$\langle dim \rangle$	1ex
	Gap between bars	
<b>fill-options</b>	$\langle prop \rangle$	{fill=none}
	TikZ options to fill the bar with	
<b>draw-options</b>	$\langle prop \rangle$	{fill=black}
	TikZ options to draw the bar with	
<b>label-options</b>	$\langle prop \rangle$	{}
	TikZ options for dimensions axis	
<b>label-cs</b>	$\langle str \rangle$	identity
	Macro name to format labels	
<b>label-pos</b>	$\langle str \rangle$	left
	Position of the label. Possible values :	
	<ul style="list-style-type: none"> <li>• left, right</li> <li>• above, below</li> <li>• above right, above left</li> <li>• below right, below left</li> </ul>	
<b>value-cs</b>	$\langle str \rangle$	nop
	cs name to format values with	
<b>*</b>	$\langle keyval \rangle$	
	All other options are passed to <code>tikzpicture</code> ( <i>env</i> )	
<b>\value</b>	<code>\value{\label}{\percent}</code> is used to add a new bar.	

## 5.2 Examples

### 5.2.1 Simple




```
\begin{barchart}
  \value{Dim 1}{60}
  \value{Dim 2}{100}
  \value{Dim 3}{70}
  \value{Dim 4}{70}
  \value{Dim 5}{40}
  \value{Dim 6}{60}
\end{barchart}
```



```
\begin{barchart}[
  % inverted labels
  label-cs=textinv,
  % to the right
  label-pos=right,
  % closer to bar
  label-options={xshift=-8mm}]
  \value{Dim 1}{60}
  \value{Dim 2}{100}
  \value{Dim 3}{70}
  \value{Dim 4}{70}
  \value{Dim 5}{40}
  \value{Dim 6}{60}
\end{barchart}
```

### 5.2.2 Gauge



```
\begin{barchart}[
  % 4cm wide bars
  width=4cm,
  % inverted labels
  label-cs=redbf,
  % closer to bar
  label-options={xshift=4mm},
  % show values
  value-cs=whitebf,
  % bigger gap
  gap=1.5ex,
  % bar in red
  draw-options={
    draw=red!50,
    fill=red!50},
  % show borders in red
  fill-options={
    fill=red!30,
    draw=red!30}]
  \value{Dim 1}{60}
  \value{Dim 2}{100}
  \value{Dim 3}{70}
  \value{Dim 4}{70}
  \value{Dim 5}{40}
  \value{Dim 6}{60}
\end{barchart}
```


## 6 Bubble chart

## 6.1 Usage


<code>\begin{bubblechart}</code>	Environment that hold a bubble chart. Accepts an optional argument [ <i>&lt;clist&gt;</i> ] which is comma separated list of keywords and values :		
<code>\end{bubblechart}</code>			
<b>radius</b>	<i>&lt;dim&gt;</i>		1cm
	Max radius		
<b>gap</b>	<i>&lt;dim&gt;</i>		1ex
	Gap between bubbles		
<b>fill-options</b>	<i>&lt;prop&gt;</i>		{fill=none,draw=none}
	TikZ options to fill/draw the background with		
<b>draw-options</b>	<i>&lt;prop&gt;</i>		{fill=black}
	TikZ options to fill/draw the bubble with		
<b>label-cs</b>	<i>&lt;str&gt;</i>		identity
	Macro name to format labels		
<b>label-pos</b>	<i>&lt;str&gt;</i>		above
	Position of the label. Possible values :		
	<ul style="list-style-type: none"> <li>• left, right</li> <li>• above, below</li> <li>• above right, above left</li> <li>• below right, below left</li> </ul>		
<b>value-cs</b>	<i>&lt;str&gt;</i>		nop
	cs name to format values with		
<b>vertical</b>	<i>&lt;bool&gt;</i>		false
	Stack the bubble vertically instead of horizontally		
<b>*</b>	<i>&lt;keyval&gt;</i>		
	All other options are passed to <code>tikzpicture</code> ( <i>env</i> )		
<b>\value</b>	<code>\value{&lt;label&gt;}{&lt;percent&gt;}</code> is used to add a new bubble.		

## 6.2 Examples


### 6.2.1 Horizontal



```
\begin{bubblechart}
  \value{Dim 1}{80}
  \value{Dim 2}{90}
  \value{Dim 3}{50}
\end{bubblechart}
```




```
\begin{bubblechart}[
  % inverted labels
  label-cs=textinv,
  % below bubble
  label-pos=below,
  % show borders
  fill-options={
    fill=none,
    draw=black!30}]
  \value{Dim 1}{80}
  \value{Dim 2}{90}
  \value{Dim 3}{50}
\end{bubblechart}
```



```
\begin{bubblechart}[
  % label in red
  label-cs=redbf,
  % below bubble
  label-pos=below,
  % show value
  value-cs=whitebf,
  % bubble in red
  draw-options={
    draw=red!50,
    fill=red!50},
  % background in light red
  fill-options={
    fill=red!10}]
  \value{Dim 1}{80}
  \value{Dim 2}{90}
  \value{Dim 3}{50}
\end{bubblechart}
```

### 6.2.2 Vertical



```
\begin{bubblechart}[
  % stack bubbles vertically
  vertical,
  % label in bold
  label-cs=textbf,
  % show values
  value-cs=whitebf,
  % to the right
  label-pos=right,
  % show max as dotted line
  fill-options={
    fill=none,
    draw=black,
    dotted}]
\value{Dim 1}{80}
\value{Dim 2}{90}
\value{Dim 3}{50}
\end{bubblechart}
```

## 7 Radial chart

### 7.1 Usage

<code>\begin{radialchart}</code>	Environment that hold a radial chart. Accepts an optional argument [ <i>&lt;clist&gt;</i> ] which is comma separated list of keywords and values :		
<code>\end{radialchart}</code>			
<b>radius</b>	<i>&lt;dim&gt;</i>		1cm
	Max radius		
<b>gap</b>	<i>&lt;dim&gt;</i>		2.5ex
	Gap between radials		
<b>line width</b>	<i>&lt;dim&gt;</i>		3mm
	Line width to draw the radials with		
<b>fill-options</b>	<i>&lt;prop&gt;</i>	{fill=none,draw=black!10}	
	TikZ options to fill/draw the center of the radial with		
<b>draw-options</b>	<i>&lt;prop&gt;</i>	black	
	TikZ options to draw the radial with		
<b>label-options</b>	<i>&lt;prop&gt;</i>	{}	
	TikZ options drawing for unit labels		
<b>label-cs</b>	<i>&lt;str&gt;</i>	identity	
	cs name to format labels with		
<b>label-pos</b>	<i>&lt;str&gt;</i>	above	
	Position of the label. Possible values :		
	<ul style="list-style-type: none"> <li>• left, right</li> <li>• above, below</li> <li>• above right, above left</li> <li>• below right, below left</li> </ul>		
<b>value-cs</b>	<i>&lt;str&gt;</i>	identity	
	cs name to format values with		
<b>vertical</b>	<i>&lt;bool&gt;</i>	false	

Stack radials vertically instead of horizontally


\*  $\langle keyval \rangle$

line cap=round


All other options are passed to `tikzpicture` (*env*)

## 7.2 Examples

### 7.2.1 Horizontal




```
\begin{radialchart}
  \value{Dim 1}{80}
  \value{Dim 2}{90}
  \value{Dim 3}{50}
\end{radialchart}
```



```
\begin{radialchart}[
  % inverted label,
  label-cs=textinv,
  % below radial,
  label-pos=below,
  % in red bold.
  value-cs=redbf,
  % ring is red
  draw-options={red!50},
  % disk is light red
  fill-options={
    fill=red!10}]
  \value{Dim 1}{80}
  \value{Dim 2}{90}
  \value{Dim 3}{50}
\end{radialchart}
```

### 7.2.2 Vertical



```
\begin{radialchart}[
  % stack radials vertically
  vertical,
  % label as tenth fraction
  value-cs=tenrate,
  % to the right
  label-pos=right,
  % thicker line
  line width=3.5mm,
  % with rect end
  line cap=butt,
  % same color for disk and ring
  fill-options={
    draw=black!10,
    fill=black!10}]
  \value{Dim 1}{80}
  \value{Dim 2}{90}
  \value{Dim 3}{50}
\end{radialchart}
```

## 8 Arc chart

## 8.1 Usage

<code>\begin{arcchart}</code>	Environment that hold an arc chart. Accepts an optional argument [ <i>&lt;clist&gt;</i> ] which is comma separated list of keywords and values :		
<code>\end{arcchart}</code>			
<b>radius</b>	<i>&lt;dim&gt;</i>	1cm	Radius of outer arc
<b>gap</b>	<i>&lt;dim&gt;</i>	2.5ex	Gap between arcs
<b>line width</b>	<i>&lt;dim&gt;</i>	4mm	Line width to draw the arc with
<b>fill-options</b>	<i>&lt;prop&gt;</i>	{fill=none,draw=black!10}	TikZ options to fill/draw the background of the arcs with
<b>draw-options</b>	<i>&lt;prop&gt;</i>	black	TikZ options to draw the arcs with
<b>label-options</b>	<i>&lt;prop&gt;</i>	{}	TikZ options drawing for unit labels
<b>label-cs</b>	<i>&lt;str&gt;</i>	identity	cs name to format labels with
<b>value-options</b>	<i>&lt;prop&gt;</i>		TikZ options to draw values with
<b>value-cs</b>	<i>&lt;str&gt;</i>	nop	cs name to format values with
<b>value-angle</b>	<i>&lt;fp&gt;</i>	90	Angle at which to draw the values
<b>*</b>	<i>&lt;keyval&gt;</i>	line cap=round	All other options are passed to <code>tikzpicture</code> ( <i>env</i> )

## 8.2 Examples


### 8.2.1 Simple



```
\begin{arcchart}
  \value{Dim 1}{100}
  \value{Dim 2}{90}
  \value{Dim 3}{60}
  \value{Dim 4}{45}
\end{arcchart}
```



## 8.2.2 Colorful



```
\begin{arcchart}[
  % bigger radius,
  radius=2.5cm,
  % and gap
  gap=1.5mm,
  % show values
  value-cs=whitebf,
  % at 30°
  value-angle=30,
  % thicker line width,
  line width=4.5mm,
  % with square end
  line cap=butt]
  % each ring has its own color
  \value[blue!50]{Dim 1}{100}
  \value[cyan!50]{Dim 2}{90}
  \value[purple!50]{Dim 3}{60}
  \value[red!50]{Dim 4}{45}
\end{arcchart}
```

## 9 Macros

### 9.1 Package

These are macros defined in `l3charts.sty` and used as default value for `label-cs` or `value-cs` options.

`\tinytt` Macro used to format its argument as tiny monospace

```
\cs_set:Npn \tinytt #1 {\texttt{\tiny #1}}
```

`\identity` Macro used to return the first argument as is

```
\cs_set:Npn \identity #1 {#1}
```

`\nop` Macro used to consume the first argument and do nothing

```
\cs_set:Npn \nop #1 {}
```

`\percent` Macro used to append a percent to its argument

```
\cs_set:Npn \percent #1 {#1\%}
```

### 9.2 Examples

These macros are defined for the examples presented in this document and are not part of the module `l3charts.sty`.

`\textbfp` Macro used to format its argument as bold with appended %

```
\NewDocumentCommand\textbfp{m}{\textbf{\percent{#1}}}
```

`\tenrate` Macro used to format its argument as fraction of ten

```
\ExplSyntaxOn
\NewDocumentCommand\tenrate{m}{\int_eval:n{#1/10}/10}
\ExplSyntaxOff
```

`\textinv` Macro used to format its argument as white text on black background

```
\NewDocumentCommand\textinv{m}{\colorbox{black}{\textcolor{white}{#1}}}
```

- `\redbf` Macro used to format its argument as bold and red
- `\NewDocumentCommand\redbf{m}{\textcolor{red!50}{\textbf{#1}}}`
- `\redbfp` Macro used to format its argument as bold and red with appended %
- `\NewDocumentCommand\redbfp{m}{\textcolor{red!50}{\textbfp{#1}}}`
- `\whitebf` Macro used to format its argument as bold and white
- `\NewDocumentCommand\whitebf{m}{\textcolor{white}{\textbf{#1}}}`
- `\whitebfp` Macro used to format its argument as bold and white with appended %
- `\NewDocumentCommand\whitebfp{m}{\textcolor{white}{\textbfp{#1}}}`

## 10 Index

Numbers in upright shape refer to the *page* where the corresponding entry is described (bold face) resp. occurs.

- |                 |   |   |
|-----------------|---|---|
| <b>Options</b>  | <code>* (option)</code> ..... <b>3, 4, 8, 10, 12, 15, 16</b>          | <code>label-pos</code> ..... <b>8, 10, 12, 14</b>                     |
|                 | <code>*</code> ..... <b>3, 4, 8, 10, 12, 15, 16</b>                   | <code>line width</code> ..... <b>14, 16</b>                           |
|                 | <code>angle</code> ..... <b>4</b>                                     | <code>n</code> ..... <b>8</b>   |
|                 | <code>cgap</code> ..... <b>8</b>                                      | <code>radius</code> ..... <b>3, 8, 12, 14, 16</b>                     |
|                 | <code>dim-options</code> ..... <b>4</b>                               | <code>rounded</code> ..... <b>3</b>                                   |
|                 | <code>dot-options</code> ..... <b>4</b>                               | <code>unit-cs</code> ..... <b>4</b>                                   |
|                 | <code>draw-options</code> ..... <b>8, 10, 12, 14, 16</b>              | <code>unit-options</code> ..... <b>4</b>                              |
|                 | <code>fill-options</code> ..... <b>8, 10, 12, 14, 16</b>              | <code>units</code> ..... <b>3</b>                                     |
|                 | <code>gap</code> ..... <b>8, 10, 12, 14, 16</b>                       | <code>value-angle</code> ..... <b>16</b>                              |
|                 | <code>height</code> ..... <b>10</b>                                   | <code>value-cs</code> ..... <b>8, 10, 12, 14, 16</b>                  |
|                 | <code>label-cs</code> ..... <b>4, 8, 10, 12, 14, 16</b>               | <code>value-options</code> ..... <b>16</b>                            |
|                 | <code>label-on</code> ..... <b>3</b>                                  | <code>vertical</code> ..... <b>12, 14</b>                             |
|                 | <code>label-options</code> ..... <b>4, 8, 10, 14, 16</b>              | <code>width</code> ..... <b>9</b>                                     |
| <b>Commands</b> | <code>identity</code> ..... <b>17</b>                                 | <code>textbfp</code> ..... <b>17</b>                                  |
|                 | <code>nop</code> ..... <b>17</b>                                      | <code>textinv</code> ..... <b>17</b>                                  |
|                 | <code>percent</code> ..... <b>17</b>                                  | <code>tinytt</code> ..... <b>17</b>                                   |
|                 | <code>redbf</code> ..... <b>18</b>                                    | <code>value</code> ..... <b>4, 8, 10, 12</b>                          |
|                 | <code>redbfp</code> ..... <b>18</b>                                   | <code>whitebf</code> ..... <b>18</b>                                  |
|                 | <code>tenrate</code> ..... <b>17</b>                                  | <code>whitebfp</code> ..... <b>18</b>                                 |
| <b>A</b>        | <code>angle (option)</code> ..... <b>4, 19</b>                        | <code>arcchart (environment)</code> ..... <b>16, 19</b>               |
| <b>B</b>        | <code>ballchart (environment)</code> ..... <b>8, 19</b>               | <code>bubblechart (environment)</code> ..... <b>12, 19</b>            |
|                 | <code>barchart (environment)</code> ..... <b>9, 19</b>                |   |
| <b>C</b>        | <code>cgap (option)</code> ..... <b>8, 19</b>                         |   |
| <b>D</b>        | <code>dim-options (option)</code> ..... <b>4</b>                      | <code>dot-options (option)</code> ..... <b>4</b>                      |
|                 | <code>dims (environment)</code> ..... <b>3, 3, 4, 8, 19</b>           | <code>\draw</code> ..... <b>4</b>                                     |
|                 | <code>docstrip (package)</code> ..... <b>3</b>                        | <code>draw-options (option)</code> ..... <b>8, 10, 12, 14, 16, 19</b> |
| <b>E</b>        | <code>expl3 (package)</code> ..... <b>3</b>                           |   |
| <b>F</b>        | <code>fill-options (option)</code> ..... <b>8, 10, 12, 14, 16, 19</b> |   |
| <b>G</b>        | <code>gap (option)</code> ..... <b>8, 10, 12, 14, 16, 19</b>          |   |
| <b>H</b>        | <code>h-sep (option)</code> ..... <b>19</b>                           | <code>height (option)</code> ..... <b>10</b>                          |
| <b>I</b>        | <code>\identity</code> ..... <b>17</b>                                |   |
| <b>K</b>        | <code>kiviatchart (environment)</code> ..... <b>3, 3, 19</b>          |   |
| <b>L</b>        | <code>l3charts.sty (package)</code> ..... <b>17</b>                   | <code>label-pos (option)</code> ..... <b>8, 10, 12, 14, 19</b>        |
|                 | <code>label-cs (option)</code> ..... <b>4, 8, 10, 12, 14, 16, 17</b>  | <code>labels-radius (option)</code> ..... <b>19</b>                   |
|                 | <code>label-on (option)</code> ..... <b>3, 19</b>                     | <code>line width (option)</code> ..... <b>14, 16, 19</b>              |
|                 | <code>label-options (option)</code> ..... <b>4, 8, 10, 14, 16</b>     | <code>line-width (option)</code> ..... <b>19</b>                      |

<b>M</b>	<code>microtype</code> (package) . . . . .	3, 19	
<b>N</b>	<code>n</code> (option) . . . . .	8	<code>\nop</code> . . . . . 17
<b>P</b>	<code>\percent</code> . . . . .	17	
<b>R</b>	<code>radialchart</code> (environment) . . . . .	14, 19	<code>\redbf</code> . . . . . 18
	<code>radius</code> (option) . . . . .	3, 3, 8, 12, 14, 16, 19	<code>rounded</code> (option) . . . . . 3, 19
	<code>\redbf</code> . . . . .	18	
<b>S</b>	<code>set</code> (environment) . . . . .	3, 4, 4, 8, 19	
<b>T</b>	<code>\tenrate</code> . . . . .	17	<code>tikzpicture</code> (environment) . . . 3, 8, 10, 12, 15, 16
	<code>\textbfp</code> . . . . .	17	<code>\tinytt</code> . . . . . 17
	<code>\textinv</code> . . . . .	17	
<b>U</b>	<code>unit-cs</code> (option) . . . . .	4	<code>units</code> (option) . . . . . 3
	<code>unit-options</code> (option) . . . . .	4	
<b>V</b>	<code>v-sep</code> (option) . . . . .	19	<code>value-cs</code> (option) . . . . . 8, 10, 12, 14, 16, 17
	<code>\value</code> . . . . .	4, 4, 8, 8, 10, 10, 12, 12	<code>value-options</code> (option) . . . . . 16
	<code>value-angle</code> (option) . . . . .	16	<code>vertical</code> (option) . . . . . 12, 14
<b>W</b>	<code>\whitebf</code> . . . . .	18	<code>width</code> (option) . . . . . 9
	<code>\whitebfp</code> . . . . .	18	

## 11 Changes

### 0.7.1 (2023/01/04)

- add a `rounded` option to `kiviatchart` (*env*) to use circles for the scale and curves for the sets.

### 0.7.0 (2022/08/01)

- add a `arcchart` (*env*)
- rename `line-width` to `line width` for consistency with TikZ
- use choice to restrict values on `label-pos`
- remove spurious `;` and replace `c_space_tl` by `~`

### 0.6.1 (2022/07/26)

- add a `label-on` option for `dims` (*env*) of `kiviatchart` (*env*)

### 0.6.0 (2022/07/26)

- draw `kiviatchart` (*env*) dimensions clockwise with a starting angle of 90
- allow value of 0 for `set` (*env*)
- rename `labels-radius` to `radius` and move to `dims` (*env*)

### 0.5.1 (2022/07/19)

- remove hard coded % in value.

### 0.5.0 (2022/07/18)

- convert all `<fp>` to `<dim>` for usability
- rename `v-sep` and `h-sep` options of `ballchart` (*env*) to `gap` and `cgap` for consistency

### 0.4.0 (2022/07/17)

- add values to `bubblechart` (*env*)
- label positioning on `barchart` (*env*) and `ballchart` (*env*)
- swap `fill-options` and `draw-options` for `barchart` (*env*) for consistency

### 0.3.0 (2022/07/15)

- add a `radialchart` (*env*) to draw radials
- add a vertical mode to `bubblechart` (*env*) and allow positioning of the label
- swap `fill-options` and `draw-options` for `bubblechart` (*env*) for consistency

### 0.2.0 (2022/07/04)

- define a document class borrowed from `microtype`

### 0.1.0 (2022/07/01)

- Initial version