

The l3charts package

Éric BURGHARD

2022/07/15

<https://git.itsufficient.me/latex/l3charts>

Abstract

This package defines a few simple TikZ charts that can be drawn using L^AT_EX environments. This has mainly been developed as an experimentation of `expl3` for checking what L^AT_EX3 really brought to facilitate package development (expansion control, seq, prop, keys, int, bool, fp, dim, ...).

Contents

1	About this documentation	2
2	Kiviat chart	2
2.1	Usage	2
2.1.1	Dimensions	2
2.1.2	Set	2
2.2	Examples	3
2.2.1	Simple	3
2.2.2	Multi-set	4
2.3	To do	4
3	Ball chart	5
3.1	Usage	5
3.2	Examples	5
3.2.1	Simple	6
3.2.2	Delimited	6
4	Bar chart	6
4.1	Usage	6
4.2	Examples	7
4.2.1	Simple	7
4.2.2	Gauge	8
5	Bubble chart	8
5.1	Usage	8
5.2	Examples	9
5.2.1	Horizontal	9
5.2.2	Vertical	10
6	Radial chart	10
6.1	Usage	10
6.2	Examples	10
6.2.1	Horizontal	11
6.2.2	Vertical	11
7	Macros	11
7.1	Package	11
7.2	Examples	12
8	Index	12
9	Changes	13

1 About this documentation

I doubt that \LaTeX will have one day a modern documentation system as powerful as **cargo doc** due to its typeless and syntaxless nature. In my opinion \LaTeX literate programming with **docstrip** is just an ugly hack that turns the code and the documentation unmaintainable, and it's probably the component of \LaTeX which aged the most.

So I chose to write the documentation separately and borrowed much of the style from the **microtype** package which by the way, pushes the **docstrip** mastery to a *black magic* level.

2 Kiviat chart

2.1 Usage

The **kiviat chart** or *radar chart* allows to represent one or several set along several dimensions.

`\begin{kiviatchart}` Environment that hold a kiviat chart. Accepts an optional argument [*<clist>*] which is comma separated list of keywords and values :

radius *<dim>* 3.5cm

Maximal diagram radius

label-radius *<dim>* 3.5cm

Radius to put dimension labels on

units *<int>* 5

Set the scale of units from 0 to the given number

* *<keyval>*

All other options are passed to **tikzpicture** (*env*)

A **kiviatchart** (*env*) should begin with a **dims** (*env*), followed by one or several **set** (*env*).

2.1.1 Dimensions

`\begin{dims}` Environment that hold the definition of all dimensions. Accepts an optional argument [*<clist>*] which is comma separated list of keywords and values :

dim-options *<prop>* {opacity=0.8}

TikZ options for drawing dimensions axis with

unit-options *<prop>* {opacity=0.3}

TikZ options for drawing unit polygons with

label-options *<prop>* {opacity=0.5,below}

TikZ options drawing for unit labels

label-cs *<str>* identity

Name of the cs used to format labels

unit-cs *<str>* tinytt

Name of the cs used to format unit scale

\value `\value[<clist>]{<label>}` is used to add a dimension to the kiviat chart. [*<clist>*] is passed to TikZ to draw the nodes corresponding to the labels.

2.1.2 Set

`\begin{set}` **set** (*env*) is used to add a new set to the kiviat chart. Accepts an optional argument [*<clist>*] which is comma separated list of keywords and values :

dot-options *<prop>* {fill,circle,inner sep=1pt}

Options for polygon node

* *<keyval>* color=black,line width=1.5pt,opacity=1,fill opacity=0.3,fill=gray

All other options are passed to `\draw cs` which draws the polygon


`\value` `\value{<int>}` is used to add a value to the set.

There must be the same number of `\value` inside `set (env)` and `dims (env)`, and each `\value` corresponds to the dimension in `dims (env)` at the same index.

2.2 Examples


2.2.1 Simple

Use `label-cs` to call `\textinv` to format the labels.



```
% scale is passed to tikzpicture
\begin{kiviatchart}[scale=0.75]
% Define all the dimensions
\begin{dims}[label-cs=textinv]
% Specify placement of each
% labels
\value[above]{Dim 1}
\value[above]{Dim 2}
\value[left]{Dim 3}
\value[right]{Dim 4}
\value[right]{Dim 5}
\end{dims}
% Add one or several sets.
% Each value corresponds to
% the dimension at the same
% index in dims
\begin{set}
\value{4}
\value{3}
\value{4}
\value{5}
\value{3}
\end{set}
\end{kiviatchart}
```

2.2.2 Multi-set



```
% scale is passed to tikzpicture
\begin{kiviatchart}[scale=0.75]
  \begin{dims}
    \value[above]{Dim 1}
    \value[above]{Dim 2}
    \value[left]{Dim 3}
    \value[right]{Dim 4}
    \value[right]{Dim 5}
  \end{dims}
  % Fill this set in red
  % with rectangle dots
  \begin{set}[
    fill=red,
    dot-options={
      fill,rectangle,
      inner sep=2pt
    }
  ]
    \value{4}
    \value{3}
    \value{4}
    \value{5}
    \value{2}
  \end{set}
  % Fill this set in green
  % with diamond dots
  \begin{set}[
    fill=green,
    dot-options={
      fill,diamond,
      inner sep=2pt
    }
  ]
    \value{2}
    \value{4}
    \value{3}
    \value{4}
    \value{5}
  \end{set}
  % Fill this set in blue
  % with semicircle dots
  \begin{set}[
    fill=blue,
    dot-options={
      fill,semicircle,
      inner sep=2pt
    }
  ]
    \value{5}
    \value{2}
    \value{4}
    \value{3}
    \value{4}
  \end{set}
\end{kiviatchart}
```

2.3 To do

At the moment the environments are not user friendly. We could provide basic sanity checks, with error messages when these rules are violated :

- one and only one `dims (env)` declared before any `set (env)`
- all `set (env)` have the same number of `\value` than the `dims (env)`
- `\value` in `set (env)` is between 0 and **units**


3 Ball chart

3.1 Usage


<code>\begin{ballchart}</code>	Environment that hold a ball chart. Accepts an optional argument [<i><clist></i>] which is comma separated list of keywords and values :		
<code>\end{ballchart}</code>			
n	<i><int></i>		5
	The number of circles per bar		
gap	<i><dim></i>		1ex
	Gap between bars		
cgap	<i><dim></i>		1pt
	Gap between circles		
radius	<i><dim></i>		2.5mm
	Radius of the circles		
label-cs	<i><str></i>		identity
	Macro name to format labels		
fill-options	<i><prop></i>		{fill=black}
	TikZ options to fill the balls with		
draw-options	<i><prop></i>		{draw=none}
	TikZ options to draw the balls with		
label-options	<i><prop></i>		{left}
	TikZ options for dimensions axis		
label-cs	<i><str></i>		identity
	Macro name to format labels		
label-pos	<i><str></i>		left
	Position of the label		
value-cs	<i><str></i>		nop
	cs name to format values with		
*	<i><keyval></i>		
	All other options are passed to <code>tikzpicture</code> (<i>env</i>)		
\value	<code>\value{<label>}{<percent>}</code> is used to add a new bar.		

3.2 Examples

3.2.1 Simple




```
\begin{ballchart}
  \value{Dim 1}{95}
  \value{Dim 2}{80}
  \value{Dim 3}{80}
  \value{Dim 4}{20}
\end{ballchart}
```



```
\begin{ballchart}[
  % inverted labels
  label-cs=textinv,
  % to the right
  label-pos=right,
  % closer to the bar
  label-options={xshift=-8mm},
  % show circle
  draw-options={draw=black!30}]
  \value{Dim 1}{95}
  \value{Dim 2}{80}
  \value{Dim 3}{80}
  \value{Dim 4}{20}
\end{ballchart}
```

3.2.2 Delimited



```
\begin{ballchart}[
  % 6 circles per bar
  n=6,
  % red labels
  label-cs=redbf,
  % closer to bar
  label-options={xshift=4mm},
  % bigger gap
  gap=1.5ex,
  cgap=3pt,
  % fill in red
  fill-options={fill=red!50},
  % black circle
  draw-options={draw=black}]
  \value{Dim 1}{95}
  \value{Dim 2}{80}
  \value{Dim 3}{80}
  \value{Dim 4}{20}
\end{ballchart}
```

4 Bar chart


4.1 Usage

<code>\begin{barchart}</code>	Environment that hold a bar chart. Accepts an optional argument [<i><clist></i>] which is comma separated list of keywords and values :	
<code>\end{barchart}</code>		
<code>width</code>	<i><dim></i>	3cm
	Maximum width	
<code>height</code>	<i><dim></i>	3.5mm
	Bar height	

gap	$\langle dim \rangle$ Gap between bars	1ex
fill-options	$\langle prop \rangle$ TikZ options to fill the bar with	{fill=none}
draw-options	$\langle prop \rangle$ TikZ options to draw the bar with	{fill=black}
label-options	$\langle prop \rangle$ TikZ options for dimensions axis	{}
label-cs	$\langle str \rangle$ Macro name to format labels	identity
label-pos	$\langle str \rangle$ Position of the label	left
value-cs	$\langle str \rangle$ cs name to format values with	nop
*	$\langle keyval \rangle$ All other options are passed to <code>tikzpicture</code> (<i>env</i>)	
\value	<code>\value{<label>}{<percent>}</code> is used to add a new bar.	

4.2 Examples

4.2.1 Simple




```
\begin{barchart}
  \value{Dim 1}{60}
  \value{Dim 2}{100}
  \value{Dim 3}{70}
  \value{Dim 4}{70}
  \value{Dim 5}{40}
  \value{Dim 6}{60}
\end{barchart}
```



```
\begin{barchart}[
  % inverted labels
  label-cs=textinv,
  % to the right
  label-pos=right,
  % closer to bar
  label-options={xshift=-8mm}]
  \value{Dim 1}{60}
  \value{Dim 2}{100}
  \value{Dim 3}{70}
  \value{Dim 4}{70}
  \value{Dim 5}{40}
  \value{Dim 6}{60}
\end{barchart}
```

4.2.2 Gauge



```
\begin{barchart}[
  % 4cm wide bars
  width=4cm,
  % inverted labels
  label-cs=redbf,
  % closer to bar
  label-options={xshift=4mm},
  % show values
  value-cs=whitebfp,
  % bigger gap
  gap=1.5ex,
  % bar in red
  draw-options={
    draw=red!50,
    fill=red!50},
  % show borders in red
  fill-options={
    fill=red!30,
    draw=red!30}]
\value{Dim 1}{60}
\value{Dim 2}{100}
\value{Dim 3}{70}
\value{Dim 4}{70}
\value{Dim 5}{40}
\value{Dim 6}{60}
\end{barchart}
```

5 Bubble chart


5.1 Usage

<code>\begin{bubblechart}</code>	Environment that hold a bubble chart. Accepts an optional argument [<i><clist></i>] which is comma separated list of keywords and values :		
<code>\end{bubblechart}</code>			
radius	<i><dim></i>		1cm
	Max radius		
gap	<i><dim></i>		1ex
	Gap between bubbles		
fill-options	<i><prop></i>		{fill=none,draw=none}
	TikZ options to fill/draw the background with		
draw-options	<i><prop></i>		{fill=black}
	TikZ options to fill/draw the bubble with		
label-cs	<i><str></i>		identity
	Macro name to format labels		
label-pos	<i><str></i>		above
	Position of the label		
value-cs	<i><str></i>		nop
	cs name to format values with		
vertical	<i><bool></i>		false
	Stack the bubble vertically instead of horizontally		
*	<i><keyval></i>		
	All other options are passed to <code>tikzpicture</code> (<i>env</i>)		


`\value` `\value{⟨label⟩}{⟨percent⟩}` is used to add a new bubble.

5.2 Examples


5.2.1 Horizontal



```
\begin{bubblechart}
  \value{Dim 1}{80}
  \value{Dim 2}{90}
  \value{Dim 3}{50}
\end{bubblechart}
```




```
\begin{bubblechart}[
  % inverted labels
  label-cs=textinv,
  % below bubble
  label-pos=below,
  % show borders
  fill-options={
    fill=none,
    draw=black!30}]
  \value{Dim 1}{80}
  \value{Dim 2}{90}
  \value{Dim 3}{50}
\end{bubblechart}
```



```
\begin{bubblechart}[
  % label in red
  label-cs=redbf,
  % below bubble
  label-pos=below,
  % show value
  value-cs=whitebf,
  % bubble in red
  draw-options={
    draw=red!50,
    fill=red!50},
  % background in light red
  fill-options={
    fill=red!10}]
  \value{Dim 1}{80}
  \value{Dim 2}{90}
  \value{Dim 3}{50}
\end{bubblechart}
```

5.2.2 Vertical



```
\begin{bubblechart}[
  % stack bubbles vertically
  vertical,
  % label in bold
  label-cs=textbf,
  % show values
  value-cs=whitebf,
  % to the right
  label-pos=right,
  % show max as dotted line
  fill-options={
    fill=none,
    draw=black,
    dotted}]
  \value{Dim 1}{80}
  \value{Dim 2}{90}
  \value{Dim 3}{50}
\end{bubblechart}
```


6 Radial chart

6.1 Usage


<code>\begin{radialchart}</code>	Environment that hold a radial chart. Accepts an optional argument [<i><clist></i>] which is comma separated list of keywords and values :		
<code>\end{radialchart}</code>			
radius	<i><dim></i>		1cm
	Max radius		
gap	<i><dim></i>		2.5ex
	Gap between radials		
fill-options	<i><prop></i>	{fill=none,draw=black!10}	
	TikZ options to fill/draw the center of the radial with		
draw-options	<i><prop></i>	black	
	TikZ options to draw the radial with		
label-options	<i><prop></i>	{}	
	TikZ options drawing for unit labels		
label-cs	<i><str></i>	identity	
	cs name to format labels with		
label-pos	<i><str></i>	above	
	Label position relative to radial		
value-cs	<i><str></i>	identity	
	cs name to format values with		
vertical	<i><bool></i>	false	
	Stack radials vertically instead of horizontally		
*	<i><keyval></i>	line width=2mm,line cap=round	
	All other options are passed to tikzpicture (<i>env</i>)		

6.2 Examples

6.2.1 Horizontal




```
\begin{radialchart}
\value{Dim 1}{80}
\value{Dim 2}{90}
\value{Dim 3}{50}
\end{radialchart}
```



```
\begin{radialchart}[
% inverted label,
label-cs=textinv,
% below radial,
label-pos=below,
% in red bold.
value-cs=redbfp,
% ring is red
draw-options={red!50},
% disk is light red
fill-options={
fill=red!10}]
\value{Dim 1}{80}
\value{Dim 2}{90}
\value{Dim 3}{50}
\end{radialchart}
```

6.2.2 Vertical



```
\begin{radialchart}[
% stack radials vertically
vertical,
% label as tenth fraction
value-cs=tenrate,
% to the right
label-pos=right,
% rect ring
line cap=rect,
% same color for disk and ring
fill-options={
draw=black!10,
fill=black!10}]
\value{Dim 1}{80}
\value{Dim 2}{90}
\value{Dim 3}{50}
\end{radialchart}
```

7 Macros

7.1 Package

These are macros defined in `l3charts.sty` and used as default value for `label-cs` or `value-cs` options.

`\tinytt` Macro used to format its argument as tiny monospace

```
\cs_set:Npn \tinytt #1 {\texttt{\tiny #1}}
```

`\identity` Macro used to return the first argument as is

```
\cs_set:Npn \identity #1 {#1}
```

`\nop` Macro used to consume the first argument and do nothing

```
\cs_set:Npn \nop #1 {}
```

`\percent` Macro used to append a percent to its argument

```
\cs_set:Npn \percent#1 {#1\%}
```

7.2 Examples

These macros are defined for the examples presented in this document and are not part of the module `l3charts.sty`.

`\textbfp` Macro used to format its argument as bold with appended %

```
\NewDocumentCommand\textbfp{m}{\textbf{\percent{#1}}}
```

`\tenrate` Macro used to format its argument as fraction of ten

```
\ExplSyntaxOn
\NewDocumentCommand\tenrate{m}{\int_eval:n{#1/10}/10}
\ExplSyntaxOff
```

`\textinv` Macro used to format its argument as white text on black background

```
\NewDocumentCommand\textinv{m}{\colorbox{black}{\textcolor{white}{#1}}}
```

`\redbf` Macro used to format its argument as bold and red

```
\NewDocumentCommand\redbf{m}{\textcolor{red!50}{\textbf{#1}}}
```

`\redbfp` Macro used to format its argument as bold and red with appended %

```
\NewDocumentCommand\redbfp{m}{\textcolor{red!50}{\textbfp{#1}}}
```

`\whitebf` Macro used to format its argument as bold and white

```
\NewDocumentCommand\whitebf{m}{\textcolor{white}{\textbf{#1}}}
```

`\whitebfp` Macro used to format its argument as bold and white with appended %

```
\NewDocumentCommand\whitebfp{m}{\textcolor{white}{\textbfp{#1}}}
```

8 Index

Numbers in upright shape refer to the *page* where the corresponding entry is described (bold face) resp. occurs.

Options	* (option)	2, 5, 7, 8, 10	label-pos	5, 7, 8, 10
	*	2, 5, 7, 8, 10	label-radius	2
	cgap	5	n	5
	dim-options	2	radius	2, 5, 8, 10
	dot-options	2	unit-cs	2
	draw-options	5, 7, 8, 10	unit-options	2
	fill-options	5, 7, 8, 10	units	2
	gap	5, 7, 8, 10	value-cs	5, 7, 8, 10
	height	6	vertical	8, 10
	label-cs	2, 5, 7, 8, 10	width	6
	label-options	2, 5, 7, 10		

Commands	identity	12	textbfp	12
	nop	12	textinv	12
	percent	12	tinytt	11
	redbf	12	value	2, 3, 5, 7, 9
	redbfp	12	whitebf	12
	tenrate	12	whitebfp	12
B	ballchart (environment)	5, 13	bubblechart (environment)	8, 13
	barchart (environment)	6, 13		
C	cgap (option)	5, 13		
D	dim-options (option)	2	dot-options (option)	2
	dims (environment)	2, 2-4	\draw	3
	docstrip (package)	2	draw-options (option)	5, 7, 8, 10, 13
F	fill-options (option)	5, 7, 8, 10, 13		
G	gap (option)	5, 7, 8, 10, 13		
H	h-sep (option)	13	height (option)	6
I	\identity	12		
K	kiviatchart (environment)	2, 2		
L	l3charts.sty (package)	11, 12	label-pos (option)	5, 7, 8, 10
	label-cs (option)	2, 5, 7, 8, 10, 11	label-radius (option)	2
	label-options (option)	2, 5, 7, 10		
M	microtype (package)	2, 13		
N	n (option)	5	\nop	12
P	\percent	12		
R	radialchart (environment)	10, 13	\redbf	12
	radius (option)	2, 5, 8, 10	\redbfp	12
S	set (environment)	2, 2-4		
T	\tenrate	12	tikzpicture (environment)	2, 5, 7, 8, 10
	\textbfp	12	\tinytt	11
	\textinv	3, 12		
U	unit-cs (option)	2	units (option)	2
	unit-options (option)	2		
V	v-sep (option)	13	value-cs (option)	5, 7, 8, 10, 11
	\value	2, 2, 3, 3, 4, 5, 5, 7, 7, 9, 9	vertical (option)	8, 10
W	\whitebf	12	width (option)	6
	\whitebfp	12		

9 Changes

0.5.1 (2022/07/19)

- remove hard coded % in value.

0.5.0 (2022/07/18)

- convert all $\langle fp \rangle$ to $\langle dim \rangle$ for usability
- rename **v-sep** and **h-sep** options of **ballchart** (*env*) to **gap** and **cgap** for consistency

0.4.0 (2022/07/17)

- add values to **bubblechart** (*env*)
- label positioning on **barchart** (*env*) and **ballchart** (*env*)
- swap **fill-options** and **draw-options** for **barchart** (*env*) for consistency

0.3.0 (2022/07/15)

- add a **radialchart** (*env*) to draw radials
- add a vertical mode to **bubblechart** (*env*) and allow positioning of the label
- swap **fill-options** and **draw-options** for **bubblechart** (*env*) for consistency

0.2.0 (2022/07/04)

- define a document class borrowed from **microtype**

0.1.0 (2022/07/01)

- Initial version