

13

Object-Oriented Programming: Polymorphism



*One Ring to rule them all, One Ring to find them,
One Ring to bring them all and in the darkness bind them.*

— John Ronald Reuel Tolkien

*The silence often of pure innocence
Persuades when speaking fails.*

— William Shakespeare

General propositions do not decide concrete cases.

— Oliver Wendell Holmes

*A philosopher of imposing stature doesn't think in a
vacuum. Even his most abstract ideas are, to some extent,
conditioned by what is or is not known in the time when he
lives.*

— Alfred North Whitehead



OBJECTIVES

In this chapter you will learn:

- What polymorphism is, how it makes programming more convenient, and how it makes systems more extensible and maintainable.
- To declare and use `virtual` functions to effect polymorphism.
- The distinction between abstract and concrete classes.
- To declare pure `virtual` functions to create abstract classes.
- How to use run-time type information (RTTI) with downcasting, `dynamic_cast`, `typeid` and `type_info`.
- How C++ implements `virtual` functions and dynamic binding "under the hood."
- How to use `virtual` destructors to ensure that all appropriate destructors run on an object.



- 13.1** Introduction
- 13.2** Polymorphism Examples
- 13.3** Relationships Among Objects in an Inheritance Hierarchy
 - 13.3.1** Invoking Base-Class Functions from Derived-Class Objects
 - 13.3.2** Aiming Derived-Class Pointers at Base-Class Objects
 - 13.3.3** Derived-Class Member-Function Calls via Base-Class Pointers
 - 13.3.4** Virtual Functions
 - 13.3.5** Summary of the Allowed Assignments Between Base-Class and Derived-Class Objects and Pointers
- 13.4** Type Fields and `switch` Statements
- 13.5** Abstract Classes and Pure `virtual` Functions



- 13.6 Case Study: Payroll System Using Polymorphism**
 - 13.6.1 Creating Abstract Base Class** `Employee`
 - 13.6.2 Creating Concrete Derived Class** `salariedEmployee`
 - 13.6.3 Creating Concrete Derived Class** `HourlyEmployee`
 - 13.6.4 Creating Concrete Derived Class** `CommissionEmployee`
 - 13.6.5 Creating Indirect Concrete Derived Class**
`BasePlusCommissionEmployee`
 - 13.6.6 Demonstrating Polymorphic Processing**
- 13.7 (Optional) Polymorphism, Virtual Functions and Dynamic Binding "Under the Hood"**
- 13.8 Case Study: Payroll System Using Polymorphism and Run-Time Type Information with Downcasting, `dynamic_cast`, `typeid` and `type_info`**
- 13.9 Virtual Destructors**
- 13.10 (Optional) Software Engineering Case Study: Incorporating Inheritance into the ATM System**
- 13.11 Wrap-Up**



13.1 Introduction

- **Polymorphism with inheritance hierarchies**
 - “Program in the general” vs. “program in the specific”
 - Process objects of classes that are part of the same hierarchy as if they are all objects of the base class
 - Each object performs the correct tasks for that object’s type
 - Different actions occur depending on the type of object
 - New classes can be added with little or not modification to existing code



13.1 Introduction (Cont.)

- **Example: Animal hierarchy**
 - **Animal** base class – every derived class has function **move**
 - Different animal objects maintained as a **vector** of **Animal** pointers
 - Program issues same message (**move**) to each animal generically
 - Proper function gets called
 - A **Fish** will move by swimming
 - A **Frog** will move by jumping
 - A **Bird** will move by flying



13.2 Polymorphism Examples

- **Polymorphism occurs when a program invokes a virtual function through a base-class pointer or reference**
 - C++ dynamically chooses the correct function for the class from which the object was instantiated
- **Example: SpaceObjects**
 - Video game manipulates objects of types that inherit from **SpaceObject**, which contains member function **draw**
 - Function **draw** implemented differently for the different classes
 - Screen-manager program maintains a container of **SpaceObject** pointers
 - Call **draw** on each object using **SpaceObject** pointers
 - **Proper draw function is called based on object's type**
 - A new class derived from **SpaceObject** can be added without affecting the screen manager



Software Engineering Observation 13.1

With virtual functions and polymorphism, you can deal in generalities and let the execution-time environment concern itself with the specifics. You can direct a variety of objects to behave in manners appropriate to those objects without even knowing their types (as long as those objects belong to the same inheritance hierarchy and are being accessed off a common base-class pointer).



Software Engineering Observation 13.2

Polymorphism promotes extensibility: Software written to invoke polymorphic behavior is written independently of the types of the objects to which messages are sent. Thus, new types of objects that can respond to existing messages can be incorporated into such a system without modifying the base system. Only client code that instantiates new objects must be modified to accommodate new types.



13.3 Relationships Among Objects in an Inheritance Hierarchy

- **Demonstration**

- Invoking base-class functions from derived-class objects
- Aiming derived-class pointers at base-class objects
- Derived-class member-function calls via base-class pointers
- Demonstrating polymorphism using virtual functions
 - Base-class pointers aimed at derived-class objects

- **Key concept**

- An object of a derived class can be treated as an object of its base class



13.3.1 Invoking Base-Class Functions from Derived-Class Objects

- **Aim base-class pointer at base-class object**
 - **Invoke base-class functionality**
- **Aim derived-class pointer at derived-class object**
 - **Invoke derived-class functionality**
- **Aim base-class pointer at derived-class object**
 - **Because derived-class object *is an* object of base class**
 - **Invoke base-class functionality**
 - **Invoked functionality depends on type of the handle used to invoke the function, not type of the object to which the handle points**
 - **virtual functions**
 - **Make it possible to invoke the object type's functionality, rather than invoke the handle type's functionality**
 - **Crucial to implementing polymorphic behavior**



Outline

Commission Employee.h

(1 of 2)

```
1 // Fig. 13.1: CommissionEmployee.h
2 // CommissionEmployee class definition represents a commission employee.
3 #ifndef COMMISSION_H
4 #define COMMISSION_H
5
6 #include <string> // C++ standard string class
7 using std::string;
8
9 class CommissionEmployee
10 {
11 public:
12     CommissionEmployee( const string &, const string &, const string &,
13         double = 0.0, double = 0.0 );
14
15     void setFirstName( const string & ); // set first name
16     string getFirstName() const; // return first name
17
18     void setLastName( const string & ); // set last name
19     string getLastName() const; // return last name
20
21     void setSocialSecurityNumber( const string & ); // set SSN
22     string getSocialSecurityNumber() const; // return SSN
23
24     void setGrossSales( double ); // set gross sales amount
25     double getGrossSales() const; // return gross sales amount
```



Outline

Function **earnings** will be redefined in derived classes to calculate the employee's earnings

Employee.h

(2 of 2)

Function **print** will be redefined in derived class to print the employee's information

```
26
27 void setCommissionRate( double ); // set commission rate
28 double getCommissionRate() const; // return commission rate
29
30 double earnings() const; // calculate earnings
31 void print() const; // print CommissionEmployee object
32 private:
33     string firstName;
34     string lastName;
35     string socialSecurityNumber;
36     double grossSales; // gross weekly sales
37     double commissionRate; // commission percentage
38 }; // end class CommissionEmployee
39
40 #endif
```



Outline

Commission Employee.cpp

(1 of 4)

```
1 // Fig. 13.2: CommissionEmployee.cpp
2 // Class CommissionEmployee member-function definitions.
3 #include <iostream>
4 using std::cout;
5
6 #include "CommissionEmployee.h" // CommissionEmployee class definition
7
8 // constructor
9 CommissionEmployee::CommissionEmployee(
10     const string &first, const string &last, const string &ssn,
11     double sales, double rate )
12     : firstName( first ), lastName( last ), socialSecurityNumber( ssn )
13 {
14     setGrossSales( sales ); // validate and store gross sales
15     setCommissionRate( rate ); // validate and store commission rate
16 } // end CommissionEmployee constructor
17
18 // set first name
19 void CommissionEmployee::setFirstName( const string &first )
20 {
21     firstName = first; // should validate
22 } // end function setFirstName
23
24 // return first name
25 string CommissionEmployee::getFirstName() const
26 {
27     return firstName;
28 } // end function getFirstName
```



Outline

Commission Employee.cpp

(2 of 4)

```
29 // set last name
30 void CommissionEmployee::setLastName( const string &last )
31 {
32     lastName = last; // should validate
33 } // end function setLastName
34
35 // return last name
36 string CommissionEmployee::getLastName() const
37 {
38     return lastName;
39 } // end function getLastName
40
41 // set social security number
42 void CommissionEmployee::setSocialSecurityNumber( const string &ssn )
43 {
44     socialSecurityNumber = ssn; // should validate
45 } // end function setSocialSecurityNumber
46
47 // return social security number
48 string CommissionEmployee::getSocialSecurityNumber() const
49 {
50     return socialSecurityNumber;
51 } // end function getSocialSecurityNumber
52
53 // set gross sales amount
54 void CommissionEmployee::setGrossSales( double sales )
55 {
56     grossSales = ( sales < 0.0 ) ? 0.0 : sales;
57 } // end function setGrossSales
```




Outline

Commission Employee.cpp

(3 of 4)

```
59
60 // return gross sales amount
61 double CommissionEmployee::getGrossSales() const
62 {
63     return grossSales;
64 } // end function getGrossSales
65
66 // set commission rate
67 void CommissionEmployee::setCommissionRate( double rate )
68 {
69     commissionRate = ( rate > 0.0 && rate < 1.0 ) ? rate : 0.0;
70 } // end function setCommissionRate
71
72 // return commission rate
73 double CommissionEmployee::getCommissionRate() const
74 {
75     return commissionRate;
76 } // end function getCommissionRate
77
78 // calculate earnings
79 double CommissionEmployee::earnings() const
80 {
81     return getCommissionRate() * getGrossSales();
82 } // end function earnings
```

Calculate earnings based on
commission rate and gross sales




Outline

Commission Employee.cpp

(4 of 4)

```
83
84 // print CommissionEmployee object
85 void CommissionEmployee::print() const
86 {
87     cout << "commission employee: "
88         << getFirstName() << ' ' << getLastName()
89         << "\nsocial security number: " << getSocialSecurityNumber()
90         << "\ngross sales: " << getGrossSales()
91         << "\ncommission rate: " << getCommissionRate();
92 } // end function print
```



Display name, social
security number, gross
sales and commission rate



Outline

BasePlus
Commission
Employee.h

(1 of 1)

```
1 // Fig. 13.3: BasePlusCommissionEmployee.h
2 // BasePlusCommissionEmployee class derived from class
3 // CommissionEmployee.
4 #ifndef BASEPLUS_H
5 #define BASEPLUS_H
6
7 #include <string> // C++ standard string class
8 using std::string;
9
10 #include "CommissionEmployee.h" // CommissionEmployee class declaration
11
12 class BasePlusCommissionEmployee : public CommissionEmployee
13 {
14 public:
15     BasePlusCommissionEmployee( const string &, const string &,
16         const string &, double = 0.0, double = 0.0, double = 0.0 );
17
18     void setBaseSalary( double ); // set base salary
19     double getBaseSalary() const; // return base salary
20
21     double earnings() const; // calculate earnings
22     void print() const; // print BasePlusCommissionEmployee object
23 private:
24     double baseSalary; // base salary
25 }; // end class BasePlusCommissionEmployee
26
27 #endif
```

Redefine functions
earnings and **print**



Outline

BasePlus Commission Employee.cpp

(1 of 2)

```
1 // Fig. 13.4: BasePlusCommissionEmployee.cpp
2 // Class BasePlusCommissionEmployee member-function definitions.
3 #include <iostream>
4 using std::cout;
5
6 // BasePlusCommissionEmployee class definition
7 #include "BasePlusCommissionEmployee.h"
8
9 // constructor
10 BasePlusCommissionEmployee::BasePlusCommissionEmployee(
11     const string &first, const string &last, const string &ssn,
12     double sales, double rate, double salary )
13     // explicitly call base-class constructor
14     : CommissionEmployee( first, last, ssn, sales, rate )
15 {
16     setBaseSalary( salary ); // validate and store base salary
17 } // end BasePlusCommissionEmployee constructor
18
19 // set base salary
20 void BasePlusCommissionEmployee::setBaseSalary( double salary )
21 {
22     baseSalary = ( salary < 0.0 ) ? 0.0 : salary;
23 } // end function setBaseSalary
24
25 // return base salary
26 double BasePlusCommissionEmployee::getBaseSalary() const
27 {
28     return baseSalary;
29 } // end function getBaseSalary
```



Outline

BasePlus
Commission
Employee.cpp

```
30
31 // calculate earnings
32 double BasePlusCommissionEmployee::earnings() const
33 {
34     return getBaseSalary() + CommissionEmployee::earnings();
35 } // end function earnings
36
37 // print BasePlusCommissionEmployee object
38 void BasePlusCommissionEmployee::print() const
39 {
40     cout << "base-salaried ";
41
42     // invoke CommissionEmployee's print function
43     CommissionEmployee::print();
44
45     cout << "\nbase salary: " << getBaseSalary();
46 } // end function print
```

Redefined earnings function
incorporates base salary

Redefined print function displays additional
BasePlusCommissionEmployee details



Outline

fig13_05.cpp

(1 of 5)

```
1 // Fig. 13.5: fig13_05.cpp
2 // Aiming base-class and derived-class pointers at base-class
3 // and derived-class objects, respectively.
4 #include <iostream>
5 using std::cout;
6 using std::endl;
7 using std::fixed;
8
9 #include <iomanip>
10 using std::setprecision;
11
12 // include class definitions
13 #include "CommissionEmployee.h"
14 #include "BasePlusCommissionEmployee.h"
15
16 int main()
17 {
18     // create base-class object
19     CommissionEmployee commissionEmployee(
20         "Sue", "Jones", "222-22-2222", 10000, .06 );
21
22     // create base-class pointer
23     CommissionEmployee *commissionEmployeePtr = 0;
```



Outline

fig13_05.cpp

(2 of 5)

```
24 // create derived-class object
25 BasePlusCommissionEmployee basePlusCommissionEmployee(
26     "Bob", "Lewis", "333-33-3333", 5000, .04, 300 );
27
28
29 // create derived-class pointer
30 BasePlusCommissionEmployee *basePlusCommissionEmployeePtr = 0;
31
32 // set floating-point output formatting
33 cout << fixed << setprecision( 2 );
34
35 // output objects commissionEmployee and basePlusCommissionEmployee
36 cout << "Print base-class and derived-class objects:\n\n";
37 commissionEmployee.print(); // invokes base-class print
38 cout << "\n\n";
39 basePlusCommissionEmployee.print(); // invokes derived-class print
40
41 // aim base-class pointer at base-class object and print
42 commissionEmployeePtr = &commissionEmployee; // perfectly natural
43 cout << "\n\nCalling print with base-class pointer to "
44     << "\nbase-class object invokes base-class print function:\n\n";
45 commissionEmployeePtr->print(); // invokes base-class print
```

Aiming base-class pointer at base-class object
and invoking base-class functionality



Outline

fig13_05.cpp

(3 of 5)

```
46 // aim derived-class pointer at derived-class object and print
47 basePlusCommissionEmployeePtr = &basePlusCommissionEmployee; // natural
48
49 cout << "\n\nCalling print with derived-class pointer to "
50      << "\nderived-class object invokes derived-class "
51      << "print function:\n\n";
52 basePlusCommissionEmployeePtr->print(); // invokes derived-class print
53
54 // aim base-class pointer at derived-class object and print
55 commissionEmployeePtr = &basePlusCommissionEmployee;
56 cout << "\n\nCalling print with base-class pointer to "
57      << "derived-class object\ninvokes base-class print "
58      << "function on that derived-class object:\n\n";
59 commissionEmployeePtr->print(); // invokes base-class print
60 cout << endl;
61 return 0;
62 } // end main
```

Aiming derived-class pointer at derived-class object and invoking derived-class functionality

Aiming base-class pointer at derived-class object and invoking base-class functionality



Print base-class and derived-class objects:

```
commission employee: Sue Jones  
social security number: 222-22-2222  
gross sales: 10000.00  
commission rate: 0.06
```

```
base-salaried commission employee: Bob Lewis  
social security number: 333-33-3333  
gross sales: 5000.00  
commission rate: 0.04  
base salary: 300.00
```

Calling print with base-class pointer to
base-class object invokes base-class print function:

```
commission employee: Sue Jones  
social security number: 222-22-2222  
gross sales: 10000.00  
commission rate: 0.06
```

(Continued at top of next slide...)



Outline

fig13_05.cpp

(5 of 5)

Calling print with derived-class pointer to
derived-class object invokes derived-class print function:

```
base-salaried commission employee: Bob Lewis  
social security number: 333-33-3333  
gross sales: 5000.00  
commission rate: 0.04  
base salary: 300.00
```

Calling print with base-class pointer to derived-class object
invokes base-class print function on that derived-class object:

```
commission employee: Bob Lewis  
social security number: 333-33-3333  
gross sales: 5000.00  
commission rate: 0.04
```



13.3.2 Aiming Derived-Class Pointers at Base-Class Objects

- **Aim a derived-class pointer at a base-class object**
 - **C++ compiler generates error**
 - **CommissionEmployee (base-class object) is not a BasePlusCommissionEmployee (derived-class object)**
 - **If this were to be allowed, programmer could then attempt to access derived-class members which do not exist**
 - **Could modify memory being used for other data**



Outline

fig13_06.cpp

(1 of 2)

```
1 // Fig. 13.6: fig13_06.cpp
2 // Aiming a derived-class pointer at a base-class object.
3 #include "CommissionEmployee.h"
4 #include "BasePlusCommissionEmployee.h"
5
6 int main()
7 {
8     CommissionEmployee commissionEmployee(
9         "Sue", "Jones", "222-22-2222", 10000, .06 );
10    BasePlusCommissionEmployee *basePlusCommissionEmployeePtr = 0;
11
12    // aim derived-class pointer at base-class object
13    // Error: a CommissionEmployee is not a BasePlusCommissionEmployee
14    basePlusCommissionEmployeePtr = &commissionEmployee;
15    return 0;
16 } // end main
```

Cannot assign base-class object to derived-class pointer because *is-a* relationship does not apply



Outline

fig13_06.cpp

(2 of 2)

Borland C++ command-line compiler error messages:

```
Error E2034 Fig13_06\fig13_06.cpp 14: Cannot convert 'CommissionEmployee *'  
to 'BasePlusCommissionEmployee *' in function main()
```

GNU C++ compiler error messages:

```
fig13_06.cpp:14: error: invalid conversion from `CommissionEmployee*' to  
`BasePlusCommissionEmployee*'
```

Microsoft Visual C++.NET compiler error messages:

```
C:\cpphttp5_examples\ch13\Fig13_06\fig13_06.cpp(14) : error C2440:  
'=' : cannot convert from 'CommissionEmployee *__w64 ' to  
'BasePlusCommissionEmployee *'  
Cast from base to derived requires dynamic_cast or static_cast
```



13.3.3 Derived-Class Member-Function Calls via Base-Class Pointers

- **Aiming base-class pointer at derived-class object**
 - Calling functions that exist in base class causes base-class functionality to be invoked
 - Calling functions that do not exist in base class (may exist in derived class) will result in error
 - Derived-class members cannot be accessed from base-class pointers
 - However, they can be accomplished using downcasting (Section 13.8)



Outline

fig13_07.cpp

(1 of 2)

```
1 // Fig. 13.7: fig13_07.cpp
2 // Attempting to invoke derived-class-only member functions
3 // through a base-class pointer.
4 #include "CommissionEmployee.h"
5 #include "BasePlusCommissionEmployee.h"
6
7 int main()
8 {
9     CommissionEmployee *commissionEmployeePtr = 0; // base class
10    BasePlusCommissionEmployee basePlusCommissionEmployee(
11        "Bob", "Lewis", "333-33-3333", 5000, .04, 300 ); // derived class
12
13    // aim base-class pointer at derived-class object
14    commissionEmployeePtr = &basePlusCommissionEmployee;
15
16    // invoke base-class member functions on derived-class
17    // object through base-class pointer
18    string firstName = commissionEmployeePtr->getFirstName();
19    string lastName = commissionEmployeePtr->getLastName();
20    string ssn = commissionEmployeePtr->getSocialSecurityNumber();
21    double grossSales = commissionEmployeePtr->getGrossSales();
22    double commissionRate = commissionEmployeePtr->getCommissionRate();
23
24    // attempt to invoke derived-class-only member functions
25    // on derived-class object through base-class pointer
26    double baseSalary = commissionEmployeePtr->getBaseSalary();
27    commissionEmployeePtr->setBaseSalary( 500 );
28    return 0;
29 } // end main
```

Cannot invoke derived-class-only members from base-class pointer



Outline

fig13_07.cpp

(2 of 2)

Borland C++ command-line compiler error messages:

```
Error E2316 Fig13_07\fig13_07.cpp 26: 'getBaseSalary' is not a member of
'CommissionEmployee' in function main()
Error E2316 Fig13_07\fig13_07.cpp 27: 'setBaseSalary' is not a member of
'CommissionEmployee' in function main()
```

Microsoft Visual C++.NET compiler error messages:

```
C:\cpphttp5_examples\ch13\Fig13_07\fig13_07.cpp(26) : error C2039:
'getBaseSalary' : is not a member of 'CommissionEmployee'
    C:\cpphttp5_examples\ch13\Fig13_07\CommissionEmployee.h(10) :
    see declaration of 'CommissionEmployee'
C:\cpphttp5_examples\ch13\Fig13_07\fig13_07.cpp(27) : error C2039:
'setBaseSalary' : is not a member of 'CommissionEmployee'
    C:\cpphttp5_examples\ch13\Fig13_07\CommissionEmployee.h(10) :
    see declaration of 'CommissionEmployee'
```

GNU C++ compiler error messages:

```
fig13_07.cpp:26: error: `getBaseSalary' undeclared (first use this function)
fig13_07.cpp:26: error: (Each undeclared identifier is reported only once for
each function it appears in.)
fig13_07.cpp:27: error: `setBaseSalary' undeclared (first use this function)
```



Software Engineering Observation 13.3

If the address of a derived-class object has been assigned to a pointer of one of its direct or indirect base classes, it is acceptable to cast that base-class pointer back to a pointer of the derived-class type. In fact, this must be done to send that derived-class object messages that do not appear in the base class.



13.3.4 Virtual Functions

- **Which class's function to invoke**
 - Normally
 - Handle determines which class's functionality to invoke
 - With `virtual` functions
 - Type of the object being pointed to, not type of the handle, determines which version of a `virtual` function to invoke
 - Allows program to dynamically (at runtime rather than compile time) determine which function to use
 - Called dynamic binding or late binding



13.3.4 Virtual Functions (Cont.)

- **virtual functions**

- Declared by preceding the function's prototype with the keyword **virtual** in base class
- Derived classes override function as appropriate
- Once declared **virtual**, a function remains **virtual** all the way down the hierarchy
- Static binding
 - When calling a **virtual** function using specific object with dot operator, function invocation resolved at compile time
- Dynamic binding
 - **Dynamic binding occurs only off pointer and reference handles**



Software Engineering Observation 13.4

Once a function is declared `virtual`, it remains `virtual` all the way down the inheritance hierarchy from that point, even if that function is not explicitly declared `virtual` when a class overrides it.



Good Programming Practice 13.1

Even though certain functions are implicitly `virtual` because of a declaration made higher in the class hierarchy, explicitly declare these functions `virtual` at every level of the hierarchy to promote program clarity.



Error-Prevention Tip 13.1

When a programmer browses a class hierarchy to locate a class to reuse, it is possible that a function in that class will exhibit `virtual` function behavior even though it is not explicitly declared `virtual`. This happens when the class inherits a `virtual` function from its base class, and it can lead to subtle logic errors. Such errors can be avoided by explicitly declaring all `virtual` functions `virtual` throughout the inheritance hierarchy.



Software Engineering Observation 13.5

When a derived class chooses not to override a `virtual` function from its base class, the derived class simply inherits its base class's `virtual` function implementation.



Outline

Commission Employee.h

(1 of 2)

```
1 // Fig. 13.8: CommissionEmployee.h
2 // CommissionEmployee class definition represents a commission employee.
3 #ifndef COMMISSION_H
4 #define COMMISSION_H
5
6 #include <string> // C++ standard string class
7 using std::string;
8
9 class CommissionEmployee
10 {
11 public:
12     CommissionEmployee( const string &, const string &, const string &,
13         double = 0.0, double = 0.0 );
14
15     void setFirstName( const string & ); // set first name
16     string getFirstName() const; // return first name
17
18     void setLastName( const string & ); // set last name
19     string getLastName() const; // return last name
20
21     void setSocialSecurityNumber( const string & ); // set SSN
22     string getSocialSecurityNumber() const; // return SSN
23
24     void setGrossSales( double ); // set gross sales amount
25     double getGrossSales() const; // return gross sales amount
```



Outline

Commission
Employee.h

```
26
27 void setCommissionRate( double ); // set commission rate
28 double getCommissionRate() const; // return commission rate
29
30 virtual double earnings() const; // calculate earnings
31 virtual void print() const; // print CommissionEmployee object
32 private:
33     string firstName;
34     string lastName;
35     string socialSecurityNumber;
36     double grossSales; // gross weekly sales
37     double commissionRate; // commission percentage
38 }; // end class CommissionEmployee
39
40 #endif
```

Declaring **earnings** and **print** as **virtual** allows them to be overridden, not redefined



Outline

BasePlus
Commission
Employee.h

(1 of 1)

```

1 // Fig. 13.9: BasePlusCommissionEmployee.h
2 // BasePlusCommissionEmployee class derived from class
3 // CommissionEmployee.
4 #ifndef BASEPLUS_H
5 #define BASEPLUS_H
6
7 #include <string> // C++ standard string class
8 using std::string;
9
10 #include "CommissionEmployee.h" // CommissionEmployee class declaration
11
12 class BasePlusCommissionEmployee : public CommissionEmployee
13 {
14 public:
15     BasePlusCommissionEmployee( const string &, const string &,
16         const string &, double = 0.0, double = 0.0, double = 0.0 );
17
18     void setBaseSalary( double ); // set base salary
19     double getBaseSalary() const; // return base salary
20
21     virtual double earnings() const; // calculate earnings
22     virtual void print() const; // print BasePlusCommissionEmployee object
23 private:
24     double baseSalary; // base salary
25 }; // end class BasePlusCommissionEmployee
26
27 #endif

```

Functions **earnings** and **print** are already **virtual** – good practice to declare **virtual** even when overriding function



Outline

fig13_10.cpp

(1 of 5)

```
1 // Fig. 13.10: fig13_10.cpp
2 // Introducing polymorphism, virtual functions and dynamic binding.
3 #include <iostream>
4 using std::cout;
5 using std::endl;
6 using std::fixed;
7
8 #include <iomanip>
9 using std::setprecision;
10
11 // include class definitions
12 #include "CommissionEmployee.h"
13 #include "BasePlusCommissionEmployee.h"
14
15 int main()
16 {
17     // create base-class object
18     CommissionEmployee commissionEmployee(
19         "Sue", "Jones", "222-22-2222", 10000, .06 );
20
21     // create base-class pointer
22     CommissionEmployee *commissionEmployeePtr = 0;
23
24     // create derived-class object
25     BasePlusCommissionEmployee basePlusCommissionEmployee(
26         "Bob", "Lewis", "333-33-3333", 5000, .04, 300 );
27
28     // create derived-class pointer
29     BasePlusCommissionEmployee *basePlusCommissionEmployeePtr = 0;
```



Outline

fig13_10.cpp

(2 of 5)

```
30 // set floating-point output formatting
31 cout << fixed << setprecision( 2 );
32
33
34 // output objects using static binding
35 cout << "Invoking print function on base-class and derived-class "
36     << "\nobjects with static binding\n\n";
37 commissionEmployee.print(); // static binding
38 cout << "\n\n";
39 basePlusCommissionEmployee.print(); // static binding
40
41 // output objects using dynamic binding
42 cout << "\n\n\nInvoking print function on base-class and "
43     << "derived-class \nobjects with dynamic binding";
44
45 // aim base-class pointer at base-class object and print
46 commissionEmployeePtr = &commissionEmployee;
47 cout << "\n\nCalling virtual function print with base-class pointer"
48     << "\nto base-class object invokes base-class "
49     << "print function:\n\n";
50 commissionEmployeePtr->print(); // invokes base-class print
```

Aiming base-class pointer at
base-class object and invoking
base-class functionality



Outline

fig13_10.cpp

(3 of 5)

```
51 // aim derived-class pointer at derived-class object and print
52 basePlusCommissionEmployeePtr = &basePlusCommissionEmployee;
53 cout << "\n\nCalling virtual function print with derived-class "
54     << "pointer\nto derived-class object invokes derived-class "
55     << "print function:\n\n";
56 basePlusCommissionEmployeePtr->print(); // invokes derived-class print
57
58 // aim base-class pointer at derived-class object and print
59 commissionEmployeePtr = &basePlusCommissionEmployee;
60 cout << "\n\nCalling virtual function print with base-class poi
61     << "\nto derived-class object invokes derived-class "
62     << "print function:\n\n";
63
64 // polymorphism; invokes BasePlusCommissionEmployee's print;
65 // base-class pointer to derived-class object
66 commissionEmployeePtr->print();
67 cout << endl;
68 return 0;
69 } // end main
```

Aiming derived-class pointer at derived-class object and invoking derived-class functionality

Aiming base-class pointer at derived-class object and invoking derived-class functionality via polymorphism and **virtual** functions



Invoking print function on base-class and derived-class
objects with static binding

```
commission employee: Sue Jones  
social security number: 222-22-2222  
gross sales: 10000.00  
commission rate: 0.06
```

```
base-salaried commission employee: Bob Lewis  
social security number: 333-33-3333  
gross sales: 5000.00  
commission rate: 0.04  
base salary: 300.00
```

Invoking print function on base-class and derived-class
objects with dynamic binding

Calling virtual function print with base-class pointer
to base-class object invokes base-class print function:

```
commission employee: Sue Jones  
social security number: 222-22-2222  
gross sales: 10000.00  
commission rate: 0.06
```

Calling virtual function print with derived-class pointer
to derived-class object invokes derived-class print function:

(Continued at the top of next slide ...)



(...Continued from the bottom of previous slide)

Outline

fig13_10.cpp

(5 of 5)

base-salaried commission employee: Bob Lewis
social security number: 333-33-3333
gross sales: 5000.00
commission rate: 0.04
base salary: 300.00

Calling virtual function print with base-class pointer
to derived-class object invokes derived-class print function:

base-salaried commission employee: Bob Lewis
social security number: 333-33-3333
gross sales: 5000.00
commission rate: 0.04
base salary: 300.00



13.3.5 Summary of the Allowed Assignments Between Base-Class and Derived-Class Objects and Pointers

- **Four ways to aim base-class and derived-class pointers at base-class and derived-class objects**
 - **Aiming a base-class pointer at a base-class object**
 - Is straightforward
 - **Aiming a derived-class pointer at a derived-class object**
 - Is straightforward
 - **Aiming a base-class pointer at a derived-class object**
 - Is safe, but can be used to invoke only member functions that base-class declares (unless downcasting is used)
 - Can achieve polymorphism with virtual functions
 - **Aiming a derived-class pointer at a base-class object**
 - Generates a compilation error



Common Programming Error 13.1

After aiming a base-class pointer at a derived-class object, attempting to reference derived-class-only members with the base-class pointer is a compilation error.



Common Programming Error 13.2

Treating a base-class object as a derived-class object can cause errors.



13.4 Type Fields and switch Statements

- **switch statement could be used to determine the type of an object at runtime**
 - Include a type field as a data member in the base class
 - Enables programmer to invoke appropriate action for a particular object
 - Causes problems
 - A type test may be forgotten
 - May forget to add new types



Software Engineering Observation 13.6

Polymorphic programming can eliminate the need for unnecessary `switch` logic. By using the C++ polymorphism mechanism to perform the equivalent logic, programmers can avoid the kinds of errors typically associated with `switch` logic.



Software Engineering Observation 13.7

An interesting consequence of using polymorphism is that programs take on a simplified appearance. They contain less branching logic and more simple, sequential code. This simplification facilitates testing, debugging and program maintenance.



13.5 Abstract Classes and Pure virtual Functions

- **Abstract classes**

- **Classes from which the programmer never intends to instantiate any objects**
 - **Incomplete—derived classes must define the “missing pieces”**
 - **Too generic to define real objects**
- **Normally used as base classes, called abstract base classes**
 - **Provides an appropriate base class from which other classes can inherit**
 - **Classes used to instantiate objects are called concrete classes**
 - **Must provide implementation for every member function they define**



13.5 Abstract Classes and Pure virtual Functions (Cont.)

- Pure virtual function

- A class is made abstract by declaring one or more of its virtual functions to be “pure”
 - Placing “= 0” in its declaration
 - Example
 - `virtual void draw() const = 0;`
 - “= 0” is known as a pure specifier
- Do not provide implementations
 - Every concrete derived class must override all base-class pure virtual functions with concrete implementations
 - If not overridden, derived-class will also be abstract
- Used when it does not make sense for base class to have an implementation of a function, but the programmer wants all concrete derived classes to implement the function



Software Engineering Observation 13.8

An abstract class defines a common public interface for the various classes in a class hierarchy. An abstract class contains one or more pure `virtual` functions that concrete derived classes must override.



Common Programming Error 13.3

Attempting to instantiate an object of an abstract class causes a compilation error.



Common Programming Error 13.4

Failure to override a pure virtual function in a derived class, then attempting to instantiate objects of that class, is a compilation error.



Software Engineering Observation 13.9

An abstract class has at least one pure virtual function. An abstract class also can have data members and concrete functions (including constructors and destructors), which are subject to the normal rules of inheritance by derived classes.



13.5 Abstract Classes and Pure virtual Functions (Cont.)

- **We can use the abstract base class to declare pointers and references**
 - **Can refer to objects of any concrete class derived from the abstract class**
 - **Programs typically use such pointers and references to manipulate derived-class objects polymorphically**
- **Polymorphism particularly effective for implementing layered software systems**
 - **Reading or writing data from and to devices**
- **Iterator class**
 - **Can traverse all the objects in a container**



13.6 Case Study: Payroll System Using Polymorphism

- **Enhanced CommissionEmployee-BasePlusCommissionEmployee hierarchy using an abstract base class**
 - **Abstract class Employee represents the general concept of an employee**
 - **Declares the “interface” to the hierarchy**
 - **Each employee has a first name, last name and social security number**
 - **Earnings calculated differently and objects printed differently for each derived classe**



Software Engineering Observation 13.10

A derived class can inherit interface or implementation from a base class. Hierarchies designed for **implementation inheritance tend to have their functionality high in the hierarchy—each new derived class inherits one or more member functions that were defined in a base class, and the derived class uses the base-class definitions. Hierarchies designed for **interface inheritance** tend to have their functionality lower in the hierarchy—a base class specifies one or more functions that should be defined for each class in the hierarchy (i.e., they have the same prototype), but the individual derived classes provide their own implementations of the function(s).**






Fig.13.11 | Employee hierarchy UML class diagram.

13.6.1 Creating Abstract Base Class Employee

- **Class Employee**

- Provides various *get* and *set* functions
- Provides functions **earnings** and **print**
 - **Function earnings depends on type of employee, so declared pure virtual**
 - Not enough information in class **Employee** for a default implementation
 - **Function print is virtual, but not pure virtual**
 - Default implementation provided in **Employee**
- **Example maintains a vector of Employee pointers**
 - **Polymorphically invokes proper earnings and print functions**



	earnings	print
Employee	= 0	<i>firstName lastName</i> social security number: <i>SSN</i>
Salaried- Employee	weeklySalary	salaried employee: <i>firstName lastName</i> social security number: <i>SSN</i> weekly salary: <i>weeklySalary</i>
Hourly- Employee	If <i>hours</i> <= 40 <i>wage</i> * <i>hours</i> If <i>hours</i> > 40 (40 * <i>wage</i>) + ((<i>hours</i> - 40) * <i>wage</i> * 1.5)	hourly employee: <i>firstName lastName</i> social security number: <i>SSN</i> hourly wage: <i>wage</i> ; hours worked: <i>hours</i>
Commission- Employee	<i>commissionRate</i> * <i>grossSales</i>	commission employee: <i>firstName lastName</i> social security number: <i>SSN</i> gross sales: <i>grossSales</i> ; commission rate: <i>commissionRate</i>
BasePlus- Commission- Employee	<i>baseSalary</i> + (<i>commissionRate</i> * <i>grossSales</i>)	base salaried commission employee: <i>firstName lastName</i> social security number: <i>SSN</i> gross sales: <i>grossSales</i> ; commission rate: <i>commissionRate</i> ; base salary: <i>baseSalary</i>




Fig.13.12 | Polymorphic interface for the Employee hierarchy classes.

Outline

Employee.h

(1 of 2)

```
1 // Fig. 13.13: Employee.h
2 // Employee abstract base class.
3 #ifndef EMPLOYEE_H
4 #define EMPLOYEE_H
5
6 #include <string> // C++ standard string class
7 using std::string;
8
9 class Employee
10 {
11 public:
12     Employee( const string &, const string &, const string & );
13
14     void setFirstName( const string & ); // set first name
15     string getFirstName() const; // return first name
16
17     void setLastName( const string & ); // set last name
18     string getLastName() const; // return last name
19
20     void setSocialSecurityNumber( const string & ); // set SSN
21     string getSocialSecurityNumber() const; // return SSN
```



Outline

```
22 // pure virtual function makes Employee abstract base class
23 virtual double earnings() const = 0; // pure virtual
24 virtual void print() const; // virtual
25
26 private:
27     string firstName;
28     string lastName;
29     string socialSecurityNumber;
30 }; // end class Employee
31
32 #endif // EMPLOYEE_H
```

Function **earnings** is pure **virtual**, not enough data to provide a default, concrete implementation

(2 of 2)

Function **print** is **virtual**, default implementation provided but derived-classes may override



Outline

Employee.cpp

(1 of 2)

```
1 // Fig. 13.14: Employee.cpp
2 // Abstract-base-class Employee member-function definitions.
3 // Note: No definitions are given for pure virtual functions.
4 #include <iostream>
5 using std::cout;
6
7 #include "Employee.h" // Employee class definition
8
9 // constructor
10 Employee::Employee( const string &first, const string &last,
11     const string &ssn )
12     : firstName( first ), lastName( last ), socialSecurityNumber( ssn )
13 {
14     // empty body
15 } // end Employee constructor
16
17 // set first name
18 void Employee::setFirstName( const string &first )
19 {
20     firstName = first;
21 } // end function setFirstName
22
23 // return first name
24 string Employee::getFirstName() const
25 {
26     return firstName;
27 } // end function getFirstName
28
```



Outline

Employee.cpp

(2 of 2)

```
29 // set last name
30 void Employee::setLastName( const string &last )
31 {
32     lastName = last;
33 } // end function setLastName
34
35 // return last name
36 string Employee::getLastName() const
37 {
38     return lastName;
39 } // end function getLastName
40
41 // set social security number
42 void Employee::setSocialSecurityNumber( const string &ssn )
43 {
44     socialSecurityNumber = ssn; // should validate
45 } // end function setSocialSecurityNumber
46
47 // return social security number
48 string Employee::getSocialSecurityNumber() const
49 {
50     return socialSecurityNumber;
51 } // end function getSocialSecurityNumber
52
53 // print Employee's information (virtual, but not pure virtual)
54 void Employee::print() const
55 {
56     cout << getFirstName() << ' ' << getLastName()
57         << "\nsocial security number: " << getSocialSecurityNumber();
58 } // end function print
```



13.6.2 Creating Concrete Derived Class `SalariedEmployee`

- **`SalariedEmployee` inherits from `Employee`**
 - Includes a weekly salary
 - Overridden `earnings` function incorporates weekly salary
 - Overridden `print` function incorporates weekly salary
 - Is a concrete class (implements all pure `virtual` functions in abstract base class)



Outline

Salaried Employee.h

```
1 // Fig. 13.15: SalariedEmployee.h
2 // SalariedEmployee class derived from Employee.
3 #ifndef SALARIED_H
4 #define SALARIED_H
5
6 #include "Employee.h" // Employee class definition
7
8 class SalariedEmployee : public Employee
9 {
10 public:
11     SalariedEmployee( const string &, const string &,
12                     const string &, double = 0.0 );
13
14     void setWeeklySalary( double ); // set weekly salary
15     double getWeeklySalary() const; // return weekly salary
16
17     // keyword virtual signals intent to override
18     virtual double earnings() const; // calculate earnings
19     virtual void print() const; // print SalariedEmployee object
20 private:
21     double weeklySalary; // salary per week
22 }; // end class SalariedEmployee
23
24 #endif // SALARIED_H
```

SalariedEmployee inherits from **Employee**,
must override **earnings** to be concrete

Functions will be overridden
(or defined for the first time)



Outline

Salaried Employee.cpp

(1 of 2)

```
1 // Fig. 13.16: SalariedEmployee.cpp
2 // SalariedEmployee class member-function definitions.
3 #include <iostream>
4 using std::cout;
5
6 #include "SalariedEmployee.h" // SalariedEmployee class definition
7
8 // constructor
9 SalariedEmployee::SalariedEmployee( const string &first,
10     const string &last, const string &ssn, double salary )
11     : Employee( first, last, ssn )
12 {
13     setWeeklySalary( salary );
14 } // end SalariedEmployee constructor
15
16 // set salary
17 void SalariedEmployee::setWeeklySalary( double salary )
18 {
19     weeklySalary = ( salary < 0.0 ) ? 0.0 : salary;
20 } // end function setWeeklySalary
21
22 // return salary
23 double SalariedEmployee::getWeeklySalary() const
24 {
25     return weeklySalary;
26 } // end function getWeeklySalary
```

Maintain new data member
weeklySalary



Outline

Salaried
Employee.cpp

(1 of 2)

```
27
28 // calculate earnings;
29 // override pure virtual function earnings in Employee
30 double SalariedEmployee::earnings() const
31 {
32     return getWeeklySalary();
33 } // end function earnings
34
35 // print SalariedEmployee's information
36 void SalariedEmployee::print() const
37 {
38     cout << "salaried employee: ";
39     Employee::print(); // reuse abstract base-class print function
40     cout << "\nweekly salary: " << getWeeklySalary();
41 } // end function print
```

Overridden earnings and print
functions incorporate weekly salary



13.6.3 Creating Concrete Derived Class `HourlyEmployee`

- **`HourlyEmployee` inherits from `Employee`**
 - Includes a wage and hours worked
 - Overridden `earnings` function incorporates the employee's wages multiplied by hours (taking time-and-a-half pay into account)
 - Overridden `print` function incorporates wage and hours worked
 - Is a concrete class (implements all pure virtual functions in abstract base class)



Outline

Hourly Employee.h

```

1 // Fig. 13.17: HourlyEmployee.h
2 // HourlyEmployee class definition.
3 #ifndef HOURLY_H
4 #define HOURLY_H
5
6 #include "Employee.h" // Employee class definition
7
8 class HourlyEmployee : public Employee
9 {
10 public:
11     HourlyEmployee( const string &, const string &,
12                    const string &, double = 0.0, double = 0.0 );
13
14     void setWage( double ); // set hourly wage
15     double getWage() const; // return hourly wage
16
17     void setHours( double ); // set hours worked
18     double getHours() const; // return hours worked
19
20     // keyword virtual signals intent to override
21     virtual double earnings() const; // calculate earnings
22     virtual void print() const; // print HourlyEmployee object
23 private:
24     double wage; // wage per hour
25     double hours; // hours worked for week
26 }; // end class HourlyEmployee
27
28 #endif // HOURLY_H

```

HourlyEmployee inherits from Employee,
must override **earnings** to be concrete

1 2 3 4 5
6
override

Functions will be overridden
(or defined for first time)



Outline

Hourly Employee.cpp

(1 of 2)

```
1 // Fig. 13.18: HourlyEmployee.cpp
2 // HourlyEmployee class member-function definitions.
3 #include <iostream>
4 using std::cout;
5
6 #include "HourlyEmployee.h" // HourlyEmployee class definition
7
8 // constructor
9 HourlyEmployee::HourlyEmployee( const string &first, const string &last,
10     const string &ssn, double hourlywage, double hoursworked )
11     : Employee( first, last, ssn )
12 {
13     setWage( hourlywage ); // validate hourly wage
14     setHours( hoursworked ); // validate hours worked
15 } // end HourlyEmployee constructor
16
17 // set wage
18 void HourlyEmployee::setWage( double hourlywage )
19 {
20     wage = ( hourlywage < 0.0 ? 0.0 : hourlywage );
21 } // end function setWage
22
23 // return wage
24 double HourlyEmployee::getWage() const
25 {
26     return wage;
27 } // end function getWage
```

Maintain new data member, **hourlyWage**



Outline

```

28 // set hours worked
29 void HourlyEmployee::setHours( double hoursworked )
30 {
31     hours = ( ( ( hoursworked >= 0.0 ) && ( hoursworked <= 168.0 ) ) ?
32         hoursworked : 0.0 );
33 } // end function setHours
34
35 // return hours worked
36 double HourlyEmployee::getHours() const
37 {
38     return hours;
39 } // end function getHours
40
41 // calculate earnings;
42 // override pure virtual function earnings in Employee
43 double HourlyEmployee::earnings() const
44 {
45     if ( getHours() <= 40 ) // no overtime
46         return getWage() * getHours();
47     else
48         return 40 * getWage() + ( ( getHours() - 40 ) * getWage() * 1.5 );
49 } // end function earnings
50
51 // print HourlyEmployee's information
52 void HourlyEmployee::print() const
53 {
54     cout << "hourly employee: ";
55     Employee::print(); // code reuse
56     cout << "\nhourly wage: " << getWage() <<
57         "; hours worked: " << getHours();
58 } // end function print

```

Maintain new data member,
hoursWorked

(2 of 2)

Overridden **earnings** and
print functions
incorporate wage and hours



13.6.4 Creating Concrete Derived Class `CommissionEmployee`

- **`CommissionEmployee` inherits from `Employee`**
 - Includes gross sales and commission rate
 - Overridden `earnings` function incorporates gross sales and commission rate
 - Overridden `print` function incorporates gross sales and commission rate
 - Concrete class (implements all pure `virtual` functions in abstract base class)



Outline

Commission Employee.h

```

1 // Fig. 13.19: CommissionEmployee.h
2 // CommissionEmployee class derived from Employee.
3 #ifndef COMMISSION_H
4 #define COMMISSION_H
5
6 #include "Employee.h" // Employee class definition
7
8 class CommissionEmployee : public Employee
9 {
10 public:
11     CommissionEmployee( const string &, const string &,
12                        const string &, double = 0.0, double = 0.0 );
13
14     void setCommissionRate( double ); // set commission rate
15     double getCommissionRate() const; // return commission rate
16
17     void setGrossSales( double ); // set gross sales amount
18     double getGrossSales() const; // return gross sales amount
19
20     // keyword virtual signals intent to override
21     virtual double earnings() const; // calculate earnings
22     virtual void print() const; // print CommissionEmployee object
23 private:
24     double grossSales; // gross weekly sales
25     double commissionRate; // commission percentage
26 }; // end class CommissionEmployee
27
28 #endif // COMMISSION_H

```

CommissionEmployee inherits from **Employee**, must override **earnings** to be concrete

Functions will be overridden (or defined for first time)



Outline

Commission Employee.cpp

(1 of 2)

```
1 // Fig. 13.20: CommissionEmployee.cpp
2 // CommissionEmployee class member-function definitions.
3 #include <iostream>
4 using std::cout;
5
6 #include "CommissionEmployee.h" // CommissionEmployee class definition
7
8 // constructor
9 CommissionEmployee::CommissionEmployee( const string &first,
10     const string &last, const string &ssn, double sales, double rate )
11     : Employee( first, last, ssn )
12 {
13     setGrossSales( sales );
14     setCommissionRate( rate );
15 } // end CommissionEmployee constructor
16
17 // set commission rate
18 void CommissionEmployee::setCommissionRate( double rate )
19 {
20     commissionRate = ( ( rate > 0.0 && rate < 1.0 ) ? rate : 0.0 );
21 } // end function setCommissionRate
22
23 // return commission rate
24 double CommissionEmployee::getCommissionRate() const
25 {
26     return commissionRate;
27 } // end function getCommissionRate
```

Maintain new data member,
commissionRate



Outline

```

28 // set gross sales amount
29 void CommissionEmployee::setGrossSales( double sales )
30 {
31     grossSales = ( ( sales < 0.0 ) ? 0.0 : sales );
32 } // end function setGrossSales
33
34 // return gross sales amount
35 double CommissionEmployee::getGrossSales() const
36 {
37     return grossSales;
38 } // end function getGrossSales
39
40 // calculate earnings;
41 // override pure virtual function earnings in Employee
42 double CommissionEmployee::earnings() const
43 {
44     return getCommissionRate() * getGrossSales();
45 } // end function earnings
46
47 // print CommissionEmployee's information
48 void CommissionEmployee::print() const
49 {
50     cout << "commission employee: ";
51     Employee::print(); // code reuse
52     cout << "\ngross sales: " << getGrossSales()
53         << "; commission rate: " << getCommissionRate();
54 } // end function print

```

Maintain new data member, **grossSales**

(2 of 2)

Overridden **earnings** and **print** functions incorporate commission rate and gross sales



13.6.5 Creating Indirect Concrete Derived Class `BasePlusCommissionEmployee`

- **`BasePlusCommissionEmployee` inherits from `CommissionEmployee`**
 - Includes base salary
 - Overridden `earnings` function that incorporates base salary
 - Overridden `print` function that incorporates base salary
 - Concrete class, because derived class is concrete
 - Not necessary to override `earnings` to make it concrete, can inherit implementation from `CommissionEmployee`
 - Although we do override `earnings` to incorporate base salary



Outline

BasePlus
Commission
Employee.h

```

1 // Fig. 13.21: BasePlusCommissionEmployee.h
2 // BasePlusCommissionEmployee class derived from Employee.
3 #ifndef BASEPLUS_H
4 #define BASEPLUS_H
5
6 #include "CommissionEmployee.h" // CommissionEmployee class definition
7
8 class BasePlusCommissionEmployee : public CommissionEmployee
9 {
10 public:
11     BasePlusCommissionEmployee( const string &, const string &,
12         const string &, double = 0.0, double = 0.0, double = 0.0 );
13
14     void setBaseSalary( double ); // set base salary
15     double getBaseSalary() const; // return base salary
16
17     // keyword virtual signals intent to override
18     virtual double earnings() const; // calculate earnings
19     virtual void print() const; // print BasePlusCommissionEmployee object
20 private:
21     double baseSalary; // base salary per week
22 }; // end class BasePlusCommissionEmployee
23
24 #endif // BASEPLUS_H

```

BasePlusCommissionEmployee inherits
from CommissionEmployee, already concrete

Functions will be overridden



Outline

BasePlus Commission Employee.cpp

(1 of 2)

```
1 // Fig. 13.22: BasePlusCommissionEmployee.cpp
2 // BasePlusCommissionEmployee member-function definitions.
3 #include <iostream>
4 using std::cout;
5
6 // BasePlusCommissionEmployee class definition
7 #include "BasePlusCommissionEmployee.h"
8
9 // constructor
10 BasePlusCommissionEmployee::BasePlusCommissionEmployee(
11     const string &first, const string &last, const string &ssn,
12     double sales, double rate, double salary )
13     : CommissionEmployee( first, last, ssn, sales, rate )
14 {
15     setBaseSalary( salary ); // validate and store base salary
16 } // end BasePlusCommissionEmployee constructor
17
18 // set base salary
19 void BasePlusCommissionEmployee::setBaseSalary( double salary )
20 {
21     baseSalary = ( ( salary < 0.0 ) ? 0.0 : salary );
22 } // end function setBaseSalary
23
24 // return base salary
25 double BasePlusCommissionEmployee::getBaseSalary() const
26 {
27     return baseSalary;
28 } // end function getBaseSalary
```

Maintain new data
member, **baseSalary**



Outline

BasePlus
Commission
Employee.cpp

Overridden **earnings** and **print** functions incorporate base salary

```

29
30 // calculate earnings;
31 // override pure virtual function earnings in Employee
32 double BasePlusCommissionEmployee::earnings() const
33 {
34     return getBaseSalary() + CommissionEmployee::earnings();
35 } // end function earnings
36
37 // print BasePlusCommissionEmployee's information
38 void BasePlusCommissionEmployee::print() const
39 {
40     cout << "base-salaried ";
41     CommissionEmployee::print(); // code reuse
42     cout << "; base salary: " << getBaseSalary();
43 } // end function print
  
```

Employee * ep;
HourlyEmployee he(...);
ep = &he; ✓
printst(ep);
CommEmp ce(...);
ep = &ce;
printst(ep);

void printst(Employee * ep){
 cout << ep->getName(); ✓
 cout << ep->print(); ✓ } HourlyEmployee print fun
 cout << ep->earnings(); ✓
 cout << ep->getHours(); ✗
}

printst2(ce); ✓
slicing problem

void printst2(Employee & ep){
 cout << ep.getName(); ✓
 cout << ep.print(); ✓ } HourlyEmployee print fun
 cout << ep.earnings(); ✓
 cout << ep.getHours(); ✗
}

~~Employee e1, e2("Ali", "Yilmaz",
"175-570");~~



13.6.6 Demonstrating Polymorphic Processing

- **Create objects of types `SalariedEmployee`, `HourlyEmployee`, `CommissionEmployee` and `BasePlusCommissionEmployee`**
 - **Demonstrate manipulating objects with static binding**
 - **Using name handles rather than pointers or references**
 - **Compiler can identify each object's type to determine which `print` and `earnings` functions to call**
 - **Demonstrate manipulating objects polymorphically**
 - **Uses a vector of `Employee` pointers**
 - **Invoke `virtual` functions using pointers and references**



Outline

fig13_23.cpp

(1 of 7)

```
1 // Fig. 13.23: fig13_23.cpp
2 // Processing Employee derived-class objects individually
3 // and polymorphically using dynamic binding.
4 #include <iostream>
5 using std::cout;
6 using std::endl;
7 using std::fixed;
8
9 #include <iomanip>
10 using std::setprecision;
11
12 #include <vector>
13 using std::vector;
14
15 // include definitions of classes in Employee hierarchy
16 #include "Employee.h"
17 #include "SalariedEmployee.h"
18 #include "HourlyEmployee.h"
19 #include "CommissionEmployee.h"
20 #include "BasePlusCommissionEmployee.h"
21
22 void virtualViaPointer( const Employee * const ); // prototype
23 void virtualViaReference( const Employee & ); // prototype
```

f (Employee e); X



Outline

ptr pointer
to base
if ref to
base

fig13_23.cpp

(2 of 7)

ptr → f()

ref. f()

```

24 int main()
25 {
26     // set floating-point output formatting
27     cout << fixed << setprecision( 2 );
28
29     // create derived-class objects
30     SalariedEmployee salariedEmployee(
31         "John", "Smith", "111-11-1111", 800 );
32     HourlyEmployee hourlyEmployee(
33         "Karen", "Price", "222-22-2222", 16.75, 40 );
34     CommissionEmployee commissionEmployee(
35         "Sue", "Jones", "333-33-3333", 10000, .06 );
36     BasePlusCommissionEmployee basePlusCommissionEmployee(
37         "Bob", "Lewis", "444-44-4444", 5000, .04, 300 );
38
39     cout << "Employees processed individually using static binding:\n\n";
40
41     // output each Employee's information and earnings using static binding
42     salariedEmployee.print();
43     cout << "\nearned $" << salariedEmployee.earnings() << "\n\n";
44     hourlyEmployee.print();
45     cout << "\nearned $" << hourlyEmployee.earnings() << "\n\n";
46     commissionEmployee.print();
47     cout << "\nearned $" << commissionEmployee.earnings() << "\n\n";
48     basePlusCommissionEmployee.print();
49     cout << "\nearned $" << basePlusCommissionEmployee.earnings()
50     << "\n\n";
51

```

Using objects (rather than pointers or references) to demonstrate static binding



Outline

```
52 // create vector of four base-class pointers
```

```
54 vector < Employee * > employees( 4 );
```

```
56 // initialize vector with Employees
```

```
57 employees[ 0 ] = &salariedEmployee;
```

```
58 employees[ 1 ] = &hourlyEmployee;
```

```
59 employees[ 2 ] = &commissionEmployee;
```

```
60 employees[ 3 ] = &basePlusCommissionEmployee;
```

vector of Employee
pointers, will be used to
demonstrate dynamic binding

```
62 cout << "Employees processed polymorphically via dynamic binding:\n\n";
```

```
64 // call virtualViaPointer to print each Employee's information
```

```
65 // and earnings using dynamic binding
```

```
66 cout << "Virtual function calls made off base-class pointers:\n\n";
```

```
67 virtualViaPointer( employees[0] );
```

```
68 for ( size_t i = 0; i < employees.size(); i++ )
```

```
69     virtualViaPointer( employees[ i ] );
```

Demonstrate dynamic
binding using first
pointers, then references

```
71 // call virtualViaReference to print each Employee's information
```

```
72 // and earnings using dynamic binding
```

```
73 cout << "Virtual function calls made off base-class references:\n\n";
```

```
75 for ( size_t i = 0; i < employees.size(); i++ )
```

```
76     virtualViaReference( *employees[ i ] ); // note dereferencing
```

```
78 return 0;
```

```
79 } // end main
```



Outline

fig13_23.cpp

(4 of 7)

Using references and pointers cause **virtual** functions to be invoked polymorphically

```
80
81 // call Employee virtual functions print and earnings off a
82 // base-class pointer using dynamic binding
83 void virtualViaPointer( const Employee * const baseClassPtr )
84 {
85     baseClassPtr->print();
86     cout << "\nearned $" << baseClassPtr->earnings() << "\n\n";
87 } // end function virtualViaPointer
88
89 // call Employee virtual functions print and earnings off a
90 // base-class reference using dynamic binding
91 void virtualViaReference( const Employee &baseClassRef )
92 {
93     baseClassRef.print();
94     cout << "\nearned $" << baseClassRef.earnings() << "\n\n";
95 } // end function virtualViaReference
```



Outline

fig13_23.cpp

(5 of 7)

Employees processed individually using static binding:

salaried employee: John Smith
social security number: 111-11-1111
weekly salary: 800.00
earned \$800.00

hourly employee: Karen Price
social security number: 222-22-2222
hourly wage: 16.75; hours worked: 40.00
earned \$670.00

commission employee: Sue Jones
social security number: 333-33-3333
gross sales: 10000.00; commission rate: 0.06
earned \$600.00

base-salaried commission employee: Bob Lewis
social security number: 444-44-4444
gross sales: 5000.00; commission rate: 0.04; base salary: 300.00
earned \$500.00

static
binding
print

(Continued at top of next slide...)



Outline

fig13_23.cpp

(6 of 7)

Employees processed polymorphically using dynamic binding:

Virtual function calls made off base-class pointers:

salaried employee: John Smith
social security number: 111-11-1111
weekly salary: 800.00
earned \$800.00

hourly employee: Karen Price
social security number: 222-22-2222
hourly wage: 16.75; hours worked: 40.00
earned \$670.00

commission employee: Sue Jones
social security number: 333-33-3333
gross sales: 10000.00; commission rate: 0.06
earned \$600.00

base-salaried commission employee: Bob Lewis
social security number: 444-44-4444
gross sales: 5000.00; commission rate: 0.04; base salary: 300.00
earned \$500.00

(Continued at the top of next slide...)



Outline

fig13_23.cpp

(7 of 7)

second loop

Virtual function calls made off base-class references:

salaried employee: John Smith
social security number: 111-11-1111
weekly salary: 800.00
earned \$800.00

hourly employee: Karen Price
social security number: 222-22-2222
hourly wage: 16.75; hours worked: 40.00
earned \$670.00

commission employee: Sue Jones
social security number: 333-33-3333
gross sales: 10000.00; commission rate: 0.06
earned \$600.00

base-salaried commission employee: Bob Lewis
social security number: 444-44-4444
gross sales: 5000.00; commission rate: 0.04; base salary: 300.00
earned \$500.00



13.7 (Optional) Polymorphism, Virtual Functions and Dynamic Binding “Under the Hood”

- How can C++ implement polymorphism, virtual functions and dynamic binding internally?
 - Three levels of pointers (“triple indirection”)
 - Virtual function table (*vtable*) created when C++ compiles a class that has one or more virtual functions
 - First level of pointers
 - Contains function pointers to virtual functions
 - Used to select the proper function implementation each time a virtual function of that class is called
 - If pure virtual, function pointer is set to 0
 - Any class that has one or more null pointers in its *vtable* is an abstract class



13.7 (Optional) Polymorphism, Virtual Functions and Dynamic Binding “Under the Hood” (Cont.)


- How can C++ implement polymorphism, virtual functions and dynamic binding internally? (Cont.)
 - If a non-pure virtual function were not overridden by a derived class
 - The function pointer in the *vtable* for that class would point to the implemented virtual function up in the hierarchy
 - Second level of pointers
 - Whenever an object of a class with one or more virtual functions is instantiated, the compiler attaches to the object a pointer to the *vtable* for that class
 - Third level of pointers
 - Handles to the objects that receive the virtual function calls



13.7 (Optional) Polymorphism, Virtual Functions and Dynamic Binding “Under the Hood” (Cont.)

- **How a typical `virtual` function call executes**
 - **Compiler determines if call is being made via a base-class pointer and that the function is `virtual`**
 - **Locates entry in *vtable* using offset or displacement**
 - **Compiler generates code that performs following operations:**
 - **Select the pointer being used in the function call from the third level of pointers**
 - **Dereference that pointer to retrieve underlying object**
 - **Begins with pointer in second level of pointers**
 - **Dereference object's *vtable* pointer to get to *vtable***
 - **Skip the offset to select the correct function pointer**
 - **Dereference the function pointer to form the “name” of the actual function to execute, and use the function call operator to execute the appropriate function**





vt able
virtual function table

employees[1] -> print();

class A{};

A a;

sizeof(a);

Fig.13.24 | How virtual function calls work.

Performance Tip 13.1

Polymorphism, as typically implemented with virtual functions and dynamic binding in C++, is efficient. Programmers may use these capabilities with nominal impact on performance.



Performance Tip 13.2

Virtual functions and dynamic binding enable polymorphic programming as an alternative to `switch` logic programming. Optimizing compilers normally generate polymorphic code that runs as efficiently as hand-coded `switch`-based logic. The overhead of polymorphism is acceptable for most applications. But in some situations—real-time applications with stringent performance requirements, for example—the overhead of polymorphism may be too high.



Software Engineering Observation 13.11

Dynamic binding enables independent software vendors (ISVs) to distribute software without revealing proprietary secrets. Software distributions can consist of only header files and object files—no source code needs to be revealed. Software developers can then use inheritance to derive new classes from those provided by the ISVs. Other software that worked with the classes the ISVs provided will still work with the derived classes and will use the overridden `virtual` functions provided in these classes (via dynamic binding).



13.8 Case Study: Payroll System Using Polymorphism and Run-Time Type Information with Downcasting, `dynamic_cast`, `typeid` and `type_info`

- **Example: Reward `BasePlusCommissionEmployees` by adding 10% to their base salaries**
- **Must use run-time type information (RTTI) and dynamic casting to “program in the specific”**
 - Some compilers require that RTTI be enabled before it can be used in a program
 - Consult compiler documentation



13.8 Case Study: Payroll System Using Polymorphism and Run-Time Type Information with Downcasting, `dynamic_cast`, `typeid` and `type_info` (Cont.)

- **`dynamic_cast` operator**

- Downcast operation
 - Converts from a base-class pointer to a derived-class pointer
- If underlying object is of derived type, cast is performed
 - Otherwise, 0 is assigned
- If `dynamic_cast` is not used and attempt is made to assign a base-class pointer to a derived-class pointer
 - A compilation error will occur



13.8 Case Study: Payroll System Using Polymorphism and Run-Time Type Information with Downcasting, `dynamic_cast`, `typeid` and `type_info` (Cont.)

- **`typeid` operator**

- Returns a reference to an object of class `type_info`
 - Contains the information about the type of its operand
 - `type_info` member function `name`
 - Returns a pointer-based string that contains the type name of the argument passed to `typeid`
- Must include header file `<typeinfo>`



Outline

fig13_25.cpp

(1 of 4)

```
1 // Fig. 13.25: fig13_25.cpp
2 // Demonstrating downcasting and run-time type information.
3 // NOTE: For this example to run in Visual C++ .NET,
4 // you need to enable RTTI (Run-Time Type Info) for the project.
5 #include <iostream>
6 using std::cout;
7 using std::endl;
8 using std::fixed;
9
10 #include <iomanip>
11 using std::setprecision;
12
13 #include <vector>
14 using std::vector;
15
16 #include <typeinfo>
17
18 // include definitions of classes in Employee hierarchy
19 #include "Employee.h"
20 #include "SalariedEmployee.h"
21 #include "HourlyEmployee.h"
22 #include "CommissionEmployee.h"
23 #include "BasePlusCommissionEmployee.h"
24
25 int main()
26 {
27     // set floating-point output formatting
28     cout << fixed << setprecision( 2 );
```



Outline

fig13_25.cpp

(2 of 4)

```
29 // create vector of four base-class pointers
30 vector < Employee * > employees( 4 );
31
32 // initialize vector with various kinds of Employees
33 employees[ 0 ] = new SalariedEmployee(
34     "John", "Smith", "111-11-1111", 800 );
35 employees[ 1 ] = new HourlyEmployee(
36     "Karen", "Price", "222-22-2222", 16.75, 40 );
37 employees[ 2 ] = new CommissionEmployee(
38     "Sue", "Jones", "333-33-3333", 10000, .06 );
39 employees[ 3 ] = new BasePlusCommissionEmployee(
40     "Bob", "Lewis", "444-44-4444", 5000, .04, 300 );
41
42 // polymorphically process each element in vector employees
43 for ( size_t i = 0; i < employees.size(); i++ )
44 {
45     employees[ i ]->print(); // output employee information
46     cout << endl;
47
48     // downcast pointer
49     BasePlusCommissionEmployee *derivedPtr =
50         dynamic_cast < BasePlusCommissionEmployee * >
51         ( employees[ i ] );
52 }
```

Create employee objects, only one of type
BasePlusCommissionEmployee

Downcast the **Employee** pointer to a
BasePlusCommissionEmployee pointer

Outline

```

53 // determine whether element points to base-salaried
54 // commission employee
55 if ( derivedPtr != 0 ) // 0 if not a BasePlusCommissionEmployee
56 {
57     double oldBaseSalary = derivedPtr->getBaseSalary();
58     cout << "old base salary: $" << oldBaseSalary << endl;
59     derivedPtr->setBaseSalary( 1.10 * oldBaseSalary );
60     cout << "new base salary with 10% increase is: $"
61         << derivedPtr->getBaseSalary() << endl;
62 } // end if

```

Determine if cast was successful

(3 of 4)

If cast was successful, modify base salary

```

63 cout << "earned $" << employees[ i ]->earnings() << "\n\n";
64 } // end for

```

```

65 // release objects pointed to by vector's elements
66 for ( size_t j = 0; j < employees.size(); j++ )
67 {
68     // output class name
69     cout << "deleting object of "
70         << typeid( *employees[ j ] ).name() << endl;
71     delete employees[ j ];
72 } // end for
73 return 0;
74 } // end main

```

Use **typeid** and function **name** to display object types



Outline

fig13_25.cpp

(4 of 4)

salaried employee: John Smith
social security number: 111-11-1111
weekly salary: 800.00
earned \$800.00

hourly employee: Karen Price
social security number: 222-22-2222
hourly wage: 16.75; hours worked: 40.00
earned \$670.00

commission employee: Sue Jones
social security number: 333-33-3333
gross sales: 10000.00; commission rate: 0.06
earned \$600.00

base-salaried commission employee: Bob Lewis
social security number: 444-44-4444
gross sales: 5000.00; commission rate: 0.04; base salary: 300.00
old base salary: \$300.00
new base salary with 10% increase is: \$330.00
earned \$530.00

deleting object of class SalariedEmployee
deleting object of class HourlyEmployee
deleting object of class CommissionEmployee
deleting object of class BasePlusCommissionEmployee



13.9 Virtual Destructors

- **Nonvirtual destructors**

- Destructors that are not declared with keyword `virtual`
- If a derived-class object is destroyed explicitly by applying the `delete` operator to a base-class pointer to the object, the behavior is undefined

- **virtual destructors**

- Declared with keyword `virtual`
 - All derived-class destructors are `virtual`
- If a derived-class object is destroyed explicitly by applying the `delete` operator to a base-class pointer to the object, the appropriate derived-class destructor is called
 - Appropriate base-class destructor(s) will execute afterwards



Good Programming Practice 13.2

If a class has `virtual` functions, provide a `virtual` destructor, even if one is not required for the class. Classes derived from this class may contain destructors that must be called properly.



Common Programming Error 13.5

Constructors cannot be `virtual`. Declaring a constructor `virtual` is a compilation error.



13.10 (Optional) Software Engineering Case Study: Incorporating Inheritance into the ATM System

- **UML model for inheritance**
 - The generalization relationship
 - The base class is a generalization of the derived classes
 - The derived classes are specializations of the base class
 - Pure **virtual** functions are abstract operations in the UML
 - Generalizations and abstract operations are written in italics
- ***Transaction*** base class
 - Contains the functions and data members **BalanceInquiry**, **Withdrawal** and **Deposit** have in common
 - *execute* function
 - **accountNumber** data member




Fig.13.26 | Attributes and operations of classes BalanceInquiry, withdrawal and Deposit.




Fig.13.27 | Class diagram modeling generalization relationship between base class Transaction and derived classes BalanceInquiry, Withdrawal and Deposit.




Fig.13.28 | Class diagram of the ATM system (incorporating inheritance). Note that abstract class name *Transaction* appears in italics.

13.10 (Optional) Software Engineering Case Study: Incorporating Inheritance into the ATM System (Cont.)

- **Incorporating inheritance into the ATM system design**
 - If class A is a generalization of class B, then class B is derived from class A
 - If class A is an abstract class and class B is a derived class of class A, then class B must implement the pure virtual functions of class A if class B is to be a concrete class






Fig.13.29 | Class diagram after incorporating inheritance into the system.

Software Engineering Observation 13.12

A complete class diagram shows all the associations among classes and all the attributes and operations for each class. When the number of class attributes, operations and associations is substantial (as in Fig. 13.28 and Fig. 13.29), a good practice that promotes readability is to divide this information between two class diagrams—one focusing on associations and the other on attributes and operations. However, when examining classes modeled in this fashion, it is crucial to consider both class diagrams to get a complete view of the classes. For example, one must refer to Fig. 13.28 to observe the inheritance relationship between Transaction and its derived classes that is omitted from Fig. 13.29.



Outline

withdrawal.h

(1 of 1)

```
1 // Fig. 13.30: withdrawal.h
2 // Definition of class Withdrawal that represents a withdrawal transaction
3 #ifndef WITHDRAWAL_H
4 #define WITHDRAWAL_H
5
6 #include "Transaction.h" // Transaction class definition
7
8 // class Withdrawal derives from base class Transaction
9 class Withdrawal : public Transaction
10 {
11 }; // end class Withdrawal
12
13 #endif // WITHDRAWAL_H
```

Class **Withdrawal** inherits
from **Transaction**




Outline

withdrawal.h

(1 of 1)

```
1 // Fig. 13.31: Withdrawal.h
2 // Definition of class Withdrawal that represents a withdrawal transaction
3 #ifndef WITHDRAWAL_H
4 #define WITHDRAWAL_H
5
6 #include "Transaction.h" // Transaction class definition
7
8 class Keypad; // forward declaration of class Keypad
9 class CashDispenser; // forward declaration of class CashDispenser
10
11 // class withdrawal derives from base class Transaction
12 class withdrawal : public Transaction
13 {
14 public:
15     // member function overriding execute in base class Transaction
16     virtual void execute(); // perform the transaction
17 private:
18     // attributes
19     double amount; // amount to withdraw
20     Keypad &keypad; // reference to ATM's keypad
21     CashDispenser &cashDispenser; // reference to ATM's cash dispenser
22 }; // end class withdrawal
23
24 #endif // WITHDRAWAL_H
```

Class **Withdrawal** inherits
from **Transaction**



Outline

Transaction.h

(1 of 1)

```
1 // Fig. 13.32: Transaction.h
2 // Transaction abstract base class definition.
3 #ifndef TRANSACTION_H
4 #define TRANSACTION_H
5
6 class Screen; // forward declaration of class Screen
7 class BankDatabase; // forward declaration of class BankDatabase
8
9 class Transaction
10 {
11 public:
12     int getAccountNumber(); // return account number
13     Screen &getScreen(); // return reference to screen
14     BankDatabase &getBankDatabase(); // return reference to bank database
15
16     // pure virtual function to perform the transaction
17     virtual void execute() = 0; // overridden in derived classes
18 private:
19     int accountNumber; // indicates account involved
20     Screen &screen; // reference to the screen of the ATM
21     BankDatabase &bankDatabase; // reference to the account info database
22 }; // end class Transaction
23
24 #endif // TRANSACTION_H
```

Transaction is an abstract class,
contains a pure **virtual** function

Declare pure **virtual** function **execute**

