

"Stupidity is **while** (1) { **tryAgain**(); }"

- Unknown

# CSE102 Computer Programming with C

2020-2021 Spring Semester

Repetition

© 2015-2021 Yakup Genç

1

## Control Structures

- Controls the flow of program execution
  - Sequence
  - Selection
  - Repetition
- Repetition structure
  - Repetition of steps (loop body): loop
  - while**, **for**, and **do-while** statements
    - Each has advantages for some type of repetitions
  - Ex: calculate payroll for several employees

March 2021

CSE102 Computer Programming

2

2

## Repetition

- How to design repetition
  - Solve the problem for a specific case
  - Try to generalize
  - Answer the following questions for repetition
    - Do I need to repeat any step?
    - How many times to repeat the steps?
    - How long to continue repetition?
  - Decide on the loop type based on the answers.
    - The flow chart on the next slide


March 2021

CSE102 Computer Programming

3

3

## Loop Choice



March 2021

CSE102 Computer Programming

4

4

## Comparison of Loop Kinds

TABLE 5.1 Comparison of Loop Kinds

Kind	When Used	C Implementation Structures	Section Containing an Example
Counting loop	We can determine before loop execution exactly how many loop repetitions will be needed to solve the problem.	while for	5.2 5.4
Sentinel-controlled loop	Input of a list of data of any length ended by a special value	while, for	5.6
Endfile-controlled loop	Input of a single list of data of any length from a data file	while, for	5.6
Input validation loop	Repeated interactive input of a data value until a value within the valid range is entered	do-while	5.8
General conditional loop	Repeated processing of data until a desired condition is met	while, for	5.5, 5.9

March 2021

CSE102 Computer Programming

5

## Counter Controlled Loop

- Repetition is managed by a loop control variable
  - For example a counter

General format:

```


set counter to 0           /* initialization */
while counter < final value /* test          */
do one or more things      /* loop body   */
increase counter by one    /* updating  */
  
```

March 2021

CSE102 Computer Programming

6

## Flowchart for a while Loop



March 2021

CSE102 Computer Programming

7

## Program Fragment with a Loop

```

1. count_emp = 0;           /* no employees processed yet */
2. while (count_emp < 7) {   /* test value of count_emp */
3.     printf("Hours> ");
4.     scanf("%d", &hours);
5.     printf("Rate> ");
6.     scanf("%lf", &rate);
7.     pay = hours * rate;
8.     printf("Pay is $%6.2f\n", pay);
9.     count_emp = count_emp + 1; /* increment count_emp */
10. }
11. printf("\nAll employees processed\n");
  
```

March 2021

CSE102 Computer Programming

8

## while statement

General syntax:

```
while (loop repetition control)
    statement
```

Example

```
count_star = 0;
while (count_star < N) {
    printf("*");
    count_star = count_star + 1;
}
```

March 2021

CSE102 Computer Programming

9

## Payroll calculator

- Calculate payroll for several employees
  - Calculate the total payroll as well
- Input:
  - For each employee
    - Hours, rate, pay
  - Number of employees
- Output
  - For each employee
    - Payroll
  - Total payroll

March 2021

CSE102 Computer Programming

10

## Payroll calculator

```
1. /* Compute the payroll for a company */
2.
3. #include <stdio.h>
4.
5. int
6. main(void)
7. {
8.     double total_pay; /* company payroll */
9.     int count_emp; /* current employee */
10.    int number_emp; /* number of employees */
11.    double hours; /* hours worked */
12.    double rate; /* hourly rate */
13.    double pay; /* pay for this period */
14.
15.    /* Get number of employees. */
16.    printf("Enter number of employees> ");
17.    scanf("%d", &number_emp);
18.
```

(continued)

March 2021

CSE102 Computer Programming

11

## Payroll calculator

```
19. /* Compute each employee's pay and add it to the payroll. */
20. total_pay = 0.0;
21. count_emp = 0;
22. while (count_emp < number_emp) {
23.     printf("Hours> ");
24.     scanf("%lf", &hours);
25.     printf("Rate > $");
26.     scanf("%lf", &rate);
27.     pay = hours * rate;
28.     printf("Pay is $%.2f\n", pay);
29.     total_pay = total_pay + pay; /* Add next pay. */
30.     count_emp = count_emp + 1;
31. }
32. printf("All employees processed\n");
33. printf("Total payroll is $%.2f\n", total_pay);
34.
35. return (0);
36. }
```

```
Enter number of employees> 3
Hours> 50
Rate > $5.25
Pay is $262.50
```

(continued)

March 2021

CSE102 Computer Programming

12

## Generalized conditional loop

- Ex: multiplying a list of numbers
  - Ask for numbers
  - Multiply as long as the product is less than 10000

```
product = 1;
while (product < 10000){
    printf("%d \n Enter next item >", product);
    scanf("%d", &item);
    product = product * item;
}
```

March 2021

CSE102 Computer Programming

13

13

## Compound assignment

### Simple assignment

```
count = count + 1;
time = time - 1;
product = product * item;
n = n / (d + 1);
value = value % 7;
```

In general:

var = var op exp

### Compound assignment

```
count += 1;
time -= 1;
product *= item;
n /= (d + 1);
value %= 7;
```

In general:

var op= exp

March 2021

CSE102 Computer Programming

14

14

## for statement

- for statement is another repetition structure
- supplies a designated space for each of the loop components
  - Initialization of the loop control variable
  - Test of the loop repetition control
  - Change of the loop control variable
- Syntax:
 

```
for (initialization expression;
    loop repetition condition;
    update expression)
    statement;
```

March 2021

CSE102 Computer Programming

15

15

## for Statement in a Counting Loop

```
1. /* Process payroll for all employees */
2. total_pay = 0.0;
3. for (count_emp = 0;                /* initialization */
4.     count_emp < number_emp;        /* loop repetition condition */
5.     count_emp += 1) {              /* update */
6.     printf("Hours> ");
7.     scanf("%lf", &hours);
8.     printf("Rate > $");
9.     scanf("%lf", &rate);
10.    pay = hours * rate;
11.    printf("Pay is $%.2f\n\n", pay);
12.    total_pay = total_pay + pay;
13. }
14. printf("All employees processed\n");
15. printf("Total payroll is $%.2f\n", total_pay);
```

March 2021

CSE102 Computer Programming

16

16

## for statement

```
for (count_star = 0;
    count_star < N;
    count_star += 1)
    printf("*");

for (i = 0; i < max; i +=1)
    printf("%d \n", i);

for (product = 1; product < 10000; product *= item)
    scanf("%d", &item);
```

March 2021

CSE102 Computer Programming

17

17

## Increment and Decrement Operators

- Unary operators
- Side effect
  - ++ increments the operand
  - -- decrements the operand
- The value of the operation depends on the position of the operator
  - Pre-increment : operand is after the operator
    - Value is the variable's value after incrementing
  - Post-increment : operand is before the operator
    - Value is the variable's value before incrementing
  - Similar for decrement operator


March 2021

CSE102 Computer Programming

18

18

## Prefix and Postfix Increments



March 2021

CSE102 Computer Programming

19

19

## Increment and Decrement Operators

- What is the result of following code fragments
 

```
n = 4;
printf("%3d", --n);
printf("%3d", n);
printf("%3d", n--);
printf("%3d", n);
y = n * 4 + ++n;
x = n++ * --n;
```
- Write a function to compute factorial of an integer

March 2021

CSE102 Computer Programming

20

20

## Function to Compute Factorial

```

1. /*
2.  * Computes n!
3.  * Pre: n is greater than or equal to zero
4.  */
5. int
6. factorial(int n)
7. {
8.     int i,      /* local variables */
9.     product;   /* accumulator for product computation */
10.
11.     product = 1;
12.     /* Computes the product n x (n-1) x (n-2) x ... x 2 x 1 */
13.     for (i = n; i > 1; --i) {
14.         product = product * i;
15.     }
16.
17.     /* Returns function result */
18.     return (product);
19. }

```

March 2021

CSE102 Computer Programming

21

21

```

1. /* Conversion of Celsius to Fahrenheit temperatures */
2.
3. #include <stdio.h>
4.
5. /* Constant macros */
6. #define CBEGIN 10
7. #define CLIMIT -5
8. #define CSTEP 5
9.
10. int
11. main(void)
12. {
13.     /* Variable declarations */
14.     int    celsius;
15.     double fahrenheit;
16.
17.     /* Display the table heading */
18.     printf(" Celsius Fahrenheit\n");
19.
20.     /* Display the table */
21.     ① for (celsius = CBEGIN;
22.         ② celsius >= CLIMIT;
23.         ③ celsius -= CSTEP) {
24.         ④ fahrenheit = 1.8 * celsius + 32.0;
25.         ⑤ printf("%6c3d%8c7.2f\n", ' ', celsius, ' ', fahrenheit);
26.     }
27.
28.     return (0);
29. }

```

Celsius	Fahrenheit
10	50.00
5	41.00
0	32.00
-5	23.00

March 2021

CSE102 Computer Programming

22

22

## Conditional Loops

- If you do not know exact number of repetitions
- Ex: ensuring valid user input
  - Continue to prompt user to enter a value as long as the response is not reasonable

Print an initial prompting message

Get the number of observed values

While the number of value is negative

Print a warning message and ask for another value

Get the number of observed values

- Where is initialization, test and update steps?
  - How to write the loop in C?

March 2021

CSE102 Computer Programming

23

23

## Conditional Loops

- Ex: Monitoring gasoline supply
  - Capacity 80000 barrels
  - Use of gasoline is entered in gallons
    - 1 barrel = 42 gallons
  - Alert if the supply falls below 10% of the capacity
- Input:
  - Current supply
  - Several uses
- Output
  - Remaining supply
  - Alert

March 2021

CSE102 Computer Programming

24

24

TABLE 5.5 Problem-Solving Questions for Loop Design

Question	Answer	Implications for the Algorithm
What are the inputs?	Initial supply of gasoline (barrels). Amounts removed (gallons).	Input variables needed: <code>start_supply</code> <code>remov_gals</code> Value of <code>start_supply</code> must be input once, but amounts removed are entered many times.
What are the outputs?	Amounts removed in gallons and barrels, and the current supply of gasoline.	Values of <code>current</code> and <code>remov_gals</code> are echoed in the output. Output variable needed: <code>remov_brls</code>
Is there any repetition?	Yes. One repeatedly 1. gets amount removed 2. converts the amount to barrels 3. subtracts the amount removed from the current supply 4. checks to see whether the supply has fallen below the minimum.	Program variable needed: <code>min_supply</code>
Do I know in advance how many times steps will be repeated?	No.	Loop will not be controlled by a counter.
How do I know how long to keep repeating the steps?	As long as the current supply is not below the minimum.	The loop repetition condition is <code>current &gt;= min_supply</code>

March 2021

CSE102 Computer Programming

25

25

## Monitoring Gasoline Storage Tank

```

1.  /*
2.  * Monitor gasoline supply in storage tank. Issue warning when supply
3.  * falls below MIN_PCT % of tank capacity.
4.  */
5.
6.  #include <stdio.h>
7.
8.  /* constant macros */
9.  #define CAPACITY 80000.0 /* number of barrels tank can hold */
10. #define MIN_PCT 10 /* warn when supply falls below this
11.                    percent of capacity */
12. #define GALS_PER_BRL 42.0 /* number of U.S. gallons in one barrel */
13.
14. /* Function prototype */
15. double monitor_gas(double min_supply, double start_supply);
16.
17. int
18. main(void)
19. {
20.     double start_supply, /* input - initial supply in barrels */
21.     min_supply, /* minimum number of barrels left without
22.                warning */
23.     current; /* output - current supply in barrels */
24.
25.     /* Compute minimum supply without warning */
26.     min_supply = MIN_PCT / 100.0 * CAPACITY;
27.

```

(continued)

March 2021

CSE102 Computer Programming

26

26

## Monitoring Gasoline Storage Tank

```

28. /* Get initial supply */
29. printf("Number of barrels currently in tank> ");
30. scanf("%lf", &start_supply);
31.
32. /* Subtract amounts removed and display amount remaining
33.    as long as minimum supply remains. */
34. current = monitor_gas(min_supply, start_supply);
35.
36. /* Issue warning */
37. printf("Only %.2f barrels are left.\n\n", current);
38. printf("*** WARNING ***\n\n");
39. printf("Available supply is less than %d percent of tank's\n",
40.        MIN_PCT);
41. printf("%.2f-barrel capacity.\n", CAPACITY);
42.
43. return (0);
44. }
45.

```

March 2021

CSE102 Computer Programming

27

27

## Monitoring Gasoline Storage Tank

```

46. /*
47. * Computes and displays amount of gas remaining after each delivery
48. * Pre : min_supply and start_supply are defined.
49. * Post: Returns the supply available (in barrels) after all permitted
50. *       removals. The value returned is the first supply amount that is
51. *       less than min_supply.
52. */
53. double
54. monitor_gas(double min_supply, double start_supply)
55. {
56.     double remov_gals, /* input - amount of current delivery */
57.     remov_brls, /* in barrels and gallons */
58.     current; /* output - current supply in barrels */
59.
60.     for (current = start_supply;
61.          current >= min_supply;
62.          current -= remov_brls) {
63.         printf("%.2f barrels are available.\n\n", current);
64.         printf("Enter number of gallons removed> ");
65.         scanf("%lf", &remov_gals);
66.         remov_brls = remov_gals / GALS_PER_BRL;
67.
68.         printf("After removal of %.2f gallons (%.2f barrels)\n",
69.                remov_gals, remov_brls);
70.     }
71.
72.     return (current);
73. }

```

March 2021

CSE102 Computer Programming

28

28

## Sentinel Controlled Loops

---

- Input one additional data item at each repetition
  - Usually number of items is not known in advance
  - When to stop reading data?
- Sentinel value: unique value to stop repetition
  - Should be an abnormal value

```

Get a line of data
While the sentinel value has not been encountered
  Process the data line
  Get another line of data
  
```

- Where is initialization, test and update stages

March 2021

CSE102 Computer Programming

29

## Sentinel Controlled Loops

---

- Ex: Calculate sum of a collection of exam scores
  - Assume the number of students is not known
  - What is the sentinel value?
- Input:
  - Exam score
- Output:
  - Sum of scores

March 2021

CSE102 Computer Programming

30

## Sentinel Controlled Loops

---

Algorithm:

```

Initialize sum to zero
while score is not the sentinel
  Get score
  Add score to sum
  
```

March 2021

CSE102 Computer Programming

31

## Sentinel Controlled Loops

---

Correct Algorithm:

```

Initialize sum to zero
Get the first score
while score is not the sentinel
  Add score to sum
  Get score
  
```

March 2021

CSE102 Computer Programming

32



## Sentinel-Controlled while Loop

```

1.  /* Compute the sum of a list of exam scores. */
2.
3.  #include <stdio.h>
4.
5.  #define SENTINEL -99
6.
7.  int
8.  main(void)
9.  {
10.     int sum = 0, /* output - sum of scores input so far */
11.         score; /* input - current score */
12.
13.     /* Accumulate sum of all scores. */
14.     printf("Enter first score (or %d to quit)> ", SENTINEL);
15.     scanf("%d", &score); /* Get first score. */
16.     while (score != SENTINEL) {
17.         sum += score;
18.         printf("Enter next score (%d to quit)> ", SENTINEL);
19.         scanf("%d", &score); /* Get next score. */
20.     }
21.     printf("\nSum of exam scores is %d\n", sum);
22.
23.     return (0);
24. }

```

March 2021

CSE102 Computer Programming

33

33

## Sentinel-Controlled for Loop

- Can we use for statement for sentinel controlled loops?

```

/* Accumulate sum of all scores. */
printf("Enter first score (or %d to quit)> ", SENTINEL);
scanf("%d", &score); /* Get first score. */
while (score != SENTINEL) {
    sum += score;
    printf("Enter next score (%d to quit)> ", SENTINEL);
    scanf("%d", &score); /* Get next score. */
}
printf("\nSum of exam scores is %d\n", sum);

```

March 2021

CSE102 Computer Programming

34

34

## Sentinel-Controlled for Loop

```

/* Accumulate sum of all scores. */
printf("Enter first score (or %d to quit)> ", SENTINEL);
scanf("%d", &score); /* Get first score. */
while (score != SENTINEL) {
    sum += score;
    printf("Enter next score (%d to quit)> ", SENTINEL);
    scanf("%d", &score); /* Get next score. */
}
printf("\nSum of exam scores is %d\n", sum);

printf(".....");
for (scanf("%d",&score);
     score != SENTINEL;
     scanf("%d",&score)) {
    sum += score;
    printf(".....");
}

```

March 2021

CSE102 Computer Programming

35

35

## End-file Controlled Loops

- Ex: Calculate sum of a list of integers in a file
- A data file is terminated by an endfile character
    - detected by fscanf functions.
  - special sentinel value is not required
    - uses the status value returned by fscanf

Algorithm:

```

Initialize sum to zero
Read the first value
while end of file is not reached
    Add value to sum
    Read the next value

```

March 2021

CSE102 Computer Programming

36

36

```

*****
*****
*****
*****
*****
*****
*****

```

March 2021

CSE102 Computer Programming

37

37

```

int i,j,n;

n = 7;

for (j=0;j<n;j++) {
    for (i=0;i<n;i++) printf("*");
    printf("\n");
}

```

March 2021

CSE102 Computer Programming

38

38

```

void printline(int n);
void main () {
    int i,j,n;
    n = 7;
    for (j=0;j<n;j++) {
        printline(n);
    }
}

void printline(int n) {
    int i;
    for (i=0;i<n;i++) rprintf("*");
    printf("\n");
}

```

March 2021

CSE102 Computer Programming

39

39

## End-file Controlled Loops

```

1  /*
2  * Compute the sum of the list of exam scores stored in the
3  * file scores.dat
4  */
5
6  #include <stdio.h>      /* defines fopen, fclose, fscanf,
7                          fprintf, and EOF
8
9  int
10 main(void)
11 {
12     FILE *inp;           /* input file pointer
13     int sum = 0,         /* sum of scores input so far
14     score,               /* current score
15     input_status;        /* status value returned by fscanf
16     inp = fopen("scores.dat", "r");
17
18     printf("Scores\n");
19
20     input_status = fscanf(inp, "%d", &score);
21     while (input_status != EOF) {
22         printf("%5d\n", score);
23         sum += score;
24         input_status = fscanf(inp, "%d", &score);
25     }
26
27     printf("\nSum of exam scores is %d\n", sum);
28     fclose(inp);
29
30     return (0);
31 }

```

March 2021

CSE102 Computer Programming

40

40

## Infinite Loop on Faulty Data

- If the file contains a faulty data 7o, fscanf
  - stops at the letter 'o',
  - stores the value 7 in score
  - leaves the letter 'o' unprocessed.
  - returns a status value of one
- On the next loop iteration, fscanf
  - finds the letter 'o' awaiting processing
  - leaves the variable score unchanged
  - leaves the letter 'o' unprocessed,
  - returns a status value of zero
- In the previous program
  - the return value of fscanf is not checked for values other than EOF
  - unsuccessful attempt to process the letter 'o' repeats over and over.

Infinite loop!...

March 2021

CSE102 Computer Programming

41

## Infinite Loop on Faulty Data

- Solution: Change the loop repetition condition to `while (input_status == 1)`
- loop exits on
  - end of file (input\_status negative) OR
  - faulty data (input\_status zero)
- Add an if statement after the loop to decide whether to print the results or to warn of bad input.

```

if (input_status == EOF)
    printf("Sum of exam scores is %d\n", sum);
else {
    fscanf(inp, "%c", &bad_char);
    printf("Error in input: %c\n", bad_char);
}

```

March 2021

CSE102 Computer Programming

42

## Nested Loops

- Loops may be nested like other control structures.
  - an outer loop with one or more inner loops.
  - Each time the outer loop is repeated, the inner loops are reentered,

Ex: Audubon Club members' sightings of bald eagles

- Input: for each month a group of integers followed by a zero
- Output: for each month total sightings
- program contains a sentinel loop (for sightings in a month) nested within a counting loop (for months).

March 2021

CSE102 Computer Programming

43

## Nested Loops

```

1  #include <stdio.h>
2
3  #define SENTINEL 0
4  #define NUM_MONTHS 12
5
6  int
7  main(void)
8  {
9
10     int month, /* number of month being processed */
11         mem_sight, /* one member's sightings for this month */
12         sightings; /* total sightings so far for this month */
13
14     printf("BALD EAGLE SIGHTINGS\n");
15     for (month = 1;
16          month <= NUM_MONTHS;
17          ++month) {
18         sightings = 0;
19         scanf("%d", &mem_sight);
20         while (mem_sight != SENTINEL) {
21             if (mem_sight >= 0)
22                 sightings += mem_sight;
23             else
24                 printf("Warning, negative count %d ignored\n",
25                        mem_sight);
26             scanf("%d", &mem_sight);
27         } /* inner while */
28         printf(" month %2d: %2d\n", month, sightings);
29     } /* outer for */
30     return (0);
31 }

```

March 2021

CSE102 Computer Programming

44

## Nested Loops

```

20.     for (month = 1;
21.         month <= NUM_MONTHS;
22.         ++month) {
23.         sightings = 0;
24.         scanf("%d", &mem_sight);
25.         while (mem_sight != SENTINEL) {
26.             if (mem_sight >= 0)
27.                 sightings += mem_sight;
28.             else
29.                 printf("Warning, negative count %d ignored\n",
30.                     mem_sight);
31.             scanf("%d", &mem_sight);
32.         } /* inner while */

```

March 2021

CSE102 Computer Programming

45

## Nested Loops

- Ex: a simple program with two nested counting loops.
  - The outer loop is repeated three times (for  $i = 1, 2, 3$ ).
  - The number of times the inner loop is repeated depends on the current value of  $i$ .

March 2021

CSE102 Computer Programming

46

## Nested Loops

```

1.  /*
2.  * Illustrates a pair of nested counting loops
3.  */
4.
5.  #include <stdio.h>
6.
7.  int
8.  main(void)
9.  {
10.     int i, j; /* loop control variables */
11.
12.     printf("      I      J\n"); /* prints column labels */
13.
14.     for (i = 1; i < 4; ++i) { /* heading of outer for loop */
15.         printf("Outer %6d\n", i);
16.         for (j = 0; j < i; ++j) { /* heading of inner loop */
17.             printf("  Inner%9d\n", j);
18.         } /* end of inner loop */
19.     } /* end of outer loop */
20.
21.     return (0);
22. }

```

March 2021

CSE102 Computer Programming

47

## Nested Loops

- The output of the algorithm:

	I	J
Outer	1	
Inner		0
Outer	2	
Inner		0
Inner		1
Outer	3	
Inner		0
Inner		1
Inner		2

March 2021

CSE102 Computer Programming

48

## Nested Loops

- What is displayed by the following program segments, assuming m is 3 and n is 5?

```
a. for (i = 1; i <= n; ++i) {
    for (j = 0; j < i; ++j) {
        printf("*");
    }
    printf("\n");
}
b. for (i = n; i > 0; --i) {
    for (j = m; j > 0; --j) {
        printf("*");
    }
    printf("\n");
}
```

March 2021

CSE102 Computer Programming

49

## do-while Statement

- for statements and while statements evaluate loop repetition condition before the first execution of the loop body.
- Pretest is usually undesirable
  - when there may be no data items to process
  - when the initial value of the loop control variable is outside its expected range.
- Sometimes loop must execute at least once
- Ex: interactive input
  - Get a data value.
  - If data value isn't in the acceptable range, go back to step 1.

March 2021

CSE102 Computer Programming

50

## do-while Statement

- C provides the do-while statement to implement such loops

- Get a data value.
- If data value isn't in the acceptable range, go back to step 1.

```
do {
    printf("Enter a letter from A to E ");
    scanf("%c", &letter);
} while (letter < 'A' || letter > 'E');
```

March 2021

CSE102 Computer Programming

51

## do-while Statement

- SYNTAX:

```
do {
    statements
} while ( loop repetition condition );
```

- Ex: Find first even input

```
do
    status = scanf("%d", &num);
while (status > 0 && (num % 2) != 0);
```

March 2021

CSE102 Computer Programming

52

## Flag Controlled Loops

- If loop repetition condition is complex
  - Use a flag is a type int (values: 1 (true) and 0 (false))
  - Flag represents whether a certain event has occurred.
- Ex: Input Validation
  - The do-while is often used in checking for valid input
    - An input is always needed
  - Two nested loops
    - Repeat reading input when the input is not valid
      - not in range OR not a number
    - Repeat reading input to skip invalid input line
      - Not to have infinite loop

March 2021

CSE102 Computer Programming

53

53

```

1.  /*
2.  * Returns the first integer between n_min and n_max entered as data.
3.  * Pre : n_min <= n_max
4.  * Post: Result is in the range n_min through n_max.
5.  */
6.  int
7.  get_int (int n_min, int n_max)
8.  {
9.      int  in_val,          /* input - number entered by user      */
10.         status;          /* status value returned by scanf */
11.      char skip_ch;        /* character to skip              */
12.      int  error;          /* error flag for bad input       */
13.      /* Get data from user until in_val is in the range.      */

```

March 2021

CSE102 Computer Programming

54

54

```

14. do {
15.     /* No errors detected yet. */
16.     error = 0;
17.     /* Get a number from the user. */
18.     printf("Enter an integer in the range from %d ", n_min);
19.     printf("to %d inclusive> ", n_max);
20.     status = scanf("%d", &in_val);
21.
22.     /* Validate the number. */
23.     if (status != 1) { /* in_val didn't get a number */
24.         error = 1;
25.         scanf("%c", &skip_ch);
26.         printf("Invalid character >>> ", skip_ch);
27.         printf("Skipping rest of line.\n");
28.     } else if (in_val < n_min || in_val > n_max) {
29.         error = 1;
30.         printf("Number %d is not in range.\n", in_val);
31.     }
32.
33.     /* Skip rest of data line. */
34.     do
35.         scanf("%c", &skip_ch);
36.     while (skip_ch != '\n');
37. } while (error);
38.
39. return (in_val);
40. }

```

March 2021

CSE102 Computer Programming

55

55

## Flag Controlled Loops

### • Execution results

Enter an integer in the range from 10 to 20 inclusive> @20  
 Invalid character >>>@>>. Skipping rest of line.  
 Enter an integer in the range from 10 to 20 inclusive> 20  
 Number 2 is not in range.  
 Enter an integer in the range from 10 to 20 inclusive> 20

March 2021

CSE102 Computer Programming

56

56

### Do While Statement and Flag Controlled Loops

- Do they behave similarly? Why?

```
scanf("%d", &num);
while (num != SENT) {
    /* process num */
    scanf("%d", &num);
}

do {
    scanf("%d", &num);
    /* process num */
} while (num != SENT);
```

March 2021

CSE102 Computer Programming

57

### Do While Statement and Flag Controlled Loops

- Which of the following code is better way to implement a sentinel-controlled loop? Why?

```
scanf("%d", &num);
while (num != SENT) {
    /* process num */
    scanf("%d", &num);
}

do {
    scanf("%d", &num);
    if (num != SENT)
        /* process num */
} while (num != SENT);
```

March 2021

CSE102 Computer Programming

58

### Do While Statement and Flag Controlled Loops

- Rewrite the following code using do-while statement with no decisions in the loop body:

```
sum = 0;
for (odd = 1; odd < n; odd+=2)
    sum += odd;
```

March 2021

CSE102 Computer Programming

59

### Case Study:

#### Problem: Collecting area for Solar-Heated House

- Area depends on several factors
  - the average number of heating degree days for each month
    - the product of the average difference between inside and outside temperatures and the number of days in the month
  - the average solar insolation for each month
    - rate at which solar radiation falls on one square foot of a given location
  - heating requirement per square foot of floor space
  - floor space
  - efficiency of the collection method

March 2021

CSE102 Computer Programming

60

## Case Study:

- The formula for the desired collecting area (A)  
 $A = \text{heat loss} / \text{energy source}$
- heat loss* is the product of the heating requirement, the floor space, and the heating degree days.
- energy resource* is the product of the efficiency of the collection method, the average solar insolation per day and the number of days.
- Two data files
  - hdd.txt contains numbers representing the *average* heating degree days for each months.
  - solar.txt contains the average solar insolation for each month

March 2021

CSE102 Computer Programming

61

## Case Study:

### Problem Inputs

```

Average heating degree days file
Average solar insolation file
heat_deg_days /* average heating degree days for coldest month */ coldest_mon /* coldest
month (number 1..12)
solar_insol /* average daily solar insolation for coldest month */ heating_req
/* Btu/degree day Ft² */
efficiency /* % of solar insolation converted to usable heat */ floor_space /*
square feet */

```

### Program Variables

```

energy_resrc /* usable solar energy available in coldest month
(Btus obtained from 1 Ft² of collecting area) */

```

### Problem Outputs

```

heat_loss /* Btus of heat lost by structure in coldest month */ collect_area /*
approximate size Ft² of collecting area needed */

```

March 2021

CSE102 Computer Programming

62


## Case Study:

- Algorithm
  - Determine the coldest month and the average heating degree days for this month.
  - Find the average daily solar insolation per Ft² for the coldest month.
  - Get the other problem inputs from the user :  
     heating\_req, efficiency, floor\_space.
    - Estimate the collecting area needed.
    - Display results.

March 2021

CSE102 Computer Programming

63



March 2021

CSE102 Computer Programming

64



### Program to Approximate Solar Collecting Area Size

```

1.  /*
2.  * Estimate necessary solar collecting area size for a particular type of
3.  * construction in a given location.
4.  */
5.  #include <stdio.h>
6.
7.  int days_in_month(int);
8.  int nth_item(FILE *, int);
9.
10. int main(void)
11. {
12.     int heat_deg_days, /* average for coldest month */
13.     solar_insol, /* average daily solar radiation per
14.                  ft^2 for coldest month */
15.     coldest_mon, /* coldest month: number in range 1..12 */
16.     heating_req, /* Btu / degree day ft^2 requirement for
17.                  given type of construction */
18.     efficiency, /* % of solar insolation converted to
19.                  usable heat */
20.     collect_area, /* ft^2 needed to provide heat for
21.                   coldest month */
22.     ct, /* position in file */
23.     status, /* file status variable */
24.     next_hdd; /* one heating degree days value */
25.     double floor_space, /* ft^2 */
26.     heat_loss, /* Btus lost in coldest month */
27.     energy_resrc; /* Btus heat obtained from 1 ft^2
28.                  collecting area in coldest month */

```

March 2021

CSE102 Computer Programming

65

65

```

29. FILE *hdd_file; /* average heating degree days for each
30.                  of 12 months */
31. FILE *solar_file; /* average solar insolation for each of
32.                   12 months */
33.
34. /* Get average heating degree days for coldest month from file */
35. hdd_file = fopen("hdd.txt", "r");
36. fscanf(hdd_file, "%d", &heat_deg_days);
37. coldest_mon = 1;
38. ct = 2;
39. status = fscanf(hdd_file, "%d", &next_hdd);
40. while (status == 1) {
41.     if (next_hdd > heat_deg_days) {
42.         heat_deg_days = next_hdd;
43.         coldest_mon = ct;
44.     }
45.     ++ct;
46.     status = fscanf(hdd_file, "%d", &next_hdd);
47. }
48. fclose(hdd_file);
49.

```

March 2021

CSE102 Computer Programming

66

66

```

51. /* Get corresponding average daily solar insolation from other file */
52. solar_file = fopen("solar.txt", "r");
53. solar_insol = nth_item(solar_file, coldest_mon);
54. fclose(solar_file);
55.
56. /* Get from user specifics of this house */
57. printf("What is the approximate heating requirement (Btu / ");
58. printf("degree day ft^2) for this type of construction?\n> ");
59. scanf("%d", &heating_req);
60. printf("What percent of solar insolation will be converted ");
61. printf("to usable heat?\n> ");
62. scanf("%d", &efficiency);
63. printf("What is the floor space (ft^2)?\n> ");
64. scanf("%lf", &floor_space);
65.

```

March 2021

CSE102 Computer Programming

67

67

```

66. /* Project collecting area needed */
67. heat_loss = heating_req * floor_space * heat_deg_days;
68. energy_resrc = efficiency * 0.01 * solar_insol *
69.               days_in_month(coldest_mon);
70. collect_area = (int)(heat_loss / energy_resrc + 0.5);
71.
72. /* Display results */
73. printf("To replace heat loss of %.0f Btu in the ", heat_loss);
74. printf("coldest month (month %d) with available ", coldest_mon);
75. printf("solar insolation of %d Btu / ft^2 / day,", solar_insol);
76. printf(" and an efficiency of %d percent,", efficiency);
77. printf(" use a solar collecting area of %d", collect_area);
78. printf(" ft^2.\n");
79.
80. return 0;
81. }
82.

```

March 2021

CSE102 Computer Programming

68

68

```

83. /*
84.  * Given a month number (1 = January, 2 = February, ...,
85.  * 12 = December ), return the number of days in the month
86.  * (nonleap year).
87.  * Pre: 1 <= monthNumber <= 12
88.  */
89. int days_in_month( int month_number )
90. {
91.

```

March 2021

CSE102 Computer Programming

69

```

92. int ans;
93.
94. switch (month_number) {
95.     case 2: ans = 28; /* February */
96.         break;
97.
98.     case 4: /* April */
99.     case 6: /* June */
100.     case 9: /* September */
101.     case 11: ans = 30; /* November */
102.         break;
103.
104.     default: ans = 31;
105. }
106.
107. return ans;
108. }
109.
110. /*
111.  * Finds and returns the nth integer in a file.
112.  * Pre: data_file accesses a file of at least n integers (n >= 1).
113.  */
114. int nth_item(FILE *data_file, int n)
115. {
116.     int i, item;
117.
118.     for (i = 1; i <= n; ++i)
119.         fscanf(data_file, "%d", &item);
120.
121.     return item;
122. }

```

March 2021

CSE102 Computer Programming

70

69

70

## Altering Normal Operation of a Loop




Figure: Flowchart of break statement


March 2021

CSE102 Computer Programming

71

71

## Altering Normal Operation of a Loop



NOTE: The break statement may also be used inside body of else statement.

March 2021

CSE102 Computer Programming

72

72

## Altering Normal Operation of a Loop




Fig: Flowchart of continue statement


March 2021

CSE102 Computer Programming

73

73

## Altering Normal Operation of a Loop



NOTE: The continue statement may also be used inside body of else statement.

March 2021

CSE102 Computer Programming

74

74

## How to Debug and Test Programs

- Error Types:
  - syntax errors
  - run time errors
  - logic errors
- run-time error or logic error is usually not obvious
  - you may spend considerable time and energy locating it.
- Method:
  - examine the program output and determine program part generating incorrect results
  - focus on the statements and try to determine the fault
- OR
  - Use Debugger programs
  - Debug without debugger

March 2021

CSE102 Computer Programming

75

75

## Common Programming Errors

### Of-by-one Loop Errors

- A common logic error with loops
  - loop executes one more time or one less time than required
- In sentinel-controlled loops, an extra repetition is more dangerous.
- In counting loops, the initial and final values of counter should be correct and the loop repetition condition should be right.
- Ex: the following loop body executes  $n + 1$  times instead of  $n$  times.
 

```
for (i=0; i <= n; ++i)
    sum += i;
```

March 2021

CSE102 Computer Programming

76

76

## Common Programming Errors

- Don't Confuse
  - Use if statement to implement decision step !!
  - Use while statement to implement loop !!
- In using while or for statements, don't forget that
  - The structure assumes that the loop body is a single statement!!
  - Use (always) braces for consisting multiple statements !!
- Keep in mind that compiler ignore indentation!!
  - Ex : x is 1000 and max is 0;

Wrong!! (infinite loop)

```
while (x > max)
    sum+=x;
    x++;
```

True

```
while (x > max) {
    sum+=x;
    x++;
}
```

March 2021

CSE102 Computer Programming

77

## Common Programming Errors

- Don't forget!!
  - = : is assignment operator
  - == : is equality operator
- Wrong!!
 

while (x=1)	True
.....	while (x==1)
	.....

March 2021

CSE102 Computer Programming

78

## Common Programming Errors

### Brace Hierarchy

```
if(ans=='Y'){
    while(x > 0){
        x--;
        sum += x; /* missing brace */
    }
    else          /* compiler error here */
    ...
```

March 2021

CSE102 Computer Programming

79

## Common Programming Errors

- Improper usage of compound statement
 

```
a = a * b + c
```

there is no short way of doing this.
- Do not use increment decrement operators twice for the same operands on the same expression.

March 2021

CSE102 Computer Programming

80

Thanks for listening!