

*"Talk is cheap. Show me the code."*

- Linus Torvalds

# CSE102

## Computer Programming with C

2020-2021 Spring Semester

Modular Programming

© 2015-2021 Yakup Genç

1

## Functions

- Functions: Components of a program
- Connect functions to generate a program
- Each function has
  - Inputs
    - Parameters
    - Computes manipulate different data each time it is called
  - Outputs
    - Returns a result with return statement
    - Output parameters to return multiple results

March 2021

CSE102 Computer Programming

2

2

## Functions

- Function call
  - Allocate memory space for each formal parameter
    - Heap vs Stack
  - Store actual parameter value in the allocated space
  - Execute function code
    - Manipulates the values of formal parameters

March 2021


CSE102 Computer Programming

3

3

## Diagram of Function separate

- Ex: Gets a double value, find and return
  - Sign
  - Whole number magnitude
  - Fractional part
- Three output parameters



March 2021

CSE102 Computer Programming

4

4

## Function separate

```

1.  /*
2.  * Separates a number into three parts: a sign (+, -, or blank),
3.  * a whole number magnitude, and a fractional part.
4.  */
5.  void
6.  separate(double num, /* input - value to be split */
7.           char *signp, /* output - sign of num */
8.           int *wholep, /* output - whole number magnitude of num */
9.           double *fracp) /* output - fractional part of num */
10. {
11.     double magnitude; /* local variable - magnitude of num */
12.
13.     /* Determines sign of num */
14.     if (num < 0)
15.         *signp = '-';
16.     else if (num == 0)
17.         *signp = ' ';
18.     else
19.         *signp = '+';
20.
21.     /* Finds magnitude of num (its absolute value) and
22.     separates it into whole and fractional parts */
23.     magnitude = fabs(num);
24.     *wholep = floor(magnitude);
25.     *fracp = magnitude - *wholep;
26. }

```

March 2021

CSE102 Computer Programming

5

## Function Output Parameters

- Use \* in front of the output parameters
  - declaration  
char \*signp,
  - assignment  
\*signp = '-';
- signp : pointer
  - contains address of a char variable
  - "p" is used because it is pointer

March 2021

CSE102 Computer Programming

6

## Program That Calls separate

```

5. #include <stdio.h>
6. #include <math.h>
7. void separate(double num, char *signp, int *wholep, double *fracp);
8.
9. int
10. main(void)
11. {
12.     double value; /* input - number to analyze */
13.     char sn; /* output - sign of value */
14.     int whl; /* output - whole number magnitude of value */
15.     double fr; /* output - fractional part of value */
16.
17.     /* Gets data */
18.     printf("Enter a value to analyze> ");
19.     scanf("%lf", &value);
20.
21.     /* Separates data value into three parts */
22.     separate(value, &sn, &whl, &fr);
23.
24.     /* Prints results */
25.     printf("Parts of %.4f\n sign: %c\n", value, sn);
26.     printf(" whole number magnitude: %d\n", whl);
27.     printf(" fractional part: %.4f\n", fr);
28.
29.     return (0);
30. }

```

March 2021

CSE102 Computer Programming

7

## Program That Calls separate

- Three variables defined in main function
  - values will be defined by function separate
  - address of sn is stored in output parameter signp
- Use & operator on the actual parameter  
separate(value, &sn, &whl, &fr);
  - separate knows where sn is in the memory.
    - Like scanf
  - &sn is of type char-pointer


March 2021

CSE102 Computer Programming

8

## Parameter Correspondence

```
separate(value, &sn, &whl, &fr);
```



March 2021


CSE102 Computer Programming

9

## Use of output parameters

### • Indirection operator: \*

- Applied to formal parameter (pointer)
- Follow the pointer referenced by the formal parameter
- Indirect reference



March 2021

CSE102 Computer Programming

10

## Function separate

```

1.  /*
2.   * Separates a number into three parts: a sign (+, -, or blank),
3.   * a whole number magnitude, and a fractional part.
4.   */
5.  void
6.  separate(double num, /* input - value to be split */
7.           char *signp, /* output - sign of num */
8.           int *wholep, /* output - whole number magnitude of num */
9.           double *fracp) /* output - fractional part of num */
10. {
11.     double magnitude; /* local variable - magnitude of num */
12.
13.     /* Determines sign of num */
14.     if (num < 0)
15.         *signp = '-';
16.     else if (num == 0)
17.         *signp = ' ';
18.     else
19.         *signp = '+';
20.
21.     /* Finds magnitude of num (its absolute value) and
22.      separates it into whole and fractional parts */
23.     magnitude = fabs(num);
24.     *wholep = floor(magnitude);
25.     *fracp = magnitude - *wholep;
26. }

```

March 2021

CSE102 Computer Programming

11

## Meanings of \* Symbol

### • Three distinct meanings

- Multiplication
- Declaration
  - char \*sn : means sn is pointer to char
- Indirection operator
  - Follow pointer
  - \*sn is of type char

March 2021

CSE102 Computer Programming

12

## Input/Output Parameters

- Single parameter for
  - Bring data to the function
  - Carry result out of the function
- Ex: Arrange three values in increasing order
- Input:
  - num1, num2, num3
- Output:
  - num1 is the smallest of input values,
  - num2 is the second smallest of input values,
  - num3 is the largest of input values,
- Function order orders two arguments

March 2021

CSE102 Computer Programming

13

## Program to Sort Three Numbers

```


1.  /*
2.  * Tests function order by ordering three numbers
3.  */
4.  #include <stdio.h>
5.
6.  void order(double *smp, double *lgp);
7.
8.  int
9.  main(void)
10. {
11.     double num1, num2, num3; /* three numbers to put in order */
12.
13.     /* Gets test data */
14.     printf("Enter three numbers separated by blanks ");
15.     scanf("%lf%lf%lf", &num1, &num2, &num3);
16.
17.     /* Orders the three numbers */
18.     order(&num1, &num2);
19.     order(&num1, &num3);
20.     order(&num2, &num3);
21.
22.     /* Displays results */
23.     printf("The numbers in ascending order are: %.2f %.2f %.2f\n",
24.           num1, num2, num3);
25.
26.     return (0);
27. }
```

March 2021

CSE102 Computer Programming

14

## Data Areas of order(&num1, &num3);



March 2021

CSE102 Computer Programming

15

## Program to Sort Three Numbers

```

29. /*
30. * Arranges arguments in ascending order.
31. * Pre: smp and lgp are addresses of defined type double variables
32. * Post: variable pointed to by smp contains the smaller of the type
33. *       double values; variable pointed to by lgp contains the larger
34. */
35. void
36. order(double *smp, double *lgp) /* input/output */
37. {
38.     double temp; /* temporary variable to hold one number during swap */
39.     /* Compares values pointed to by smp and lgp and switches if necessary */
40.     if (*smp > *lgp) {
41.         temp = *smp;
42.         *smp = *lgp;
43.         *lgp = temp;
44.     }
45. }
46.
Enter three numbers separated by blanks> 7.5 9.6 5.5
The numbers in ascending order are: 5.50 7.50 9.60
```

March 2021

CSE102 Computer Programming

16

## Program Style

- Use functions take input parameters and return a value
  - Easier to understand and maintain
    - No indirect reference
    - No address operator
    - Return value is assigned to a variable at caller
- Math function are of this type

March 2021

CSE102 Computer Programming

17

## Subprograms

**TABLE 6.3** Different Kinds of Function Subprograms

Purpose	Function Type	Parameters	To Return Result
To compute or obtain as input a single numeric or character value.	Same as type of value to be computed or obtained.	Input parameters hold copies of data provided by calling function.	Function code includes a <code>return</code> statement with an expression whose value is the result.
To produce printed output containing values of numeric or character arguments.	<code>void</code>	Input parameters hold copies of data provided by calling function.	No result is returned.

March 2021

CSE102 Computer Programming

18

## Subprograms

To compute multiple numeric or character results.	<code>void</code>	Input parameters hold copies of data provided by calling function.	Results are stored in the calling function's data area by indirect assignment through output parameters. No <code>return</code> statement is required.
To modify argument values.	<code>void</code>	Input/output parameters are pointers to actual arguments. Input data is accessed by indirect reference through parameters.	Results are stored in the calling function's data area by indirect assignment through output parameters. No <code>return</code> statement is required.

March 2021

CSE102 Computer Programming

19

## Scope of Names

- Region of program that the name is visible
- Scope of
  - constant macros
    - From definition to the end of source file
  - function names
    - From function prototype to the end of source file
  - variables
    - From declaration to closing brace
- What if an identifier is defined before?

March 2021

CSE102 Computer Programming

20

## Program for Studying Scope of Names

```

1. #define MAX 950
2. #define LIMIT 200
3.
4. void one(int anarg, double second); /* prototype 1 */
5.
6. int fun_two(int one, char anarg); /* prototype 2 */
7.
8. int
9. main(void)
10. {
11.     int localvar;
12.     . . .
13. } /* end main */
14.
15. void
16. one(int anarg, double second) /* header 1 */
17. {
18.     int onelocal; /* local 1 */
19.     . . .
20. } /* end one */
21.
22. int
23. fun_two(int one, char anarg) /* header 2 */
24. {
25.     int localvar; /* local 2 */
26.     . . .
27. } /* end fun_two */

```

March 2021

CSE102 Computer Programming

21

## Scope of Names

```

1. #define MAX 950
2. #define LIMIT 200
3.
4. void one(int anarg, double second); /* prototype 1 */
5.
6. int fun_two(int one, char anarg); /* prototype 2 */
7.
8. int
9. main(void)
10. {
11.     int localvar;
12.     . . .
13. } /* end main */
14.
15. void
16. one(int anarg, double second) /* header 1 */
17. {
18.     int onelocal; /* local 1 */
19.     . . .
20. } /* end one */
21.
22. int
23. fun_two(int one, char anarg) /* header 2 */
24. {
25.     int localvar; /* local 2 */
26.     . . .
27. } /* end fun_two */

```

March 2021

CSE102 Computer Programming

22

TABLE 6.4 Scope of Names in Fig. 6.8

Name	Visible in one	Visible in fun_two	Visible in main
MAX	yes	yes	yes
LIMIT	yes	yes	yes
main	yes	yes	yes
localvar (in main)	no	no	yes
one (the function)	yes	no	yes
anarg (int)	yes	no	no
second	yes	no	no
onelocal	yes	no	no
fun_two	yes	yes	yes
one (formal parameter)	no	yes	no
anarg (char)	no	yes	no
localvar (in fun_two)	no	yes	no

21

22

## Formal Output Parameters as Actual Arguments

- Passing output parameters to other functions
  - Ex: Reading values into output parameters
- Ex: Write a function to read a common fraction
  - numerator / denominator
- Function scan\_fraction
  - Two output parameters
  - Reads a fraction until a valid fraction is entered

March 2021

CSE102 Computer Programming

23

## Function scan\_fraction

```

1. /*
2.  * Gets and returns a valid fraction as its result
3.  * A valid fraction is of this form: integer/positive integer
4.  * Pre : none
5.  */
6. void
7. scan_fraction(int *nump, int *denomp)
8. {
9.     char slash; /* character between numerator and denominator */
10.    int status; /* status code returned by scanf indicating
11.                number of valid values obtained */
12.    int error; /* flag indicating presence of an error */
13.    char discard; /* unprocessed character from input line */
14.
15.    do {
16.        /* No errors detected yet
17.        error = 0;

```

March 2021

CSE102 Computer Programming

(continued)

24

23

24

## Function scan\_fraction

```

18.  /* Get a fraction from the user          */
19.  printf("Enter a common fraction as two integers separated ");
20.  printf("by a slash\n");
21.  status = scanf("%d %ld", &num, &denom);
22.
23.  /* Validate the fraction                  */
24.  if (status < 3) {
25.      error = 1;
26.      printf("Invalid-please read directions carefully\n");
27.  } else if (slash != '/') {
28.      error = 1;
29.      printf("Invalid-separate numerator and denominator\n");
30.      printf(" by a slash (/)\n");
31.  } else if (*denom <= 0) {
32.      error = 1;
33.      printf("Invalid-denominator must be positive\n");
34.  }
35.
36.  /* Discard extra input characters          */
37.  do {
38.      scanf("%c", &discard);
39.  } while (discard != '\n');
40.  } while (error);
41. }


```

March 2021

CSE102 Computer Programming

25

## Data Areas for scan\_fraction and Its Caller



March 2021

CSE102 Computer Programming

26

## Case Study: Common Fraction Problem

- **Problem:** Write a program to add, subtract, multiply and divide pairs of common fractions
- **Inputs:**
  - First fraction: numerator and denominator
  - Second fraction: numerator and denominator
  - Operator
- **Output:**
  - Resulting fraction

March 2021

CSE102 Computer Programming

27

## Case Study: Common Fraction Problem

### Algorithm

1. Repeat as long as user wants to continue
2. Get a fraction problem
3. Compute the result
4. Display the problem and result
5. Check if user wants to continue

March 2021

CSE102 Computer Programming

28

## Case Study: Common Fraction Problem

### Algorithm

1. Repeat as long as user wants to continue
2. Get a fraction problem
  1. Get first fraction (scan\_fraction)
  2. Get operator (get\_operator)
  3. Get second fraction (scan\_fraction)
3. Compute the result
4. Display the problem and result
5. Check if user wants to continue

March 2021

CSE102 Computer Programming

29

29

## Case Study: Common Fraction Problem

### Algorithm

1. Repeat as long as user wants to continue
2. Get a fraction problem
3. Compute the result
  1. Select and perform task based on operator
    - Add the fractions (add\_fractions)
    - Add the first fraction and the negation of the second fraction
    - Multiply the fractions (multiply\_fractions)
    - Multiply the first fraction with reciprocal of the second fraction
  2. Put the result fraction in reduced form
4. Display the problem and result
5. Check if user wants to continue

March 2021

CSE102 Computer Programming

30

30

## Case Study: Common Fraction Problem

### Algorithm


1. Repeat as long as user wants to continue
2. Get a fraction problem
3. Compute the result
  1. Select and perform task based on operator
  2. Put the result fraction in reduced form
    - Find the GCD of the numerator and denominator (find\_gcd)
    - Divide numerator and denominator by the GCD (reduce\_fraction)
4. Display the problem and result (print\_fraction)
5. Check if user wants to continue

March 2021

CSE102 Computer Programming

31

31



March 2021

CSE102 Computer Programming

32

32



```

1.  /*
2.  * Adds, subtracts, multiplies and divides common fractions, displaying
3.  * results in reduced form.
4.  */
5.
6.  #include <stdio.h>
7.  #include <stdlib.h> /* provides function abs */
8.
9.  /* Function prototypes */
10. void scan_fraction(int *nump, int *denomp);
11.
12. char get_operator(void);
13.
14. void add_fractions(int n1, int d1, int n2, int d2,
15.                  int *n_ansp, int *d_ansp);
16.
17. void multiply_fractions(int n1, int d1, int n2, int d2,
18.                       int *n_ansp, int *d_ansp);
19.
20. int find_gcd (int n1, int n2);
21.
22. void reduce_fraction(int *nump, int *denomp);
23.
24. void print_fraction(int num, int denom);
25.
26. int
27. main(void)
28. {
29.     int n1, d1; /* numerator, denominator of first fraction */
30.     int n2, d2; /* numerator, denominator of second fraction */
31.     char op; /* arithmetic operator + - * or / */
32.     char again; /* y or n depending on user's desire to continue */
33.     int n_ans, d_ans; /* numerator, denominator of answer */

```

March 2021

CSE102 Computer Programming

33

33

```

34. /* While the user wants to continue, gets and solves arithmetic
35.  * problems with common fractions */
36. do {
37.     /* Gets a fraction problem */
38.     scan_fraction(&n1, &d1);
39.     op = get_operator();
40.     scan_fraction(&n2, &d2);
41.
42.     /* Computes the result */
43.     switch (op) {
44.         case '+':
45.             add_fractions(n1, d1, n2, d2, &n_ans, &d_ans);
46.             break;
47.
48.         case '-':
49.             add_fractions(n1, d1, -n2, d2, &n_ans, &d_ans);
50.             break;
51.
52.         case '*':
53.             multiply_fractions(n1, d1, n2, d2, &n_ans, &d_ans);
54.             break;
55.
56.         case '/':
57.             multiply_fractions(n1, d1, d2, n2, &n_ans, &d_ans);
58.             reduce_fraction(&n_ans, &d_ans);
59.
60.     }
61.     /* Displays problem and result */
62.     printf("\n");
63.     print_fraction(n1, d1);
64.     printf(" %c ", op);
65.     print_fraction(n2, d2);
66.     printf(" = ");
67.     print_fraction(n_ans, d_ans);
68.
69.     /* Asks user about doing another problem */
70.     printf("\ndo another problem? (y/n)> ");
71.     scanf(" %c", &again);
72.     } while (again == 'y' || again == 'r');
73.     return (0);
74. }

```

March 2021

CSE102 Computer Programming

34

34

```

75. /* Insert function scan_fraction from Fig. 6.9 here. */
76.
77. /*
78.  * Gets and returns a valid arithmetic operator. Skips over newline
79.  * characters and permits reentry of operator in case of error.
80.  */
81. char
82. get_operator(void)
83. {
84.     char op;
85.
86.     printf("Enter an arithmetic operator (+,-,*, or /)\n> ");
87.     for (scanf("%c", &op);
88.          op != '+' && op != '-' &&
89.          op != '*' && op != '/';
90.          scanf("%c", &op)) {
91.         if (op != '\n')
92.             printf("%c invalid, reenter operator (+,-,*,/)\n> ", op);
93.     }
94.     return (op);
95. }
96.

```

March 2021

CSE102 Computer Programming

35

35

```

97. /*
98.  * Adds fractions represented by pairs of integers.
99.  * Pre: n1, d1, n2, d2 are defined;
100.  *      n_ansp and d_ansp are addresses of type int variables.
101.  * Post: sum of n1/d1 and n2/d2 is stored in variables pointed
102.  *       to by n_ansp and d_ansp. Result is not reduced.
103.  */
104. void
105. add_fractions(int n1, int d1, /* input - first fraction */
106.              int n2, int d2, /* input - second fraction */
107.              int *n_ansp, int *d_ansp) /* output - sum of 2 fractions */
108. {
109.     int denom, /* common denominator used for sum (may not be least) */

```

March 2021

CSE102 Computer Programming

36

36

```

110.     numer,      /* numerator of sum          */
111.     sign_factor; /* -1 for a negative, 1 otherwise */
112.     */
113.
114.     /* Finds a common denominator          */
115.     denom = d1 * d2;
116.
117.     /* Computes numerator                    */
118.     numer = n1 * d2 + n2 * d1;
119.
120.     /* Adjusts sign (at most, numerator should be negative) */
121.     if (numer * denom >= 0)
122.         sign_factor = 1;
123.     else
124.         sign_factor = -1;
125.
126.     numer = sign_factor * abs(numer);
127.     denom = abs(denom);
128.
129.     /* Returns result                        */
130.     *n_ansp = numer;
131.     *d_ansp = denom;
132. }

```

March 2021

CSE102 Computer Programming

37

37

```

133. /*
134.  **** STUB ****
135.  * Multiplies fractions represented by pairs of integers.
136.  * Pre: n1, d1, n2, d2 are defined;
137.  *      n_ansp and d_ansp are addresses of type int variables.
138.  * Post: product of n1/d1 and n2/d2 is stored in variables pointed
139.  *       to by n_ansp and d_ansp. Result is not reduced.
140.  */
141. void
142. multiply_fractions(int n1, int d1, /* input - first fraction */
143.                  int n2, int d2, /* input - second fraction */
144.                  int *n_ansp, /* output - */
145.                  int *d_ansp) /* output - product of 2 fractions */
146. {
147.     /* Displays trace message */
148.     printf("\nEnter multiply_fractions with\n");
149.     printf("n1 = %d, d1 = %d, n2 = %d, d2 = %d\n", n1, d1, n2, d2);
150.     /* Defines output arguments */
151.     *n_ansp = 1;
152.     *d_ansp = 1;
153. }
154.

```

March 2021

CSE102 Computer Programming

38

38

```

156.  **** STUB ****
157.  * Finds greatest common divisor of two integers
158.  */
159. int
160. find_gcd (int n1, int n2) /* input - two integers */
161. {
162.     int gcd;
163.
164.     /* Displays trace message */
165.     printf("\nEnter find_gcd with n1 = %d, n2 = %d\n", n1, n2);
166.
167.     /* Asks user for gcd */
168.     printf("gcd of %d and %d?> ", n1, n2);
169.     scanf("%d", &gcd);
170.
171.     /* Displays exit trace message */
172.     printf("find_gcd returning %d\n", gcd);
173.     return (gcd);
174. }
175.

```

March 2021

CSE102 Computer Programming

39

39

```

176. /*
177.  * Reduces a fraction by dividing its numerator and denominator by their
178.  * greatest common divisor.
179.  */
180. void
181. reduce_fraction(int *nump, /* input/output - */
182.                int *denomp) /* numerator and denominator of fraction */
183. {
184.     int gcd; /* greatest common divisor of numerator & denominator */
185.
186.     gcd = find_gcd(*nump, *denomp);
187.     *nump = *nump / gcd;
188.     *denomp = *denomp / gcd;
189. }
190.
191. /*
192.  * Displays pair of integers as a fraction.
193.  */
194. void
195. print_fraction(int num, int denom) /* input - numerator & denominator */
196. {
197.     printf("%d/%d", num, denom);
198. }

```

March 2021

CSE102 Computer Programming

40

40

## Sample Run

```

Enter a common fraction as two integers separated by a slash> 3/-4
Input invalid--denominator must be positive
Enter a common fraction as two integers separated by a slash> 3/4
Enter an arithmetic operator (+,-,*, or /)
> +
Enter a common fraction as two integers separated by a slash> 5/8
Entering find_gcd with n1 = 44, n2 = 32
gcd of 44 and 32> 4
find_gcd returning 4

3/4 + 5/8 = 11/8
Do another problem? (y/n)> y
Enter a common fraction as two integers separated by a slash> 1/2
Enter an arithmetic operator (+,-,*, or /)
> *
5 invalid, reenter operator (+,-,*,/)
> *
Enter a common fraction as two integers separated by a slash> 5/7
Entering multiply_fractions with
n1 = 1, d1 = 2, n2 = 5, d2 = 7
Entering find_gcd with n1 = 1, n2 = 1
gcd of 1 and 1> 1
find_gcd returning 1

1/2 * 5/7 = 5/14
Do another problem? (y/n)> n

```

March 2021

CSE102 Computer Programming

41

## Program Style

- Keep the functions to a manageable size
  - Less error
  - Easier to read and test

March 2021

CSE102 Computer Programming

42

## Testing

- Top-down testing
  - Test general flow of control
    - stubs
- Stubs
  - Used instead of functions not yet written
  - Team work!..
    - Enables testing and debugging
  - Displays an identification message
  - Assign values to output parameters

March 2021

CSE102 Computer Programming

43

## Stub for Function multiply\_fractions

```

1. /*
2.  ***** STUB *****
3.  * Multiplies fractions represented by pairs of integers.
4.  * Pre: n1, d1, n2, d2 are defined;
5.  *       n_ansp and d_ansp are addresses of type int variables.
6.  * Post: product of n1/d1 and n2/d2 is stored in variables pointed
7.  *       to by n_ansp and d_ansp. Result is not reduced.
8.  */
9. void
10. multiply_fractions(int n1, int d1, /* input - first fraction */
11.                   int n2, int d2, /* input - second fraction */
12.                   int *n_ansp, /* output - */
13.                   int *d_ansp) /* product of 2 fractions */
14. {
15.     /* Displays trace message */
16.     printf("\nEnter multiply_fractions with\n");
17.     printf("n1 = %d, d1 = %d, n2 = %d, d2 = %d\n", n1, d1, n2, d2);
18.
19.     /* Defines output arguments */
20.     *n_ansp = 1;
21.     *d_ansp = 1;
22. }

```

March 2021

CSE102 Computer Programming

44

## Testing

- **Bottom-up Testing**
  - First test individual functions
    - **Unit test**
  - Test entire system later
    - **System integration test**
- **Unit Test**
  - Preliminary test of a function separate from the whole program
  - Using driver program
    - Driver gives values to input parameters
    - Calls the function
    - Display and check function results

March 2021

CSE102 Computer Programming

45

## Driver for Function scan\_fraction

```

1.  /* Driver for scan_fraction */
2.
3.  int
4.  main(void)
5.  {
6.      int num, denom;
7.      printf("To quit, enter a fraction with a zero numerator\n");
8.      scan_fraction(&num, &denom);
9.      while (num != 0) {
10.         printf("Fraction is %d/%d\n", num, denom);
11.         scan_fraction(&num, &denom);
12.     }
13.
14.     return (0);
15. }

```

March 2021

CSE102 Computer Programming

46

## Debugging

- Good documentation is essential
  - Function's purpose, parameters, local variables
- Debug each function as you write them
- Create a trace
  - Display the function name as you enter it
  - Display and verify the input parameters as you enter a function
  - Display and verify return values after function returns
  - After it works fine do not erase display statements, comment them out. You may need them later
- Use debugger
  - First execute a function as a single statement
  - If the result is incorrect step in its statements

March 2021

CSE102 Computer Programming

47

Thanks for listening!

48