

# ecalj tutorial

---

Here are minimum GetStated to obtain QSGW band plot.

[Qiita Japanese](#)

[Qiita English](#)

## Minimum flowchart to perform QSGW in ecalj.

### 1. Get ctrls from POSCAR

ctrls.fooobar is the structure file in ecalj.

We obtain ctrls from POSCAR by a converter.

We already have POSCAR in ecalj/ecalj\_auto/INPUT/testSGA/POSCARALL as

```
cd ecalj
mkdir TEST
cd TEST
mkdir test1
mkdir test2
cat ecalj_auto/INPUT/testSGA/joblist.bk
cp ../ecalj_auto/INPUT/testSGA/POSCARALL/POSCAR.mp-2534 test1
cp ../ecalj_auto/INPUT/testSGA/POSCARALL/POSCAR.mp-8062 test2
```

Then we convert POSCAR by vasp2ctrl. If you have cif, you need to convert the cif to POSCAR at first.

```
vasp2ctrl POSCAR.mp-2534
mv ctrls.POSCAR.mp-2534.vasp2ctrl ctrls.POSCAR.mp-2534
cat ctrls.mp-2534
```

ctrls.mp-2534 contains crystal structure equivalent to POSCAR:

```
cat ctrls.mp-2534
STRUC
  ALAT=1.8897268777743552
  PLAT=      3.52125300000      0.00000000000      2.03299700000
           1.17375100000      3.31986900000      2.03299700000
           0.00000000000      0.00000000000      4.06599300000
  NBAS=2
  SITE
    ATOM=Ga POS=      0.00000000000      0.00000000000
0.00000000000
```

```
ATOM=As POS= 1.17375100000 0.82996725000
2.03299675000
```

- MEMO:
  - ctrl2vasp ctrl.mp-2534 can convert back to VASP file. Check this by VESTA. We can use viewvesta (convert and invoke VESTA).
  - many unused files are generated (forget them).

## 2. Get ctrl from ctrls

ctrl is a basis input file for ecalj. We generate template of ctrl by ctrlgenM1.py.

Minimum explanations are embedded in the generated ctrl file.

Number of k points (nk1 nk2 nk3), APW cutoff (pwemax), nspin, so (spin orbit switch) are only what we need to tweak usually.

When we run lmf, we can add command line option such as -vnspin=2. Then const foobar=1 defined in the ctrl file is overridden (referred with {foobar}). save.\* file show which -vfoobar you used.

It is possible to enforce symmetry, antiferro symmetry.

We only need ctrl file in the following calculations (while some tmp\* kinds of files are generated).

```
ctrlgenM1.py mp-2534
cp ctrlgenM1.ctrl.mp-2534 ctrl.mp-2534
```

- important settings in ctrl
  - nk1,nk2,nk3
  - xcfun
  - ssig
  - pwemax
  - gmax
  - so
  - socaxis

[Here is a list of ctrl file.](#)

## 3. LDA計算

Run lmfa at first. It is for spherical atomic electron density. It ends instantaneously.

If you run `lmfa foobar | grep conf`, we can see electronic configuration. No side effects if you repeat lmfa.

```
lmfa ctrl.mp-2534
```

gives spherical atom calculation for initialization. No side effects to repeat.

```
lmfa ctrl.mp-2534 |grep conf
show atomic configuration (not necessary).
```

Files:

```
save.* : computational history. DFT total energy is shown at each iteration (See lmf next).
atmpnu* : radial derivative file. Used at lmf
atm.* : atom potential Used at lmf (only init)
ves* : obsolete
log* : just for debug log
```

Main part calculation:

```
mpirun -np 8 lmf mp-2534 |tee llmf
```

- mp-2534 gives 5.75 Å for GaAs, while the experimental value is 5.65 Å
- llmf contains iteration log, band eigenvalue, and so on. Check band gap.
- rst.mp-2534 is generated. Self-consistent charge included.
- You can change lattice constant as  $ALAT=1.889726877743552*5.65/5.75$  in ctrl file. simple math can be possible in ctrl
- Note: ctrlp is intermediate file generated by python from ctrl. Fortran calls a python code internally.
- check save.mp-2534. Show history of lmfa and lmf. one line per iteration. Show your console options. c,x,i,h  
LDA energy shown two values need to be the same (but slight difference).  
Repeat lmf stops with two iteration.
- SiteInfo.lmchk : Site info
- PlatQlat.chk : Lattice info
- estaticpot.dat : electrostatic potential of smooth part.

---

PROF

#### 4. job\_pdos, job\_tdos, job\_fermisurface, job\_band

For band plot, we use job\_band. Before this, we need to generate symmetry lines written in [syml.foobar](#). This can be generated by getsyml foobar.

```
getsyml mp-2534
```

This generates syml.mp-2534.

[BZ.html](#) contains BZ and symmetry lines.

For bandplot,

```
job_band mp-2534 -np 8 [options]
```

At the end of job\_band, you can add options for lmf as -vso=1 -vnspin=2.

(these are for SOC as perturbation)

We use gnuplot for band plot bandplot.isp1.glt.

In the similar manner, we can run job\_pdos, job\_tdos, job\_fermisurface.

## 5. QSGW calculation

We need one additional input file GWinput, whose template can be generated by mkGWinputでGWinput as

```
mkGWinput ctrl.mp-2534
```

The edit GWinput.tmp to GWinput.

n1n2n3 should be something smaller than nk1 nk2 nk3 in ctrl file.

If 6x6x6 for Si, it is reasonable. Except k points, not need to modify so much

(ask us).

## QSGW計算の流れ

We can run QSGW calculation with gwsc. For semiconductors, several iterations are fine. QPU file contains diagonal components of GW calculations.

Note that our Mixed Product basis is a key technology for the GW calculation.

```
gwsc -np NP [--phispinsym] [--gpu] [--mp] nloop extension
```

(--phispinsym is for magnetic materials to keep the same basis for up and down)

Then console outputs of gwsc is something like

```
#### START gwsc: ITERADD= 1, MPI size= 4, 4 TARGET= si
===== Initial band structure =====
--> No sigm. LDA calculation for eigenfunctions
0:00:00.226245 mpirun -np 1 /home/takao/ecalj/SRC/TestInstall/bin/lmfa
si >llmfa
0:00:00.807062 mpirun -np 4 /home/takao/ecalj/SRC/TestInstall/bin/lmf
si >llmf_lda
===== QSGW iteration start iter 1 ===
0:00:03.071054 mpirun -np 1 /home/takao/ecalj/SRC/TestInstall/bin/lmf
si --jobgw=0 >llmfgw00
0:00:03.904403 mpirun -np 1
/home/takao/ecalj/SRC/TestInstall/bin/qg4gw --job=1 > lqg4gw
0:00:04.431022 mpirun -np 4 /home/takao/ecalj/SRC/TestInstall/bin/lmf
si --jobgw=1 >llmfgw01
0:00:05.918216 mpirun -np 1
/home/takao/ecalj/SRC/TestInstall/bin/hefttet --job=1 > lefttet
```

```

0:00:06.444439 mpirun -np 1
/home/takao/ecalj/SRC/TestInstall/bin/hbasfp0 --job=3 >lbasC
0:00:07.064558 mpirun -np 4
/home/takao/ecalj/SRC/TestInstall/bin/hvccfp0 --job=3 > lvccC
0:00:07.812283 mpirun -np 4
/home/takao/ecalj/SRC/TestInstall/bin/hsfp0_sc --job=3 >lsxC
0:00:08.545956 mpirun -np 1
/home/takao/ecalj/SRC/TestInstall/bin/hbasfp0 --job=0 > lbas
0:00:09.156775 mpirun -np 4
/home/takao/ecalj/SRC/TestInstall/bin/hvccfp0 --job=0 > lvcc
0:00:09.884064 mpirun -np 4
/home/takao/ecalj/SRC/TestInstall/bin/hsfp0_sc --job=1 >lsx
0:00:10.644292 mpirun -np 4
/home/takao/ecalj/SRC/TestInstall/bin/hrcxq > lrcxq
0:00:11.482931 mpirun -np 4
/home/takao/ecalj/SRC/TestInstall/bin/hsfp0_sc --job=2 > lsc
0:00:12.460776 mpirun -np 1
/home/takao/ecalj/SRC/TestInstall/bin/hqpe_sc > lqpe
0:00:13.019735 mpirun -np 4 /home/takao/ecalj/SRC/TestInstall/bin/lmf
si >llmf
===== QSGW iteration end iter 1 ===
OK! ===== All calculation finished for gwsc =====
Comparison OK! max(abs(QPU-QPU))= 0.0050000000000002558 <etol= 0.011
for QPU
Comparison OK! MaxDiff= 0.00019999999999997797 < tol= 0.003 for
log.si
=== EndOf si_gwsc at /home/takao/ecalj/SRC/TestInstall/work/si_gwsc

```

...

The log files of console outputs are staring from l. C at the ends means Core-related parts. lsxC is the exchange self-energy due to cores.

lsx is for exchange. lsc is correlation. lvcc is for Coulomb matrix.

In this calculation we run **gwsc -np 8 1 si**, where 1 is the number of QSGW iteration.

PROF

If you repeat gwsc, you can add additional QSGW iterations added to your previous calculations.

## How to start over calcualtions

Remove mix\* rst\* (mix\* is mixing files)

If MT changes, start over from lmfa (remove atm\* files)

- As long as converged, no problem.
- If you have 3d spaghetti bands at  $E_f$ , need caution.

6. Dielectric function, ESM, spin fluctuation, life time of QP, Wannier method,...

Ask us.

7.lmchk

lmchk mp-2534

is to check the crystal symmetry. In addition determine MT radius. and Check the overlap of MTs. Defaults setting is with -3% overlap.(no overlap).

- symmetry
- MT overlap

If you have less symmetry rather than the symmetry of lattice for magnetic systems, you have to set crystal symmetry by hand.

This can be done by adding space group symmetry generator to SYMGRP (instead of find).

We need to pay attention for this point in the case of SOC.

## memo

band plot with spin orbit coupling.

method 1: only band plot

```
job_band mp-2534 -np 8 -vso=1 -vnspin=2: band plot only
```

Caution: when you set nspin=2, rst is twiced. No way to move it back to rst for nspin=1.

method 2. single iteration and SO=1

```
mpirun -np 8 lmf -vso=1 -vnspin=2 -vnit=1
```

job\_band mp-2534 -np 8 : band plot only

method 3. full iteration SO=1

```
mpirun -np 8 lmf -vso=1 -vnspin=2 -vnit=1
```

job\_band mp-2534 -np 8 : band plot only

Caution: when you set nspin=2, rst is twiced. No way to move it back to rst for nspin=1.

ecalj/Samples/MgO\_PROCAR

This is a sample of fat band. Run job\_procarを実行する。 You will have eps file.